

# Package ‘fftw’

May 8, 2026

**Version** 1.0-9

**Title** Fast FFT and DCT Based on the FFTW Library

**Description** Provides a simple and efficient wrapper around the fastest Fourier transform in the west (FFTW) library <<http://www.fftw.org/>>.

**Depends** R (>= 3.0.0)

**SystemRequirements** fftw3 (>= 3.1.2)

**License** GPL-2

**RoxygenNote** 6.0.1

**NeedsCompilation** yes

**Author** Olaf Mersmann [aut],  
Sebastian Krey [ctb],  
Uwe Ligges [ctb, cre]

**Maintainer** Uwe Ligges <ligges@statistik.tu-dortmund.de>

**Repository** CRAN

**Date/Publication** 2024-09-20 16:00:02 UTC

## Contents

FFT . . . . .	1
planFFT . . . . .	2

<b>Index</b>	<b>4</b>
--------------	----------

---

FFT	<i>Calculate (inverse) DFT using the FFT method</i>
-----	---

---

## Description

see title

**Usage**

```

FFT(x, ..., plan, inverse=FALSE)
IFFT(x, ..., plan, scale=TRUE)
DCT(x, ..., plan, type=1, inverse=FALSE)
IDCT(x, ..., plan, type=1, scale=TRUE)

```

**Arguments**

x	(complex) vector to process
...	ignored
plan	FFTW plan, can be missing
inverse	perform inverse transform, provided for fft compatibility.
scale	scale results
type	type of DCT

**Author(s)**

Olaf Mersmann <olafm@statistik.uni-dortmund.de>

**See Also**

[planFFT](#)

**Examples**

```

n <- 2**16
x <- rnorm(n)
p <- planFFT(n)
y <- FFT(x, plan=p)

Mod(x - IFFT(FFT(x)))

```

---

planFFT

*Create FFTW plan*

---

**Description**

see title

**Usage**

```

planFFT(n, effort=0)
planDCT(n, type=1, effort=0)

```

**Arguments**

n	size of transform
type	type of DCT
effort	how hard fftw tries to find an optimal plan (0 to 3)

**Author(s)**

Olaf Mersmann <olafm@statistik.uni-dortmund.de>

**See Also**

[FFT](#) and [IFFT](#)

# Index

DCT (FFT), 1

FFT, 1, 3

IDCT (FFT), 1

IFFT, 3

IFFT (FFT), 1

planDCT (planFFT), 2

planFFT, 2, 2