

Package ‘forcis’

May 8, 2026

Type Package

Title Handle the FORCIS Foraminifera Database

Version 1.0.1

Description Provides an interface to the 'FORCIS' database (Chaabane et al. (2024) <[doi:10.5281/zenodo.7390791](https://doi.org/10.5281/zenodo.7390791)>) on global foraminifera distribution. This package allows to download and to handle 'FORCIS' data. It is part of the FRB-CESAB working group FORCIS. <<https://www.fondationbiodiversite.fr/en/the-frb-in-action/programs-and-projects/le-cesab/forcis/>>.

URL <https://docs.ropensci.org/forcis/>,
<https://github.com/ropensci/forcis>

BugReports <https://github.com/ropensci/forcis/issues>

License GPL (>= 2)

Encoding UTF-8

RoxygenNote 7.3.2

VignetteBuilder knitr

Depends R (>= 4.1.0)

Imports ggplot2, httr2, rlang, sf, tibble, tidyr, utils, vroom

Suggests fs, dplyr, httptest2, knitr, rmarkdown, testthat (>= 3.0.0),
vdiff, withr

Config/testthat/edition 3

NeedsCompilation no

Author Nicolas Casajus [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0002-5537-5294>>),
Mattia Greco [aut] (ORCID: <<https://orcid.org/0000-0003-2416-6235>>),
Sonia Chaabane [aut] (ORCID: <<https://orcid.org/0000-0002-4653-8610>>),
Xavier Giraud [aut] (ORCID: <<https://orcid.org/0000-0001-5067-8176>>),
Thibault de Garidel-Thoron [aut] (ORCID:
<<https://orcid.org/0000-0001-8983-9571>>),
Khalil Hammami [ctb],
Air Forbes [rev] (ORCID: <<https://orcid.org/0000-0002-9842-7648>>),
FRB-CESAB [fnd]

Maintainer Nicolas Casajus <nicolas.casajus@fondationbiodiversite.fr>

Repository CRAN

Date/Publication 2025-05-23 12:02:02 UTC

Contents

compute_abundances	2
convert_to_long_format	3
data_to_sf	4
download_forcis_db	5
filter_by_bbox	7
filter_by_month	8
filter_by_ocean	9
filter_by_polygon	10
filter_by_species	11
filter_by_year	12
geom_basemap	13
get_available_versions	13
get_ocean_names	14
get_required_columns	14
get_species_names	15
get_version_metadata	16
ggmap_data	16
plot_record_by_depth	17
plot_record_by_month	18
plot_record_by_season	18
plot_record_by_year	19
read_cpr_north_data	20
select_forcis_columns	21
select_taxonomy	22

Index 24

compute_abundances	<i>Compute count conversions</i>
--------------------	----------------------------------

Description

Functions to convert species counts between different formats: raw abundance, relative abundance, and number concentration, using counts metadata.

Usage

```
compute_abundances(data, aggregate = TRUE)
```

```
compute_concentrations(data, aggregate = TRUE)
```

```
compute_frequencies(data, aggregate = TRUE)
```

Arguments

data	a tibble or a data.frame. One obtained by read_*_data() functions.
aggregate	a logical of length 1. If FALSE counts will be derived for each subsample. If TRUE (default) subsample counts will be aggregated by sample_id.

Details

- compute_concentrations() converts all counts to number concentrations (n specimens/m³).
- compute_frequencies() converts all counts to relative abundances (% specimens per sampling unit).
- compute_abundances() converts all counts to raw abundances (n specimens/sampling unit).

Value

A tibble in long format with two additional columns: taxa, the taxon name and counts_*, the number concentration (counts_n_conc) or the relative abundance (counts_rel_ab) or the raw abundance (counts_raw_ab).

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Select a taxonomy ----
net_data <- select_taxonomy(net_data, taxonomy = "VT")

# Dimensions of the data.frame ----
dim(net_data)

# Compute concentration ----
net_data_conc <- compute_concentrations(net_data)

# Dimensions of the data.frame ----
dim(net_data_conc)
```

convert_to_long_format

Reshape and simplify FORCIS data

Description

Reshapes FORCIS data by pivoting species columns into two columns: taxa (taxon names) and counts (taxon abundances). It converts wider data.frame to a long format.

Usage

```
convert_to_long_format(data)
```

Arguments

`data` a tibble or a `data.frame`, i.e. a FORCIS dataset, except for CPR North data.

Value

A tibble reshaped in a long format.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Dimensions of the data.frame ----
dim(net_data)

# Reshape data ----
net_data <- convert_to_long_format(net_data)

# Dimensions of the data.frame ----
dim(net_data)

# Column names ----
colnames(net_data)
```

data_to_sf

Convert a data frame into an sf object

Description

This function can be used to convert a `data.frame` into an `sf` object. Note that coordinates (columns `site_lon_start_decimal` and `site_lat_start_decimal`) are projected in the Robinson coordinate system.

Usage

```
data_to_sf(data)
```

Arguments

`data` a tibble or a `data.frame`, i.e. a FORCIS dataset or the output of a `filter_*()` function.

Value

An sf POINTS object.

Examples

```
# Attach package ----
library("ggplot2")

# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Dimensions of the data.frame ----
dim(net_data)

# Filter by years ----
net_data_sub <- filter_by_year(net_data, years = 1992)

# Convert to an sf object ----
net_data_sub_sf <- data_to_sf(net_data_sub)

# World basemap ----
ggplot() +
  geom_basemap() +
  geom_sf(data = net_data_sub_sf)
```

download_forcis_db *Download the FORCIS database*

Description

Downloads the entire FORCIS database as a collection of five csv files from Zenodo (<https://zenodo.org/doi/10.5281/zenodo.7390791>). Additional files will be also downloaded.

Usage

```
download_forcis_db(
  path,
  version = options()$forcis_version,
  check_for_update = options()$forcis_check_for_update,
  overwrite = FALSE,
  timeout = 60
)
```

Arguments

path	a character of length 1. The folder in which the FORCIS database will be saved. Note that a subdirectory will be created, e.g. forcis-db/version-99/ (with 99 the version number).
version	a character of length 1. The version number (with two numbers, e.g. 08 instead of 8) of the FORCIS database to use. Default is the latest version. Note that this argument can be handle with the global option forcis_version. For example, if user calls options(forcis_version = "07"), the version 07 will be used by default for the current R session. Note that it is recommended to use the latest version of the database.
check_for_update	a logical. If TRUE (default) the function will check if a newer version of the FORCIS database is available on Zenodo and will print an informative message. Note that this argument can be handle with the global option forcis_check_for_update. For example, if user calls options(forcis_check_for_update = FALSE), the message to download the latest version will be disabled for the current R session.
overwrite	a logical. If TRUE it will override the downloaded files of the FORCIS database. Default is FALSE.
timeout	an integer. The timeout for downloading files from Zenodo. Default is 60. This number can be increased for low Internet connection.

Details

The FORCIS database is regularly updated. The global structure of the tables doesn't change between versions but some bugs can be fixed and new records can be added. This is why it is recommended to use the latest version of the database. The package is designed to handle the versioning of the database on Zenodo and will inform the user if a new version is available each time he/she uses one of the read*_data() functions.

For more information, please read the vignette available at <https://docs.ropensci.org/forcis/articles/database-versions.html>.

Value

No return value. The FORCIS files will be saved in the path folder.

References

Chaabane S, De Garidel-Thoron T, Giraud X, *et al.* (2023) The FORCIS database: A global census of planktonic Foraminifera from ocean waters. *Scientific Data*, 10, 354. DOI: [doi:10.1038/s41597-023022642](https://doi.org/10.1038/s41597-023022642).

See Also

[read_plankton_nets_data\(\)](#) to import the FORCIS database.

Examples

```
# Folder in which the database will be saved ----
# N.B. In this example we use a temporary folder but you should select an
# existing folder (for instance "data/").
path <- tempdir()

# Download the database ----
download_forcis_db(path, timeout = 300)

# Check the content of the folder ----
list.files(path, recursive = TRUE)
```

filter_by_bbox	<i>Filter FORCIS data by a spatial bounding box</i>
----------------	---

Description

Filters FORCIS data by a spatial bounding box.

Usage

```
filter_by_bbox(data, bbox)
```

Arguments

data	a tibble or a data.frame. One obtained by read*_data() functions.
bbox	an object of class bbox (package sf) or a vector of four numeric values defining a square bounding box. Values must follow this order: minimum longitude (xmin), minimum latitude (ymin), maximum longitude (xmax), and maximum latitude (ymax). Important: if a vector of numeric values is provided, coordinates must be defined in the system WGS 84 (epsg=4326).

Value

A tibble containing a subset of data for the desired bounding box.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Dimensions of the data.frame ----
dim(net_data)
```

```
# Filter by oceans ----
net_data_sub <- filter_by_bbox(net_data, bbox = c(45, -61, 82, -24))

# Dimensions of the data.frame ----
dim(net_data_sub)
```

filter_by_month *Filter FORCIS data by month of sampling*

Description

Filters FORCIS data by month of sampling.

Usage

```
filter_by_month(data, months)
```

Arguments

`data` a tibble or a data.frame. One obtained by read*_data() functions.
`months` a numeric containing one or several months.

Value

A tibble containing a subset of data for the desired months.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Dimensions of the data.frame ----
dim(net_data)

# Filter by months ----
net_data_sub <- filter_by_month(net_data, months = 1:2)

# Dimensions of the data.frame ----
dim(net_data_sub)
```

filter_by_ocean	<i>Filter FORCIS data by ocean</i>
-----------------	------------------------------------

Description

Filters FORCIS data by one or several oceans.

Usage

```
filter_by_ocean(data, ocean)
```

Arguments

data	a tibble or a data.frame. One obtained by read*_data() functions.
ocean	a character vector of one or several ocean names. Use the function get_ocean_names() to find the correct spelling.

Value

A tibble containing a subset of data for the desired oceans.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Dimensions of the data.frame ----
dim(net_data)

# Get ocean names ----
get_ocean_names()

# Filter by oceans ----
net_data_sub <- filter_by_ocean(net_data, ocean = "Indian Ocean")

# Dimensions of the data.frame ----
dim(net_data_sub)
```

filter_by_polygon *Filter FORCIS data by a spatial polygon*

Description

Filters FORCIS data by a spatial polygon.

Usage

```
filter_by_polygon(data, polygon)
```

Arguments

data a tibble or a data.frame. One obtained by read*_data() functions.
polygon an sf POLYGON object.

Value

A tibble containing a subset of data for the desired spatial polygon.

Examples

```
# Import example dataset ----  
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),  
                          package = "forcis")  
  
net_data <- read.csv(file_name)  
  
# Dimensions of the data.frame ----  
dim(net_data)  
  
# Import Indian Ocean spatial polygons ----  
file_name <- system.file(file.path("extdata",  
                                    "IHO_Indian_ocean_polygon.gpkg"),  
                          package = "forcis")  
  
indian_ocean <- sf::st_read(file_name)  
  
# Filter by polygon ----  
net_data_sub <- filter_by_polygon(net_data, polygon = indian_ocean)  
  
# Dimensions of the data.frame ----  
dim(net_data_sub)
```

filter_by_species *Filter FORCIS data by species*

Description

Filters FORCIS data by a species list.

Usage

```
filter_by_species(data, species)
```

Arguments

`data` a tibble or a data.frame. One obtained by `read*_data()` functions.
`species` a character vector listing species of interest.

Value

A tibble containing a subset of data.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Select a taxonomy ----
net_data <- select_taxonomy(net_data, taxonomy = "VT")

# Select only required columns (and taxa) ----
net_data <- select_forcis_columns(net_data)

# Dimensions of the data.frame ----
dim(net_data)

# Get species names ----
get_species_names(net_data)

# Select records for three species ----
net_data_sub <- filter_by_species(data = net_data,
                                  species = c("g_inflata_VT",
                                              "g_elongatus_VT",
                                              "g_glutinata_VT"))

# Dimensions of the data.frame ----
dim(net_data_sub)
```

```
# Get species names ----  
get_species_names(net_data_sub)
```

filter_by_year	<i>Filter FORCIS data by year of sampling</i>
----------------	---

Description

Filters FORCIS data by year of sampling.

Usage

```
filter_by_year(data, years)
```

Arguments

data	a tibble or a data.frame. One obtained by read*_data() functions.
years	a numeric containing one or several years.

Value

A tibble containing a subset of data for the desired years.

Examples

```
# Import example dataset ----  
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),  
                          package = "forcis")  
  
net_data <- read.csv(file_name)  
  
# Dimensions of the data.frame ----  
dim(net_data)  
  
# Filter by years ----  
net_data_sub <- filter_by_year(net_data, years = 1992)  
  
# Dimensions of the data.frame ----  
dim(net_data_sub)
```

geom_basemap	<i>Add a World basemap to a ggplot object</i>
--------------	---

Description

Creates a World base map that can be added to a ggplot object. Spatial layers come from the Natural Earth project (<https://www.naturalearthdata.com/>) and are defined in the Robinson coordinate system.

Usage

```
geom_basemap()
```

Value

A ggplot object.

Examples

```
# Attach package ----  
library("ggplot2")  
  
# World basemap ----  
ggplot() +  
  geom_basemap()
```

get_available_versions	<i>Get available versions of the FORCIS database</i>
------------------------	--

Description

Gets all available versions of the FORCIS database by querying the Zenodo API (<https://developers.zenodo.org>).

Usage

```
get_available_versions()
```

Value

A tibble with three columns:

- `publication_date`: the date of the release of the version
- `version`: the label of the version
- `access_right`: is the version open or restricted?

Examples

```
# Versions of the FORCIS database ----  
get_available_versions()
```

get_ocean_names	<i>Get World ocean names</i>
-----------------	------------------------------

Description

This function returns the name of World oceans according to the IHO Sea Areas dataset version 3 (Flanders Marine Institute, 2018).

Usage

```
get_ocean_names()
```

Value

A character vector with World ocean names.

References

Flanders Marine Institute (2018). IHO Sea Areas, version 3. Available online at: <https://www.marineregions.org/>. DOI: [doi:10.14284/323](https://doi.org/10.14284/323).

Examples

```
# Print the name of World oceans ----  
get_ocean_names()
```

get_required_columns	<i>Get required column names</i>
----------------------	----------------------------------

Description

Gets required column names (except taxa names) for the package. This function is designed to help users to add additional columns in `select_forcis_columns()` (argument `cols`) if missing from this list.

These columns are required by some functions (`compute_*()`, `plot_*()`, etc.) of the package and shouldn't be deleted.

Usage

```
get_required_columns()
```

Value

A character vector.

Examples

```
# Get required column names (expect taxa names) ----  
get_required_columns()
```

get_species_names	<i>Get species names from column names</i>
-------------------	--

Description

Gets species names from column names. This function is just an utility to easily retrieve taxon names.

Usage

```
get_species_names(data)
```

Arguments

data a tibble or a data.frame. One obtained by read*_data() functions.

Value

A character vector of species names.

Examples

```
# Import example dataset ----  
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),  
                          package = "forcis")  
  
net_data <- read.csv(file_name)  
  
# Select a taxonomy ----  
net_data <- select_taxonomy(net_data, taxonomy = "VT")  
  
# Retrieve taxon names ----  
get_species_names(net_data)
```

`get_version_metadata` *Print information of a specific version of the FORCIS database*

Description

Prints information of a specific version of the FORCIS database by querying the Zenodo API (<https://developers.zenodo.org>).

Usage

```
get_version_metadata(version = NULL)
```

Arguments

`version` a character of length 1. The label of the version. Use `get_available_versions()` to list available versions. If NULL (default) the latest version is used.

Value

A list with all information about the version, including: `title`, `doi`, `publication_date`, `description`, `access_right`, `creators`, `keywords`, `version`, `resource_type`, `license`, and `files`.

Examples

```
# Get information for the latest version of the FORCIS database ----
get_version_metadata()
```

`ggmap_data` *Map the spatial distribution of FORCIS data*

Description

Maps the spatial distribution of FORCIS data.

Usage

```
ggmap_data(data, col = "red", ...)
```

Arguments

`data` a data.frame. One obtained by `read_*_data()` functions.
`col` a character of length 1. The color of data on the map.
`...` other graphical parameters passed on to `geom_sf()`.

Value

A ggplot object.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Map data (default) ----
ggmap_data(net_data)

# Map data ----
ggmap_data(net_data, col = "black", fill = "red", shape = 21, size = 2)
```

plot_record_by_depth *Plot sample records by depth of collection*

Description

This function produces a barplot of FORCIS sample records by depth.

Usage

```
plot_record_by_depth(data)
```

Arguments

data a tibble or a data.frame, i.e. a FORCIS dataset.

Value

A ggplot object.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Plot data by year (example dataset) ----
plot_record_by_depth(net_data)
```

plot_record_by_month *Plot sample records by month*

Description

This function produces a barplot of FORCIS sample records by month.

Usage

```
plot_record_by_month(data)
```

Arguments

data a tibble or a data.frame, i.e. a FORCIS dataset.

Value

A ggplot object.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Plot data by year (example dataset) ----
plot_record_by_month(net_data)
```

plot_record_by_season *Plot sample records by season*

Description

This function produces a barplot of FORCIS sample records by season.

Usage

```
plot_record_by_season(data)
```

Arguments

data a tibble or a data.frame, i.e. a FORCIS dataset.

Value

A ggplot object.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Plot data by year (example dataset) ----
plot_record_by_season(net_data)
```

plot_record_by_year *Plot sample records by year*

Description

This function produces a barplot of FORCIS sample records by year.

Usage

```
plot_record_by_year(data)
```

Arguments

data a tibble or a data.frame, i.e. a FORCIS dataset.

Value

A ggplot object.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Plot data by year (example dataset) ----
plot_record_by_year(net_data)
```

read_cpr_north_data *Read FORCIS data*

Description

These functions read one specific csv file of the FORCIS database (see below) stored in the folder path. The function `download_forcis_db()` must be used first to store locally the database.

Usage

```
read_cpr_north_data(
  path,
  version = options()$forcis_version,
  check_for_update = options()$forcis_check_for_update
)

read_cpr_south_data(
  path,
  version = options()$forcis_version,
  check_for_update = options()$forcis_check_for_update
)

read_plankton_nets_data(
  path,
  version = options()$forcis_version,
  check_for_update = options()$forcis_check_for_update
)

read_pump_data(
  path,
  version = options()$forcis_version,
  check_for_update = options()$forcis_check_for_update
)

read_sediment_trap_data(
  path,
  version = options()$forcis_version,
  check_for_update = options()$forcis_check_for_update
)
```

Arguments

path	a character of length 1. The folder in which the FORCIS database has been saved.
version	a character of length 1. The version number (with two numbers, e.g. 08 instead of 8) of the FORCIS database to use. Default is the latest version. Note that this argument can be handle with the global option <code>forcis_version</code> . For

example, if user calls `options(forcis_version = "07")`, the version 07 will be used by default for the current R session. Note that it is recommended to use the latest version of the database.

`check_for_update`

a logical. If TRUE (default) the function will check if a newer version of the FORCIS database is available on Zenodo and will print an informative message. Note that this argument can be handle with the global option `forcis_check_for_update`. For example, if user calls `options(forcis_check_for_update = FALSE)`, the message to download the latest version will be disabled for the current R session.

Details

- `read_plankton_nets_data()` reads the FORCIS plankton nets data
- `read_pump_data()` reads the FORCIS pump data
- `read_cpr_north_data()` reads the FORCIS CPR North data
- `read_cpr_south_data()` reads the FORCIS CPR South data
- `read_sediment_trap_data()` reads the FORCIS sediment traps data

Value

A tibble. See <https://zenodo.org/doi/10.5281/zenodo.7390791> for a preview of the datasets.

See Also

[download_forcis_db\(\)](#) to download the complete FORCIS database.

Examples

```
# Folder in which the database will be saved ----
# N.B. In this example we use a temporary folder but you should select an
# existing folder (for instance "data/").
path <- tempdir()

# Download the database ----
download_forcis_db(path, timeout = 300)

# Import plankton nets data ----
plankton_nets_data <- read_plankton_nets_data(path)
```

`select_forcis_columns` *Select columns in FORCIS data*

Description

Selects columns in FORCIS data. Because FORCIS data contains more than 100 columns, this function can be used to lighten the `data.frame` to easily handle it and to speed up some computations.

Usage

```
select_forcis_columns(data, cols = NULL)
```

Arguments

data a tibble or a data.frame. One obtained by read*_data() functions.

cols a character vector of column names to keep in addition to the required ones (see [get_required_columns\(\)](#)) and to the taxa columns. Can be NULL (default).

Value

A tibble.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Dimensions of the data.frame ----
dim(net_data)

# Select a taxonomy ----
net_data <- select_taxonomy(net_data, taxonomy = "VT")

# Dimensions of the data.frame ----
dim(net_data)

# Select only required columns (and taxa) ----
net_data <- select_forcis_columns(net_data)

# Dimensions of the data.frame ----
dim(net_data)
```

<code>select_taxonomy</code>	<i>Select a taxonomy in FORCIS data</i>
------------------------------	---

Description

Selects a taxonomy in FORCIS data. FORCIS database provides three different taxonomies: "LT" (lumped taxonomy), "VT" (validated taxonomy) and "OT" (original taxonomy). See [doi:10.1038/s41597023022642](https://doi.org/10.1038/s41597023022642) for further information.

Usage

```
select_taxonomy(data, taxonomy)
```

Arguments

`data` a tibble or a data.frame. One obtained by `read*_data()` functions.
`taxonomy` a character of length 1. One among "LT", "VT", "OT".

Value

A tibble.

Examples

```
# Import example dataset ----
file_name <- system.file(file.path("extdata", "FORCIS_net_sample.csv"),
                          package = "forcis")

net_data <- read.csv(file_name)

# Dimensions of the data.frame ----
dim(net_data)

# Select a taxonomy ----
net_data <- select_taxonomy(net_data, taxonomy = "VT")

# Dimensions of the data.frame ----
dim(net_data)
```

Index

computations (compute_abundances), 2
compute_abundances, 2
compute_concentrations
 (compute_abundances), 2
compute_frequencies
 (compute_abundances), 2
convert_to_long_format, 3

data_to_sf, 4
download_forcis_db, 5
download_forcis_db(), 20, 21

filter_by_bbox, 7
filter_by_month, 8
filter_by_ocean, 9
filter_by_polygon, 10
filter_by_species, 11
filter_by_year, 12

geom_basemap, 13
get_available_versions, 13
get_available_versions(), 16
get_ocean_names, 14
get_required_columns, 14
get_required_columns(), 22
get_species_names, 15
get_version_metadata, 16
ggmap_data, 16

plot_record_by_depth, 17
plot_record_by_month, 18
plot_record_by_season, 18
plot_record_by_year, 19

read_cpr_north_data, 20
read_cpr_south_data
 (read_cpr_north_data), 20
read_data (read_cpr_north_data), 20
read_plankton_nets_data
 (read_cpr_north_data), 20
read_plankton_nets_data(), 6

read_pump_data (read_cpr_north_data), 20
read_sediment_trap_data
 (read_cpr_north_data), 20

select_forcis_columns, 21
select_forcis_columns(), 14
select_taxonomy, 22