

Package ‘fwlplot’

May 8, 2026

Title Scatter Plot After Residualizing Using 'fixest' Package

Version 0.3.0

Description Creates a scatter plot after residualizing using a set of covariates. The residuals are calculated using the 'fixest' package which allows very fast estimation that scales. Details of the (Yule-)Frisch-Waugh-Lovell theorem is given in Basu (2023) <[doi:10.48550/arXiv.2307.00369](https://doi.org/10.48550/arXiv.2307.00369)>.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.1

Imports data.table, fixest, tinyplot

Suggests ggplot2

NeedsCompilation no

Author Kyle Butts [aut, cre] (ORCID: <<https://orcid.org/0000-0002-9048-8059>>)

Maintainer Kyle Butts <kbutts@uark.edu>

Repository CRAN

Date/Publication 2024-06-24 13:30:02 UTC

Contents

fml_breaker	1
fwl_plot	2
get_fml_parts	3

Index	4
--------------	----------

fml_breaker	<i>Break apart formula (from right to left) based on a symbole (~ or)</i>
-------------	---

Description

Break apart formula (from right to left) based on a symbole (~ or |)

Usage

```
fml_breaker(fml, op)
```

Arguments

fml	Formula following fixest syntax.
op	String. Either ~ or

Value

list of symbol or language from right to left that are split at each occurrence of op.

fml_plot	<i>FWL Plot</i>
----------	-----------------

Description

This function creates a bivariate plot of y and x after residualizing over a set of covariates w.

Usage

```
fml_plot(fml, data, ggplot = FALSE, n_sample = 1000, alpha = 0.5, ...)
```

```
fmlplot(fml, data, ggplot = FALSE, n_sample = 1000, alpha = 0.5, ...)
```

Arguments

fml	Of the form $y \sim x + covs \mid fes$ following the fixest formula syntax. The x variable you want plotted should come first.
data	A dataframe object that contains the variables in fml.
ggplot	Boolean. Default is to use base R plot but if TRUE, use ggplot.
n_sample	Numeric. Number of observations to sample for each facet.
alpha	Numeric. Alpha transparency of each individual point. If NULL, will plot all rows.
...	Additional arguments passed to <code>fixest::feols</code> .

Value

Either NULL if ggplot = FALSE or a ggplot object if ggplot = TRUE. In either case, plots the figure.

Examples

```
fml_plot(mpg ~ hp + wt | cyl, mtcars)
```

get_fm1_parts	<i>Split formula into terms</i>
---------------	---------------------------------

Description

Split formula into terms

Usage

```
get_fm1_parts(formula, parts_as_formula = FALSE)
```

Arguments

formula	Full formula following fixest syntax: $y \sim W \mid W_FE \mid T \sim Z \mid Z_FE$.
parts_as_formula	Logical. If TRUE, then each part will be a right-hand side formula. Default is FALSE

Value

List of expressions/formula for each part of the formula. It will be of type symbol/language unless `parts_as_formula = TRUE`. Can be used with `fixest::xpd` and the dot bracket syntax to create formula. Any missing elements will be given a value of NULL. The list contains the following:

y_fm1	The LHS
W_lin	The linear part of the exogenous variables
W_FE	The fixed effects part of the exogenous variables
T_fm1	The endogenous variable
Z_lin	The linear part of the instruments
Z_FE	The fixed effects part of the instruments

Index

fml_breaker, 1

fwl_plot, 2

fwlplot (fwl_plot), 2

get_fml_parts, 3