

Package ‘gghighlight’

May 8, 2026

Type Package

Title Highlight Lines and Points in 'ggplot2'

Version 0.5.0

Description Make it easier to explore data with highlights.

License MIT + file LICENSE

URL <https://yutanihilation.github.io/gghighlight/>,
<https://github.com/yutanihilation/gghighlight>

BugReports <https://github.com/yutanihilation/gghighlight/issues>

Depends ggplot2 (>= 3.3.6), R (>= 3.4.0)

Imports dplyr (>= 1.0.4), ggrepel, lifecycle, purrr, rlang, tibble,
scales, grDevices

Suggests geomtextpath, knitr, rmarkdown, sf, testthat, vdiff (>= 0.3.0)

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.3.2

Config/testthat/edition 3

NeedsCompilation no

Author Hiroaki Yutani [aut, cre] (ORCID:
<https://orcid.org/0000-0002-3385-7233>)

Maintainer Hiroaki Yutani <yutani.ini@gmail.com>

Repository CRAN

Date/Publication 2025-06-14 07:50:02 UTC

Contents

gghighlight-package	2
gghighlight	2
Index	5

gghighlight-package *Highlight Lines and Points in 'ggplot2'*

Description

Make it easier to explore data with highlights.

Author(s)

Maintainer: Hiroaki Yutani <yutani.ini@gmail.com> ([ORCID](#))

See Also

Useful links:

- <https://yutanihilation.github.io/gghighlight/>
- <https://github.com/yutanihilation/gghighlight>
- Report bugs at <https://github.com/yutanihilation/gghighlight/issues>

gghighlight *Highlight Data With Predicate*

Description

`gghighlight()` highlights (almost) any geoms according to the given predicates.

Usage

```
gghighlight(  
  ...,  
  n = NULL,  
  max_highlight = 5L,  
  unhighlighted_params = list(),  
  use_group_by = NULL,  
  use_direct_label = NULL,  
  label_key = NULL,  
  label_params = list(fill = "white"),  
  keep_scales = FALSE,  
  calculate_per_facet = FALSE,  
  line_label_type = c("ggrepel_label", "ggrepel_text", "text_path", "label_path",  
    "sec_axis"),  
  unhighlighted_colour = NULL  
)
```

Arguments

...	Expressions to filter data, which is passed to <code>dplyr::filter()</code> .
n	Number of layers to clone.
max_highlight	Max number of series to highlight.
unhighlighted_params	Aesthetics (e.g. colour, fill, and size) for unhighlighted geoms. Specifying colour = NULL or fill = NULL will preserve the original colour.
use_group_by	If TRUE, use <code>dplyr::group_by()</code> to evaluate predicate.
use_direct_label	If TRUE, add labels directly on the plot instead of using a legend.
label_key	Column name for label aesthetics.
label_params	A list of parameters, which is passed to <code>ggrepel::geom_label_repel()</code> .
keep_scales	If TRUE, keep the original data with <code>ggplot2::geom_blank()</code> so that the highlighted plot has the same scale with the data.
calculate_per_facet	(Experimental) If TRUE, include the facet variables to calculate the grouping; in other words, highlighting is done on each facet individually.
line_label_type	(Experimental) Method to add labels (or texts) on the highlighted lines. "ggrepel_label" Use <code>ggrepel::geom_label_repel()</code> . "ggrepel_text" Use <code>ggrepel::geom_text_repel()</code> . "text_path" Use <code>geomtextpath::geom_textline()</code> for lines and <code>geomtextpath::geom_textpath()</code> for paths. "label_path" Use <code>geomtextpath::geom_labelline()</code> for lines and <code>geomtextpath::geom_labelpath()</code> for paths. "sec_axis" Use secondary axis. Please refer to Simon Jackson's blog post for the trick.
unhighlighted_colour	(Deprecated) Colour for unhighlighted geoms.

Examples

```
d <- data.frame(
  idx = c(1, 1, 1, 2, 2, 2, 3, 3, 3),
  value = c(1, 2, 3, 10, 11, 12, 9, 10, 11),
  category = rep(c("a", "b", "c"), 3),
  stringsAsFactors = FALSE
)

# Highlight the lines whose max values are larger than 10
ggplot(d, aes(idx, value, colour = category)) +
  geom_line() + gghighlight(max(value) > 10)

# Highlight the points whose values are larger than 10
ggplot(d, aes(idx, value)) +
  geom_point() +
```

```
gghighlight(value > 10, label_key = category)

# Specify the styles for unhighlighted layer
ggplot(d, aes(idx, value, colour = category)) +
  geom_line(linewidth = 5) +
  gghighlight(max(value) > 10,
    unhighlighted_params = list(linewidth = 1)
  )
```

Index

`dplyr::filter()`, 3
`dplyr::group_by()`, 3

`geomtextpath::geom_labelline()`, 3
`geomtextpath::geom_labelpath()`, 3
`geomtextpath::geom_textline()`, 3
`geomtextpath::geom_textpath()`, 3
`gghighlight`, 2
`gghighlight-package`, 2
`ggplot2::geom_blank()`, 3
`ggrepel::geom_label_repel()`, 3
`ggrepel::geom_text_repel()`, 3