

Package ‘gkgraphR’

May 8, 2026

Title Accessing the Official 'Google Knowledge Graph' API

Version 1.0.3

Date 2026-03-04

Description A simple way to interact with and extract data from the official 'Google Knowledge Graph' API <<https://developers.google.com/knowledge-graph/>>.

Language en-US

URL <https://github.com/racorreia/gkgraphR>

BugReports <https://github.com/racorreia/gkgraphR/issues>

Depends R (>= 3.4.0)

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.1.1

Imports jsonlite(>= 1.5), httr(>= 1.4.1), ISOcodes(>= 2020.03.16)

Suggests knitr, rmarkdown, qpdf

VignetteBuilder knitr

NeedsCompilation no

Author Ricardo Correia [aut, cre] (ORCID: <<https://orcid.org/0000-0001-7359-9091>>)

Maintainer Ricardo Correia <rahc85@gmail.com>

Repository CRAN

Date/Publication 2026-03-04 16:20:02 UTC

Contents

querykg	2
Index	4

 querygkg

Performs a query on the Google Knowledge Graph API

Description

Performs a query on the Google Knowledge Graph API

Usage

```
querygkg(
  query = NULL,
  ids = NULL,
  lang = NULL,
  types = NULL,
  indent = NULL,
  prefix = NULL,
  limit = NULL,
  json = FALSE,
  itemList = TRUE,
  cleanIDs = TRUE,
  api.key
)
```

Arguments

query	A character string to search for in Google Knowledge Graph.
ids	A list of one or more entity IDs to search for in Google Knowledge Graph. Should be a Google Knowledge Graph or Freebase ID code in character string format.
lang	A character argument defining the language filter. The list of language codes (defined in ISO 639) to run the query with, for instance 'en'. Defaults to NULL.
types	A character argument restricting returned entities to those of the specified types. See schema.org for valid types (e.g. 'Person' as defined in http://schema.org/Person restricts the results to entities representing people). If multiple types are specified, returned entities will contain one or more of these types. Defaults to NULL.
indent	A logical argument enabling indenting of JSON results. Defaults to NULL.
prefix	A logical argument enabling prefix (initial substring) matching against names and aliases of entities. For example, a prefix 'Jung' will match entities and aliases such as 'Jung', 'Jungle', and 'Jung-ho Kang'. Defaults to NULL.
limit	A numeric value limiting the number of entities to be returned. Maximum is 500. Defaults to 20. Please note that requests with high limits have a higher chance of timing out.
json	A logical argument defining whether the API query should be returned in the original JSON format or as an R object. Defaults to FALSE.

<code>itemList</code>	Should the query contain only the Google Knowledge Graph item list returned by the query? Defaults to TRUE. Only valid when returning R objects (i.e. <code>parameter json = FALSE</code>).
<code>cleanIDs</code>	If the output is an item list, should it return clean IDs? Defaults to TRUE. Only valid when returning an item list (i.e. <code>parameter json = FALSE</code> and <code>parameter itemList = TRUE</code>).
<code>api.key</code>	A Google API key.

Value

Returns the Google Knowledge Graph output.

Examples

```
## Not run:  
# Note: Function querygkg requires a valid Google API key to work  
  
# Run a text-based query for the term "apple"  
querygkg(query = "apple", api.key = "YOUR_API_KEY")  
  
# Run an ID-based query for the entity "apple" representing the fruit  
querygkg(ids = "/m/014j1m", api.key = "YOUR_API_KEY")  
  
# Run an ID-based query and get the original JSON object returned by the API  
querygkg(ids = "/m/014j1m", json = TRUE, api.key = "YOUR_API_KEY")  
  
## End(Not run)
```

Index

querygk, [2](#)