

Package ‘growthTrendR’

May 8, 2026

Type Package

Title Toolkit for Data Processing, Quality, and Statistical Models

Version 0.2.2

Date 2026-01-19

Maintainer Xiao Jing Guo <xiaojing.guo@nrcan-rncan.gc.ca>

Description Offers tools for data formatting, anomaly detection, and classification of tree-ring data using spatial comparisons and cross-correlation. Supports flexible detrending and climate–growth modeling via generalized additive mixed models (Wood 2017, ISBN:978-1498728331) and the 'mgcv' package (<<https://CRAN.R-project.org/package=mgcv>>), enabling robust analysis of non-linear trends and autocorrelated data. Provides standardized visual reporting, including summaries, diagnostics, and model performance. Compatible with '.rw1' files and tailored for the Canadian Forest Service Tree-Ring Data (CFS-TREND) repository (Girardin et al. (2021) <[doi:10.1139/er-2020-0099](https://doi.org/10.1139/er-2020-0099)>), offering a comprehensive and adaptable framework for dendrochronologists working with large and complex datasets.

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.3

Imports data.table (>= 1.17.8), stringr (>= 1.4.0), stats (>= 4.3.2), mgcv (>= 1.8.0), ggplot2 (>= 3.0.0), nlme (>= 3.0.0), patchwork (>= 1.0.0), terra (>= 1.7-71), raster (>= 3.6-26), furr (>= 0.3.1), future (>= 1.34.0), htmltools (>= 0.5.9), curl (>= 7.0.0), dplyr (>= 1.1.4)

Suggests knitr, geosphere, ggeffects (>= 2.3.0), ggforce (>= 0.4.2), gstat (>= 2.1-3), scales (>= 1.3.0), purrr (>= 1.0.0), parallel (>= 4.3.0), MuMIn (>= 1.48.2), rmarkdown (>= 2.29), rstudioapi (>= 0.16), MASS (>= 7.3-60), sf (>= 1.0-15), sp (>= 2.1.0), spdep (>= 1.3), magick (>= 2.8.6), gt (>= 1.2.0), kableExtra (>= 1.4.0), httr (>= 1.4.7)

Depends R (>= 4.3.0)

VignetteBuilder knitr

NeedsCompilation no

Author Xiao Jing Guo [aut, cre],
 Martin Girardin [aut],
 Juha Metsaranta [aut],
 David Gervais [aut],
 Elizabeth Campbell [aut]

Repository CRAN

Date/Publication 2026-02-12 16:40:10 UTC

Contents

bam_spatial	2
calc_bai	4
CFS_format	5
CFS_freq	6
CFS_mapping	7
CFS_qa	8
CFS_scale	10
ci_resp	11
gamm_radius	12
gamm_site	14
gamm_spatial	15
gam_mod	16
generate_report	18
plot_freq	19
plot_mapping	19
plot_qa	21
plot_resp	22
plot_scale	23
prepare_samples_clim	24
read_rwl	25
sterm_imp	27
Index	28

bam_spatial	<i>spatial growth model for large dataset or vast geographical coverage</i>
-------------	---

Description

To address the computational limitations of GAMMs for large datasets, this function offers a hybrid solution combining the efficiency of the `mgcv::bam()` function

Usage

```
bam_spatial(data, resp_scale = "resp_gamma", m.candidates)
```

Arguments

data	data containing all necessary columns to run the model
resp_scale	Character. Specifies how the response variable is treated in the model. <ul style="list-style-type: none"> • "resp_gaussian": Uses the response on its original scale, assuming a Gaussian distribution with an identity link (no transformation applied). • "resp_log": Log-transforms the response before modelling. The transformed response is then assumed to follow a Gaussian distribution with an identity link. • "resp_gamma": Keeps the response on its original scale, fitted under a Gamma distribution with a log link. Suitable for strictly positive and right-skewed data.
m.candidates	the list of candidate equations.

Details

This function accounts for within-site variability and temporal autocorrelation by including series identity as random effects and a first-order autoregressive (AR1) correlation structures, respectively. Among-site variability and spatial effects are captured by incorporating site identity as random effects. The model is refitted automatically by introducing a smooth term for latitude and longitude using the thin plate ("tp") basis if significant spatial autocorrelation persists. "Normalized" residuals are provided for future analysis.

This function supports parallel computation for the large-scale, geographically distributed datasets.

If users specify multiple candidate models through the m.candidates argument, the function will fit each candidate model using the maximum likelihood (ML) method. The corrected Akaike Information Criterion (AICc) will then be compared to determine the best-fitting model. Once the optimal model is identified, it will be refitted using the restricted maximum likelihood (REML) method and output the results.

If users specify only 1 candidate model through the m.candidates argument, the model is fitted with "REML" method.

Value

list including model, fitting statistics, ptable, stable and prediction table

Examples

```
# loading processed data
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
# climate
dt.clim <- data.table::fread(system.file("extdata", "dt.clim.csv", package = "growthTrendR"))
# pre-data for model
dt.samples_clim <- prepare_samples_clim(dt.samples_trt, dt.clim)
dt.m <- dt.samples_clim[ageC > 1]
# bam_spatial model
m.sp <- bam_spatial(data = dt.m, resp_scale = "resp_log",
  m.candidates = c(
    "bai_cm2 ~ log(ba_cm2_t_1) + s(ageC) + s(FFD)",
```

```
"bai_cm2 ~ log(ba_cm2_t_1) + s(ageC) + FFD",  
"bai_cm2 ~ log(ba_cm2_t_1) + s(ageC)")
```

calc_bai	<i>calculate annual basal area increment</i>
----------	--

Description

calculate basal area (cm2) and basal area increment (cm2)

Usage

```
calc_bai(data)
```

Arguments

data data in long format containing at least 3 columns: id, year, rw

Value

add 3 columns to the original input data, ageC for cambial age, ba_cm2_t_1 for basal area of the previous year in cm2, and bai_cm2 for annual basal area increment in cm2

Examples

```
# generate data  
dt.rw <- data.table::data.table(  
  uid_radius = rep(paste0("R", 1:3), each = 5),  
  year       = rep(2001:2005, times = 3),  
  rw_mm      = round(runif(15, 0.5, 3.5), 2)  
)  
data.table::setorder(dt.rw, uid_radius, year)  
# calculate bai  
dt.rw <- calc_bai(dt.rw)
```

`CFS_format`*Convert tree-ring data into CFS-TRenD format*

Description

converts tree-ring data from various formats into a format compatible with hierarchical structure of the CFS-TRenD data collection (Girardin et al., 2021).

Usage

```
CFS_format(data, usage, out.csv = NULL)
```

Arguments

<code>data</code>	a list, first is input data in wide format; second is a flat sequence referring to the column indices of ring measurement variables
<code>usage</code>	1: for submission data, 2: for cfstrend id structure to perform the analyse
<code>out.csv</code>	output csv file (default is NULL, otherwise to specify the directory to output)

Value

A list of 3 elements: 1) A list containing seven tables compatible with CFS-TRenD data structure; 2) A data table containing all the meta-data and ring width measurement in wide format; 3) A data table for the percentage of completeness of each variable.

References

Girardin, M.P., Guo, X.J., Metsaranta, J., Gervais, D., Campbell, E., Arsenault, A., Isaac-Rentone, M., Harvey, J.E., Bhatti, J., Hogg, E.A. 2021. A national tree-ring repository for Canadian forests (CFS-TRenD): structure, synthesis and applications. *Environmental Reviews*, 29 (999), 1-17. <https://doi.org/10.1139/er-2020-0099>

Examples

```
# ring measurement
dt.samples <- data.table::fread(
  system.file("extdata", "dt.samples.csv", package = "growthTrendR"))
# formatting the users' data conformed to CFS-TRenD data structure
dt.samples_trt <- CFS_format(data = list(dt.samples, 39:68), usage = 1, out.csv = NULL)
# save it to extdata for further use
# saveRDS(dt.samples_trt, file = "inst/extdata/dt.samples_trt.rds")
```

CFS_freq

*frequency distributions by geo-location per species***Description**

frequency distributions by geo-location per species

Usage

```
CFS_freq(
  tr_meta,
  freq.label_data = "",
  freq.uid_level = "uid_radius",
  freq.cutoff_year = -999,
  freq.geo_resolution = NULL
)
```

Arguments

`tr_meta` meta table from function `CFS_format()`

`freq.label_data` description of `tr_meta`

`freq.uid_level` which uid level to count(`uid_project`, `uid_site`, `uid_tree`, `uid_meas`, `uid_sample`, `uid_radius`)

`freq.cutoff_year` cut-off year for a subset which series were recorded on or after

`freq.geo_resolution` resolution of longitude and latitude in degree, default: `c(5,5)`

Value

a data table of counts of uid by latitude-longitude per species

Examples

```
# treated ring measurement
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
# Compute frequency statistics at radius level
dt.freq <- CFS_freq(
  dt.samples_trt$str_all_wide,
  freq.label_data = "demo-samples",
  freq.uid_level = "uid_radius"
)
class(dt.freq)
```

Description

This function performs inverse distance weighting (IDW) interpolation of tree-ring data across a spatial grid, either for all species combined or by individual species. It generates yearly interpolated raster maps over a user-defined extent or the extent of the input data.

Usage

```
CFS_mapping(
  data,
  year.span = c(1801, 2017),
  extent.lim = NULL,
  grid.step = 0.1,
  by.spc = FALSE
)
```

Arguments

<code>data</code>	input in wide format.
<code>year.span</code>	Numeric vector of length 2 giving the range of years to include.
<code>extent.lim</code>	Optional numeric vector defining the spatial extent (c(xmin, xmax, ymin, ymax)). If NULL, the extent is determined from the input data.
<code>grid.step</code>	Numeric value specifying the grid spacing in degrees.
<code>by.spc</code>	Logical; if TRUE, maps are generated by species; if FALSE, all species are combined.

Value

An object of class `cfs_map`, a list of interpolated raster layers by species and year.

Examples

```
# loading processed data
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
cols.meta = c("uid_tree", "uid_site", "longitude", "latitude", "species")
dt.mapping <- dt.samples_trt$tr_all_wide[
  , c(..cols.meta, as.character(1991:1995)), with = FALSE]
results_mapping <- CFS_mapping(dt.mapping, year.span = c(1991:1993))
```

CFS_qa

*Quality assessment: radius alignment***Description**

Performs comprehensive quality assurance analysis for tree-ring crossdating using pairwise cross-correlation functions and iterative chronologies refinement with automatic memory-efficient batch processing.

Usage

```
CFS_qa(
  dt.input,
  qa.label_data = "",
  qa.label_trt = "",
  qa.max_lag = 10,
  qa.max_iter = 100,
  qa.min_nseries = 100,
  qa.blcrit = 0.1,
  qa.mem_target = 0.6
)
```

Arguments

<code>dt.input</code>	A data.table containing tree-ring measurements with required columns: species Character. Species identifier (must be single species) SampleID Character/Integer. Unique sample identifier Year Integer. Year of measurement RawRing Numeric. Raw ring-width measurement RW_trt Numeric. Treated/detrended ring-width series
<code>qa.label_data</code>	Character. Label identifier for the dataset (required)
<code>qa.label_trt</code>	Character. Label identifier for the treatment method (required)
<code>qa.max_lag</code>	Integer. Maximum lag for cross-correlation analysis (default: 10)
<code>qa.max_iter</code>	Integer. Maximum iterations for chronologies refinement (default: 100)
<code>qa.min_nseries</code>	Integer. Minimum number of series required (default: 100)
<code>qa.blcrit</code>	Numeric. Borderline threshold criterion for quasi-pass classification (default: 0.1)
<code>qa.mem_target</code>	Numeric. Proportion of free memory to use for batch processing (0-1, default: 0.6). Higher values use more memory but may be faster.

Details

The function performs a two-step quality assurance process:

Step 1: Pairwise Cross-Correlation

- Computes CCF for all pairs of treated series
- Uses auto-batching to manage memory efficiently
- Identifies initial qualified samples with max CCF at lag 0

Step 2: Iterative chronologies Refinement

- Computes chronologies from qualified samples
- Evaluates each sample by running CCF with the chronologies
- Iteratively refines the qualified samples until convergence

QA Code Classification:

- `pass`: Maximum correlation at lag 0
- `borderline`: Second highest correlation at lag 0 (within threshold)
- `pm1`: Maximum correlation at lag +/- 1 (slight misalignment)
- `highpeak`: Maximum at non-zero lag, >2x second highest
- `fail`: All other cases

Auto-batching: The function automatically determines optimal batch size based on:

- Available system memory
- Number of CPU cores
- Estimated memory per CCF operation
- Safety margins to prevent out-of-memory errors

Value

An object of class `cfs_qa` containing:

dt.ccf data.table with CCF results and QA codes (`qa_code`) for each series

dt.chron data.table with chronologies statistics

dt.stats data.table with summary statistics per radius

dt.plots List of data.tables formatted for plotting (raw and treated series, CCF plots)

qa.parms List of parameters used in the analysis

See Also

[ccf](#) for cross-correlation function

Examples

```

# loading processed data
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
# data processing
dt.samples_long <- prepare_samples_clim(dt.samples_trt, calbai = FALSE)
# rename to the reserved column name
data.table::setnames(dt.samples_long,
c("sample_id", "year", "rw_mm"), c("SampleID", "Year", "RawRing"))
# assign treated series
# users can decide their own treated series
# for rhub::rhub_check() on macos VECTOR_ELT issues
data.table::setorder(dt.samples_long, SampleID, Year)
dt.samples_long$RW_trt <-
  ave(
    as.numeric(dt.samples_long$RawRing),
    dt.samples_long$SampleID,
    FUN = function(x)
      if (length(x) > 1L) c(NA_real_, diff(x)) else NA_real_
  )
# quality check on radius alignment based on the treated series
dt.qa <-CFS_qa(dt.input = dt.samples_long, qa.label_data = "demo-samples",
qa.label_trt = "difference", qa.min_nseries = 5)

```

CFS_scale

*Quality assessment: ring-width measurement at plot level***Description**

Apply a k-nearest neighbors (k-NN) method based on geographic location for the same species. It compares the median tree-ring measurements of a specific site to those of nearby sites

Usage

```

CFS_scale(
  target_site,
  ref_sites,
  scale.label_data_ref = "",
  scale.max_dist_km = 20,
  scale.N_nbs = 10
)

```

Arguments

target_site	data.table with columns uid_site, site_id, species, longitude and latitude
ref_sites	reference sites including species, uid_site, latitude, longitude, uid_radius, year, rw_mm in long format

```

scale.label_data_ref
      description of ref_sites
scale.max_dist_km
      maximum distance to search the neighbors in km
scale.N_nbs
      number of nearest-neighbors (maximum)

```

Value

A data table containing the median ring-width measurements of the involved sites, along with the distances from the specific site

Examples

```

# loading formatted
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
all_sites <- dt.samples_trt$str_all_wide[, .N, by = c("species", "uid_site", "site_id")][, N:=NULL]
dupes <- all_sites[, .N, by = .(species, site_id)][N > 1]
# e.g. taking the target sites
target_site <- all_sites[c(1,2), -"uid_site"]
ref_sites <- merge(
  dt.samples_trt$str_all_wide[,c("species", "uid_site", "site_id",
    "latitude", "longitude", "uid_radius")],
  dt.samples_trt$str_all_long$str_7_ring_widths, by = c("uid_radius"))
dt.scale <- CFS_scale( target_site = target_site, ref_sites = ref_sites,
  scale.label_data_ref = "demo-samples", scale.max_dist_km = 200, scale.N_nbs = 2)

```

ci_resp	<i>Compute prediction and confidence intervals of smooth terms on response scale</i>
---------	--

Description

This function computes predicted values and confidence intervals from a fitted GAM model with a log-link (or other link) and optionally back-transforms predictions to the response scale. Five methods are supported: 1. **delta_link**: classic delta method on the linear predictor (link) scale; back-transformed CI is asymmetric. 2. **delta_resp**: delta method applied directly on the response scale using $\text{Var}[\exp(\eta)] \approx \exp(2\eta) \text{Var}(\eta)$. 3. **bootstrap_link**: parametric bootstrap on the linear predictor; quantiles back-transformed. 4. **bootstrap_resp**: parametric bootstrap on the response scale; quantiles computed after exponentiating. 5. **posterior**: Bayesian posterior simulation using the model covariance matrix; quantiles on response scale.

Usage

```

ci_resp(
  model,
  newdata,
  nboot = 100,

```

```

method = c("posterior", "delta_link", "delta_resp", "bootstrap_link", "bootstrap_resp"),
  level = 0.95
)

```

Arguments

model	A fitted GAM object from <code>mgcv::gam</code> .
newdata	A <code>data.frame</code> containing values at which to predict.
nboot	Integer. Number of bootstrap or posterior samples. Default 1000.
method	Character. One of "delta_link", "delta_resp", "bootstrap_link", "bootstrap_resp", "posterior".
level	Numeric. Confidence level, default 0.95.

Details

References: - Wood, S.N. (2017) *Generalized Additive Models: An Introduction with R*, 2nd Edition*. CRC Press. - Efron, B., & Tibshirani, R. (1993) *An Introduction to the Bootstrap**. Chapman & Hall. - Gelman, A., et al. (2013) *Bayesian Data Analysis*, 3rd Edition*. CRC Press.

Value

A `data.table` with columns: `fit`, `lwr`, `upr`.

Examples

```

# loading processed data
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
# climate
dt.clim <- data.table::fread(system.file("extdata", "dt.clim.csv", package = "growthTrendR"))
# pre-data for model
dt.samples_clim <- prepare_samples_clim(dt.samples_trt, dt.clim)
dt.m <- dt.samples_clim[ageC > 1]
# using gamm_spatial model as an example
m.sp <- gamm_spatial(data = dt.m, resp_scale = "resp_log",
  m.candidates = "bai_cm2 ~ log(ba_cm2_t_1) + s(ageC) + s(FFD)")

dt.m[, uid_site.fac := as.factor(as.character(uid_site))]
dt.ci <- ci_resp(m.sp$model$gam, newdata = dt.m)

```

`gamm_radius`

detrending model on tree-ring width series

Description

models the biological growth trends in individual tree-ring width series using `mgcv::gamm`

gamm_site	<i>growth model at site-level</i>
-----------	-----------------------------------

Description

models the growth trend or climate-growth relationship per site.

Usage

```
gamm_site(data, resp_scale = "resp_gamma", m.candidates)
```

Arguments

data	data containing all necessary columns to run the model
resp_scale	Character. Specifies how the response variable is treated in the model. <ul style="list-style-type: none"> • "resp_gaussian": Uses the response on its original scale, assuming a Gaussian distribution with an identity link (no transformation applied). • "resp_log": Log-transforms the response before modelling. The transformed response is then assumed to follow a Gaussian distribution with an identity link. • "resp_gamma": Keeps the response on its original scale, fitted under a Gamma distribution with a log link. Suitable for strictly positive and right-skewed data.
m.candidates	the list of candidate equations.

Details

This function accounts for within-site variability and temporal autocorrelation by including series identity as random effects and a first-order autoregressive (AR1) correlation structures, respectively. using `mgcv::gamm()`

If users specify multiple candidate models through the `m.candidates` argument, the function will fit each candidate model using the maximum likelihood (ML) method. The corrected Akaike Information Criterion (AICc) will then be compared to determine the best-fitting model. Once the optimal model is identified, it will be refitted using the restricted maximum likelihood (REML) method and output the results.

If users specify only 1 candidate model through the `m.candidates` argument, the model is fitted with "REML" method.

Value

list including model, fitting statistics, `ptable`, `stable` and prediction table

Examples

```

#' @examples
# loading processed data
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
# climate
dt.clim <- data.table::fread(system.file("extdata", "dt.clim.csv", package = "growthTrendR"))
# pre-data for model
dt.samples_clim <- prepare_samples_clim(dt.samples_trt, dt.clim)

dt.m <- dt.samples_clim[uid_site == 1][ageC > 1]

# gamm_site model
m.site <- gamm_site(data = dt.m, resp_scale = "resp_log",
  m.candidates = c(
    "bai_cm2 ~ log(ba_cm2_t_1) + s(ageC) + s(FFD)",
    "bai_cm2 ~ log(ba_cm2_t_1) + s(ageC) + FFD",
    "bai_cm2 ~ log(ba_cm2_t_1) + s(ageC)"))

```

gamm_spatial

spatial growth model at regional-level (multiple sites)

Description

models the growth trend or climate-growth relationship at regional-level with multiple sites

Usage

```
gamm_spatial(data, resp_scale = "resp_gamma", m.candidates)
```

Arguments

data	data containing all necessary columns to run the model
resp_scale	Character. Specifies how the response variable is treated in the model. <ul style="list-style-type: none"> • "resp_gaussian": Uses the response on its original scale, assuming a Gaussian distribution with an identity link (no transformation applied). • "resp_log": Log-transforms the response before modelling. The transformed response is then assumed to follow a Gaussian distribution with an identity link. • "resp_gamma": Keeps the response on its original scale, fitted under a Gamma distribution with a log link. Suitable for strictly positive and right-skewed data.
m.candidates	the list of candidate equations.

Details

This function accounts for within-site variability and temporal autocorrelation by including series identity as random effects and a first-order autoregressive (AR1) correlation structures, respectively. Among-site variability and spatial effects are captured by incorporating site identity as random effects. The model is refitted automatically by introducing a smooth term for latitude and longitude using the thin plate ("tp") basis if significant spatial autocorrelation persists. "Normalized" residuals are provided for future analysis.

If users specify multiple candidate models through the `m.candidates` argument, the function will fit each candidate model using the maximum likelihood (ML) method. The corrected Akaike Information Criterion (AICc) will then be compared to determine the best-fitting model. Once the optimal model is identified, it will be refitted using the restricted maximum likelihood (REML) method and output the results.

If users specify only 1 candidate model through the `m.candidates` argument, the model is fitted with "REML" method.

Value

list including model, fitting statistics, `pstable`, `stable`, prediction table and spatial effect(`morani`)

Examples

```
# loading processed data
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
# climate
dt.clim <- data.table::fread(system.file("extdata", "dt.clim.csv", package = "growthTrendR"))
# pre-data for model
dt.samples_clim <- prepare_samples_clim(dt.samples_trt, dt.clim)
dt.m <- dt.samples_clim[ageC > 1]
# gamm_spatial model
m.sp <- gamm_spatial(data = dt.m, resp_scale = "resp_gamma",
  m.candidates = c(
    "bai_cm2 ~ log(ba_cm2_t_1) + s(ageC) + s(FFD)",
    "bai_cm2 ~ log(ba_cm2_t_1) + s(ageC) + FFD",
    "bai_cm2 ~ log(ba_cm2_t_1) + s(ageC)"))
```

gam_mod

generalized additive model

Description

generalized additive model that captures non-linear relationships between a response variable and predictors using smooth functions, while allowing inclusion of random effects or complex structures.

generate_report *Generate Automated Reports*

Description

Creates HTML reports from various analysis objects using predefined R Markdown templates. The function automatically selects the appropriate template based on the input object's class and renders a comprehensive report with visualizations and analysis results.

Usage

```
generate_report(
  robj,
  data_report.reports_sel = c(1, 2, 3, 4),
  output_file = NULL,
  ...
)
```

Arguments

robj	An R object containing analysis results from functions in this package. The object's class determines which report template is used. Supported classes depend on available templates in the package.
data_report.reports_sel	Numeric vector. Specifies which sections of the data report to include in the output: 1 = project level; 2 = species level; 3 = site level; 4 = radius level. The default is 'c(1, 2, 3, 4)', which includes all sections.
output_file	Character string. Optional path and filename for the output HTML file. If NULL (default), the report is generated with an automatic filename and opened in RStudio viewer.
...	Additional parameters passed to the R Markdown template. Available parameters vary by template type and are filtered to only include those recognized by the selected template.

Value

Invisibly returns the file path of the generated report. The function is primarily called for its side effect of generating the report file.

Examples

```
# loading processed data

dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
# generate data summary report at project level
outfile_data <- tempfile(fileext = ".html")
generate_report(robj = dt.samples_trt, data_report.reports_sel = c(1), output_file = outfile_data)
```

plot_freq	<i>plot frequency distribution by geo-location per species</i>
-----------	--

Description

This function plots the frequency distribution by geo-location for each species

Usage

```
plot_freq(dt.freq, out.species = "all")
```

Arguments

dt.freq	a table with class "cfs_freq", resulting from function CFS_freq()
out.species	species list, default is 'all' to output the frequency distribution for all species

Value

A list of ggplot objects corresponding to the species requested via out.species. Each element of the list contains a faceted spatial plot of tree locations, with point size proportional to the number of samples.

Examples

```
# loading processed data
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
dt.freq <- CFS_freq(
  dt.samples_trt$tr_all_wide,
  freq.label_data = "demo-samples",
  freq.uid_level = "uid_radius")

plots.lst <- plot_freq(dt.freq)
```

plot_mapping	<i>Plot spatially interpolated tree-ring growth maps</i>
--------------	--

Description

Visualizes spatial interpolation results produced by [CFS_mapping](#) and optionally exports raster files, static maps, and animations.

Usage

```
plot_mapping(
  mapping_results,
  crs.src = "EPSG:4326",
  parms.out = c("csv", "tif", "png", "gif"),
  dir.shp = NULL,
  dir.out = NULL,
  animation_fps = 1,
  ...
)
```

Arguments

mapping_results	A list returned by CFS_mapping containing spatially interpolated rasters by species and year.
crs.src	Coordinate Reference System of the input data, specified as a string in the format 'EPSG:<ID>' (for example, 'EPSG:4326'). The function will stop with an error if 'crs.src' is not provided in this format.
parms.out	Character vector indicating output formats to generate. Supported values are "csv", "tif", "png", and "gif".
dir.shp	Character or NULL. Path to the folder containing shapefiles for cropping data to the Canadian boreal regions. Only used for specific research purposes; if NULL (default), no cropping is applied and all data are included.
dir.out	Output directory used to save generated files. Required when parms.out is not empty.
animation_fps	Frames per second used when creating GIF animations.
...	Additional arguments passed to plot_tree_ring_map , such as png.text.

Details

This function assumes that spatial interpolation has already been performed using [CFS_mapping](#). The input object is iterated by species and year to generate maps and optional exports.

When "gif" is requested in parms.out, yearly PNG images are combined into animated GIFs.

Value

A magick-image object representing an animated GIF composed of the generated frames.

See Also

[CFS_mapping](#)

Examples

```

# Load processed demo data
dt.samples_trt <- readRDS(
  system.file("extdata", "dt.samples_trt.rds",
             package = "growthTrendR")
)
# prepare data for IDW model
cols.meta = c("uid_tree", "uid_site", "longitude", "latitude", "species")
dt.mapping <- dt.samples_trt$str_all_wide[
  , c(..cols.meta, as.character(1991:1995)), with = FALSE]

# Run spatial interpolation
mapping_results <- CFS_mapping(
  dt.mapping,
  year.span = c(1991, 1993)
)

# generate png plots
img_ani <- plot_mapping(
  mapping_results = mapping_results,
  parms.out = NULL,
  dir.shp = NULL,
  dir.out = NULL,
  png.text = list(
    text_top = "Ring width measurement - ",
    text_bott = "Source: demo-samples",
    text_side = "ring width (mm)"
  )
)

```

plot_qa

plotting quality assessment per radius

Description

Plotting the time series and cross-correlation to contrast each radius with the chronologies, using both raw ring-width measurements and treated series.

Usage

```
plot_qa(qa.trt, qa.out_series = "all")
```

Arguments

qa.trt object "cfs_qa" from CFS_qa() function.
qa.out_series series_id list to be plotted, default "all" for plotting the graphs for all.

Value

A named list of tree-ring series, where each element corresponds to a series requested via `qa.out_series`. Each element is itself a list containing four ggplot objects:

plot.raw.series Raw tree-ring series vs year.

plot.trt.series Treated (detrended/standardized) series vs year.

plot.raw.ccf Cross-correlation function of the raw series.

plot.trt.ccf Cross-correlation function of the treated series.

Examples

```
# loading processed data
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
# data processing
dt.samples_long <- prepare_samples_clim(
  dt.samples_trt = dt.samples_trt, calbai = FALSE )
# rename to the reserved column name
data.table::setnames(
  dt.samples_long,
  c("sample_id", "year", "rw_mm"),
  c("SampleID", "Year", "RawRing"))
# assign treated series
# users can decide their own treated series

# for rhub::rhub_check() on macos VECTOR_ELT issues
data.table::setorder(dt.samples_long, SampleID, Year)
dt.samples_long$RW_trt <-
  ave(
    as.numeric(dt.samples_long$RawRing),
    dt.samples_long$SampleID,
    FUN = function(x)
      if (length(x) > 1L) c(NA_real_, diff(x)) else NA_real_
  )
# quality check on radius alignment based on the treated series
dt.qa <-CFS_qa(dt.input = dt.samples_long, qa.label_data = "demo-samples",
  qa.label_trt = "difference", qa.min_nseries = 5)
plots.lst <- plot_qa(dt.qa, qa.out_series = "X003_101_005")
```

Description

This function generates ggplot objects for each smooth term in a GAM model. Predictions vary one smooth term at a time, keeping all other terms fixed at reference values. Confidence intervals are computed using `ci_resp()`, supporting multiple methods: "delta_link", "delta_resp", "bootstrap_link", "bootstrap_resp", and "posterior". Small samples automatically trigger the "posterior" method for more robust CIs.

Usage

```
plot_resp(robj, ...)
```

Arguments

`robj` R object from the modelling functions.
`...` Additional arguments passed to `ci_resp()`.

Value

A list of ggplot objects, one per smooth term.

Examples

```
# loading processed data
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
# climate
dt.clim <- data.table::fread(system.file("extdata", "dt.clim.csv", package = "growthTrendR"))
# pre-data for model
dt.samples_clim <- prepare_samples_clim(dt.samples_trt, dt.clim)
dt.m <- dt.samples_clim[ageC > 1]
# gamm_site model
m.spatial <- gamm_spatial(
  data = dt.m, resp_scale = "resp_log",
  m.candidates = c("bai_cm2 ~ log(ba_cm2_t_1) + s(ageC) + s(FFD)")
)
plots.lst <- plot_resp(m.spatial)
```

plot_scale

plot median of ring width of the target site and its neighbours

Description

This function plots the time series and the geographical distribution of the median ring-width measurements to contrast the target site with its neighbouring sites.

Usage

```
plot_scale(dt.scale)
```

Arguments

`dt.scale` a table with class "cfs_scale", resulting from function `CFS_scale()`

Value

A named list with two ggplot objects showing the contrast between the target site and its neighboring sites:

plot.year A time-series plot of median ring width by year.

plot.ll A spatial plot showing the geographic location of the sites, with point size proportional to the magnitude of site-level ring-width measurements.

Examples

```
# loading formatted
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
all_sites <- dt.samples_trt$tr_all_wide[, .N, by = c("species", "uid_site", "site_id")][, N:=NULL]
# e.g. taking the target sites
target_site <- all_sites[c(1,2), -"uid_site"]
ref_sites <- merge(
  dt.samples_trt$tr_all_wide[, c("species", "uid_site", "site_id",
    "latitude", "longitude", "uid_radius")],
  dt.samples_trt$tr_all_long$tr_7_ring_widths, by = c("uid_radius"))
dt.scale <- CFS_scale( target_site = target_site, ref_sites = ref_sites,
  scale.label_data_ref = "demo-samples", scale.max_dist_km = 200, scale.N_nbs = 2)
plots.lst <- plot_scale(dt.scale[[1]])
```

prepare_samples_clim *Prepare tree-ring data for downstream analysis*

Description

This function prepares tree-ring data including ring-width measurements, and optionally computes basal area increment (BAI) and merges climate variables.

Usage

```
prepare_samples_clim(dt.samples_trt, dt.clim = NULL, calbai = TRUE)
```

Arguments

`dt.samples_trt` A list of tree-ring data formatted by `CFS_format()`.

`dt.clim` An optional data frame containing climate variables, joined by `site_id` and year. Default is `NULL`.

`calbai` Logical. If `TRUE`, basal area increment (BAI) is computed. Default is `TRUE`.

Value

A data frame or data.table containing tree-ring measurements, optionally including basal area increment and merged climate variables.

Examples

```
# loading processed data
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
# climate
dt.clim <- data.table::fread(system.file("extdata", "dt.clim.csv", package = "growthTrendR"))
# pre-data for model
dt.samples_clim <- prepare_samples_clim(dt.samples_trt, dt.clim)
```

read_rwl

Import raw ring-width measurements from the ITRDB

Description

Import raw ring-width measurements from the ITRDB

Usage

```
read_rwl(dir.src, rwl)
```

Arguments

dir.src	Character string specifying the directory path or URL where the RWL file is located. Users typically provide a local directory containing a user-downloaded ITRDB file, but an online source may also be used.
rwl	Character string giving the file name of the RWL file.

Details

The International Tree-Ring Data Bank (ITRDB) is maintained by the NOAA National Centers for Environmental Information (NCEI) as part of the World Data Service for Paleoclimatology. See: <https://www.ncei.noaa.gov/products/paleoclimatology/tree-ring>

Raw ring-width measurement files (‘.rwl’) distributed through the ITRDB follow the *Tucson fixed-width format*. In this convention, header records encode site-level metadata (e.g., site identifier, site name, species code, geographic information, and temporal coverage), followed by ring-width measurements stored in a decadal layout (ten annual values per line).

Record 1

- Columns 1–6: Site ID
- Columns 10–61: Site name
- Columns 62–65: Species code
- Optional ID fields

Record 2

- Columns 1–6: Site ID
- Columns 10–22: State / country
- Columns 23–30: Species
- Columns 41–45: Elevation
- Columns 48–57: Latitude–longitude
- Columns 62–63: Measurement type code
- Columns 68–76: First and last year

Latitude–longitude values are expressed in degrees and minutes ('ddmm' or 'dddmm').

Record 3

- Columns 1–6: Site ID
- Columns 10–72: Investigators
- Columns 73–80: Optional completion date

Value

A list with two elements:

- header: a table containing site-level metadata
- rwl: a table containing raw ring-width measurements

Examples

```
## Online example (not run to avoid timeout and internet dependency)

dir.src <- "https://www.ncei.noaa.gov/pub/data/paleo/treering/measurements/northamerica/canada"
rwl <- "cana615.rwl"
dt.rwl <- read_rwl(dir.src, rwl)

## Local example using packaged data
file <- system.file("extdata", "cana615.rwl", package = "growthTrendR")
stopifnot(file != "")
dir.src <- dirname(file)
rwl <- basename(file)
dt.rwl <- read_rwl(dir.src, rwl)
```

stern_imp	<i>variable importance of smooth terms in a GAM model</i>
-----------	---

Description

Evaluates the relative influence of each smooth term in a GAM model by computing its contribution to the fitted values using the linear predictor matrix (type = "lpmatrix"). Three summary methods are available: sum of squares, variance, and mean absolute value across all observations. #'

Usage

```
stern_imp(gam_model, method = c("ssq", "var", "meanabs"))
```

Arguments

gam_model	A GAM model object.
method	A character string specifying the method to compute importance. One of "ssq", "var", or "meanabs".

Value

A data.table with columns:

var Name of the smooth term.

importance_pct Relative importance as a percentage.

method The method used for calculating the importance.

Examples

```
# loading processed data
dt.samples_trt <- readRDS(system.file("extdata", "dt.samples_trt.rds", package = "growthTrendR"))
# climate
dt.clim <- data.table::fread(system.file("extdata", "dt.clim.csv", package = "growthTrendR"))
# pre-data for model
dt.samples_clim <- prepare_samples_clim(dt.samples_trt, dt.clim)
dt.m <- dt.samples_clim[ageC > 1]
# using gamm_spatial model as an example
m.sp <- gamm_spatial(data = dt.m, resp_scale = "resp_log",
  m.candidates = "bai_cm2 ~ log(ba_cm2_t_1) + s(ageC) + s(FFD)")

dt.m[, uid_site.fac := as.factor(as.character(uid_site))]
dt.imp <- stern_imp(m.sp$model$gam)
```

Index

`bam_spatial`, 2

`calc_bai`, 4

`ccf`, 9

`CFS_format`, 5

`CFS_freq`, 6

`CFS_mapping`, 7, 19, 20

`CFS_qa`, 8

`CFS_scale`, 10

`ci_resp`, 11

`gam_mod`, 16

`gamm_radius`, 12

`gamm_site`, 14

`gamm_spatial`, 15

`generate_report`, 18

`plot_freq`, 19

`plot_mapping`, 19

`plot_qa`, 21

`plot_resp`, 22

`plot_scale`, 23

`prepare_samples_clim`, 24

`read_rwl`, 25

`sterm_imp`, 27