

Package ‘growthcleanr’

May 9, 2026

Type Package

Title Data Cleaner for Anthropometric Measurements

Version 2.2.3

Description Identifies implausible anthropometric (e.g., height, weight) measurements in irregularly spaced longitudinal datasets, such as those from electronic health records.

URL <https://carriedaymont.github.io/growthcleanr/index.html>,
<https://github.com/carriedaymont/growthcleanr>

BugReports <https://github.com/carriedaymont/growthcleanr/issues>

Imports R.utils (>= 2.11.0), data.table (>= 1.13.0), tidyr (>= 1.1.0),
plyr (>= 1.8.6), dplyr (>= 1.0.1), foreach (>= 1.5.0),
doParallel (>= 1.0.15), labelled (>= 2.5.0), magrittr (>= 1.5),
rlang (>= 0.4.0)

Depends R (>= 2.10)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Suggests argparser (>= 0.6), bit64 (>= 4.0.2), knitr (>= 1.29),
rmarkdown (>= 2.3), testthat (>= 2.3.2)

RoxygenNote 7.3.3

NeedsCompilation no

Author Carrie Daymont [ctb, cre],
Robert Grundmeier [aut],
Jeffrey Miller [aut],
Diego Campos [aut],
Dan Chudnov [ctb],
Hannah De los Santos [ctb],
Lusha Cao [ctb],
Steffani Silva [ctb],
Hanzhe Zhang [ctb],
Matt Boyas [ctb],

David Freedman [ctb],
 Andreas Achilleos [ctb],
 Jessica Butts [ctb],
 Sheila Nguyen [ctb],
 Taraneh Soleymani [ctb],
 Max Olivier [ctb]

Maintainer Carrie Daymont <cdaymont@pennstatehealth.psu.edu>

Repository CRAN

Date/Publication 2026-05-09 15:20:02 UTC

Contents

acf_answers	3
adjustcarryforward	4
bmianthro	6
CDCref_d	7
cleangrowth	7
ewma	11
ext_bmiz	12
growth_cdc_ext	14
growth_cdc_ext_infants	14
growth_who_ext	15
lenanthro	15
longwide	16
nhanes-reference-medians	17
rc-reference-medians	18
read_anthro	18
recode_sex	19
ref_for_corraga	20
ref_for_corrz	20
sd_median	20
simple_bmi	21
splitinput	22
syngrowth	23
tanner_ht_vel	24
tanner_ht_vel_rev	24
tanner_ht_vel_with_2sd	25
testacf	25
test_syngrowth_sas_output_compare	26
test_syngrowth_wide	27
weianthro	27
who_hc_maxvel	27
who_hc_vel_3sd	28
who_ht_maxvel	28
who_ht_maxvel_2sd	28
who_ht_vel_2sd	29
who_ht_vel_3sd	29

acf_answers *Answers for adjustcarryforward*

Description

Determines what should absolutely be reincluded or definitely excluded for a given dataset, already run through cleangrowth.

Usage

```
acf_answers(
  subjid,
  param,
  agedays,
  sex,
  measurement,
  orig.exclude,
  sd.recenter = NA,
  ewma.exp = -1.5,
  ref.data.path = "",
  quietly = TRUE
)
```

Arguments

subjid	Vector of unique identifiers for each subject in the database.
param	Vector identifying each measurement, may be 'WEIGHTKG', 'HEIGHTCM', or 'LENGTHCM' vs. 'HEIGHTCM' only affects z-score calculations between ages 24 to 35 months (730 to 1095 days). All linear measurements below 731 days of life (age 0-23 months) are interpreted as supine length, and all linear measurements above 1095 days of life (age 36+ months) are interpreted as standing height. Note: at the moment, all LENGTHCM will be converted to HEIGHTCM. In the future, the algorithm will be updated to consider this difference.
agedays	Numeric vector containing the age in days at each measurement.
sex	Vector identifying the gender of the subject, may be 'M', 'm', or 0 for males, vs. 'F', 'f' or 1 for females.
measurement	Numeric vector containing the actual measurement data. Weight must be in kilograms (kg), and linear measurements (height vs. length) in centimeters (cm).
orig.exclude	Vector of exclusion assessment results from cleangrowth()
sd.recenter	Data frame or table with median SD-scores per day of life

<code>ewma.exp</code>	Exponent to use for weighting measurements in the exponentially weighted moving average calculations. Defaults to -1.5. This exponent should be negative in order to weight growth measurements closer to the measurement being evaluated more strongly. Exponents that are further from zero (e.g. -3) will increase the relative influence of measurements close in time to the measurement being evaluated compared to using the default exponent.
<code>ref.data.path</code>	Path to reference data. If not supplied, the year 2000 Centers for Disease Control (CDC) reference data will be used.
<code>quietly</code>	Determines if function messages are to be displayed and if log files (parallel only) are to be generated. Defaults to TRUE.

Value

A data frame, containing an index "n" of rows, corresponding to the original order of the input vectors, and "acf_answers", containing the answers on whether a height value should be kept or excluded (returns "Definitely Exclude", "Definitely Include", or "Unknown" for height values, NA for weight values).

<code>adjustcarryforward</code>	<i>adjustcarryforward</i> <code>adjustcarryforward</code> <i>Uses absolute height velocity to identify values excluded as carried forward values for reinclusion.</i>
---------------------------------	---

Description

`adjustcarryforward` `adjustcarryforward` *Uses absolute height velocity to identify values excluded as carried forward values for reinclusion.*

Usage

```
adjustcarryforward(
  subjid,
  param,
  agedays,
  sex,
  measurement,
  orig.exclude,
  exclude_opt = 0,
  sd.recenter = NA,
  ewma.exp = -1.5,
  ref.data.path = "",
  quietly = TRUE,
  minfactor = 0.5,
  maxfactor = 2,
  banddiff = 3,
  banddiff_plus = 5.5,
  min_ht.exp_under = 2,
```

```

    min_ht.exp_over = 0,
    max_ht.exp_under = 0.33,
    max_ht.exp_over = 1.5
)

```

Arguments

subjid	Vector of unique identifiers for each subject in the database.
param	Vector identifying each measurement, may be 'WEIGHTKG', 'HEIGHTCM', or 'LENGTHCM' 'HEIGHTCM' vs. 'LENGTHCM' only affects z-score calculations between ages 24 to 35 months (730 to 1095 days). All linear measurements below 731 days of life (age 0-23 months) are interpreted as supine length, and all linear measurements above 1095 days of life (age 36+ months) are interpreted as standing height. Note: at the moment, all LENGTHCM will be converted to HEIGHTCM. In the future, the algorithm will be updated to consider this difference.
agedays	Numeric vector containing the age in days at each measurement.
sex	Vector identifying the gender of the subject, may be 'M', 'm', or 0 for males, vs. 'F', 'f' or 1 for females.
measurement	Numeric vector containing the actual measurement data. Weight must be in kilograms (kg), and linear measurements (height vs. length) in centimeters (cm).
orig.exclude	Vector of exclusion assessment results from cleangrowth()
exclude_opt	Number from 0 to 3 indicating which option to use to handle strings of carried-forwards: 0. no change. <ol style="list-style-type: none"> 1. when deciding to exclude values, if we have a string of carried forwards, drop the most deviant value, and all CFs in the same string, and move on as normal. 2. when deciding to exclude values, if the most deviant in a string of carried forwards is flagged, check all the CFs in that string from 1:N. Exclude all after the first that is flagged for exclusion when comparing to the Include before and after. Do not remove things designated as include. 3. when deciding to exclude values, if the most deviant in a string of carried forwards is flagged, check all the CFs in that string from 1:N. Exclude all after the first that is flagged for exclusion when comparing to the Include before and after. Make sure remove things designated as include.
sd.recenter	Data frame or table with median SD-scores per day of life
ewma.exp	Exponent to use for weighting measurements in the exponentially weighted moving average calculations. Defaults to -1.5. This exponent should be negative in order to weight growth measurements closer to the measurement being evaluated more strongly. Exponents that are further from zero (e.g. -3) will increase the relative influence of measurements close in time to the measurement being evaluated compared to using the default exponent.
ref.data.path	Path to reference data. If not supplied, the year 2000 Centers for Disease Control (CDC) reference data will be used.
quietly	Determines if function messages are to be displayed and if log files (parallel only) are to be generated. Defaults to TRUE.

minfactor	Sweep variable for computing mindiff.next.ht in 15f, default 0.5
maxfactor	Sweep variable for computing maxdiff.next.ht in 15f, default 2
banddiff	Sweep variable for computing mindiff.next.ht in 15f, default 3
banddiff_plus	Sweep variable for computing maxdiff.next.ht in 15, default 5.5
min_ht.exp_under	
	Sweep variable for computing ht.exp in 15f, default 2
min_ht.exp_over	
	Sweep variable for computing ht.exp in 15f, default 0
max_ht.exp_under	
	Sweep variable for computing ht.exp in 15f, default 0.33
max_ht.exp_over	
	Sweep variable for computing ht.exp in 15f, default 1.5

Value

Re-evaluated exclusion assessments based on height velocity.

Examples

```
# Run on a small subset of given data
df <- as.data.frame(syngrowth)
df <- df[df$subjid %in% unique(df[, "subjid"])[1:2], ]
clean_df <- cbind(df,
                  "gcr_result" = cleangrowth(df$subjid,
                                             df$param,
                                             df$agedays,
                                             df$sex,
                                             df$measurement))

# Adjust carry forward values in cleaned data
adj_clean <- adjustcarryforward(subjid = clean_df$subjid,
                               param = clean_df$param,
                               agedays = clean_df$agedays,
                               sex = clean_df$sex,
                               measurement = clean_df$measurement,
                               orig.exclude = clean_df$gcr_result)
```

bmianthro

BMI Anthro

Description

Part of default CDC-derived tables

Details

Contains BMI data for calculating BMI

bmianthro.txt.gz

Used in function cleangrowth()

CDCref_d	<i>CDC BMI reference data</i>
----------	-------------------------------

Description

Used for extended BMIz computation

CDCref_d.csv.gz

Used for extended BMI computation

cleangrowth	<i>Clean growth measurements</i>
-------------	----------------------------------

Description

Clean growth measurements

Usage

```
cleangrowth(
  subjid,
  param,
  agedays,
  sex,
  measurement,
  recover.unit.error = FALSE,
  sd.extreme = 25,
  z.extreme = 25,
  lt3.exclude.mode = "default",
  height.tolerance.cm = 2.5,
  error.load.mincount = 2,
  error.load.threshold = 0.5,
  sd.recenter = NA,
  sdmedian.filename = "",
  sdrecentered.filename = "",
  include.carryforward = FALSE,
  ewma.exp = -1.5,
  ref.data.path = "",
  log.path = NA,
  parallel = FALSE,
  num.batches = NA,
```

```

quietly = TRUE,
adult_cutpoint = 20,
weight_cap = Inf,
adult_columns_filename = "",
prelim_infants = FALSE
)

```

Arguments

subjid	Vector of unique identifiers for each subject in the database.
param	Vector identifying each measurement, may be 'WEIGHTKG', 'WEIGHTLBS', 'HEIGHTCM', 'HEIGHTIN', 'LENGTHCM', or 'HEADCM'. 'HEIGHTCM'/'HEIGHTIN' vs. 'LENGTHCM' only affects z-score calculations between ages 24 to 35 months (730 to 1095 days). All linear measurements below 731 days of life (age 0-23 months) are interpreted as supine length, and all linear measurements above 1095 days of life (age 36+ months) are interpreted as standing height. Note: at the moment, all LENGTHCM will be converted to HEIGHTCM. In the future, the algorithm will be updated to consider this difference. Additionally, imperial 'HEIGHTIN' and 'WEIGHTLBS' measurements are converted to metric during algorithm calculations.
agedays	Numeric vector containing the age in days at each measurement.
sex	Vector identifying the gender of the subject, may be 'M', 'm', or 0 for males, vs. 'F', 'f' or 1 for females.
measurement	Numeric vector containing the actual measurement data. Weight must be in kilograms (kg), and linear measurements (height vs. length) in centimeters (cm).
recover.unit.error	Indicates whether the cleaning algorithm should attempt to identify unit errors (I.e. inches vs. cm, lbs vs. kg). If unit errors are identified, the value will be corrected and retained within the cleaning algorithm as a valid measurement. Defaults to FALSE.
sd.extreme	Measurements more than sd.extreme standard deviations from the mean (either above or below) will be flagged as invalid. Defaults to 25.
z.extreme	Measurements with an absolute z-score greater than z.extreme will be flagged as invalid. Defaults to 25.
lt3.exclude.mode	Determines type of exclusion procedure to use for 1 or 2 measurements of one type without matching same ageday measurements for the other parameter. Options include "default" (standard growthcleanr approach), and "flag.both" (in case of two measurements of one type without matching values for the other parameter, flag both for exclusion if beyond threshold)
height.tolerance.cm	maximum decrease in height tolerated for sequential measurements
error.load.mincount	minimum count of exclusions on parameter before considering excluding all measurements. Defaults to 2.

<code>error.load.threshold</code>	threshold of percentage of excluded measurement count to included measurement count that must be exceeded before excluding all measurements of either parameter. Defaults to 0.5.
<code>sd.recenter</code>	<p>specifies how to recenter medians. May be a data frame or table w/median SD-scores per day of life by gender and parameter, or "NHANES" or "derive" as a character vector.</p> <ul style="list-style-type: none"> • If <code>sd.recenter</code> is specified as a data set, use the data set • If <code>sd.recenter</code> is specified as "nhanes", use NHANES reference medians • If <code>sd.recenter</code> is specified as "derive", derive from input • If <code>sd.recenter</code> is not specified or NA: <ul style="list-style-type: none"> – If the input set has at least 5,000 observations, derive medians from input – If the input set has fewer than 5,000 observations, use NHANES <p>If specifying a data set, columns must include <code>param</code>, <code>sex</code>, <code>agedays</code>, and <code>sd.median</code> (referred to elsewhere as "modified Z-score"), and those medians will be used for recentering. A summary of how the NHANES reference medians were derived is available in <code>README.md</code>. Defaults to NA.</p>
<code>sdmedian.filename</code>	Name of file to save <code>sd.median</code> data calculated on the input dataset to as CSV. Defaults to "", for which this data will not be saved. Use for extracting medians for parallel processing scenarios other than the built-in parallel option.
<code>sdrecentered.filename</code>	Name of file to save re-centered data to as CSV. Defaults to "", for which this data will not be saved. Useful for post-processing and debugging.
<code>include.carryforward</code>	Determines whether Carry-Forward values are kept in the output. Defaults to False.
<code>ewma.exp</code>	Exponent to use for weighting measurements in the exponentially weighted moving average calculations. Defaults to -1.5. This exponent should be negative in order to weight growth measurements closer to the measurement being evaluated more strongly. Exponents that are further from zero (e.g. -3) will increase the relative influence of measurements close in time to the measurement being evaluated compared to using the default exponent.
<code>ref.data.path</code>	Path to reference data. If not supplied, the year 2000 Centers for Disease Control (CDC) reference data will be used.
<code>log.path</code>	Path to log file output when running in parallel (non-quiet mode). Default is NA. A new directory will be created if necessary. Set to NA to disable log files.
<code>parallel</code>	Determines if function runs in parallel. Defaults to FALSE.
<code>num.batches</code>	Specify the number of batches to run in parallel. Only applies if <code>parallel</code> is set to TRUE. Defaults to the number of workers returned by the <code>getDoParWorkers</code> function in the <code>foreach</code> package.
<code>quietly</code>	Determines if function messages are to be displayed and if log files (parallel only) are to be generated. Defaults to TRUE

<code>adult_cutpoint</code>	Number between 18 and 20, describing ages when the pediatric algorithm should not be applied ($<$ <code>adult_cutpoint</code>), and the adult algorithm should apply (\geq <code>adult_cutpoint</code>). Numbers outside this range will be changed to the closest number within the range. Defaults to 20.
<code>weight_cap</code>	Positive number, describing a weight cap in kg (rounded to the nearest .1, +/- .1) within the adult dataset. If there is no weight cap, set to Inf. Defaults to Inf.
<code>adult_columns_filename</code>	Name of file to save original adult data, with additional output columns to as CSV. Defaults to "", for which this data will not be saved. Useful for post-analysis. For more information on this output, please see README.
<code>prelim_infants</code>	TRUE/FALSE. Run the in-development release of the infants algorithm (expands pediatric algorithm to improve performance for children 0 – 2 years). Not recommended for use in research. For more information regarding the logic of the algorithm, see the vignette 'Preliminary Infants Algorithm.' Defaults to FALSE.

Value

Vector of exclusion codes for each of the input measurements.

Possible values for each code are:

- 'Include', 'Unit-Error-High', 'Unit-Error-Low', 'Swapped-Measurements', 'Missing',
- 'Exclude-Carried-Forward', 'Exclude-SD-Cutoff', 'Exclude-EWMA-Extreme', 'Exclude-EWMA-Extreme-Pair',
- 'Exclude-Extraneous-Same-Day',
- 'Exclude-EWMA-8', 'Exclude-EWMA-9', 'Exclude-EWMA-10', 'Exclude-EWMA-11', 'Exclude-EWMA-12', 'Exclude-EWMA-13', 'Exclude-EWMA-14',
- 'Exclude-Min-Height-Change', 'Exclude-Max-Height-Change',
- 'Exclude-Pair-Delta-17', 'Exclude-Pair-Delta-18', 'Exclude-Pair-Delta-19',
- 'Exclude-Single-Outlier', 'Exclude-Too-Many-Errors', 'Exclude-Too-Many-Errors-Other-Parameter'

Examples

```
# Run calculation using a small subset of given data
df_stats <- as.data.frame(syngrowth)
df_stats <- df_stats[df_stats$subjid %in% unique(df_stats[, "subjid"])[1:5], ]

clean_stats <- cleangrowth(subjid = df_stats$subjid,
                          param = df_stats$param,
                          agedays = df_stats$agedays,
                          sex = df_stats$sex,
                          measurement = df_stats$measurement)

# Once processed you can filter data based on result value
df_stats <- cbind(df_stats, "clean_result" = clean_stats)
clean_df_stats <- df_stats[df_stats$clean_result == "Include",]
```

```
# Parallel processing: run using 2 cores and batches
clean_stats <- cleangrowth(subjid = df_stats$subjid,
                          param = df_stats$param,
                          agedays = df_stats$agedays,
                          sex = df_stats$sex,
                          measurement = df_stats$measurement,
                          parallel = TRUE,
                          num.batches = 2)
```

ewma

Exponentially Weighted Moving Average (EWMA)

Description

ewma calculates the exponentially weighted moving average (EWMA) for a set of numeric observations over time.

Usage

```
ewma(agedays, z, ewma.exp, ewma.adjacent = TRUE)
```

Arguments

agedays	Vector of age in days for each z score (potentially transformed to adjust weighting).
z	Input vector of numeric z-score data.
ewma.exp	Exponent to use for weighting.
ewma.adjacent	Specify whether EWMA values excluding adjacent measurements should be calculated. Defaults to TRUE.

Value

Data frame with 3 variables:

- The first variable (ewma.all) contains the EWMA at observation time excluding only the actual observation for that time point.
- The second variable (ewma.before) contains the EWMA for each observation excluding both the actual observation and the immediate prior observation.
- The third variable (ewma.after) contains the EWMA for each observation excluding both the actual observation and the subsequent observation.

Examples

```
# Run on 1 subject, 1 type of parameter
df_stats <- as.data.frame(syngrowth)
df_stats <- df_stats[df_stats$subjid == df_stats$subjid[1] &
                    df_stats$param == "HEIGHTCM", ]

# Get the uncentered z-scores
measurement_to_z <- read_anthro(cdc.only = TRUE)
sd <- measurement_to_z(df_stats$param,
                      df_stats$agedays,
                      df_stats$sex,
                      df_stats$measurement,
                      TRUE)

# Calculate exponentially weighted moving average
e_df <- ewma(df_stats$agedays, sd, ewma.exp = -1.5)
```

 ext_bmix

Calculate extended BMI measures

Description

ext_bmix Calculates the sigma (scale parameter for the half-normal distribution), extended BMI percentile, extended BMIz, and the CDC LMS Z-scores for weight, height, and BMI for children between 2 and 19.9 years of age. Note that for BMIs \leq 95th percentile of the CDC growth charts, the extended values for BMI are equal to the LMS values. The extended values differ only for children who have a BMI $>$ 95th percentile.

Usage

```
ext_bmix(
  data,
  age = "agem",
  wt = "wt",
  ht = "ht",
  bmi = "bmi",
  adjust.integer.age = TRUE,
  ref.data.path = ""
)
```

Arguments

data	Input data frame or data table
age	Name of input column containing subject age in months in quotes, default "agem"
wt	Name of input column containing weight (kg) value in quotes, default "wt"
ht	Name of input column containing height (cm) value in quotes, default "ht"
bmi	Name of input column containing calculated BMI in quotes, default "bmi"

adjust.integer.age If age inputs are all integer, add 0.5 if TRUE; default TRUE
 ref.data.path Path to directory containing reference data

Details

This function should produce output equivalent to the SAS macro provided at <https://www.cdc.gov/growth-chart-training/hcp/computer-programs/sas.html>. The macro was updated in December, 2022, according to the findings of the NCHS report available at <https://dx.doi.org/10.15620/cdc:121711>. This function has been updated to match it as of growthcleanr v2.1.0.

The extended BMIz is the inverse cumulative distribution function (CDF) of the extended BMI percentile. If the extended percentile is very close to 100, the qnorm function in R produces an infinite value. This occurs only if the the extended BMI percentile is > 99.99999999999999 . This occurs infrequently, such as a 48-month-old with a BMI > 39 , and it is likely that these BMIs represent data entry errors. For these cases, extended BMIz is set to 8.21, a value that is slightly greater than the largest value that can be calculated.

See the README.md file for descriptions of the output columns generated by this function.

data must have columns for at least age, sex, weight, height, and bmi.

age should be coded in months, using the most precise values available. To convert to months from age in years, multiply by 12. To convert to months from age in days, divide by 30.4375 (365.25 / 12).

sex is coded as 1, boys, Boys, b, B, males, Males, m, or M for male subjects or 2, girls, Girls, g, G, females, Females, f, or F for female subjects. Note that this is different from cleangrowth, which uses 0 (Male) and 1 (Female).

wt should be in kilograms.

ht should be in centimeters.

Specify the input data parameter names for age, wt, ht, bmi using quotation marks. See example below.

If the parameter adjust.integer.age is TRUE (the default), 0.5 will be added to all age if all input values are integers. Set to FALSE to disable.

By default, the reference data file CDCref_d.csv, made available at <https://www.cdc.gov/growth-chart-training/hcp/computer-programs/sas.html>, is included in this package for convenience. If you are developing this package, use ref.data.path to adjust the path to this file from your working directory if necessary.

Value

Expanded data frame containing computed BMI values

Examples

```
# Run on a small subset of given data
df <- as.data.frame(syngrowth)
df <- df[df$subjid %in% unique(df[, "subjid"])[1:5], ]
df <- cbind(df,
            "gcr_result" = cleangrowth(df$subjid,
```

```

df$param,
df$agedays,
df$sex,
df$measurement))
df_wide <- longwide(df) # convert to wide format for ext_bmiz
df_wide_bmi <- simple_bmi(df_wide) # compute simple BMI

# Calling the function with default column names
df_bmiz <- ext_bmiz(df_wide_bmi)

# Specifying different column names; note that quotes are used
dfc <- simple_bmi(df_wide)
colnames(dfc)[colnames(dfc) %in% c("agem", "wt", "ht")] <-
  c("agemos", "weightkg", "heightcm")
df_bmiz <- ext_bmiz(dfc, age="agemos", wt="weightkg", ht="heightcm")

# Disabling conversion of all-integer age in months to (age + 0.5)
dfc <- simple_bmi(df_wide)
df_bmiz <- ext_bmiz(dfc, adjust.integer.age=FALSE)

```

growth_cdc_ext *CDC Growth Percentile Table*

Description

Part of default CDC-derived tables

Details

Contains percentiles for various ages, gender, and weights, pre-calculated by CDC

growthfile_cdc_ext.csv.gz

Used in function cleangrowth()

growth_cdc_ext_infants
 CDC Growth Percentile Table for Infants

Description

Part of default CDC-derived tables

Details

Contains percentiles for various ages, gender, and weights, pre-calculated by CDC for infants algorithm

growthfile_cdc_ext_infants.csv.gz

Used in function cleangrowth()

growth_who_ext	<i>WHO Growth Percentile Table</i>
----------------	------------------------------------

Description

Part of default WHO-derived tables

Details

Contains percentiles for various ages, gender, and weights, pre-calculated by WHO

growthfile_who.csv.gz

Used in function cleangrowth()

lenanthro	<i>Length to Age Table</i>
-----------	----------------------------

Description

Part of default CDC-derived tables

Details

Contains percentiles for various ages, gender, and weights, pre-calculated by CDC

lenanthro.txt.gz

Used in function cleangrowth()

longwide	<i>Transform data in growthcleanr format into wide structure for BMI calculation</i>
----------	--

Description

longwide transforms data from long to wide format. Ideal for transforming output from growthcleanr::cleangrowth() into a format suitable for growthcleanr::ext_bmiz().

Usage

```
longwide(
  long_df,
  id = "id",
  subjid = "subjid",
  sex = "sex",
  agedays = "agedays",
  param = "param",
  measurement = "measurement",
  gcr_result = "gcr_result",
  include_all = FALSE,
  inclusion_types = c("Include"),
  extra_cols = NULL,
  keep_unmatched_data = FALSE
)
```

Arguments

long_df	A data frame to be transformed. Expects columns: id, subjid, sex, agedays, param, measurement, and gcr_result.
id	name of observation ID column
subjid	name of subject ID column
sex	name of sex descriptor column
agedays	name of age (in days) descriptor column
param	name of parameter column to identify each type of measurement
measurement	name of measurement column containing the actual measurement data
gcr_result	name of column of results from growthcleanr::cleangrowth()
include_all	Determines whether the function keeps all exclusion codes. If TRUE, all exclusion types are kept and the inclusion_types argument is ignored. Defaults to FALSE.
inclusion_types	Vector indicating which exclusion codes from the cleaning algorithm should be included in the data, given that include_all is FALSE. For all options, see growthcleanr::cleangrowth(). Defaults to c("Include").

extra_cols Vector of additional columns to include in the output. If a column C1 differs on agedays matched height and weight values, then include separate ht_C1 and wt_C1 columns as well as a match_C1 column that gives booleans indicating where ht_C1 and wt_C1 are the same. If the agedays matched height and weight columns are identical, then only include a single version of C1. Defaults to empty vector (not keeping any additional columns).

keep_unmatched_data boolean indicating whether to keep height/weight observations that do not have a matching weight/height on that day

Value

Returns a data frame transformed from long to wide. Includes only values flagged with indicated inclusion types. Potentially includes additional columns if arguments are passed to `extra_cols`. For each subject, heights without corresponding weights for a given age (and vice versa) will be dropped unless `keep_unmatched_data` is set to TRUE.

Examples

```
# Run on a small subset of given data
df <- as.data.frame(syngrowth)
df <- df[df$subjid %in% unique(df[, "subjid"])[1:2], ]
df <- cbind(df,
            "gcr_result" = cleangrowth(df$subjid,
                                     df$param,
                                     df$agedays,
                                     df$sex,
                                     df$measurement))

# Convert to wide format
wide_df <- longwide(df)

# Include all inclusion types
wide_df <- longwide(df, include_all = TRUE)

# Specify all inclusion codes
wide_df <- longwide(df, inclusion_types = c("Include", "Exclude-Carried-Forward"))
```

nhanes-reference-medians

NHANES reference medians

Description

Contains reference median values for default recentering, derived from NHANES years 2009-2018

nhanes-reference-medians.csv.gz

Used in function `cleangrowth()`

rc-reference-medians *Infants reference medians*

Description

Contains reference median values for default recentering in the infants algorithm

rcfile-2023-08-15_format.csv.gz

Used in function cleangrowth()

read_anthro *Function to calculate z-scores and csd-scores based on anthro tables.*

Description

Function to calculate z-scores and csd-scores based on anthro tables.

Usage

```
read_anthro(path = "", cdc.only = FALSE, prelim_infants = FALSE)
```

Arguments

`path` Path to supplied reference anthro data. Defaults to package anthro tables.

`cdc.only` Whether or not only CDC data should be used. Defaults to false.

`prelim_infants` TRUE/FALSE. Run the in-development release of the infants algorithm (expands pediatric algorithm to improve performance for children 0–2 years). Not recommended for use in research. For more information regarding the logic of the algorithm, see the vignette 'Preliminary Infants Algorithm.' Defaults to FALSE.

Value

Function for calculating BMI based on measurement, age in days, sex, and measurement value.

Examples

```
# Return calculating function with all defaults
afunc <- read_anthro()

# Return calculating function while specifying a path and using only CDC data
afunc <- read_anthro(path = system.file("extdata", package = "growthcleanr"),
  cdc.only = TRUE)
```

recode_sex	<i>Recode binary sex variable for compatibility</i>
------------	---

Description

recode_sex recodes a binary sex variable for a given source column in a data frame or data table. Useful in transforming output from growthcleanr::cleangrowth() into a format suitable for growthcleanr::ext_bmiz().

Usage

```
recode_sex(  
  input_data,  
  sourcecol = "sex",  
  sourcem = "0",  
  sourcef = "1",  
  targetcol = "sex_recoded",  
  targetm = 1L,  
  targetf = 2L  
)
```

Arguments

input_data	a data frame or data table to be transformed. Expects a source column containing a binary sex variable.
sourcecol	name of sex descriptor column. Defaults to "sex"
sourcem	variable indicating "male" sex in input data. Defaults to "0"
sourcef	variable indicating "female" sex in input data. Defaults to "1"
targetcol	desired name of recoded sex descriptor column. Defaults to "sex_recoded"
targetm	desired name of recoded sex variable indicating "male" sex in output data. Defaults to 1
targetf	desired name of recoded sex variable indicating "female" sex in output data. Defaults to 2

Value

Returns a data table with recoded sex variables.

Examples

```
# Run on given data  
df <- as.data.frame(syngrowth)  
  
# Run with all defaults  
df_r <- recode_sex(df)
```

```
# Specify different targets
df_rt <- recode_sex(df, targetcol = "sexr", targetm = "Male", targetf = "Female")

# Specify different inputs
df_ri <- recode_sex(df_rt, sourcecol = "sexr", sourcem = "Male", sourcef = "Female")
```

ref_for_corraga	<i>Fenton-Based Corrected Age Reference (Weight to GA Lookup)</i>
-----------------	---

Description

Reference values for premature infant corrected-age estimation, derived from data extracted from published Fenton (2013) growth curves. Provides a reverse lookup from integer weight (grams, rounded to 10) to estimated gestational age in days, by sex.

ref_for_corraga.csv.gz

Used in function cleangrowth()

ref_for_corrz	<i>Fenton-Based Corrected Z-Score Reference</i>
---------------	---

Description

Reference values for premature infant corrected z-score calculation, derived from data extracted from published Fenton (2013) growth curves. Provides weight, length, and head circumference reference values by gestational age and sex.

ref_for_corrz.csv.gz

Used in function cleangrowth()

sd_median	<i>Calculate median SD score by age for each parameter.</i>
-----------	---

Description

Calculate median SD score by age for each parameter.

Usage

```
sd_median(param, sex, agedays, sd.orig)
```

Arguments

param	Vector identifying each measurement, may be 'WEIGHTKG', or 'HEIGHTCM'.
sex	Vector identifying the gender of the subject, may be 'M', 'm', or 0 for males, vs. 'F', 'f' or 1 for females.
agedays	Numeric vector containing the age in days at each measurement.
sd.orig	Vector of previously calculated standard deviation (SD) scores for each measurement before re-centering.

Value

Table of data with median SD-scores per day of life by gender and parameter.

Examples

```
# Run on 1 subject
df_stats <- as.data.frame(syngrowth)
df_stats <- df_stats[df_stats$subjid == df_stats$subjid[1], ]

# Get the original standard deviations
measurement_to_z <- read_anthro(cdc.only = TRUE)
sd.orig <- measurement_to_z(df_stats$param,
                           df_stats$agedays,
                           df_stats$sex,
                           df_stats$measurement,
                           TRUE)

# Calculate median standard deviations
sd.m <- sd_median(df_stats$param,
                  df_stats$sex,
                  df_stats$agedays,
                  sd.orig)
```

simple_bmi

Compute BMI using standard formula

Description

simple_bmi Computes BMI using standard formula. Assumes input compatible with output from longwide().

Usage

```
simple_bmi(wide_df, wtcoll = "wt", htcol = "ht")
```

Arguments

wide_df	A data frame or data table containing heights and weights in wide format, e.g., after transformation with longwide()
wtcol	name of observation height value column, default 'wt'
htcol	name of subject weight value column, default 'ht'

Value

Returns a data table with the added column "bmi"

Examples

```
# Simple usage
# Run on a small subset of given data
df <- as.data.frame(syngrowth)
df <- df[df$subjid %in% unique(df[, "subjid"])[1:2], ]
df <- cbind(df,
            "gcr_result" = cleangrowth(df$subjid,
                                      df$param,
                                      df$agedays,
                                      df$sex,
                                      df$measurement))

# Convert to wide format
wide_df <- longwide(df)
wide_df_with_bmi <- simple_bmi(wide_df)

# Specifying different column names; note that quotes are used
colnames(wide_df)[colnames(wide_df) %in% c("wt", "ht")] <-
  c("weight", "height")
wide_df_with_bmi <- simple_bmi(wide_df, wtcol = "weight", htcol = "height")
```

splitinput

Split input data into multiple files

Description

splitinput Splits input based on keepcol specified, yielding csv files each with at least the minimum number of rows that are written and saved separately (except for the last split file written, which may be smaller). Allows splitting input data while ensuring all records for each individual subject will stay together in one file. Pads split filenames with zeros out to five digits for consistency, assuming < 100,000 file count result.

Usage

```
splitinput(  
  df,  
  fname = deparse(substitute(df)),  
  fdir = NA,  
  min_nrow = 10000,  
  keepcol = "subjid"  
)
```

Arguments

df	data frame to split
fname	new name for each of the split files to start with
fdir	directory to put each of the split files (use "." for working directory). Must be changed from default (NA), which will trigger error.
min_nrow	minimum number of rows for each split file (default 10000)
keepcol	the column name (default "subjid") to use to keep records with the same values together in the same single split file

Value

the count number referring to the last split file written

Examples

```
# Run on given data  
df <- as.data.frame(syngrowth)  
  
# Run with all defaults (specifying directory)  
splitinput(df, fdir = tempdir())  
  
# Specifying the name, directory and minimum row size  
splitinput(df, fname = "syngrowth", fdir = tempdir(), min_nrow = 5000)  
  
# Specifying a different subject ID column  
colnames(df)[colnames(df) == "subjid"] <- "sub_id"  
splitinput(df, fdir = tempdir(), keepcol = "sub_id")
```

syngrowth

syngrowth

Description

A synthetic set of measurements from ~3,500 subjects generated using Synthea, with measurement errors for testing with growthcleanr. Contains both pediatric and adult data.

Usage

syngrowth

Format

A data frame with six variables: id, subjid, sex, agedays, param, and measurement

Details

Example electronic health record (heightcm, weightkg) data.

tanner_ht_vel	<i>Tanner Growth Velocity Table</i>
---------------	-------------------------------------

Description

Part of default CDC-derived tables

Details

Contains velocities for growth pre-calculated by CDC

tanner_ht_vel.csv.gz

Used in function cleangrowth()

tanner_ht_vel_rev	<i>Tanner Growth Velocity Table for Infants</i>
-------------------	---

Description

Part of default CDC-derived tables

Details

Contains velocities for growth pre-calculated by CDC, used for the infants algorithm

tanner_ht_vel_rev.csv.gz

Used in function cleangrowth()

 tanner_ht_vel_with_2sd

Tanner Growth Velocity Table with (2 σ)

Description

Part of default CDC-derived tables

Details

Contains velocities for growth pre-calculated by CDC, including those 2 standard deviations away.

tanner_ht_vel_with_2sd.csv.gz

Used in function `acf_answers()`

 testacf

Function to test adjust carried forward

Description

The goal of this script is to consider the height values that `growthcleanr` excludes as “carried forward” for potential re-inclusion by using a reverse absolute height velocity check based on step 15 of the Daymont et al. algorithm

Usage

```
testacf(
  infile,
  seed = 7,
  searchtype = "random",
  grid.length = 9,
  writeout = FALSE,
  outfile = paste0("test_adjustcarryforward_", format(Sys.time(),
    "%m-%d-%Y_%H-%M-%S")),
  quietly = FALSE,
  param = "none",
  debug = FALSE,
  maxrecs = 0,
  exclude_opt = 0,
  add_answers = TRUE
)
```

Arguments

infile	Input data frame/data table, cleaned by cleangrowth(), with columns as described in main README.md
seed	Numeric random seed, used only when performing random search
searchtype	Type of search to perform: random (default), line-grid, full-grid
grid.length	Number of steps in grid to search
writeout	Write output to file? Default FALSE.
outfile	"Output file name, default 'test_adjustcarrforward_DATE_TIME', where DATE is the current system date and time"
quietly	Verbose progress info
param	"none", or data frame to specify which parameters to run full search on, and values to use if not, used only when performing full-grid search
debug	Produce extra data files for debugging
maxrecs	Limit to specified # subjects, default 0 (no limit)
exclude_opt	Type of exclusion method for carried forward strings, 0 to 3. See adjustcarry-forward documentation for more information
add_answers	TRUE or FALSE, indicating whether or not to add answers (definely include/exclude) for the given dataset. Defaults to TRUE

Value

A list containing: testacf_res: data frame with adjustcarryforward results for each run, params: a data frame containing parameter values for each run. debug_filtered_data: data frame with original data, returned if debug TRUE

test_syngrowth_sas_output_compare
CDC SAS BMI Output

Description

Contains results of CDC SAS macro for calculating BMI values.

test_syngrowth_sas_output_compare.csv.gz

Used to test function ext_bmiz()

test_syngrowth_wide	<i>CDC SAS BMI Input</i>
---------------------	--------------------------

Description

Contains input data for CDC SAS macro for calculating BMI values.

test_syngrowth_wide.csv.gz

Used to test function ext_bmi()

weianthro	<i>Weight Anthro Table</i>
-----------	----------------------------

Description

Part of default CDC-derived tables

Details

Contains median and standard deviation for weight by age and gender

weianthro.csv.gz

Used in function cleangrowth()

who_hc_maxvel	<i>WHO Maximum Head Circumference Velocity for (3σ)</i>
---------------	---

Description

Part of default WHO-derived tables

Details

Contains three standard deviations for the World Health Organization values of maximum head circumference velocities.

who_hc_maxvel_3sd_infants.csv.gz

Used in function cleangrowth()

who_hc_vel_3sd	<i>WHO Head Circumference Velocity for (3σ)</i>
----------------	---

Description

Part of default WHO-derived tables

Details

Contains three standard deviations for the World Health Organization values of head circumference velocities.

who_hc_vel_3sd_infants.csv.gz

Used in function cleangrowth()

who_ht_maxvel	<i>WHO Maximum Height Velocity for (3σ)</i>
---------------	---

Description

Part of default WHO-derived tables

Details

Contains three standard deviations for the World Health Organization values of maximum height velocities.

who_ht_maxvel_3sd.csv.gz

Used in function cleangrowth()

who_ht_maxvel_2sd	<i>WHO Maximum Height Velocity for (2σ)</i>
-------------------	---

Description

Part of default WHO-derived tables

Details

Contains two standard deviations for the World Health Organization values of maximum height velocities.

who_ht_maxvel_2sd.csv.gz

Used in function acf_answers()

who_ht_vel_2sd	<i>WHO Height Velocity for (2σ)</i>
----------------	---

Description

Part of default WHO-derived tables

Details

Contains two standard deviations for the World Health Organization values of height velocities.

who_ht_vel_2sd.csv.gz

Used in function `acf_answers()`

who_ht_vel_3sd	<i>WHO Height Velocity for (3σ)</i>
----------------	---

Description

Part of default WHO-derived tables

Details

Contains three standard deviations for the World Health Organization values of height velocities.

who_ht_vel_3sd.csv.gz

Used in function `cleangrowth()`

Index

* datasets

- syngrowth, [23](#)
- acf_answers, [3](#)
- adjustcarryforward, [4](#)
- bmianthro, [6](#)
- CDCref_d, [7](#)
- cleangrowth, [7](#)
- ewma, [11](#)
- ext_bmiz, [12](#)
- growth_cdc_ext, [14](#)
- growth_cdc_ext_infants, [14](#)
- growth_who_ext, [15](#)
- lenanthro, [15](#)
- longwide, [16](#)
- nhanes-reference-medians, [17](#)
- rc-reference-medians, [18](#)
- read_anthro, [18](#)
- recode_sex, [19](#)
- ref_for_corruga, [20](#)
- ref_for_corrz, [20](#)
- sd_median, [20](#)
- simple_bmi, [21](#)
- splitinput, [22](#)
- syngrowth, [23](#)
- tanner_ht_vel, [24](#)
- tanner_ht_vel_rev, [24](#)
- tanner_ht_vel_with_2sd, [25](#)
- test_syngrowth_sas_output_compare, [26](#)
- test_syngrowth_wide, [27](#)
- testacf, [25](#)
- weianthro, [27](#)
- who_hc_maxvel, [27](#)
- who_hc_vel_3sd, [28](#)
- who_ht_maxvel, [28](#)
- who_ht_maxvel_2sd, [28](#)
- who_ht_vel_2sd, [29](#)
- who_ht_vel_3sd, [29](#)