

Package ‘harbinger’

May 8, 2026

Title A Unified Time Series Event Detection Framework

Version 2.0.707

Author Eduardo Ogasawara [aut, ths, cre] (ORCID:
<<https://orcid.org/0000-0002-0466-0626>>),
Antonio Castro [aut],
Antonio Mello [aut],
Diego Carvalho [ctb],
Eduardo Bezerra [ctb],
Ellen Paixão [aut],
Fernando Fraga [aut],
Heraldo Borges [aut],
Igor Andrade [aut],
Isabele Rocha [aut],
Janio Lima [aut],
Janio Lima [aut],
Jessica Souza [aut],
Lais Baroni [aut],
Lucas Tavares [aut],
Michel Reis [aut],
Rebecca Salles [aut],
CEFET/RJ [cph]

Maintainer Eduardo Ogasawara <eogasawara@ieee.org>

Description By analyzing time series, it is possible to observe significant changes in the behavior of observations that frequently characterize events. Events present themselves as anomalies, change points, or motifs. In the literature, there are several methods for detecting events. However, searching for a suitable time series method is a complex task, especially considering that the nature of events is often unknown. This work presents Harbinger, a framework for integrating and analyzing event detection methods. Harbinger contains several state-of-the-art methods described in Salles et al. (2020) <[doi:10.5753/sbbd.2020.13626](https://doi.org/10.5753/sbbd.2020.13626)>.

License MIT + file LICENSE

URL <https://cefet-rj-dal.github.io/harbinger/>,
<https://github.com/cefet-rj-dal/harbinger>

BugReports <https://github.com/cefet-rj-dal/harbinger/issues>

Encoding UTF-8
Depends R (>= 4.1.0)
RoxygenNote 8.0.0
Imports tspredit, changepoint, daltoolbox, forecast, ggplot2, hht,
 RcppHungarian, dplyr, dtwclust, rugarch, patchwork, stats,
 stringr, strucchange, tsm, wavelets, zoo
Suggests ocp
NeedsCompilation no
Repository CRAN
Date/Publication 2026-05-08 16:21:27 UTC

Contents

A1Benchmark	4
A2Benchmark	5
A3Benchmark	6
A4Benchmark	7
detect	8
detect.har_ensemble_fuzzy	8
examples_anomalies	9
examples_changepoints	10
examples_harbinger	11
examples_motifs	12
gecco	13
hanct_dtw	14
hanct_kmeans	15
hanc_ml	16
hanr_arima	17
hanr_emd	18
hanr_fbiad	19
hanr_fft	20
hanr_fft_amoc	21
hanr_fft_amoc_cusum	22
hanr_fft_binseg	23
hanr_fft_binseg_cusum	24
hanr_fft_sma	25
hanr_garch	26
hanr_histogram	27
hanr_ml	28
hanr_remd	29
hanr_rtad	30
hanr_wavelet	31
han_autoencoder	33
harbinger	34
harutils	35

har_ensemble	36
har_ensemble_fuzzy	37
har_ensemble_plot	38
har_ensemble_plot_models	38
har_eval	39
har_eval_soft	40
har_plot	41
hcp_amoc	43
hcp_binseg	44
hcp_bocpd	45
hcp_cf_arima	46
hcp_cf_ets	47
hcp_cf_lr	48
hcp_chow	49
hcp_garch	49
hcp_gft	50
hcp_kswin	51
hcp_page_hinkley	52
hcp_pelt	53
hcp_scp	54
hcp_waypoint	55
hdis_mp	57
hdis_sax	58
hmo_mp	59
hmo_sax	60
hmo_xsax	61
hmu_pca	62
loadfulldata	63
mas	64
mit_bih_MLII	65
mit_bih_V1	66
mit_bih_V2	67
mit_bih_V5	68
nab_artificialWithAnomaly	69
nab_realAdExchange	70
nab_realAWSCloudwatch	71
nab_realKnownCause	72
nab_realTraffic	73
nab_realTweets	74
oil_3w_Type_1	75
oil_3w_Type_2	76
oil_3w_Type_4	77
oil_3w_Type_5	78
oil_3w_Type_6	79
oil_3w_Type_7	80
oil_3w_Type_8	81
trans_sax	82
trans_xsax	82

ucr_ecg	83
ucr_int_bleeding	84
ucr_nasa	85
ucr_power_demand	86

Index	87
--------------	-----------

A1Benchmark	<i>Yahoo Webscope S5 – A1 Benchmark (Real)</i>
-------------	--

Description

Part of the Yahoo Webscope S5 labeled anomaly detection dataset. A1 contains real-world time series with binary anomaly labels. Useful for evaluating anomaly detection methods on real traffic-like data. Labels available: Yes.

Usage

```
data(A1Benchmark)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[doi:10.1371/journal.pone.0262463](https://doi.org/10.1371/journal.pone.0262463)

References

- Yoshihara K, Takahashi K (2022) A simple method for unsupervised anomaly detection: An application to Web time series data. *PLoS ONE* 17(1).
- Chandola, V., Banerjee, A., & Kumar, V. (2009). Anomaly detection: A survey. *ACM Computing Surveys*, 41(3), 1–58.

Examples

```
data(A1Benchmark)
# Access the first series and visualize
s <- A1Benchmark[[1]]
plot(ts(s$value), main = names(A1Benchmark)[1], ylab = "value")
mean(s$event) # proportion of labeled anomalies
```

A2Benchmark	<i>Yahoo Webscope S5 – A2 Benchmark (Synthetic)</i>
-------------	---

Description

Part of the Yahoo Webscope S5 dataset. A2 contains synthetic time series with labeled anomalies designed to stress-test algorithms. Labels available: Yes.

Usage

```
data(A2Benchmark)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[doi:10.1371/journal.pone.0262463](https://doi.org/10.1371/journal.pone.0262463)

References

Yoshihara K, Takahashi K (2022) A simple method for unsupervised anomaly detection: An application to Web time series data. *PLoS ONE* 17(1).

Chandola, V., Banerjee, A., & Kumar, V. (2009). Anomaly detection: A survey. *ACM Computing Surveys*, 41(3), 1–58.

Examples

```
data(A2Benchmark)
s <- A2Benchmark[[1]]
summary(s$value)
```

A3Benchmark

Yahoo Webscope S5 – A3 Benchmark (Synthetic with Outliers)

Description

Part of the Yahoo Webscope S5 dataset. A3 contains synthetic time series with labeled outliers/anomalies. Labels available: Yes.

Usage

```
data(A3Benchmark)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[doi:10.1371/journal.pone.0262463](https://doi.org/10.1371/journal.pone.0262463)

References

Yoshihara K, Takahashi K (2022) A simple method for unsupervised anomaly detection: An application to Web time series data. PLoS ONE 17(1).

Examples

```
library(harbinger)
data(A3Benchmark)
s <- A3Benchmark[[1]]
# Quick visualization with harbinger
har_plot(harbinger(), s$value)
```

A4Benchmark	<i>Yahoo Webscope S5 – A4 Benchmark (Synthetic with Anomalies and CPs)</i>
-------------	--

Description

Part of the Yahoo Webscope S5 dataset. A4 contains synthetic time series with labeled anomalies and change points. Labels available: Yes.

Usage

```
data(A4Benchmark)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[doi:10.1371/journal.pone.0262463](https://doi.org/10.1371/journal.pone.0262463)

References

Yoshihara K, Takahashi K (2022) A simple method for unsupervised anomaly detection: An application to Web time series data. *PLoS ONE* 17(1).

Truong, C., Oudre, L., & Vayatis, N. (2020). Selective review of change point detection methods. *Signal Processing*, 167, 107299.

Examples

```
data(A4Benchmark)
s <- A4Benchmark[[1]]
mean(s$event) # proportion of anomalous or change-point timestamps
```

detect	<i>Detect events in time series</i>
--------	-------------------------------------

Description

Generic S3 method for event detection using a fitted Harbinger model. Concrete methods are implemented by each detector class.

Usage

```
detect(obj, ...)
```

Arguments

obj	A harbinger detector object.
...	Additional arguments passed to methods.

Value

A data frame with columns: idx (index), event (logical), and type (character: "anomaly", "change-point", or ""). Some detectors may also attach attributes (e.g., threshold) or extra columns (e.g., seq, seqlen).

Examples

```
# See detector-specific examples in the package site for usage patterns
# and plotting helpers.
```

detect.har_ensemble_fuzzy	<i>Detect events using Harbinger Fuzzy Ensemble</i>
---------------------------	---

Description

Detect events using Harbinger Fuzzy Ensemble

Usage

```
## S3 method for class 'har_ensemble_fuzzy'
detect(
  obj,
  serie,
  threshold = NULL,
  threshold_type = NULL,
  time_tolerance = NULL,
  use_nms = NULL,
```

```

    outliers_check = NULL,
    outlier_filter = NULL,
    ...
)

```

Arguments

obj	A har_ensemble_fuzzy object.
serie	Input time series.
threshold	Numeric detection threshold.
threshold_type	Either "fixed" or "percentile".
time_tolerance	Integer window for temporal fuzzification and NMS.
use_nms	Logical; whether to apply non-maximum suppression.
outliers_check	Optional refinement function.
outlier_filter	Optional post-filter over the ensemble score. It may return a logical mask or integer positions.
...	Additional arguments.

Value

A detection object with score and per-model events as attributes.

examples_anomalies	<i>Time series for anomaly detection</i>
--------------------	--

Description

A list of time series designed for anomaly detection tasks.

- simple: simple synthetic series with isolated anomalies.
- contextual: contextual anomalies relative to local behavior.
- trend: synthetic series with trend and anomalies.
- multiple: multiple anomalies.
- sequence: repeated anomalous sequences.
- tt: train-test split synthetic series.
- tt_warped: warped train-test synthetic series.

Usage

```
data(examples_anomalies)
```

Format

A list of time series for anomaly detection.

Source

[Harbinger package](#)

References

[Harbinger package](#)

Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
data(examples_anomalies)
# Select a simple anomaly series
serie <- examples_anomalies$simple
head(serie)
```

examples_changepoints *Time series for change point detection*

Description

A list of time series for change point experiments.

- simple: simple synthetic series with one change point.
- sinusoidal: sinusoidal pattern with a regime change.
- incremental: gradual change in mean/variance.
- abrupt: abrupt level shift.
- volatility: variance change.

Usage

```
data(examples_changepoints)
```

Format

A list of time series for change point detection.

Source

[Harbinger package](#)

References

[Harbinger package](#)

Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
data(examples_changepoints)
# Select a simple change point series
serie <- examples_changepoints$simple
head(serie)
```

examples_harbinger *Time series for event detection*

Description

A list of time series for demonstrating event detection tasks.

- nonstationarity: synthetic nonstationary time series.
- global_temperature_yearly: yearly global temperature.
- global_temperature_monthly: monthly global temperature.
- multidimensional: multivariate series with a change point.
- seattle_week: Seattle weekly temperature in 2019.
- seattle_daily: Seattle daily temperature in 2019.

Usage

```
data(examples_harbinger)
```

Format

A list of time series.

Source

[Harbinger package](#)

References

[Harbinger package](#)

Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
data(examples_harbinger)
# Inspect a series (Seattle daily temperatures)
serie <- examples_harbinger$seattle_daily
head(serie)
```

examples_motifs	<i>Time series for motif/discord discovery</i>
-----------------	--

Description

A list of time series for motif (repeated patterns) and discord (rare patterns) discovery.

- simple: simple synthetic series with motifs.
- mitdb100: sample from MIT-BIH arrhythmia database (record 100).
- mitdb102: sample from MIT-BIH arrhythmia database (record 102).

Usage

```
data(examples_motifs)
```

Format

A list of time series for motif discovery.

Source

[Harbinger package](#)

References

[Harbinger package](#)

Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
data(examples_motifs)
# Select a simple motif series
serie <- examples_motifs$simple
head(serie)
```

Description

Benchmark time series for water quality monitoring composed of multiple sensors and an associated binary event label. This dataset supports research in anomaly and event detection for environmental data streams. See [cefet-rj-dal/united](#) for usage guidance and links to the preprocessing steps used to build the package-ready object. Labels available: Yes.

Usage

```
data(gecco)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

GECCO Challenge 2018 (legacy challenge page unavailable)

References

Genetic and Evolutionary Computation Conference (GECCO), Association for Computing Machinery (ACM). See also: Chandola, V., Banerjee, A., & Kumar, V. (2009). Anomaly detection: A survey. *ACM Computing Surveys*, 41(3), 1–58.

Examples

```
data(gecco)
# Select the first univariate series and inspect
series <- gecco[[1]]
summary(series$value)
# Plot values with event markers
plot(ts(series$value), main = names(gecco)[1], ylab = "value")
```

`hanct_dtw`*Anomaly detector using DTW*

Description

Distance-based anomaly and discord detection using dynamic time warping. The detector clusters the series with DTW and flags observations or subsequences that are far from the nearest centroid. When `seq` equals one, isolated observations are labeled as anomalies. When `seq` is greater than one, subsequences are labeled as discords. Wraps the `tsclust` implementation from the `dtwclust` package.

Usage

```
hanct_dtw(seq = 1, centers = NA)
```

Arguments

<code>seq</code>	sequence size
<code>centers</code>	number of centroids

Value

`hanct_dtw` object

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure DTW-based detector
model <- hanct_dtw()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)
```

```
# Show detected events
print(detection[(detection$event),])
```

hanct_kmeans	<i>Anomaly detector using k-means</i>
--------------	---------------------------------------

Description

Distance-based anomaly and discord detection using k-means clustering. The detector clusters the series and flags observations or subsequences that are far from the nearest centroid. When seq equals one, isolated observations are labeled as anomalies. When seq is greater than one, subsequences are labeled as discords. Wraps the kmeans implementation from the stats package.

Usage

```
hanct_kmeans(seq = 1, centers = NA)
```

Arguments

seq	sequence size
centers	number of centroids

Value

hanct_kmeans object

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure k-means detector
model <- hanct_kmeans()

# Fit the model
model <- fit(model, dataset$serie)
```

```
# Run detection
detection <- detect(model, dataset$serie)

# Show detected events
print(detection[(detection$event),])
```

hanc_ml

Anomaly detector based on ML classification

Description

Supervised anomaly detection using a DALToolbox classifier trained with labeled events. Predictions above a probability threshold are flagged.

A set of preconfigured classification methods are listed at <https://cefet-rj-dal.github.io/daltoolbox/> (e.g., cla_majority, cla_dtree, cla_knn, cla_mlp, cla_nb, cla_rf, cla_svm).

Usage

```
hanc_ml(model, threshold = 0.5)
```

Arguments

model	A DALToolbox classification model.
threshold	Numeric. Probability threshold for positive class.

Value

hanc_ml object.

References

- Bishop CM (2006). Pattern Recognition and Machine Learning. Springer.
- Hyndman RJ, Athanasopoulos G (2021). Forecasting: Principles and Practice. OTexts.
- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

# Load labeled anomaly dataset
data(examples_anomalies)

# Use train-test example
dataset <- examples_anomalies$tt
dataset$event <- factor(dataset$event, labels=c("FALSE", "TRUE"))
slevels <- levels(dataset$event)
```

```
# Split into training and test
train <- dataset[1:80,]
test <- dataset[-(1:80),]

# Normalize features
norm <- minmax()
norm <- fit(norm, train)
train_n <- daltoolbox::transform(norm, train)

# Configure a decision tree classifier
model <- hanc_ml(cla_dtree("event", slevels))

# Fit the classifier
model <- fit(model, train_n)

# Evaluate detections on the test set
test_n <- daltoolbox::transform(norm, test)

detection <- detect(model, test_n)
print(detection[(detection$event),])
```

hanr_arima

Anomaly detector using ARIMA

Description

Fits an ARIMA model to the series and flags observations with large model residuals as anomalies. Wraps ARIMA from the forecast package.

Usage

```
hanr_arima()
```

Details

The detector estimates ARIMA(p,d,q) and computes standardized residuals. Residual magnitudes are summarized via a distance function and thresholded with outlier heuristics from `harutils()`.

Value

hanr_arima object.

References

- Box GEP, Jenkins GM, Reinsel GC, Ljung GM (2015). Time Series Analysis: Forecasting and Control. Wiley.

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure ARIMA anomaly detector
model <- hanr_arima()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected anomalies
print(detection[(detection$event),])
```

hanr_emd

Anomaly detector using EMD

Description

Empirical Mode Decomposition (CEEMD) to extract intrinsic mode functions and flag anomalies from high-frequency components. Wraps `hht::CEEMD`.

Usage

```
hanr_emd(noise = 0.1, trials = 5)
```

Arguments

noise	Numeric. Noise amplitude for CEEMD.
trials	Integer. Number of CEEMD trials.

Value

hanr_emd object

References

- Huang NE, et al. (1998). The empirical mode decomposition and the Hilbert spectrum for nonlinear and non-stationary time series analysis. Proc. Royal Society A.

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure EMD-based anomaly detector
model <- hanr_emd()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected anomalies
print(detection[(detection$event),])
```

hanr_fbiad

Anomaly detector using FBIAD

Description

Forward and Backward Inertial Anomaly Detector (FBIAD) detects anomalies in time series by comparing each observation against both forward and backward inertial context.

Usage

```
hanr_fbiad(sw_size = 30)
```

Arguments

`sw_size` Window size for FBIAD.

Value

hanr_fbiad object.

References

- Lima, J., Salles, R., Porto, F., Coutinho, R., Alpis, P., Escobar, L., Pacitti, E., Ogasawara, E. Forward and Backward Inertial Anomaly Detector: A Novel Time Series Event Detection Method. Proceedings of the International Joint Conference on Neural Networks, 2022. doi:10.1109/IJCNN55064.2022.9892088

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure FBIAD detector
model <- hanr_fbiad()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected anomalies
print(detection[(detection$event),])
```

hanr_fft

Anomaly detector using FFT

Description

High-pass filtering via FFT isolates high-frequency components. Anomalies are flagged where the filtered magnitude departs strongly from baseline.

Usage

```
hanr_fft()
```

Details

The spectrum is computed by FFT, a cutoff is selected from the power spectrum, low frequencies are nulled, and the inverse FFT reconstructs a high-pass signal. Magnitudes are summarized and thresholded using `harutils()`.

Value

hanr_fft object

References

- Sobrinho, E. P., Souza, J., Lima, J., Giusti, L., Bezerra, E., Coutinho, R., Baroni, L., Pacitti, E., Porto, F., Belloze, K., Ogasawara, E. Fine-Tuning Detection Criteria for Enhancing Anomaly Detection in Time Series. In: Simpósio Brasileiro de Banco de Dados (SBBDD). SBC, 29 Sep. 2025. doi:10.5753/sbbd.2025.247063

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure FFT-based anomaly detector
model <- hanr_fft()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected anomalies
print(detection[(detection$event),])
```

hanr_fft_amoc

Anomaly Detector using FFT with AMOC Cutoff

Description

This detector combines FFT-based spectral filtering with an AMOC change-point cutoff on the power spectrum. Frequencies below the selected cutoff are removed, the signal is reconstructed from the remaining high-frequency content, and the residual is scored for anomalies.

This function extends the HARBINGER framework and returns an object of class `hanr_fft_amoc`.

Usage

```
hanr_fft_amoc()
```

Value

`hanr_fft_amoc` object

References

- Sobrinho, E. P., Souza, J., Lima, J., Giusti, L., Bezerra, E., Coutinho, R., Baroni, L., Pacitti, E., Porto, F., Belloze, K., Ogasawara, E. Fine-Tuning Detection Criteria for Enhancing Anomaly Detection in Time Series. In: Simpósio Brasileiro de Banco de Dados (SBBDD). SBC, 29 Sep. 2025. doi:10.5753/sbbd.2025.247063

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure FFT+AMOC detector
model <- hanr_fft_amoc()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Inspect detected anomalies
print(detection[detection$event, ])
```

hanr_fft_amoc_cusum *Anomaly Detector using FFT with AMOC and CUSUM Cutoff*

Description

This detector combines FFT-based spectral filtering with an AMOC change-point cutoff applied to the cumulative spectrum. The lower-frequency components are removed, the signal is reconstructed, and the residual is scored for anomalies.

This function extends the HARBINGER framework and returns an object of class `hanr_fft_amoc_cusum`.

Usage

```
hanr_fft_amoc_cusum()
```

Value

```
hanr_fft_amoc_cusum object
```

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure FFT+CUSUM+AMOC detector
model <- hanr_fft_amoc_cusum()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Inspect detected anomalies
print(detection[detection$event, ])
```

`hanr_fft_binseg`*Anomaly Detector using FFT with Binary Segmentation Cutoff*

Description

This detector combines FFT-based spectral filtering with a Binary Segmentation change-point cut-off on the power spectrum. Frequencies below the selected cutoff are removed, the signal is reconstructed from the remaining high-frequency content, and the residual is scored for anomalies.

This function is part of the HARBINGER framework and returns an object of class `hanr_fft_binseg`.

Usage

```
hanr_fft_binseg()
```

Value

`hanr_fft_binseg` object

References

- Sobrinho, E. P., Souza, J., Lima, J., Giusti, L., Bezerra, E., Coutinho, R., Baroni, L., Pacitti, E., Porto, F., Belloze, K., Ogasawara, E. Fine-Tuning Detection Criteria for Enhancing Anomaly Detection in Time Series. In: Simpósio Brasileiro de Banco de Dados (SBBDD). SBC, 29 Sep. 2025. doi:10.5753/sbbd.2025.247063

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure FFT+BinSeg detector
model <- hanr_fft_binseg()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Inspect detected anomalies
print(detection[detection$event, ])
```

hanr_fft_binseg_cusum *Anomaly Detector using FFT with BinSeg and CUSUM Cutoff*

Description

This detector combines FFT-based spectral filtering with a Binary Segmentation change-point cutoff applied to the cumulative spectrum. The lower-frequency components are removed, the signal is reconstructed, and the residual is scored for anomalies.

This function extends the HARBINGER framework and returns an object of class `hanr_fft_binseg_cusum`.

Usage

```
hanr_fft_binseg_cusum()
```

Value

`hanr_fft_binseg_cusum` object

References

- Sobrinho, E. P., Souza, J., Lima, J., Giusti, L., Bezerra, E., Coutinho, R., Baroni, L., Pacitti, E., Porto, F., Belloze, K., Ogasawara, E. Fine-Tuning Detection Criteria for Enhancing Anomaly Detection in Time Series. In: Simpósio Brasileiro de Banco de Dados (SBBDD). SBC, 29 Sep. 2025. doi:10.5753/sbbd.2025.247063

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

#Using simple example
dataset <- examples_anomalies$simple
head(dataset)

# setting up time series fft detector
model <- hanr_fft_binseg_cusum()

# fitting the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# filtering detected events
print(detection[(detection$event),])
```

hanr_fft_sma

Anomaly Detector using Adaptive FFT and Moving Average

Description

This detector combines FFT-based spectral analysis with an adaptive moving-average filter. The residual signal is scored for anomalies, and a grouping strategy reduces false positives by keeping a representative point from each cluster.

This function extends the HARBINGER framework and returns an object of class `hanr_fft_sma`.

Usage

```
hanr_fft_sma()
```

Value

`hanr_fft_sma` object

References

- Sobrinho, E. P., Souza, J., Lima, J., Giusti, L., Bezerra, E., Coutinho, R., Baroni, L., Pacitti, E., Porto, F., Belloze, K., Ogasawara, E. Fine-Tuning Detection Criteria for Enhancing Anomaly Detection in Time Series. In: Simpósio Brasileiro de Banco de Dados (SBBDD). SBC, 29 Sep. 2025. doi:10.5753/sbbd.2025.247063

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

#Using simple example
dataset <- examples_anomalies$simple
head(dataset)

# setting up time series fft detector
model <- hanr_fft_sma()

# fitting the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# filtering detected events
print(detection[(detection$event),])
```

hanr_garch

Anomaly detector using GARCH

Description

Fits a GARCH model to capture conditional heteroskedasticity and flags observations with large standardized residuals as anomalies. Wraps rugarch.

Usage

```
hanr_garch()
```

Details

A sGARCH(1,1) with ARMA(1,1) mean is estimated. Standardized residuals are summarized and thresholded via harutils().

Value

hanr_garch object.

References

- Engle RF (1982). Autoregressive Conditional Heteroscedasticity with Estimates of the Variance of United Kingdom Inflation. *Econometrica*, 50(4):987–1007.
- Bollerslev T (1986). Generalized Autoregressive Conditional Heteroskedasticity. *Journal of Econometrics*, 31(3):307–327.

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure GARCH anomaly detector
model <- hanr_garch()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected anomalies
print(detection[(detection$event),])
```

hanr_histogram

Anomaly detector using histograms

Description

Flags observations that fall into low-density histogram bins or outside the observed bin range.

Usage

```
hanr_histogram(density_threshold = 0.05)
```

Arguments

`density_threshold`
Numeric between 0 and 1. Minimum bin density to avoid being considered an anomaly (default 0.05).

Value

hanr_histogram object

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure histogram-based detector
model <- hanr_histogram()

# Fit the model (no-op)
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected anomalies
print(detection[(detection$event),])
```

hanr_ml

Anomaly detector based on ML regression

Description

Trains a regression model to forecast the next value from a sliding window and flags large prediction errors as anomalies. Uses DALToolbox regressors.

A set of preconfigured regression methods are described at <https://cefet-rj-dal.github.io/daltoolbox/> (e.g., ts_elm, ts_conv1d, ts_lstm, ts_mlp, ts_rf, ts_svm).

Usage

```
hanr_ml(model, sw_size = 15)
```

Arguments

model	A DALToolbox regression model.
sw_size	Integer. Sliding window size.

Value

hanr_ml object.

References

- Hyndman RJ, Athanasopoulos G (2021). Forecasting: Principles and Practice. OTexts.
- Goodfellow I, Bengio Y, Courville A (2016). Deep Learning. MIT Press.

Examples

```
library(daltoolbox)
library(tspredit)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure a time series regression model
model <- hanr_ml(tspredit::ts_elm(tspredit::ts_norm_gminmax(),
                                input_size=4, nhid=3, actfun="purelin"))

# Fit the model
model <- daltoolbox::fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected anomalies
print(detection[(detection$event),])
```

hanr_remd

Anomaly detector using REMD

Description

Anomaly detection using REMD with EMD-based decomposition. The detector decomposes the series, selects components according to curvature, and flags large residual deviations as anomalies. Wraps the EMD-based model presented in the forecast package.

Usage

```
hanr_remd(noise = 0.1, trials = 5)
```

Arguments

noise	Noise amplitude for the decomposition.
trials	Number of trials used by the decomposition step.

Value

hanr_remd object

References

- Souza, J., Paixão, E., Fraga, F., Baroni, L., Alves, R. F. S., Belloze, K., Dos Santos, J., Bezerra, E., Porto, F., Ogasawara, E. REMD: A Novel Hybrid Anomaly Detection Method Based on EMD and ARIMA. Proceedings of the International Joint Conference on Neural Networks, 2024. doi:10.1109/IJCNN60899.2024.10651192

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure REMD detector
model <- hanr_remd()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected anomalies
print(detection[(detection$event),])
```

hanr_rtad

Resilient Transformation Anomaly Detector (RTAD)

Description

Hybrid anomaly detector built from the Resilient Transformation (RT) proposed in the RT/RTAD paper. The series is decomposed with CEEMD, the highest-frequency structure is selected from IMF roughness, the transformed signal is differentiated, and local dispersion is used to normalize deviations before thresholding.

RTAD is not a generic wrapper around EMD. It is the standalone detector obtained when the resilient transformation is coupled with a simple decision rule.

Usage

```
hanr_rtad(sw_size = 30, noise = 0.001, trials = 5, sigma = sd)
```

Arguments

sw_size	Sliding window size used to compute local dispersion.
noise	CEEMD noise amplitude.
trials	Number of CEEMD trials.
sigma	Function used to compute local dispersion.

Value

hanr_rtad object

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)
library(zoo)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure RTAD detector
model <- hanr_rtad()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected events
print(detection[(detection$event),])
```

hanr_wavelet

Anomaly detector using Wavelets

Description

Multiresolution decomposition via wavelets; anomalies are flagged where aggregated wavelet detail coefficients indicate unusual energy.

Usage

```
hanr_wavelet(filter = "haar")
```

Arguments

`filter` Character. Available wavelet filters: haar, d4, la8, bl14, c6.

Details

The series is decomposed with MODWT and detail bands are aggregated to compute a magnitude signal that is thresholded using `harutils()`.

Value

hanr_wavelet object

References

- Mallat S (1989). A theory for multiresolution signal decomposition: The wavelet representation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 11(7):674–693.

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure wavelet-based anomaly detector
model <- hanr_wavelet()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected anomalies
print(detection[(detection$event),])
```

han_autoencoder	<i>Anomaly detector using autoencoders</i>
-----------------	--

Description

Trains an encoder-decoder (autoencoder) to reconstruct sliding windows of the series; large reconstruction errors indicate anomalies.

Usage

```
han_autoencoder(input_size, encode_size, encoderclass = autoenc_base_ed, ...)
```

Arguments

input_size	Integer. Input (and output) window size for the autoencoder.
encode_size	Integer. Size of the encoded (bottleneck) representation.
encoderclass	DALToolbox encoder-decoder constructor to instantiate.
...	Additional arguments forwarded to encoderclass.

Value

han_autoencoder object

References

- Sakurada M, Yairi T (2014). Anomaly Detection Using Autoencoders with Nonlinear Dimensionality Reduction. MLSDA 2014.

Examples

```
library(daltoolbox)
library(tspredit)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure an autoencoder-based anomaly detector
model <- han_autoencoder(input_size = 5, encode_size = 3)

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)
```

```
# Inspect detected anomalies
print(detection[detection$event, ])
```

harbinger

Harbinger

Description

Base class for time series event detection in the Harbinger framework. It provides shared state handling and helper methods used by anomaly, change-point, and motif detectors. Concrete detectors extend this class and implement their own `fit()` and/or `detect()` S3 methods.

Usage

```
harbinger()
```

Details

Internally, this class stores references to the original series, indices of non-missing observations, and helper structures to restore detection results in the original series index space. It also exposes utility hooks for distance computation and outlier post-processing provided by `harutils()`.

Value

A harbinger object that can be extended by detectors.

References

- Harbinger documentation: <https://cefet-rj-dal.github.io/harbinger>
- Salles, R., Escobar, L., Baroni, L., Zorrilla, R., Ziviani, A., Kreischer, V., Delicato, F., Pires, P. F., Maia, L., Coutinho, R., Assis, L., Ogasawara, E. Harbinger: Um framework para integração e análise de métodos de detecção de eventos em séries temporais. Anais do Simpósio Brasileiro de Banco de Dados (SBBDD). In: Anais do XXXV Simpósio Brasileiro de Bancos de Dados. SBC, 28 Sep. 2020. doi:10.5753/sbbd.2020.13626

Examples

```
# See the specific detector examples for anomalies, change points, and motifs
# at https://cefet-rj-dal.github.io/harbinger
```

harutils	<i>Harbinger Utilities</i>
----------	----------------------------

Description

Utility object that groups common distance measures, threshold heuristics, and outlier grouping rules used by Harbinger detectors.

Usage

```
harutils()
```

Details

Provided helpers include:

- L1 and L2 distance aggregations over vectors or rows of matrices/data frames.
- Thresholding heuristics: boxplot-based (IQR), Gaussian 3-sigma, and a ratio-based rule.
- Grouping strategies for contiguous outliers: keep first index or keep highest-magnitude index.
- Optional fuzzification over detections to propagate influence within a tolerance window.

These utilities centralize common tasks and ensure consistent behavior across detectors.

Value

A `harutils` object exposing the helper functions.

References

- Tukey JW (1977). *Exploratory Data Analysis*. Addison-Wesley. (boxplot/IQR heuristic)
- Shewhart WA (1931). *Economic Control of Quality of Manufactured Product*. D. Van Nostrand. (three-sigma rule)
- Silva, E. P., Balbi, H., Pacitti, E., Porto, F., Santos, J., Ogasawara, E. Cutoff Frequency Adjustment for FFT-Based Anomaly Detectors. In: *Simpósio Brasileiro de Banco de Dados (SBBD)*. SBC, 14 Oct. 2024. doi:10.5753/sbbd.2024.243319

Examples

```
# Basic usage of utilities
utils <- harutils()

# Compute L2 distance on residuals
res <- c(0.1, -0.5, 1.2, -0.3)
d2 <- utils$har_distance_l2(res)
print(d2)

# Apply 3-sigma outlier rule and keep only first index of contiguous runs
idx <- utils$har_outliers_gaussian(d2)
```

```
flags <- utils$har_outliers_checks_firstgroup(idx, d2)
print(which(flags))
```

har_ensemble	<i>Harbinger Ensemble</i>
--------------	---------------------------

Description

Majority-vote ensemble across multiple Harbinger detectors.

Usage

```
har_ensemble(...)
```

Arguments

... One or more detector objects.

Value

A har_ensemble object

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use a simple example
dataset <- examples_anomalies$simple
head(dataset)

# Configure an ensemble of detectors
model <- har_ensemble(hanr_arima(), hanr_arima(), hanr_arima())
# model <- har_ensemble(hanr_fbiad(), hanr_arima(), hanr_emd())

# Fit all ensemble members
model <- fit(model, dataset$serie)

# Run ensemble detection
detection <- detect(model, dataset$serie)

# Show detected events
```

```
print(detection[(detection$event),])
```

har_ensemble_fuzzy *Harbinger Fuzzy Ensemble*

Description

Score-based ensemble across multiple Harbinger detectors with optional temporal fuzzification, thresholding, and non-maximum suppression.

This variant preserves the richer aggregation logic that was previously mixed into `har_ensemble()`, but keeps the simple majority-vote ensemble separate.

Usage

```
har_ensemble_fuzzy(...)
```

Arguments

... One or more detector objects.

Value

A `har_ensemble_fuzzy` object.

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

data(examples_changepoints)
dataset <- examples_changepoints$simple

model <- har_ensemble_fuzzy(hcp_amoc(), hcp_pelt(), hcp_cf_lr())
model <- fit(model, dataset$serie)
detection <- detect(model, dataset$serie, time_tolerance = 8, use_nms = TRUE)
print(detection[detection$event, ])
```

har_ensemble_plot *Plot Harbinger Ensemble Outputs*

Description

Visualize ensemble detection results and the individual model votes stored by `har_ensemble_fuzzy()`. The plotting helpers do not recompute detections. They use the attributes attached to the detection object as the source of truth.

Usage

```
har_ensemble_plot(detection, serie, threshold = NULL, time_idx = NULL)
```

Arguments

detection	A detection object returned by <code>detect.har_ensemble_fuzzy</code> .
serie	Numeric vector with the original time series.
threshold	Optional threshold override for the score panel.
time_idx	Optional x-axis vector.

Value

A patchwork object.

har_ensemble_plot_models
Plot individual model detections in a Harbinger fuzzy ensemble

Description

Visualizes the original series and the per-model detections stored in the `model_events` attribute returned by `detect.har_ensemble_fuzzy()`.

Usage

```
har_ensemble_plot_models(detection, serie, time_idx = NULL)
```

Arguments

detection	A detection object returned by <code>detect.har_ensemble_fuzzy</code> .
serie	Numeric vector with the original time series.
time_idx	Optional x-axis vector.

Value

A patchwork object.

`har_eval`*Evaluation of event detection*

Description

Hard evaluation of event detection producing confusion matrix and common metrics (accuracy, precision, recall, F1, etc.).

Usage

```
har_eval()
```

Value

har_eval object

References

- Harbinger documentation: <https://cefet-rj-dal.github.io/harbinger>
- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

dataset <- examples_anomalies$simple
head(dataset)

# Configure a change-point detector (GARCH)
model <- hcp_garch()

# Fit the detector
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected events
print(detection[(detection$event),])

# Evaluate detections
evaluation <- evaluate(har_eval(), detection$event, dataset$event)
print(evaluation$confMatrix)

# Plot the results
```

```
grf <- har_plot(model, dataset$serie, detection, dataset$event)
plot(grf)
```

har_eval_soft

Evaluation of event detection (SoftED)

Description

Soft evaluation of event detection using SoftED [doi:10.48550/arXiv.2304.00439](https://doi.org/10.48550/arXiv.2304.00439). The metric assigns partial credit to detections that fall within a tolerance window around the ground-truth event.

Usage

```
har_eval_soft(sw_size = 15)
```

Arguments

sw_size Integer. Tolerance window size for soft matching.

Value

har_eval_soft object.

References

- Salles, R., Lima, J., Reis, M., Coutinho, R., Pacitti, E., Masegla, F., Akbarinia, R., Chen, C., Garibaldi, J., Porto, F., Ogasawara, E. SoftED: Metrics for soft evaluation of time series event detection. Computers and Industrial Engineering, 2024. doi:10.1016/j.cie.2024.110728

Examples

```
library(daltoolbox)

# Load anomaly example data
data(examples_anomalies)

# Use the simple series
dataset <- examples_anomalies$simple
head(dataset)

# Configure a change-point detector (GARCH)
model <- hcp_garch()

# Fit the detector
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)
```

```

# Show detected events
print(detection[(detection$event),])

# Evaluate detections (SoftED)
evaluation <- evaluate(har_eval_soft(), detection$event, dataset$event)
print(evaluation$confMatrix)

# Plot the results
grf <- har_plot(model, dataset$serie, detection, dataset$event)
plot(grf)

```

har_plot

Plot event detection on a time series

Description

Convenience plotting helper for Harbinger detections. It accepts a detector, the input series, an optional detection data frame, and optional ground-truth events to color-code true positives (TP), false positives (FP), and false negatives (FN). It can also mark detected change points and draw reference horizontal lines.

Usage

```

har_plot(
  obj,
  serie,
  detection = NULL,
  event = NULL,
  mark.cp = TRUE,
  ylim = NULL,
  idx = NULL,
  pointsize = 0.5,
  colors = c("green", "blue", "red", "purple"),
  yline = NULL
)

```

Arguments

obj	A harbinger detector used to produce detection.
serie	Numeric vector with the time series to plot.
detection	Optional detection data.frame as returned by detect().
event	Optional logical vector with ground-truth events (same length as serie).
mark.cp	Logical; if TRUE, marks detected change points with dashed vertical lines.
ylim	Optional numeric vector of length 2 for y-axis limits.

idx	Optional x-axis labels or indices (defaults to seq_along(serie)).
pointsize	Base point size for observations.
colors	Character vector of length 4 with colors for TP, FN, FP, and motif segments.
ylines	Optional numeric vector with y values to draw dotted horizontal lines.

Value

A ggplot object showing the time series with detected events highlighted.

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

# Load an example anomaly dataset
data(examples_anomalies)

# Use the simple time series
dataset <- examples_anomalies$simple
head(dataset)

# Set up an ARIMA-based anomaly detector
model <- hanr_arima()

# Fit the detector
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Inspect detected events
print(detection[(detection$event),])

# Evaluate detections (soft evaluation)
evaluation <- evaluate(har_eval_soft(), detection$event, dataset$event)
print(evaluation$confMatrix)

# Plot the results
grf <- har_plot(model, dataset$serie, detection, dataset$event)
plot(grf)
```

hcp_amoc	<i>At Most One Change (AMOC)</i>
----------	----------------------------------

Description

Change-point detection method focusing on identifying at most one change in mean and/or variance. This is a wrapper around the AMOC implementation from the `changepoint` package.

Usage

```
hcp_amoc()
```

Details

AMOC detects a single most significant change point under a cost function optimized for a univariate series. It is useful when at most one structural break is expected.

Value

hcp_amoc object.

References

- Hinkley DV (1970). Inference about the change-point in a sequence of random variables. *Biometrika*, 57(1):1–17. doi:10.1093/biomet/57.1.1
- Killick R, Fearnhead P, Eckley IA (2012). Optimal detection of changepoints with a linear computational cost. *JASA*, 107(500):1590–1598.

Examples

```
library(daltoolbox)

# Load change-point example data
data(examples_changepoints)

# Use a simple example
dataset <- examples_changepoints$simple
head(dataset)

# Configure the AMOC detector
model <- hcp_amoc()

# Fit the detector (no-op for AMOC)
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected change point(s)
```

```
print(detection[(detection$event),])
```

hcp_binseg

Binary Segmentation (BinSeg)

Description

Multi-change-point detection via Binary Segmentation on mean/variance using the changepoint package.

Usage

```
hcp_binseg(Q = 2)
```

Arguments

Q Integer. Maximum number of change points to search for.

Details

Binary Segmentation recursively partitions the series around the largest detected change until a maximum number of change points or stopping criterion is met. This is a fast heuristic widely used in practice.

Value

hcp_binseg object.

References

- Vostrikova L (1981). Detecting "disorder" in multidimensional random processes. Soviet Mathematics Doklady, 24, 55–59.
- Killick R, Fearnhead P, Eckley IA (2012). Optimal detection of changepoints with a linear computational cost. JASA, 107(500):1590–1598. [context](#)

Examples

```
library(daltoolbox)

# Load change-point example data
data(examples_changepoints)

# Use a simple example
dataset <- examples_changepoints$simple
head(dataset)

# Configure the BinSeg detector
model <- hcp_binseg()
```

```
# Fit the detector (no-op for BinSeg)
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected change points
print(detection[(detection$event),])
```

hcp_bocpd

Bayesian Online Change Point Detection

Description

Online Bayesian change-point detection using the ocp package.

This implementation follows the Adams & MacKay formulation and uses the ocp backend to infer changepoint evidence over the full series.

Usage

```
hcp_bocpd(
  hazard = 100,
  dist = c("gaussian", "poisson"),
  threshold = NULL,
  min_distance = 5,
  burn_in = 5
)
```

Arguments

hazard	Positive scalar controlling the constant hazard function.
dist	Probability model used by ocp; one of "gaussian" or "poisson".
threshold	Numeric threshold for changepoint evidence.
min_distance	Minimum distance between selected changepoints.
burn_in	Number of initial observations to ignore.

Value

An hcp_bocpd object.

References

- Adams RP, MacKay DJC (2007). Bayesian Online Changepoint Detection. arXiv:0710.3742
- Pagotto A (2019). ocp: Bayesian Online Changepoint Detection. R package.

hcp_cf_arima	<i>Change Finder using ARIMA</i>
--------------	----------------------------------

Description

Change-point detection by modeling residual deviations with ARIMA and applying a second-stage smoothing and thresholding, inspired by ChangeFinder [doi:10.1109/TKDE.2006.1599387](https://doi.org/10.1109/TKDE.2006.1599387). Wraps ARIMA from the forecast package.

Usage

```
hcp_cf_arima(sw_size = NULL)
```

Arguments

`sw_size` Integer. Sliding window size for smoothing/statistics.

Value

hcp_cf_arima object.

References

- Takeuchi J, Yamanishi K (2006). A unifying framework for detecting outliers and change points from time series. IEEE Transactions on Knowledge and Data Engineering.

Examples

```
library(daltoolbox)

# Load change-point example data
data(examples_changepoints)

# Use a simple example
dataset <- examples_changepoints$simple
head(dataset)

# Configure ChangeFinder-ARIMA detector
model <- hcp_cf_arima()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected change points
print(detection[(detection$event),])
```

`hcp_cf_ets`*Change Finder using ETS*

Description

Change-point detection by modeling residual deviations with ETS and applying a second-stage smoothing and thresholding, inspired by ChangeFinder [doi:10.1109/TKDE.2006.1599387](https://doi.org/10.1109/TKDE.2006.1599387). Wraps ETS from the forecast package.

Usage

```
hcp_cf_ets(sw_size = 7)
```

Arguments

`sw_size` Integer. Sliding window size for smoothing/statistics.

Value

hcp_cf_ets object.

Examples

```
library(daltoolbox)

# Load change-point example data
data(examples_changepoints)

# Use a simple example
dataset <- examples_changepoints$simple
head(dataset)

# Configure ChangeFinder-ETS detector
model <- hcp_cf_ets()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected change points
print(detection[(detection$event),])
```

`hcp_cf_lr`*Change Finder using Linear Regression*

Description

Change-point detection by modeling residual deviations with linear regression and applying a second-stage smoothing and thresholding, inspired by ChangeFinder [doi:10.1109/TKDE.2006.1599387](https://doi.org/10.1109/TKDE.2006.1599387).

Usage

```
hcp_cf_lr(sw_size = 30)
```

Arguments

`sw_size` Integer. Sliding window size for smoothing/statistics.

Value

hcp_cf_lr object.

Examples

```
library(daltoolbox)

# Load change-point example data
data(examples_changepoints)

# Use a simple example
dataset <- examples_changepoints$simple
head(dataset)

# Configure ChangeFinder-LR detector
model <- hcp_cf_lr()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected change points
print(detection[(detection$event),])
```

hcp_chow	<i>Chow Test (structural break)</i>
----------	-------------------------------------

Description

Change-point detection for linear models using F-based structural break tests from the strucchange package [doi:10.18637/jss.v007.i02](https://doi.org/10.18637/jss.v007.i02). Wraps the Fstats and breakpoints implementations from the strucchange package.

Usage

```
hcp_chow()
```

Value

hcp_chow object

Examples

```
library(daltoolbox)

# Load change-point example data
data(examples_changepoints)

# Use a simple example
dataset <- examples_changepoints$simple
head(dataset)

# Configure the Chow detector
model <- hcp_chow()

# Fit the detector (no-op for Chow)
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected change points
print(detection[(detection$event),])
```

hcp_garch	<i>Change Finder using GARCH</i>
-----------	----------------------------------

Description

Change-point detection for variance shifts using a GARCH-based residual model. The detector flags change points when the observed series departs from the expected volatility pattern estimated by the fitted GARCH model. Wraps the GARCH model presented in the rugarch package.

Usage

```
hcp_garch(sw_size = 5)
```

Arguments

```
sw_size      Sliding window size
```

Value

```
hcp_garch object
```

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

# Load change-point example data
data(examples_changepoints)

# Use a volatility example
dataset <- examples_changepoints$volatility
head(dataset)

# Configure ChangeFinder-GARCH detector
model <- hcp_garch()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected change points
print(detection[(detection$event),])
```

hcp_gft

Generalized Fluctuation Test (GFT)

Description

Structural change detection using generalized fluctuation tests via `strucchange::breakpoints()`
doi:10.18637/jss.v007.i02.

Usage

```
hcp_gft()
```

Value

hcp_gft object

References

- Zeileis A, Leisch F, Kleiber C, Hornik K (2002). strucchange: An R package for testing for structural change in linear regression models. *Journal of Statistical Software*, 7(2). doi:10.18637/jss.v007.i02
- Zeileis A, Kleiber C, Krämer W, Hornik K (2003). Testing and dating of structural changes in practice. *Computational Statistics & Data Analysis*, 44(1):109–123.

Examples

```
library(daltoolbox)

# Load change-point example data
data(examples_changepoints)

# Use a simple example
dataset <- examples_changepoints$simple
head(dataset)

# Configure the GFT detector
model <- hcp_gft()

# Fit the detector (no-op for GFT)
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected change points
print(detection[(detection$event),])
```

hcp_kswin

KSWIN change-point detector

Description

Kolmogorov-Smirnov Windowing for univariate time series. The detector keeps a sliding window, compares an early sample against the most recent observations, and flags a changepoint when the two empirical distributions differ significantly.

This implementation is restricted to univariate numeric series and is intended to capture virtual drift on the signal directly, without any classifier.

Usage

```
hcp_kswin(window_size = 100, stat_size = 30, alpha = 0.005, data = NULL)
```

Arguments

window_size	Size of the sliding window.
stat_size	Size of the statistic subwindow used for the KS test.
alpha	Significance level for the KS test.
data	Optional initial window content.

Value

An hcp_kswin object.

References

- Raab C, Heusinger M, Schleif FM (2020). Reactive Soft Prototype Computing for Concept Drift Streams. *Neurocomputing*.
- Bifet A, Gavaldà R (2007). Learning from time-changing data with adaptive windowing. *SIAM International Conference on Data Mining*.

hcp_page_hinkley	<i>Page-Hinkley change-point detector</i>
------------------	---

Description

Online change-point detection for univariate time series using the classical Page-Hinkley statistic. The detector accumulates deviations from the running mean and raises a changepoint when the cumulative score crosses the configured threshold.

This implementation is restricted to univariate numeric series. It is meant to capture virtual drift on the observed signal directly, without any classifier or multivariate preprocessing.

Usage

```
hcp_page_hinkley(  
  min_instances = 30,  
  delta = 0.005,  
  threshold = 50,  
  alpha = 1 - 1e-04  
)
```

Arguments

min_instances	Minimum number of observations required before a change can be reported.
delta	Slack term subtracted from the deviation score.
threshold	Detection threshold for the cumulative statistic.
alpha	Forgetting factor applied to the cumulative score.

Value

An hcp_page_hinkley object.

References

- Page ES (1954). Continuous Inspection Schemes. *Biometrika*, 41(1/2), 100-115.
- Raab C, Heusinger M, Schleif FM (2020). Reactive Soft Prototype Computing for Concept Drift Streams. *Neurocomputing*.

hcp_pelt

Pruned Exact Linear Time (PELT)

Description

Multiple change-point detection using the PELT algorithm for mean/variance with a linear-time cost under suitable penalty choices. This function wraps the PELT implementation in the changepoint package.

Usage

```
hcp_pelt()
```

Details

PELT performs optimal partitioning while pruning candidate change-point locations to achieve near-linear computational cost.

Value

hcp_pelt object.

References

- Killick R, Fearnhead P, Eckley IA (2012). Optimal detection of changepoints with a linear computational cost. *JASA*, 107(500):1590–1598.

Examples

```
library(daltoolbox)

# Load change-point example data
data(examples_changepoints)

# Use a simple example
dataset <- examples_changepoints$simple
head(dataset)

# Configure the PELT detector
```

```
model <- hcp_pelt()

# Fit the detector (no-op for PELT)
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected change points
print(detection[(detection$event),])
```

hcp_scp

Seminal change point

Description

Window-based change-point detection that compares two local linear models fitted on each sliding window: one using the full window and another using the same window split around its central observation. The difference between the two residual summaries is used as the change score.

The method is called "seminal" because the paper defines a seminal point for each window family, i.e. the central observation used to split the local regression into two sides. This makes the detector a local family method based on windows rather than a global segmentation algorithm.

Usage

```
hcp_scp(sw_size = 30)
```

Arguments

`sw_size` Sliding window size.

Value

hcp_scp object

References

- The seminal change-point paper referenced in Event Detection from Time Series Data.
- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

# Load change-point example data
data(examples_changepoints)

# Use a simple example
dataset <- examples_changepoints$simple
head(dataset)

# Configure the seminal change-point detector
model <- hcp_scp()

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected change points
print(detection[(detection$event),])
```

hcp_waypoint	<i>Waypoint: adaptive change-point detection with autoencoder and CUSUM</i>
--------------	---

Description

Implements the adaptive change-point detector described in the associated SBBD article: a non-supervised autoencoder learns a reference regime from temporal windows, the reconstruction error is standardized on a recent buffer, and a bilateral CUSUM supervisor validates persistent deviations. When a change is confirmed, the model is retrained on recent data and the supervisor is reset.

Usage

```
hcp_waypoint(  
  input_size,  
  encode_size,  
  warmup = 500,  
  retrain_size = 300,  
  buffer_size = 100,  
  k_factor = 0.35,  
  h_low = 3.5,  
  h_high = 6,  
  prob_tau = 0.997,  
  epochs_init = 40,  
  epochs_retrain = 20,
```

```

    encoderclass = autoenc_base_ed,
    ...
)

```

Arguments

<code>input_size</code>	Integer. Window size used to build autoencoder samples.
<code>encode_size</code>	Integer. Latent size for the autoencoder.
<code>warmup</code>	Integer. Number of leading observations used to initialize the model.
<code>retrain_size</code>	Integer. Number of recent observations used when retraining after a confirmed change.
<code>buffer_size</code>	Integer. Number of previous residuals used to standardize the current reconstruction error.
<code>k_factor</code>	Numeric. CUSUM reference value (k).
<code>h_low</code>	Numeric. Warning threshold for the bilateral CUSUM supervisor.
<code>h_high</code>	Numeric. Confirmation threshold for the bilateral CUSUM supervisor.
<code>prob_tau</code>	Numeric. Quantile used to estimate the residual threshold from the warm-up regime.
<code>epochs_init</code>	Integer. Epochs for the initial autoencoder training.
<code>epochs_retrain</code>	Integer. Epochs for retraining after a confirmed change.
<code>encoderclass</code>	DALToolbox autoencoder constructor. Defaults to <code>autoenc_base_ed</code> .
<code>...</code>	Additional arguments forwarded to <code>encoderclass</code> ; these are the autoencoder-specific parameters, not <code>hcp_waypoint</code> parameters.

Details

The method separates representation and decision:

- the autoencoder reconstructs windows and produces a scalar reconstruction error;
- the error is standardized with a rolling buffer;
- a bilateral CUSUM with lower and upper thresholds (`h_low`, `h_high`) acts as the statistical supervisor;
- after confirmation, the autoencoder is retrained on the most recent regime.

This detector is intended for regime-change monitoring rather than isolated anomaly marking.

Value

`hcp_waypoint` object.

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. (2025). *Event Detection in Time Series*.
- Salles, R. et al. (2020). Harbinger: Um framework para integração e análise de métodos de detecção de eventos em séries temporais. SBBD.
- Ygorra, B. et al. (2021). Monitoring loss of tropical forest cover from Sentinel-1 time-series: A CuSum-based approach.
- Ygorra, B. et al. (2024). A near-real-time tropical deforestation monitoring algorithm based on the CuSum change detection method.
- De Ryck, T. et al. (2021). Change Point Detection in Time Series Data Using Autoencoders with a Time-Invariant Representation.
- Cao, Z. et al. (2024). Change Point Detection in Multi-Channel Time Series via a Time-Invariant Representation.
- Corizzo, R. et al. (2022). CPDGA: Change point driven growing auto-encoder for lifelong anomaly detection.

Examples

```
library(daltoolbox)

data(examples_changepoints)
dataset <- examples_changepoints$simple

model <- hcp_waypoint(input_size = 12, encode_size = 4)
model <- fit(model, dataset$serie)
detection <- detect(model, dataset$serie)
print(detection[detection$event, ])
```

hdis_mp

Discord discovery using Matrix Profile

Description

Discovers rare, dissimilar subsequences (discords) using Matrix Profile as implemented in the `tcmp` package [doi:10.32614/RJ-2020-021](https://doi.org/10.32614/RJ-2020-021).

Usage

```
hdis_mp(mode = "stamp", w, qtd)
```

Arguments

mode	Character. Algorithm: one of "stomp", "stamp", "simple", "mstomp", "scrimp", "valmod", "pmp".
w	Integer. Subsequence window size.
qtd	Integer. Number of discords to return (≥ 3 recommended).

Value

hdis_mp object.

References

- Yeh CCM, et al. (2016). Matrix Profile I/II: All-pairs similarity joins and scalable time series motifs/discord discovery. IEEE ICDM.
- Tavenard R, et al. tsmpr: The Matrix Profile in R. The R Journal (2020). doi:10.32614/RJ-2020-021

Examples

```
library(daltoolbox)

# Load motif/discord example data
data(examples_motifs)

# Use a simple sequence example
dataset <- examples_motifs$simple
head(dataset)

# Configure discord discovery via Matrix Profile
model <- hdis_mp("stamp", 4, 3)

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected discords
print(detection[(detection$event),])
```

hdis_sax

Discord discovery using SAX

Description

Discord discovery using SAX [doi:10.1007/s10618-007-0064-z](https://doi.org/10.1007/s10618-007-0064-z)

Usage

```
hdis_sax(a, w, qtd = 2)
```

Arguments

a	alphabet size
w	word size
qtd	number of occurrences to be classified as discords

Value

hdis_sax object

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

# Load motif/discord example data
data(examples_motifs)

# Use a simple sequence example
dataset <- examples_motifs$simple
head(dataset)

# Configure discord discovery via SAX
model <- hdis_sax(26, 3, 3)

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected discords
print(detection[(detection$event),])
```

hmo_mp

Motif discovery using Matrix Profile

Description

Discovers repeated subsequences (motifs) using Matrix Profile methods as implemented in the `tsmp` package doi:10.32614/RJ-2020-021.

Usage

```
hmo_mp(mode = "stamp", w, qtd)
```

Arguments

mode	Character. Algorithm: one of "stomp", "stamp", "simple", "mstomp", "scrimp", "valmod", "pmp".
w	Integer. Subsequence window size.
qtd	Integer. Minimum number of occurrences to classify as a motif.

Value

hmo_mp object.

References

- Yeh CCM, et al. (2016). Matrix Profile I/II: All-pairs similarity joins and scalable time series motifs/discord discovery. IEEE ICDM.
- Tavenard R, et al. tsmp: The Matrix Profile in R. The R Journal (2020). doi:10.32614/RJ-2020-021

Examples

```
library(daltoolbox)

# Load motif example data
data(examples_motifs)

# Use a simple sequence example
dataset <- examples_motifs$simple
head(dataset)

# Configure motif discovery via Matrix Profile
model <- hmo_mp("stamp", 4, 3)

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected motifs
print(detection[(detection$event),])
```

hmo_sax

Motif discovery using SAX

Description

Discovers repeated subsequences (motifs) using a Symbolic Aggregate approXimation (SAX) representation [doi:10.1007/s10618-007-0064-z](https://doi.org/10.1007/s10618-007-0064-z). Subsequences are discretized and grouped by symbolic words; frequently occurring words indicate motifs.

Usage

```
hmo_sax(a, w, qtd = 2)
```

Arguments

a	Integer. Alphabet size.
w	Integer. Word/window size.
qtd	Integer. Minimum number of occurrences to classify as a motif.

Value

hmo_sax object.

References

- Lin J, Keogh E, Lonardi S, Chiu B (2007). A symbolic representation of time series, with implications for streaming algorithms. *Data Mining and Knowledge Discovery* 15, 107–144.

Examples

```
library(daltoolbox)

# Load motif example data
data(examples_motifs)

# Use a simple sequence example
dataset <- examples_motifs$simple
head(dataset)

# Configure SAX-based motif discovery
model <- hmo_sax(26, 3, 3)

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected motifs
print(detection[(detection$event),])
```

hmo_xsax

Motif discovery using XSAX

Description

Discovers repeated subsequences (motifs) using an extended SAX (XSAX) representation that supports a larger alphanumeric alphabet.

Usage

```
hmo_xsax(a, w, qtd)
```

Arguments

a	Integer. Alphabet size.
w	Integer. Word/window size.
qtd	Integer. Minimum number of occurrences to be classified as motifs.

Value

hmo_xsax object.

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

Examples

```
library(daltoolbox)

# Load motif example data
data(examples_motifs)

# Use a simple sequence example
dataset <- examples_motifs$simple
head(dataset)

# Configure XSAX-based motif discovery
model <- hmo_xsax(37, 3, 3)

# Fit the model
model <- fit(model, dataset$serie)

# Run detection
detection <- detect(model, dataset$serie)

# Show detected motifs
print(detection[(detection$event),])
```

hmu_pca

Multivariate anomaly detector using PCA

Description

Projects multivariate observations onto principal components and flags large reconstruction errors as anomalies. Based on classical PCA.

Usage

```
hmu_pca()
```

Details

The series is standardized, PCA is computed, and data are reconstructed from principal components. The reconstruction error is summarized and thresholded.

Value

hmu_pca object.

References

- Jolliffe IT (2002). *Principal Component Analysis*. Springer.

Examples

```
library(daltoolbox)

# Load multivariate example data
data(examples_harbinger)

# Use a multidimensional time series
dataset <- examples_harbinger$multidimensional
head(dataset)

# Configure PCA-based anomaly detector
model <- hmu_pca()

# Fit the model (example uses first two columns)
model <- fit(model, dataset[,1:2])

# Run detection
detection <- detect(model, dataset[,1:2])

# Show detected anomalies
print(detection[(detection$event),])

# Evaluate detections
evaluation <- evaluate(model, detection$event, dataset$event)
print(evaluation$confMatrix)
```

loadfulldata

Load full dataset from mini data object

Description

The mini datasets stored in `data/` include an `attr(url)` pointing to the full dataset in `harbinger/`. This helper downloads and loads the full data.

Usage

```
loadfulldata(x, envir = parent.frame())
```

Arguments

`x` Dataset object or its name (string or symbol).
`envir` Environment to load the full dataset into.

Value

The full dataset object.

Examples

```
data(A1Benchmark)
A1Benchmark <- loadfulldata(A1Benchmark)
```

 mas

Moving average smoothing

Description

The `mas()` function returns a simple moving average smoother of the provided time series.

Usage

```
mas(x, order)
```

Arguments

`x` A numeric vector or univariate time series.
`order` Order of moving average smoother.

Details

The moving average smoother transformation is given by

$$(1/k) * (x[t] + x[t + 1] + \dots + x[t + k - 1])$$

where $k=order$, t assume values in the range $1:(n-k+1)$, and $n=length(x)$. See also the [ma](#) of the forecast package.

Value

Numerical time series of length $length(x)-order+1$ containing the simple moving average smoothed values.

References

R.H. Shumway and D.S. Stoffer, 2010, Time Series Analysis and Its Applications: With R Examples. 3rd ed. 2011 edition ed. New York, Springer.

Examples

```
# Load change-point example data
data(examples_changepoints)

# Use a simple example
dataset <- examples_changepoints$simple
head(dataset)

# Compute a 5-point moving average
ma <- mas(dataset$serie, 5)
```

mit_bih_MLII

MIT-BIH Arrhythmia Database – MLII Lead

Description

Data collection with real-world time-series. MIT-BIH Arrhythmia Database (MIT-BIH). See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(mit_bih_MLII)
```

Format

A list of time series from the MLII sensor of the MIT-BIH Arrhythmia Database.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[doi:10.1109/51.932724](https://doi.org/10.1109/51.932724)

References

MIT-BIH Arrhythmia Database (MIT-BIH). See also: Moody, G. B., & Mark, R. G. (2001). The impact of the MIT-BIH Arrhythmia Database. IEEE Engineering in Medicine and Biology Magazine, 20(3), 45–50.

Examples

```
data(mit_bih_MLII)
data <- mit_bih_MLII[[1]]
series <- data$value
```

mit_bih_V1

MIT-BIH Arrhythmia Database – V1 Lead

Description

Data collection with real-world time-series. MIT-BIH Arrhythmia Database (MIT-BIH). See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(mit_bih_V1)
```

Format

A list of time series from the V1 sensor of the MIT-BIH Arrhythmia Database.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[doi:10.1109/51.932724](https://doi.org/10.1109/51.932724)

References

MIT-BIH Arrhythmia Database (MIT-BIH). See also: Moody, G. B., & Mark, R. G. (2001). The impact of the MIT-BIH Arrhythmia Database. *IEEE Engineering in Medicine and Biology Magazine*, 20(3), 45–50.

Examples

```
data(mit_bih_V1)
data <- mit_bih_V1[[1]]
series <- data$value
```

`mit_bih_V2`*MIT-BIH Arrhythmia Database – V2 Lead*

Description

Data collection with real-world time-series. MIT-BIH Arrhythmia Database (MIT-BIH). See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(mit_bih_V2)
```

Format

A list of time series from the V2 sensor of the MIT-BIH Arrhythmia Database.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[doi:10.1109/51.932724](https://doi.org/10.1109/51.932724)

References

MIT-BIH Arrhythmia Database (MIT-BIH). See also: Moody, G. B., & Mark, R. G. (2001). The impact of the MIT-BIH Arrhythmia Database. *IEEE Engineering in Medicine and Biology Magazine*, 20(3), 45–50.

Examples

```
data(mit_bih_V2)
data <- mit_bih_V2[[1]]
series <- data$value
```

`mit_bih_V5`*MIT-BIH Arrhythmia Database – V5 Lead*

Description

Data collection with real-world time-series. MIT-BIH Arrhythmia Database (MIT-BIH). See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(mit_bih_V5)
```

Format

A list of time series from the V5 sensor of the MIT-BIH Arrhythmia Database.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[doi:10.1109/51.932724](https://doi.org/10.1109/51.932724)

References

MIT-BIH Arrhythmia Database (MIT-BIH). See also: Moody, G. B., & Mark, R. G. (2001). The impact of the MIT-BIH Arrhythmia Database. *IEEE Engineering in Medicine and Biology Magazine*, 20(3), 45–50.

Examples

```
data(mit_bih_V5)
data <- mit_bih_V5[[1]]
series <- data$value
```

`nab_artificialWithAnomaly`*Numenta Anomaly Benchmark (NAB) – artificialWithAnomaly*

Description

Synthetic time series with injected anomalies from the Numenta Anomaly Benchmark (NAB). Designed for evaluating anomaly detection algorithms under controlled conditions. Labels available: Yes. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(nab_artificialWithAnomaly)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[Numenta Anomaly Benchmark \(NAB\) Dataset](#)

References

Lavin, A., & Ahmad, S. (2015). Evaluating real-time anomaly detection algorithms – the Numenta Anomaly Benchmark. 2015 IEEE 14th International Conference on Machine Learning and Applications (ICMLA).

Examples

```
data(nab_artificialWithAnomaly)
s <- nab_artificialWithAnomaly[[1]]
plot(ts(s$value), main = names(nab_artificialWithAnomaly)[1])
```

nab_realAdExchange *Numenta Anomaly Benchmark (NAB) – realAdExchange*

Description

Real-world time series with labeled anomalies from ad exchange data (NAB). Useful for evaluating detection methods on operational data. Labels available: Yes. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(nab_realAdExchange)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[Numenta Anomaly Benchmark \(NAB\) Dataset](#)

References

Lavin, A., & Ahmad, S. (2015). Evaluating real-time anomaly detection algorithms – the Numenta Anomaly Benchmark. 2015 IEEE 14th International Conference on Machine Learning and Applications (ICMLA).

Examples

```
data(nab_realAdExchange)
s <- nab_realAdExchange[[1]]
mean(s$event)
```

nab_realAWSCloudwatch *Numenta Anomaly Benchmark (NAB) realAWSCloudwatch*

Description

Data collection with real-world time-series. Real data from AWS Cloud with anomalies As part of the Numenta Anomaly Benchmark (NAB), this dataset contains time series with real and synthetic data. The real data comes from network monitoring and cloud computing. On the other hand, synthetic data simulate series with or without anomalies. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(nab_realAWSCloudwatch)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[Numenta Anomaly Benchmark \(NAB\) Dataset](#)

References

Lavin, A., & Ahmad, S. (2015). Evaluating real-time anomaly detection algorithms – the Numenta Anomaly Benchmark. 2015 IEEE 14th International Conference on Machine Learning and Applications (ICMLA).

Examples

```
data(nab_realAWSCloudwatch)
nab_grp <- nab_realAWSCloudwatch[[1]]
serie <- nab_grp[[1]]
```

nab_realKnownCause	<i>Numenta Anomaly Benchmark (NAB) realKnownCause</i>
--------------------	---

Description

Data collection with real-world time-series. Real data with anomalies As part of the Numenta Anomaly Benchmark (NAB), this dataset contains time series with real and synthetic data. The real data comes from network monitoring and cloud computing. On the other hand, synthetic data simulate series with or without anomalies. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(nab_realKnownCause)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[Numenta Anomaly Benchmark \(NAB\) Dataset](#)

References

Lavin, A., & Ahmad, S. (2015). Evaluating real-time anomaly detection algorithms – the Numenta Anomaly Benchmark. 2015 IEEE 14th International Conference on Machine Learning and Applications (ICMLA).

Examples

```
data(nab_realKnownCause)
nab_grp <- nab_realKnownCause[[1]]
serie <- nab_grp[[1]]
```

nab_realTraffic	<i>Numenta Anomaly Benchmark (NAB) realTraffic</i>
-----------------	--

Description

Data collection with real-world time-series. Real data from online data traffic with anomalies As part of the Numenta Anomaly Benchmark (NAB), this dataset contains time series with real and synthetic data. The real data comes from network monitoring and cloud computing. On the other hand, synthetic data simulate series with or without anomalies. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(nab_realTraffic)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[Numenta Anomaly Benchmark \(NAB\) Dataset](#)

References

Lavin, A., & Ahmad, S. (2015). Evaluating real-time anomaly detection algorithms – the Numenta Anomaly Benchmark. 2015 IEEE 14th International Conference on Machine Learning and Applications (ICMLA).

Examples

```
data(nab_realTraffic)
nab_grp <- nab_realTraffic[[1]]
serie <- nab_grp[[1]]
```

nab_realTweets	<i>Numenta Anomaly Benchmark (NAB) realTweets</i>
----------------	---

Description

Real-world time series with labeled anomalies from Twitter volumes (NAB). Labels available: Yes. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(nab_realTweets)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[Numenta Anomaly Benchmark \(NAB\) Dataset](#)

References

Lavin, A., & Ahmad, S. (2015). Evaluating real-time anomaly detection algorithms – the Numenta Anomaly Benchmark. 2015 IEEE 14th International Conference on Machine Learning and Applications (ICMLA).

Examples

```
data(nab_realTweets)
s <- nab_realTweets[[1]]
plot(ts(s$value), main = names(nab_realTweets)[1])
mean(s$event)
```

`oil_3w_Type_1`*Oil Wells Dataset – Type 1*

Description

First realistic dataset with real events in oil well drilling. The data available in this package consist of time series already analyzed and applied in research experiments by the DAL group (Data Analytics Lab). The series are divided into 7 groups (Type_0, Type_1, Type_2, Type_4, Type_5, Type_6, Type_7 and Type_8). Type 0 removed from this version due to file size. Creation date: 2019. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(oil_3w_Type_1)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[UCI Machine Learning Repository](#)

References

3W dataset (UCI repository). See also: Truong, C., Oudre, L., & Vayatis, N. (2020). Selective review of change point detection methods. *Signal Processing*, 167, 107299.

Examples

```
data(oil_3w_Type_1)
s <- oil_3w_Type_1[[1]]
plot(ts(s$p_tpt), main = names(oil_3w_Type_1)[1], ylab = "value")
```

`oil_3w_Type_2`*Oil Wells Dataset – Type 2*

Description

First realistic dataset with real events in oil well drilling. The data available in this package consist of time series already analyzed and applied in research experiments by the DAL group (Data Analytics Lab). The series are divided into 7 groups (Type_0, Type_1, Type_2, Type_4, Type_5, Type_6, Type_7 and Type_8). Creation date: 2019. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(oil_3w_Type_2)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[UCI Machine Learning Repository](#)

References

3W dataset (UCI repository). See also: Truong, C., Oudre, L., & Vayatis, N. (2020). Selective review of change point detection methods. *Signal Processing*, 167, 107299.

Examples

```
data(oil_3w_Type_2)
s <- oil_3w_Type_2[[1]]
mean(s$event) # proportion of change points
```

`oil_3w_Type_4`*Oil Wells Dataset – Type 4*

Description

First realistic dataset with real events in oil well drilling. The data available in this package consist of time series already analyzed and applied in research experiments by the DAL group (Data Analytics Lab). The series are divided into 7 groups (Type_0, Type_1, Type_2, Type_4, Type_5, Type_6, Type_7 and Type_8). Creation date: 2019. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(oil_3w_Type_4)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[UCI Machine Learning Repository](#)

References

3W dataset (UCI repository). See also: Truong, C., Oudre, L., & Vayatis, N. (2020). Selective review of change point detection methods. *Signal Processing*, 167, 107299.

Examples

```
data(oil_3w_Type_4)
serie <- oil_3w_Type_4[[1]]
```

`oil_3w_Type_5`*Oil Wells Dataset – Type 5*

Description

First realistic dataset with real events in oil well drilling. The data available in this package consist of time series already analyzed and applied in research experiments by the DAL group (Data Analytics Lab). The series are divided into 7 groups (Type_0, Type_1, Type_2, Type_4, Type_5, Type_6, Type_7 and Type_8). Creation date: 2019. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(oil_3w_Type_5)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[UCI Machine Learning Repository](#)

References

3W dataset (UCI repository). See also: Truong, C., Oudre, L., & Vayatis, N. (2020). Selective review of change point detection methods. *Signal Processing*, 167, 107299.

Examples

```
data(oil_3w_Type_5)
serie <- oil_3w_Type_5[[1]]
```

`oil_3w_Type_6`*Oil Wells Dataset – Type 6*

Description

First realistic dataset with real events in oil well drilling. The data available in this package consist of time series already analyzed and applied in research experiments by the DAL group (Data Analytics Lab). The series are divided into 7 groups (Type_0, Type_1, Type_2, Type_4, Type_5, Type_6, Type_7 and Type_8). Creation date: 2019. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(oil_3w_Type_6)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[UCI Machine Learning Repository](#)

References

3W dataset (UCI repository). See also: Truong, C., Oudre, L., & Vayatis, N. (2020). Selective review of change point detection methods. *Signal Processing*, 167, 107299.

Examples

```
data(oil_3w_Type_6)
serie <- oil_3w_Type_6[[1]]
```

`oil_3w_Type_7`*Oil Wells Dataset – Type 7*

Description

First realistic dataset with real events in oil well drilling. The data available in this package consist of time series already analyzed and applied in research experiments by the DAL group (Data Analytics Lab). The series are divided into 7 groups (Type_0, Type_1, Type_2, Type_4, Type_5, Type_6, Type_7 and Type_8). Creation date: 2019. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(oil_3w_Type_7)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[UCI Machine Learning Repository](#)

References

3W dataset (UCI repository). See also: Truong, C., Oudre, L., & Vayatis, N. (2020). Selective review of change point detection methods. *Signal Processing*, 167, 107299.

Examples

```
data(oil_3w_Type_7)
serie <- oil_3w_Type_7[[1]]
```

`oil_3w_Type_8`*Oil Wells Dataset – Type 8*

Description

First realistic dataset with real events in oil well drilling. The data available in this package consist of time series already analyzed and applied in research experiments by the DAL group (Data Analytics Lab). The series are divided into 7 groups (Type_0, Type_1, Type_2, Type_4, Type_5, Type_6, Type_7 and Type_8). Creation date: 2019. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(oil_3w_Type_8)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[UCI Machine Learning Repository](#)

References

3W dataset (UCI repository). See also: Truong, C., Oudre, L., & Vayatis, N. (2020). Selective review of change point detection methods. *Signal Processing*, 167, 107299.

Examples

```
data(oil_3w_Type_8)
serie <- oil_3w_Type_8[[1]]
```

trans_sax	<i>SAX transformation</i>
-----------	---------------------------

Description

Symbolic Aggregate approXimation (SAX) discretization of a numeric time series. The series is z-normalized, quantile-binned, and mapped to an alphabet of size alpha.

Usage

```
trans_sax(alpha)
```

Arguments

alpha Integer. Alphabet size (2–26).

Value

A trans_sax transformer object.

References

- Lin J, Keogh E, Lonardi S, Chiu B (2007). A symbolic representation of time series, with implications for streaming algorithms. *Data Mining and Knowledge Discovery* 15, 107–144.

Examples

```
library(daltoolbox)
vector <- 1:52
model <- trans_sax(alpha = 26)
model <- fit(model, vector)
xvector <- transform(model, vector)
print(xvector)
```

trans_xsax	<i>XSAX transformation</i>
------------	----------------------------

Description

Extended SAX (XSAX) discretization using a larger alphanumeric alphabet for finer symbolic resolution.

Usage

```
trans_xsax(alpha)
```

Arguments

alpha Integer. Alphabet size (2–36).

Value

A `trans_xsax` transformer object.

References

- Ogasawara, E., Salles, R., Porto, F., Pacitti, E. Event Detection in Time Series. 1st ed. Cham: Springer Nature Switzerland, 2025. doi:10.1007/978-3-031-75941-3

See Also

`trans_sax`

Examples

```
library(daltoolbox)
vector <- 1:52
model <- trans_xsax(alpha = 36)
model <- fit(model, vector)
xvector <- transform(model, vector)
print(xvector)
```

ucr_ecg

UCR Anomaly Archive – ECG

Description

Data collection with real-world time-series. Real ECG time series with labeled anomalous intervals. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(ucr_ecg)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[UCR Anomaly Archive](#)

References

UCR Time Series Anomaly Archive. See also: Chandola, V., Banerjee, A., & Kumar, V. (2009). Anomaly detection: A survey. *ACM Computing Surveys*, 41(3), 1–58.

Examples

```
data(ucr_ecg)
# Access and plot a series
s <- ucr_ecg[[1]]
plot(ts(s$value), main = names(ucr_ecg)[1])
```

ucr_int_bleeding *UCR Anomaly Archive – Internal Bleeding*

Description

Data collection with real-world time-series. Real physiological time series with labeled anomalous intervals. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(ucr_int_bleeding)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[UCR Anomaly Archive](#)

References

UCR Time Series Anomaly Archive. See also: Chandola, V., Banerjee, A., & Kumar, V. (2009). Anomaly detection: A survey. *ACM Computing Surveys*, 41(3), 1–58.

Examples

```
data(ucr_int_bleeding)
s <- ucr_int_bleeding[[1]]
plot(ts(s$value))
```

ucr_nasa

UCR Anomaly Archive – NASA Spacecraft

Description

Data collection with real-world time-series. Real NASA spacecraft monitoring time series with labeled anomalous intervals. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(ucr_nasa)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[UCR Anomaly Archive](#)

References

UCR Time Series Anomaly Archive. See also: Chandola, V., Banerjee, A., & Kumar, V. (2009). Anomaly detection: A survey. *ACM Computing Surveys*, 41(3), 1–58.

Examples

```
data(ucr_nasa)
s <- ucr_nasa[[1]]
mean(s$event)
```

ucr_power_demand *UCR Anomaly Archive – Italian Power Demand*

Description

Data collection with real-world time-series. Real power demand time series with labeled anomalous intervals. See [cefet-rj-dal/united](#) for detailed guidance on using this package and the other datasets available in it. Labels available? Yes

Usage

```
data(ucr_power_demand)
```

Format

A list of time series.

Details

This package ships a mini version of the dataset. Use `loadfulldata()` to download and load the full dataset from the URL stored in `attr(url)`.

Source

[UCR Anomaly Archive](#)

References

UCR Time Series Anomaly Archive. See also: Chandola, V., Banerjee, A., & Kumar, V. (2009). Anomaly detection: A survey. *ACM Computing Surveys*, 41(3), 1–58.

Examples

```
data(ucr_power_demand)
s <- ucr_power_demand[[1]]
summary(s$value)
```

Index

- * **average**
 - mas, [64](#)
- * **daltoolbox::transform**
 - mas, [64](#)
- * **datasets**
 - A1Benchmark, [4](#)
 - A2Benchmark, [5](#)
 - A3Benchmark, [6](#)
 - A4Benchmark, [7](#)
 - examples_anomalies, [9](#)
 - examples_changepoints, [10](#)
 - examples_harbinger, [11](#)
 - examples_motifs, [12](#)
 - gecco, [13](#)
 - mit_bih_MLII, [65](#)
 - mit_bih_V1, [66](#)
 - mit_bih_V2, [67](#)
 - mit_bih_V5, [68](#)
 - nab_artificialWithAnomaly, [69](#)
 - nab_realAdExchange, [70](#)
 - nab_realAWSCloudwatch, [71](#)
 - nab_realKnownCause, [72](#)
 - nab_realTraffic, [73](#)
 - nab_realTweets, [74](#)
 - oil_3w_Type_1, [75](#)
 - oil_3w_Type_2, [76](#)
 - oil_3w_Type_4, [77](#)
 - oil_3w_Type_5, [78](#)
 - oil_3w_Type_6, [79](#)
 - oil_3w_Type_7, [80](#)
 - oil_3w_Type_8, [81](#)
 - ucr_ecg, [83](#)
 - ucr_int_bleeding, [84](#)
 - ucr_nasa, [85](#)
 - ucr_power_demand, [86](#)
- * **moving**
 - mas, [64](#)
- * **series**
 - mas, [64](#)
- * **smoother**
 - mas, [64](#)
- * **time**
 - mas, [64](#)
- A1Benchmark, [4](#)
- A2Benchmark, [5](#)
- A3Benchmark, [6](#)
- A4Benchmark, [7](#)
- context, [44](#)
- detect, [8](#)
- detect.har_ensemble_fuzzy, [8](#)
- examples_anomalies, [9](#)
- examples_changepoints, [10](#)
- examples_harbinger, [11](#)
- examples_motifs, [12](#)
- gecco, [13](#)
- han_autoencoder, [33](#)
- hanc_ml, [16](#)
- hanct_dtw, [14](#)
- hanct_kmeans, [15](#)
- hanr_arima, [17](#)
- hanr_emd, [18](#)
- hanr_fbiad, [19](#)
- hanr_fft, [20](#)
- hanr_fft_amoc, [21](#)
- hanr_fft_amoc_cusum, [22](#)
- hanr_fft_binseg, [23](#)
- hanr_fft_binseg_cusum, [24](#)
- hanr_fft_sma, [25](#)
- hanr_garch, [26](#)
- hanr_histogram, [27](#)
- hanr_ml, [28](#)
- hanr_remd, [29](#)
- hanr_rtad, [30](#)
- hanr_wavelet, [31](#)

har_ensemble, 36
har_ensemble_fuzzy, 37
har_ensemble_plot, 38
har_ensemble_plot_models, 38
har_eval, 39
har_eval_soft, 40
har_plot, 41
harbinger, 34
harutils, 35
hcp_amoc, 43
hcp_binseg, 44
hcp_bocpd, 45
hcp_cf_arima, 46
hcp_cf_ets, 47
hcp_cf_lr, 48
hcp_chow, 49
hcp_garch, 49
hcp_gft, 50
hcp_kswin, 51
hcp_page_hinkley, 52
hcp_pelt, 53
hcp_scp, 54
hcp_waypoint, 55
hdis_mp, 57
hdis_sax, 58
hmo_mp, 59
hmo_sax, 60
hmo_xsax, 61
hmu_pca, 62

loadfulldata, 63

ma, 64
mas, 64
mit_bih_MLII, 65
mit_bih_V1, 66
mit_bih_V2, 67
mit_bih_V5, 68

nab_artificialWithAnomaly, 69
nab_realAdExchange, 70
nab_realAWSCloudwatch, 71
nab_realKnownCause, 72
nab_realTraffic, 73
nab_realTweets, 74

oil_3w_Type_1, 75
oil_3w_Type_2, 76
oil_3w_Type_4, 77
oil_3w_Type_5, 78
oil_3w_Type_6, 79
oil_3w_Type_7, 80
oil_3w_Type_8, 81

trans_sax, 82
trans_xsax, 82

ucr_ecg, 83
ucr_int_bleeding, 84
ucr_nasa, 85
ucr_power_demand, 86