

Package ‘hypertext’

May 8, 2026

Title 'HTML' Element Construction

Version 1.2.0

Description Provides a deterministic, framework-agnostic Domain-Specific Language for building 'HTML' nodes and rendering them to a string.

License MIT + file LICENSE

URL <https://github.com/sigflux/hypertext>

BugReports <https://github.com/sigflux/hypertext/issues>

Encoding UTF-8

RoxygenNote 7.3.3

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Kennedy Mwavu [aut, cre] (ORCID:
<<https://orcid.org/0009-0006-3157-7234>>),
Sigflux [cph, fnd]

Maintainer Kennedy Mwavu <mwavukennedy@gmail.com>

Repository CRAN

Date/Publication 2026-04-17 20:50:02 UTC

Contents

doctype	2
raw_html	2
render	3
tag	4
tags	5
tag_list	6
Index	7

doctype	<i>Render the <code><!DOCTYPE html></code> declaration</i>
---------	--

Description

Convenience wrapper around `raw_html()` that returns the HTML5 document-type declaration. Useful when building a full page.

Usage

```
doctype()
```

Value

A "hypertext.raw" object containing `<!DOCTYPE html>`.

Examples

```
page <- tag_list(  
  doctype(),  
  tags$html(  
    tags$head(tags$title("Home")),  
    tags$body(tags$h1("Welcome"))  
  )  
)  
render(page)
```

raw_html	<i>Mark a string as raw HTML</i>
----------	----------------------------------

Description

Wraps one or more character strings so that `render()` outputs them verbatim, **without** escaping HTML special characters.

Usage

```
raw_html(...)
```

Arguments

... Character strings of raw HTML /// Optional.

Details

This is useful for injecting pre-rendered HTML, inline `<script>/<style>` blocks, SVG markup, or any content that should not be entity-escaped.

Value

A character vector of class "hypertext.raw".

Examples

```
raw_html("<script>alert('hi')</script>")
render(tags$div(raw_html("<em>already formatted</em>")))
```

render	<i>Render an HTML node tree to a character string</i>
--------	---

Description

Converts a `hypertext.tag` object (and all its descendants) into an HTML string. Text children are escaped; nested `hypertext.tag` children are rendered recursively.

Usage

```
render(x, ...)

## S3 method for class 'hypertext.tag'
render(x, file = "", write_mode = c("overwrite", "append"), ...)

## Default S3 method:
render(x, file = "", write_mode = c("overwrite", "append"), ...)

## S3 method for class 'hypertext.raw'
render(x, file = "", write_mode = c("overwrite", "append"), ...)

## S3 method for class 'list'
render(x, file = "", write_mode = c("overwrite", "append"), ...)
```

Arguments

x	hypertext.tag object, a string, or a list of these <i>///</i> Required.
...	Further arguments passed from or to other methods.
file	String <i>///</i> Optional. Path to file to print to.
write_mode	String <i>///</i> Optional. Either "overwrite" (default) which overwrites the contents of file, or "append" which appends the HTML string to file.

Details

When `file` is provided, the rendered HTML is written to the specified file via `cat()` and the HTML string is returned invisibly.

Value

A single character string of HTML.

Examples

```
page <- tags$html(
  tags$head(
    tags$title("Home")
  ),
  tags$body(
    tags$h1("Welcome")
  )
)

# return HTML as a string:
render(page)

## Not run:
# write to a file:
render(page, file = "index.html")

## End(Not run)
```

tag

Create an HTML element node

Description

Low-level constructor. Named arguments become attributes; unnamed arguments become children (text or nested nodes).

Usage

```
tag(tag_name, ..., tag_type = c("normal", "void"))
```

Arguments

tag_name	String /// Required. The HTML element name.
...	Attributes (named) and children (unnamed) /// Optional.
tag_type	String /// Optional. Either "normal" (default) for a standard element with children, or "void" for a self-closing element whose children are ignored.

Value

List of class "hypertext.tag" with components tag, attrs, children, and tag_type.

Examples

```
# web component
tag(tag_name = "calcite-action-bar", layout = "horizontal")

# custom element with children
tag(
  tag_name = "my-card",
  class = "shadow",
  tag(tag_name = "my-card-header", "Title"),
  tag(tag_name = "my-card-body", "Content")
)

# custom void element
tag(tag_name = "my-icon", name = "home", tag_type = "void")
```

tags

*HTML tag functions***Description**

A named list of functions, one per HTML5 element. Access individual tags with `tags$div(...)`, `tags$p(...)`, etc.

Usage

```
tags
```

Format

An object of class `list` of length 115.

Details

Named arguments become HTML attributes; unnamed arguments become child nodes or text content.

Boolean / valueless attributes

Pass `NA` or `TRUE` as the attribute value to produce a valueless attribute (e.g. `disabled`). `FALSE` or `NULL` suppresses the attribute entirely.

Multi-value attributes

Character vectors of length > 1 are collapsed with a space, so `class = c("a", "b")` renders as `class="a b"`.

Examples

```
tags$p(class = "lead", "Hello, world!")
render(tags$div(id = "app", tags$h1("Title")))
```

tag_list	<i>Create a tag list (sibling container)</i>
----------	--

Description

Useful when you want to collect sibling nodes into a single object without wrapping them in a parent element.

Usage

```
tag_list(...)
```

Arguments

... Tags, text, or other renderable objects /// Optional.

Value

A list of class "hypertext.tag.list".

Examples

```
t1 <- tag_list(tags$p("one"), tags$p("two"))
render(t1)
```

Index

* **datasets**
tags, 5

cat(), 3

doctype, 2

raw_html, 2
raw_html(), 2
render, 3
render(), 2

tag, 4
tag_list, 6
tags, 5