

Package ‘iccCounts’

May 8, 2026

Title Intraclass Correlation Coefficient for Count Data

Version 1.1.4

Maintainer Josep L. Carrasco <jl.carrasco@ub.edu>

Depends R (>= 4.0)

Imports glmmTMB, ggplot2, Deriv, gridExtra, VGAM, dplyr (>= 1.1.0)

Suggests knitr, rmarkdown

Description Estimates the intraclass correlation coefficient (ICC) for count data to assess repeatability (intra-methods concordance) and concordance (between-method concordance). In the concordance setting, the ICC is equivalent to the concordance correlation coefficient estimated by variance components. The ICC is estimated using the estimates from generalized linear mixed models. The within-subjects distributions considered are: Poisson; Negative Binomial with additive and proportional extradispersion; Zero-Inflated Poisson; and Zero-Inflated Negative Binomial with additive and proportional extradispersion. The statistical methodology used to estimate the ICC with count data can be found in Carrasco (2010) <[doi:10.1111/j.1541-0420.2009.01335.x](https://doi.org/10.1111/j.1541-0420.2009.01335.x)>.

VignetteBuilder knitr

Encoding UTF-8

License GPL (>= 2)

LazyData true

RoxygenNote 7.3.3

NeedsCompilation no

Author Josep L. Carrasco [aut, cre]

Repository CRAN

Date/Publication 2026-01-30 12:00:02 UTC

Contents

AF	2
DispersionTest	2
EPP	3
GOF_check	4

Grimso	5
ICC	5
icc_counts	6
plot.GOF	8
plot_BA	9
VarComp	10
ZeroTest	11

Index	12
--------------	-----------

AF	<i>CD34+ count cell data</i>
----	------------------------------

Description

A dataset containing CD34+ count cell data obtained by two methods

Usage

AF

Format

A data frame with 40 rows and 3 variables:

y CD34+ counts

id Subject

met Method

References

Fornas, O., Garcia, J., and Petriz, J. (2000). Flow cytometry counting of CD34+ cells in whole blood. *Nature Medicine* 6, 833–836.

DispersionTest	<i>Dispersion test for GLMM</i>
----------------	---------------------------------

Description

Dispersion test for GLMM

Usage

DispersionTest(x)

Arguments

`x` An object of class *GOF* generated by *GOF_check* function.

Details

The function prints the dispersion of sample randomized quantile residuals (RQR) and the simulated P-value.

Value

A vector with the sample RQR dispersion and the P-value.

See Also

[GOF_check\(\)](#)

Examples

```
# Poisson model. Repeatability setting.
iccpois<-icc_counts(EPP,y="Social",id="id")
iccpois.gof<-GOF_check(iccpois)
DispersionTest(iccpois.gof)
```

EPP

Sparrow fledglings paternity data

Description

A dataset containing the counts of fledglings a male had in every breeding season

Usage

EPP

Format

A data frame with 193 rows and 3 variables:

Social Fledglings counts

id Subject identifier

Year Breeding season

References

Schroeder, J., Burke, T., Mannarelli, M. E., Dawson, D. A., & Nakagawa, S. (2012). Maternal effects and heritability of annual productivity. *Journal of Evolutionary Biology*, 25, 149– 156.

GOF_check

Goodness of fit for GLMM

Description

Assessment of goodness of fit for GLMM

Usage

```
GOF_check(x, nsim = 100, alpha = 0.05)
```

Arguments

x	An object of clas <i>iccc</i> .
nsim	Number of simulations to run. Default is set to 100.
alpha	Level of significance

Details

Randomized quantile residuals are computed for the fitted model. Simulations based on the fitted model are generated and the model is refitted to each simulated dataset. Envelopes for RQR are built as the appropriate quantile (in relation to the level of significance) of RQR from the refitted models. Additionally, a test for dispersion and zero inflation are carried out by comparing the RQR dispersion and the number of zeros from the original model and data to those from the refitted models and simulated data.

Value

An object of class *GOF* for which method *plot* is available. A list with the following components:

- *plot_env*. Plot of RQR envelopes with the original RQR.
- *plot_var*. Plot of the simulated RQR dispersion.
- *plot_zi*. Plot of the count of zeros in the simulated datasets.
- *res_var*. Dispersion of RQR from the original sample.
- *pval_var*. Proportion of simulated RQR dispersion that are greater than the original dispersion that can be interpreted as a simulated P-value to check the goodness of fit on dispersion.
- *zero_count*. Count of zeros in the original sample.
- *pval_zi*. Proportion of simulated zero count that are greater than that of the original sample. It can be interpreted as a simulated P-value to check the hypothesis of zero-inflation.

See Also

[plot.GOF\(\)](#), [DispersionTest\(\)](#), [ZeroTest\(\)](#)

Examples

```
# Poisson model. Repeatability setting.
iccpois<-icc_counts(EPP,y="Social",id="id")
GOF_check(iccpois)
# Zero-inflated Poisson model. Repeatability setting
icczip<-icc_counts(EPP,y="Social",id="id",fam="zip")
GOF_check(icczip)
```

Grimso

Tick counts data

Description

A dataset containing the counts of ticks in Grimsö area

Usage

Grimso

Format

A data frame with 520 rows and 3 variables:

Tot Tick counts

TransectID Subject identifier

Round Identifier of repeated measurements

References

Kjellander, P.L., Aronsson, M., Bergvall, U.A. et al. (2021). Validating a common tick survey method: cloth-dragging and line transects. *Exp Appl Acarol* 83, 131–146.

ICC

Prints the intraclass correlation coefficient

Description

Prints the intraclass correlation coefficient (ICC)

Usage

```
ICC(x, digits = getOption("digits"))
```

Arguments

x An object of class *iccc*
digits Number of digits to print

Value

A vector with the ICC estimate, its standard error and confidence interval.

See Also

[icc_counts\(\)](#)

Examples

```
# Poisson model. Repeatability setting.  
iccpois<-icc_counts(Grimso,y="Tot",id="TransectID")  
ICC(iccpois)  
# Negative Binomial with proportional extra-dispersion. Concordance setting  
iccnb2<-icc_counts(AF,y="y",id="id",met="met",type="con",fam="nbinom2")  
ICC(iccnb2)  
# Zero-inflated Poisson model. Repeatability setting  
icczip<-icc_counts(EPP,y="Social",id="id",fam="zip")  
ICC(icczip)
```

icc_counts

Intraclass correlation coefficient (ICC) for count data

Description

Estimates the intraclass correlation coefficient (ICC) for count data

Usage

```
icc_counts(  
  data,  
  y,  
  id,  
  met = NULL,  
  type = c("rep", "con"),  
  fam = c("poisson", "nbinom1", "nbinom2", "zip", "zinb1", "zinb2"),  
  conf = 0.95  
)
```

Arguments

data	A data frame containing at least two columns: outcome and subject identifier. In case of estimating the ICC for concordance setting, a third column with the method identifier will be needed.
y	Character string indicating the name of the outcome column in the dataset.
id	Character string indicating the name of the subjects column in the dataset.
met	Character string indicating the name of the methods column in the dataset. Only needed in the concordance setting.
type	Character string. It chooses the setting in which the ICC should be estimated. Valid values are: "rep" (default) for repeatability setting; "con" for concordance setting.
fam	Character string. The within-subjects pdf to use. Valid options are: "poisson" (default) for Poisson pdf; "nbinom1" for Negative Binomial pdf with variance increasing linearly with the mean; "nbinom2" for Negative Binomial pdf with variance increasing quadratically with the mean; "zip" for zero-inflated Poisson pdf; "zinb1" for zero-inflated Negative Binomial nbinom1 pdf; "zinb2" for zero-inflated Negative Binomial nbinom2 pdf;
conf	Confidence level for the confidence interval estimation. Default value is set to 95%.

Details

The intraclass correlation coefficient (ICC) is estimated using the variance components of a generalized linear mixed model (GLMM) (Carrasco, 2010).

The GLMM is estimated using the *glmmTMB* package (Brooks et al. 2017). The ICC standard error is estimated by applying the delta method (Ver Hoef, 2012) using the variance-covariance matrix of parameters involved in the ICC estimate.

The parameters involved in the estimation of the ICC depends on the within-subjects pdf family chosen: the between-subjects variance, the between-methods variability (in case of concordance analysis), and parameters implicated in the within-subjects family chosen. In all cases the output includes the overall expectation identified as μ_i ; the between-subjects variance named as $BSVar$ (log-scale); the between-methods variability (in case of concordance analysis) named as $BMVar$ (log-scale).

In the Negative Binomial pdf with variance linearly increasing with the mean (Hardin and Hilbe, 2007),

$$Var(y_i) = \mu_i * (1 + r)$$

and Negative Binomial pdf with variance quadratically increasing with the mean (Hardin and Hilbe, 2007)

$$Var(y_i) = \mu_i * (1 + r * \mu_i)$$

the extra-dispersion parameter r is included in the output.

For zero-inflated models, the probability of observing an extra zero is included in the output as pi .

Value

An object of class *iccc*. The output is a list with the following components:

- *model*. An object of class *glmmTMB*. The estimated generalized linear mixed model.
- *ICC*. Estimate of the ICC, its standard error and confidence interval.
- *varcomp*. Variance components and parameters related to ICC expression.

References

Brooks, M. E., Kristensen, K., van Benthem, K. J., Magnusson, A., Berg, C. W., Nielsen, A., Skaug, H. J., Mächler, M. and Bolker, B. M. (2017). *glmmTMB* balances speed and flexibility among packages for zero-inflated generalized linear mixed modeling. *The R Journal*, 9(2), 378–400.

Carrasco, J. (2010). A Generalized Concordance Correlation Coefficient Based on the Variance Components Generalized Linear Mixed Models for Overdispersed Count Data. *Biometrics*, 66(3), 897-904.

W. Hardin and J. Hilbe. (2007). *Generalized Linear Models and Extensions*. Stata Press.

Ver Hoef, J.M. (2012) Who Invented the Delta Method?, *The American Statistician*, 66:2, 124-127,

Examples

```
# Poisson model. Repeatability setting.
iccpois<-icc_counts(Grimso,y="Tot",id="TransectID")
# Negative Binomial with proportional extra-dispersion. Concordance setting
iccnb2<-icc_counts(AF,y="y",id="id",met="met",type="con",fam="nbinom2")
# Zero-inflated Poisson model. Repeatability setting
icczip<-icc_counts(EPP,y="Social",id="id",fam="zip")
```

plot.GOF

Goodness of fit plots

Description

Draws the plots to assess the goodness of fit

Usage

```
## S3 method for class 'GOF'
plot(x, type = c("all", "envelope", "dispersion", "zeros"), ...)
```

Arguments

x	An object of class <i>GOF</i> generated by <i>GOF_check</i> function.
type	Which plot to draw. Values: <i>all</i> (default); <i>envelope</i> for envelopes of randomized quantile residuals; <i>dispersion</i> for plot to assess the dispersion; <i>zeros</i> for plot to assess the zero inflation.
...	Ignore

See Also[GOF_check\(\)](#)**Examples**

```
# Poisson model. Repeatability setting.
iccpois<-icc_counts(EPP,y="Social",id="id")
iccpois.gof<-GOF_check(iccpois)
plot(iccpois.gof)
plot(iccpois.gof,type="envelope")
plot(iccpois.gof,type="dispersion")
plot(iccpois.gof,type="zeros")
```

plot_BA

*Bland-Altman plot***Description**

Draws the Bland-Altman plot. The differences among pair of data from the same subject is represented on y-axis. The mean of data from the same subject is represented on x-axis. Additionally, a bar plot with the proportions of differences can be drawn.

Usage

```
plot_BA(data, y, id, rm = NULL, type = c("BA", "bars"))
```

Arguments

data	A data frame containing at least two columns: outcome and subject identifier.
y	Character string indicating the name of the outcome column in the data set.
id	Character string indicating the name of the subjects column in the data set.
rm	Optional. Character string indicating the name of column that stands for the repeated measurements from the same subjects in the dataset. Only needed to identify the differences in the Bland-Altman plot.
type	Character. Which plot has to be drawn? Default option is Bland-Altman plot ("BA" option). Alternatively, the bar plot of the proportion of the differences can be created ("bars" option).

Value

A list with the following components:

- *plot*. An object of class `ggplot`. The plot generated.
- *data*. An object of class `dataframe` that contains the data used to generated the plot.

Examples

```
plot_BA(EPP,y="Social",id="id")
plot_BA(EPP,y="Social",id="id",rm="Year")
plot_BA(EPP,y="Social",id="id",type="bars")
```

 VarComp

GLMM variance components

Description

Prints the GLMM variance components and related parameters to estimate the intraclass correlation coefficient (ICC)

Usage

```
VarComp(x, digits = getOption("digits"))
```

Arguments

x	An object of class <i>iccc</i>
digits	Number of digits to print

Value

A vector with the variance components and related parameters

See Also

[icc_counts\(\)](#)

Examples

```
# Poisson model. Repeatability setting.
iccpois<-icc_counts(Grimso,y="Tot",id="TransectID")
VarComp(iccpois)
# Negative Binomial with proportional extra-dispersion. Concordance setting
iccnb2<-icc_counts(AF,y="y",id="id",met="met",type="con",fam="nbinom2")
VarComp(iccnb2)
# Zero-inflated Poisson model. Repeatability setting
icczip<-icc_counts(EPP,y="Social",id="id",fam="zip")
VarComp(icczip)
```

ZeroTest	<i>Zero-Inflation test for GLMM</i>
----------	-------------------------------------

Description

Zero-Inflation test for GLMM

Usage

```
ZeroTest(x)
```

Arguments

x An object of class *GOF* generated by *GOF_check* function.

Details

The function prints the count of zeros in the sample and the simulated P-value.

Value

A vector with the zero count and the P-value.

See Also

[GOF_check\(\)](#)

Examples

```
# Poisson model. Repeatability setting.
iccpois<-icc_counts(EPP,y="Social",id="id")
iccpois.gof<-GOF_check(iccpois)
ZeroTest(iccpois.gof)
# Zero-inflated Poisson model. Repeatability setting
icczip<-icc_counts(EPP,y="Social",id="id",fam="zip")
icczip.gof<-GOF_check(icczip)
ZeroTest(icczip.gof)
```

Index

* datasets

AF, [2](#)

EPP, [3](#)

Grimso, [5](#)

AF, [2](#)

DispersionTest, [2](#)

DispersionTest(), [4](#)

EPP, [3](#)

GOF_check, [4](#)

GOF_check(), [3](#), [9](#), [11](#)

Grimso, [5](#)

ICC, [5](#)

icc_counts, [6](#)

icc_counts(), [6](#), [10](#)

plot.GOF, [8](#)

plot.GOF(), [4](#)

plot_BA, [9](#)

VarComp, [10](#)

ZeroTest, [11](#)

ZeroTest(), [4](#)