

Package ‘image.CannyEdges’

May 8, 2026

Type Package

Title Implementation of the Canny Edge Detector for Images

Version 0.1.1

Maintainer Jan Wijffels <jwijffels@bnosac.be>

Description An implementation of the Canny Edge Detector for detecting edges in images. The package provides an interface to the algorithm available at <<https://github.com/Neseb/canny>>.

License GPL-3

URL <https://github.com/bnosac/image>

Encoding UTF-8

Imports Rcpp (>= 0.12.9)

LinkingTo Rcpp

Suggests pixmap, magick

RoxygenNote 7.1.2

SystemRequirements libpng, fftw3

NeedsCompilation yes

Author Jan Wijffels [aut, cre, cph],
BNOSAC [cph],
Vincent Maioli [ctb, cph],
IPOL Image Processing On Line [cph]

Repository CRAN

Date/Publication 2023-11-29 13:30:02 UTC

Contents

image.CannyEdges-package	2
image_canny_edge_detector	2
plot.image_canny	3

Index	5
--------------	----------

image.CannyEdges-package

Implementation of the Canny Edge Detector for Images

Description

Canny Edge Detector for Images. See https://en.wikipedia.org/wiki/Canny_edge_detector. Adapted from <https://github.com/Neseb/canny>.

See Also

[image_canny_edge_detector](#)

image_canny_edge_detector

Canny Edge Detector for Images

Description

Canny Edge Detector for Images. See https://en.wikipedia.org/wiki/Canny_edge_detector. Adapted from <https://github.com/Neseb/canny>.

Usage

```
image_canny_edge_detector(x, s = 2, low_thr = 3, high_thr = 10, accGrad = TRUE)
```

Arguments

x	a matrix of image pixel values in the 0-255 range.
s	sigma, the Gaussian filter variance. Defaults to 2.
low_thr	lower threshold value of the algorithm. Defaults to 3.
high_thr	upper threshold value of the algorithm. Defaults to 10
accGrad	logical indicating to trigger higher-order gradient

Value

a list with element edges which is a matrix with values 0 or 255 indicating in the same dimension of x. Next to that the list also contains the input parameters s, low_thr, high_thr and accGrad, the number of rows (nx) and columns of the image (ny) and the number of pixels which have value 255 (pixels_nonzero).

Examples

```

if(requireNamespace("pixmap")){

  library(pixmap)
  imagelocation <- system.file("extdata", "chairs.pgm", package="image.CannyEdges")
  image <- read.pnm(file = imagelocation, cellres = 1)
  x <- image@grey * 255

  edges <- image_canny_edge_detector(x)
  edges
  plot(edges)

}

if(requireNamespace("magick")){
##
## image_canny_edge_detector expects a matrix as input
## if you have a jpg/png/... convert it to pgm first or take the r/g/b channel
library(magick)
x <- image_read(system.file("extdata", "atomium.jpg", package="image.CannyEdges"))
x
image <- image_data(x, channels = "Gray")
image <- as.integer(image, transpose = TRUE)
edges <- image_canny_edge_detector(image)
edges
plot(edges)
}

if(requireNamespace("pixmap") && requireNamespace("magick")){
##
## image_canny_edge_detector expects a matrix as input
## if you have a jpg/png/... convert it to pgm first or take the r/g/b channel
library(magick)
library(pixmap)
f <- tempfile(fileext = ".pgm")
x <- image_read(system.file("extdata", "atomium.jpg", package="image.CannyEdges"))
x <- image_convert(x, format = "pgm", depth = 8)
image_write(x, path = f, format = "pgm")

image <- read.pnm(f, cellres = 1)
edges <- image_canny_edge_detector(image@grey * 255)
edges
plot(edges)

file.remove(f)
}

```

Description

Plot the result of [image_canny_edge_detector](#)

Usage

```
## S3 method for class 'image_canny'  
plot(x, ...)
```

Arguments

x an object of class image_canny as returned by [image_canny_edge_detector](#)
... further arguments passed on to plot, except type, xlab and ylab which are set
inside the function

Value

invisible()

Examples

```
library(pixmap)  
imagelocation <- system.file("extdata", "chairs.pgm", package="image.CannyEdges")  
image <- read.pnm(file = imagelocation, cellres = 1)  
edges <- image_canny_edge_detector(image@grey * 255)  
plot(edges)
```

Index

`image.CannyEdges`-package, [2](#)
`image_canny_edge_detector`, [2](#), [2](#), [4](#)
`plot.image_canny`, [3](#)