

Package ‘intsvy’

May 8, 2026

Version 2.9

Type Package

Title International Assessment Data Manager

Date 2024-01-16

Author Daniel Caro <dcarov@gmail.com>, Przemyslaw Biecek <przemyslaw.biecek@gmail.com>

Maintainer Daniel Caro <dcarov@gmail.com>

Description Provides tools for importing, merging, and analysing data from international assessment studies (TIMSS, PIRLS, PISA, ICILS, and PIAAC).

License GPL-2

URL <https://daniel-caro.com/r-intsvy/>,
<https://github.com/eldafani/intsvy>

BugReports <https://github.com/eldafani/intsvy/issues>

Imports dplyr, foreign, ggplot2, Hmisc, memisc, plyr, reshape, stats,
utils

LazyData yes

NeedsCompilation no

Repository CRAN

Depends R (>= 3.5.0)

Date/Publication 2024-01-16 23:00:18 UTC

Contents

intsvy-package	3
configs	4
intsvy.ben.pv	4
intsvy.config	5
intsvy.log	7
intsvy.log.pv	8
intsvy.mean	9
intsvy.mean.pv	10

intsvy.per.pv	11
intsvy.reg	12
intsvy.reg.pv	13
intsvy.rho	15
intsvy.rho.pv	16
intsvy.select.merge	17
intsvy.table	18
intsvy.var.label	19
piac.ben.pv	20
piac.mean	21
piac.mean.pv	22
piac.reg	23
piac.reg.pv	24
piac.table	25
pirls.ben.pv	26
pirls.log	27
pirls.log.pv	28
pirls.mean	29
pirls.mean.pv	30
pirls.per.pv	31
pirls.reg	32
pirls.reg.pv	33
pirls.rho	34
pirls.rho.pv	35
pirls.select.merge	36
pirls.table	37
pirls.var.label	38
pisa.ben.pv	38
pisa.log	39
pisa.log.pv	40
pisa.mean	41
pisa.mean.pv	42
pisa.per.pv	43
pisa.reg	44
pisa.reg.pv	45
pisa.rho	46
pisa.select.merge	47
pisa.table	48
pisa.var.label	49
plot.intsvy.mean	50
plot.intsvy.reg	51
plot.intsvy.table	52
timss.ben.pv	54
timss.log	55
timss.log.pv	56
timss.mean	57
timss.mean.pv	58
timss.per.pv	59

timss.reg	60
timss.reg.pv	61
timss.rho	62
timss.rho.pv	63
timss.table	64
timssg4.select.merge	65
timssg4.var.label	66
timssg8.select.merge	66
timssg8.var.label	67

Index 69

intsvy-package *International Assessment Data Manager*

Description

Provides tools for importing, merging, and analysing data from international assessment studies (TIMSS, PIRLS, PISA, and PIAAC and others)

Details

Package: intsvy
Type: Package
Version: 2.9
Date: 2024-01-16
License: GPL-2

intsvy allows useRs to work with international assessment data (e.g., TIMSS, PIRLS, PISA, ICILS, and PIAAC). Data and merge functions print variable labels and the name of participating countries in international assessments as well as import data directly into R for the variables in student, parent, school, and teacher instruments and countries selected by the useR. Analysis functions, including mean statistics, standard deviations, regression estimates, correlation coefficients, and frequency tables, calculate point estimates and standard errors that take into account the complex sample design (i.e., replicate weights) and rotated test forms (i.e., plausible achievement values).

Author(s)

Daniel Caro <dcarov@gmail.com>, Przemyslaw Biecek <przemyslaw.biecek@gmail.com>

References

PISA, PIAAC, PIRLS, and TIMSS Technical Reports

configs *Config files for intsvy studies*

Description

Each config file describes detailed study meta-data. Such meta data defined names of columns with weights, type of weighting, number of plausible values and other study parameters. Most of intsvy functions require such config objects.

Usage

pisa_conf

Format

A list with three components - input, variables and parameters.

intsvy.ben.pv *Performance international benchmarks and proficiency levels*

Description

intsvy.ben.pv calculates the percentage of students performing at or above the cut-off points (scores) given by the useR. The default are the benchmarks established by official reports.

Usage

```
intsvy.ben.pv(pvnames, by, cutoff, data, atlevel=FALSE, export = FALSE, name = "output",
  folder = getwd(), config)
```

Arguments

pvnames	The names of columns corresponding to the achievement plausible scores, for example, paste0("PV",1:10,"MATH") for PISA
cutoff	The cut-off points for the assessment benchmarks (e.g., cutoff= c(357.77, 420.07, 482.38, 544.68, 606.99, 669.30)).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
atlevel	A logical value. If TRUE, percentages at each level are calculated. Otherwise (FALSE), percentages at or above levels are reported.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.

folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

pirls.ben.pv returns a data frame with the percentage of students at or above the benchmark and the corresponding standard error.

See Also

timss.ben.pv, pirls.ben.pv, pisa.ben.pv

Examples

```
## Not run:
pisa.ben.pv(pvlabel= paste0("PV",1:10,"MATH") for PISA, by="CNT",
data=pisa, atlevel = TRUE)

intsvy.ben.pv(pvnames= paste0("PV",1:10,"MATH") for PISA by="CNT",
data=pisa, atlevel= TRUE, config=pisa_conf)

piaac.ben.pv(pvlabel= paste0("PVLIT", 1:10), by="CNTRYID", data=piaac)

intsvy.ben.pv(pvnames= paste0("PVLIT", 1:10), by="CNTRYID", data=piaac,
config=piaac_conf)

timss.ben.pv(pvlabel= paste0("BSMMAT0", 1:5), by="IDCNTRYL", data=timss4)

intsvy.ben.pv(pvnames= paste0("BSMMAT0", 1:5), by="IDCNTRYL", data=timss4,
config=timss4_conf)

## End(Not run)
```

intsvy.config *Config files for intsvy studies*

Description

intsvy.config set non standard parameters for intsvy functions. It also allo to apply intsvy functions to new studies that are similar to PIRLS, TIMSS, PISA, PIAAC, ICILS.

Usage

```
intsvy.config(variables.pvlabelpref,
              variables.pvlabelsuff,
              variables.weight,
              variables.jackknifeZone,
              variables.jackknifeRep,
```

```

parameters.cutoffs,
parameters.cutoffs2,
parameters.percentiles,
parameters.weights,
parameters.PVreps,
parameters.varpv1,
input.type,
input.prefixes,
input.student,
input.student_colnames1,
input.student_colnames2,
input.student_pattern,
input.homeinput,
input.home_colnames,
input.school,
input.school_colnames,
input.teacher,
input.teacher_colnames,
input.student_ids,
input.school_ids,
input.type_part,
input.cnt_part, base.config = pirls_conf)

```

Arguments

parameters.weights

Weighting scheme. It may be "JK" for studies like PIRLS, ICLS, TIMSS, or "BRR" for studies like PISA or "mixed_piaac" for studies with mixed design like PIAAC.

parameters.cutoffs2, parameters.cutoffs

Cut offs for plausible values, either for benchmar or for logistic regression.

parameters.percentiles, parameters.PVreps

Other parameters for weighting schemes, like number of PVs.

parameters.varpv1

Logical value, TRUE if only 1 plausible value for within variance estimation.

variables.pvlabelpref, variables.pvlabelsuff, variables.weight,
variables.jackknifeZone, variables.jackknifeRep

Names of variables that are used for jack-knife replicates.

input.type, input.prefixes, input.student, input.student_colnames1,
input.student_colnames2, input.student_pattern, input.homeinput,
input.home_colnames, input.school, input.school_colnames,
input.teacher, input.teacher_colnames, input.student_ids,
input.school_ids, input.type_part, input.cnt_part

Parameters to correctly read data from files downloaded from iea.nl website.

base.config Base config structure, either `pirls_conf`, `pisa_conf`, `piaac_conf`, `timss4_conf`, `timss8_conf`, `icils_conf`.

Value

intsvy.config returns new object with parameters. It is a list with three components - input, variables and parameters.

Examples

```
## Not run:
icils_conf <- intsvy.config(input.student_pattern = "^PV[0-5]CIL$" ,
                           parameters.cutoffs2 = 550, intsvy:::pirls_conf)

icils_conf

## End(Not run)
```

intsvy.log

Logistic regression analysis

Description

intsvy.log performs logistic regression analysis for an observed dependent variable (NOT for plausible values)

Usage

```
intsvy.log(y, x, by, data, export = FALSE, name = "output",
           folder = getwd(), config)
```

Arguments

y	Label for dependent variable
x	Data labels of independent variables (e.g., x = c("ASDHEHLA", "ITSEX")).
by	The label for the grouping variable, usually the countries (i.e., by="IDCOUNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

pirls.log prints a data frame with coefficients, standard errors, t-values, and odds ratios. Results are stored in a list object of class "intsvy.reg".

See Also

timss.log, pirls.log, pisa.log

Examples

```
## Not run:

pisa$SKIP[!(pisa$ST09Q01 == "None" & pisa$ST115Q01 == "None")] <- 1
pisa$SKIP[pisa$ST09Q01 == "None" & pisa$ST115Q01 == "None"] <- 0

pisa$LATE[!pisa$ST08Q01=="None"] <- 1
pisa$LATE[pisa$ST08Q01=="None"] <- 0

pisa.log(y="SKIP", x="LATE", by="IDCNTRYL", data = pisa)

## End(Not run)
```

intsvy.log.pv

Logistic regression analysis with plausible values

Description

intsvy.log.pv performs logistic regression with plausible values and replicate weights.

Usage

```
intsvy.log.pv(pvnames, x, cutoff, by, data, export=FALSE, name= "output",
  folder=getwd(), config)
```

Arguments

pvnames	The names of columns corresponding to the achievement plausible scores.
x	Data labels of independent variables.
cutoff	The cut-off point at which the dependent plausible values scores are dichotomised (1 is larger than the cut-off)
by	The label for the categorical grouping variable (i.e., by="IDCNTRYL") or variables (e.g., x= c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.log.pv returns a data frame with coefficients, standard errors, t-values, and odds ratios. If "by" is specified, results are reported in a list. Weights, e.g. "TOTWGT" for PIRLS, are defined in the config argument.

See Also

pisa.log.pv, pirls.log.pv, timss.log.pv

Examples

```
## Not run:
intsvy.log.pv(pvnames=paste0("PV",1:10,"MATH") , cutoff= 606.99, x="ESCS", by="IDCNTRYL",
data=pisa, config=pisa_conf)
intsvy.log.pv(pvnames=paste0("BSMMAT0", 1:5), cutoff= 550, x="ITSEX", by="IDCNTRYL",
data=timss8g, config=timss8_conf)

## End(Not run)
```

intsvy.mean	<i>Calculates mean of variable</i>
-------------	------------------------------------

Description

Calculates mean and standard error of observed variable (NOT one with plausible values).

Usage

```
intsvy.mean(variable, by, data, export = FALSE,
name = "output", folder = getwd(), config)
```

Arguments

variable	The label corresponding to the observed variable, for example, "AGE_R" for age of respondent.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIAAC.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.mean returns a data frame with means and standard errors.

See Also

pisa.mean, timss.mean, pirls.mean

Examples

```
## Not run:
intsvy.mean(variable="READHOME", by="CNTRYID", data=piaac, config=piaac_conf)
intsvy.mean(variable="PARED", by="IDCNTRYL", data=pisa, config=pisa_conf)
intsvy.mean(variable="BSBGSLM", by='IDCNTRYL', data=timss8g, config=timss8_conf)
intsvy.mean(variable='ASBHELA', by= 'IDCNTRYL', data=pirls,config=pirls_conf)

## End(Not run)
```

intsvy.mean.pv

Calculates mean achievement score

Description

The function intsvy.mean.pv uses plausible values to calculate the mean achievement score and its standard error.

Usage

```
intsvy.mean.pv(pvnames, by, data, export=FALSE, name= "output", folder=getwd(), config)
```

Arguments

pvnames	The names of columns corresponding to the achievement plausible scores, for example, paste0("PV",1:10,"MATH") for PISA.
by	The label for the grouping variable, usually the countries (e.g., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.mean.pv returns a data frame with means and standard errors.

See Also

pisa.mean.pv, timss.mean.pv, pirls.mean.pv

Examples

```
## Not run:
intsvy.mean.pv(pvnames = paste0("ASRREA0", 1:5), by= "IDCNTRYL",
  data=pirls, config=pirls_conf)

intsvy.mean.pv(pvnames = paste0("PV",1:10,"MATH"), by="CNT", data=pisa,
  config=pisa_conf)

intsvy.mean.pv(pvnames = paste0("BSMMAT0", 1:5), by= "IDCNTRYL", data=timss8g,
  config=timss8_conf)

intsvy.mean.pv(pvnames = paste0("PVNUM", 1:10), by="CNTYID", data=piaac,
  config=piaac_conf)

## End(Not run)
```

intsvy.per.pv

Calculates percentiles

Description

Calculates percentiles for plausible values

Usage

```
intsvy.per.pv(pvnames, by, per, data, export=FALSE, name= "output",
  folder=getwd(), config)
```

Arguments

pvnames	The names of columns corresponding to the achievement plausible scores.
per	User-defined percentiles (e.g., per = c(5, 10, 25, 75, 90, 95)).
by	The label of the categorical grouping variable (e.g., by="IDCNTRYL") or variables (e.g., by=c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from intsvy studies.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.per.pv returns a data frame with percentiles and associated standard errors. Default weights (e.g. "TOTWGT" in TIMSS) and percentiles are specified in the config parameter.

See Also

pisa.per.pv, pirls.per.pv, timss.per.pv

Examples

```
## Not run:
timss.per.pv(pvlabel= paste0("BSMMAT0", 1:5),
per = c(5, 10, 25, 50, 75, 90, 95), by="IDCNTRYL", data=timss8)

intsvy.per.pv(pvnames= paste0("BSMMAT0", 1:5), by="IDCNTRYL",
data=timss8, config=timss8_conf)

pirls.per.pv(pvlabel= paste0("ASRREA0", 1:5), by="IDCNTRYL", data=pirls)

intsvy.per.pv(pvnames= paste0("ASRREA0", 1:5),
per = c(5, 10, 25, 50, 75, 90, 95), by="IDCNTRYL", data=pirls,
config=pirls_conf)

pisa.per.pv(pvlabel= paste0("PV", 1:10, "MATH"),
per=c(10, 25, 75, 90), by="CNT", data=pisa)

intsvy.per.pv(pvnames= paste0("PV", 1:10, "MATH"),
by="CNT", data=pisa, config=pisa_conf)

## End(Not run)
```

intsvy.reg

Regression analysis without plausible values

Description

intsvy.reg performs linear regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
intsvy.reg(y, x, by, data, export = FALSE, name = "output", folder = getwd(),
config)
```

Arguments

y	Label for dependent variable.
x	Data labels of independent variables.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.reg returns a data frame with coefficients, standard errors and t-values. If "by" is specified, results are reported in a list. If the "by" argument is set, then the returning object is of the class "intsvy.reg" with overloaded function plot().

See Also

pisa.reg, pirls.reg, timss.reg

Examples

```
## Not run:
# install pbierek/PIAAC package from github to have access to piaac data
piaac.reg(y="AGE_R", x="GENDER_R", by="CNTRYID", data=piaac)

## End(Not run)
```

intsvy.reg.pv

Regression analysis with plausible values

Description

intsvy.reg.pv performs linear regression analysis (OLS) with plausible values and replicate weights.

Usage

```
intsvy.reg.pv(x, pvnames, by,
data, std=FALSE, export = FALSE, name = "output", folder = getwd(), config)
```

Arguments

pvnames	The names of columns corresponding to the achievement plausible scores.
x	Data labels of independent variables.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
std	A logical value. If TRUE standardised regression coefficients are calculated.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.reg.pv prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals, replicate coefficients, variance within and between, and the regression data.frame in a list object of class "intsvy.reg".

See Also

piaac.reg.pv, pirls.reg.pv, pisa.reg.pv, timss.reg.pv

Examples

```
## Not run:
intsvy.reg.pv(pvnames=paste0("PV",1:10,"MATH") , x="ST04Q01",
by = "IDCNTRYL",data=pisa, config=pisa_conf)

intsvy.reg.pv(pvnames=paste0("PVLIT", 1:10), x="GENDER_R", by = "CNTRYID",
data=piaac, config=piaac_conf)

intsvy.reg.pv(pvnames=paste0("BSMMAT0", 1:5), by="IDCNTRYL", x="ITSEX",
data=timss8g, config=timss8_conf)

intsvy.reg.pv(pvnames=paste0("ASRREA0", 1:5), by="IDCNTRYL", x="ITSEX",
data=pirls, config=pirls_conf)

## End(Not run)
```

intsvy.rho	<i>Correlation matrix</i>
------------	---------------------------

Description

intsvy.rho produces a correlation matrix for observed variables (NOT for plausible values)

Usage

```
intsvy.rho(variables, by, data,  
export = FALSE, name = "output", folder = getwd(), config)
```

Arguments

variables	Data labels for the variables in the correlation matrix (e.g., variables=c("ASRREA01", "ASDAGE"))
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.rho returns a matrix including correlation and standard error values.

See Also

timss.rho, pirls.rho.pv, timss.rho.pv

Examples

```
## Not run:  
pirls.rho(variables=c("ASRREA01", "ASDAGE"), by="IDCNTRYL", data=pirls)  
  
## End(Not run)
```

intsvy.rho.pv

*Two-way weighted correlation with plausible values***Description**

intsvy.rho.pv calculates the correlation and standard error among two achievement variables each based on 5 plausible values or one achievement variable and an observed variable (i.e., with observed scores rather than plausible values).

Usage

```
intsvy.rho.pv(variable, pvnames, by, data, export=FALSE,
name= "output", folder=getwd(), config)
```

Arguments

variable	A data label for the observed variable
pvnames	The names of columns corresponding to the achievement plausible scores.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.rho returns a matrix including correlation and standard error values.

See Also

timss.rho, pirls.rho.pv, timss.rho.pv

Examples

```
## Not run:
timss.rho.pv(variable="BSDGEDUP", pvlabel=paste0("BSMMAT0", 1:5), by="IDCNTRYL", data=timss)

## End(Not run)
```

intsvy.select.merge *Select and merge data*

Description

intsvy.select.merge selects and merges data from different international assessment studies. It was developed and it is particularly handy for importing IEA data since original files are organised by instrument, country, grade, etc., in a large number of files. Achievement and weight variables (all of them) are selected by default.

Usage

```
intsvy.select.merge(folder = getwd(), countries, student = c(), home,
  school, teacher, config)
```

Arguments

folder	Directory path where the data are located. The data could be organised within folders but duplicated files should be avoided.
countries	The selected countries, supplied with the abbreviation (e.g., countries=c("AUT", "BGR")) or codes (countries=c(40, 100)). If no countries are selected, all are selected.
student	The data labels for the selected student variables.
home	The data labels for the selected home background variables.
school	The data labels for the selected school variables.
teacher	The data labels for the selected teacher data.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.select.merge returns a data frame with the selected data from study defined in config file.

See Also

timssg4.select.merge, timssg8.select.merge, pisa.select.merge

Examples

```
## Not run:
pirls <- intsvy.select.merge(folder= getwd(),
  countries= c("AUS", "AUT", "AZE", "BFR"),
  student= c("ITSEX", "ASDAGE", "ASBGSMR"),
  home= c("ASDHEDUP", "ASDHOCCP", "ASDHELA", "ASBHELA"),
  school= c("ACDGDAS", "ACDGCMP", "ACDG03"),
  config = pirls_conf)
```

```

pirls <- intsvy.select.merge(folder= getwd(),
  countries= c(36, 40, 31, 957),
  student= c("ITSEX", "ASDAGE", "ASBGSMR"),
  home= c("ASDHEDUP", "ASDHOCCP", "ASDHELA", "ASBHELA"),
  school= c("ACDGDAS", "ACDGCMP", "ACDG03"),
  config = pirls_conf)

timss8g <- intsvy.select.merge(folder= getwd(),
  countries=c("AUS", "BHR", "ARM", "CHL"),
  student =c("BSDGEDUP", "ITSEX", "BSDAGE", "BSBGSLM", "BSDGSLM"),
  school=c("BCBGDAS", "BCDG03"), config = timss8_conf)

icils <- intsvy.select.merge(folder= getwd(),
  countries=c("AUS", "POL", "SVK"),
  student =c("S_SEX", "S_TLANG", "S_MISEI"),
  school =c("IP1G02J", "IP1G03A"),
  config = icils_conf)

pisa <- pisa.select.merge(folder= getwd(),
  school.file="INT_SCQ12_DEC03.sav",
  student.file="INT_STU12_DEC03.sav",
  student= c("ST01Q01", "ST04Q01", "ESCS", "PARED"),
  school = c("CLSIZE", "TCSHORT"),
  countries = c("HKG", "USA", "SWE", "POL", "PER"))

## End(Not run)

```

intsvy.table

Frequency table

Description

intsvy.table produces a frequency table for a categorical variable printing percentages and standard errors.

Usage

```
intsvy.table(variable, by, data, config)
```

Arguments

variable	The data label with the variable to be analysed.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.table returns a data frame with percentages and standard errors.

See Also

timss.table, pirls.table

Examples

```
## Not run:
intsvy.table(variable="ASDGSLM", by="IDCNTRYL", data=timss4,
             config = intsvy::timss_conf)
intsvy.table(variable="ST08Q01", by="CNT", data=pisa, config=pisa_conf)

## End(Not run)
```

intsvy.var.label	<i>Data labels</i>
------------------	--------------------

Description

intsvy.var.labels prints and saves variable labels and names of participating countries in a text file. The function is called by timssg4.var.label, timssg8.var.label, pirls.var.label and pisa.var.label.

Usage

```
intsvy.var.label(folder = getwd(), name = "Variable labels", output = getwd(),
                 config)
```

Arguments

folder	Directory path where the data files are located. The data could be organized within folders but duplicated files should be avoided. It is assumed that data is in 'sav' files. For TIMSS, PIRLS and ICILS studies the data can be downloaded from http://rms.iea-dpc.org/ .
name	Name of the output file.
output	Folder where the output file is located.
config	Object with configuration of a given study. Should contain the slot 'prefixes' with prefixes of filenames with the student, home, school, and teacher data.

Value

intsvy.var.label returns a list with variable labels for the student, home, school, and teacher data (if applied).

See Also

timssg4.var.label, timssg8.var.label, pirls.var.label, pisa.var.label

Examples

```
## Not run:
intsvy.var.label(folder= getwd(), config = pirls_conf)
intsvy.var.label(folder= getwd(), config = timss8_conf)
intsvy.var.label(folder= getwd(), config = icils_conf)
intsvy.var.label(folder= getwd(), config = piaac_conf)

## End(Not run)
```

piaac.ben.pv

PIAAC proficiency levels

Description

Calculates percentage of population at each proficiency level defined by PIAAC. Or at proficiency levels provided by the user.

Usage

```
piaac.ben.pv(pvlabel, by, data, cutoff, atlevel, export=FALSE,
             name= "output", folder=getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
cutoff	The cut-off points for the assessment benchmarks (e.g., cutoff= c(357.77, 420.07, 482.38, 544.68, 606.99, 669.30)).
data	An R object, normally a data frame, containing the data from PIAAC.
atlevel	A logical value. If TRUE, percentages at each level are calculated. Otherwise (FALSE), percentages at or above levels are reported.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

piaac.ben.pv returns a data frame with the percentage of students at each proficiency level and its corresponding standard error.

The total weight, "TOTWGT" and the cut-off points or benchmarks are defined in the config object.

See Also

timss.ben.pv, pirls.ben.pv, pisa.ben.pv

Examples

```
## Not run:
#Table A2.5
#Percentage of adults scoring at each proficiency level in numeracy
piaac.ben.pv(pvlabel= paste0("PVNUM", 1:10), by="COUNTRYID", data=piaac)
#Table A2.1
#Percentage of adults scoring at each proficiency level in literacy
piaac.ben.pv(pvlabel= paste0("PVLIT", 1:10), by="COUNTRYID", data=piaac)

## End(Not run)
```

piaac.mean	<i>Calculates mean of variable in PIAAC data</i>
------------	--

Description

Calculates the mean of an observed variable (NOT one with plausible values) and its standard error.

Usage

```
piaac.mean(variable, by, data, export = FALSE,
name = "output", folder = getwd())
```

Arguments

variable	The label corresponding to the observed variable, for example, "AGE_R" for age of respondent.
by	The label for the grouping variable, usually the countries (i.e., by="COUNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIAAC.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

piaac.mean returns a data frame with means and standard errors.

See Also

pisa.mean, timss.mean, pirls.mean

Examples

```
## Not run:
# install pbiemek/PIAAC package from github to have access to piaac data
piaac.mean(variable="AGE_R", by="CNTRYID", data=piaac)

## End(Not run)
```

piaac.mean.pv

Calculates mean achievement score for PIAAC data

Description

piaac.mean.pv uses ten plausible values to calculate the mean achievement score and its standard error

Usage

```
piaac.mean.pv(pvlabel, by, data, export = FALSE, name = "output", folder = getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIAAC.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

piaac.mean.pv returns a data frame with the mean values and standard errors.

See Also

pisa.mean.pv, timss.mean.pv, pirls.mean.pv

Examples

```
## Not run:
# install pbiemek/PIAAC package from github to have access to piaac data
piaac.mean.pv(pvlabel = paste0("PVLIT", 1:10), by = "CNTRYID", data = piaac)
piaac.mean.pv(pvlabel = paste0("PVNUM", 1:10), by=c("CNTRYID", "GENDER_R"), data=piaac)

## End(Not run)
```

`piaac.reg`*Regression analysis for PIAAC*

Description

`piaac.reg` performs linear regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
piaac.reg(y, x, by, data, export = FALSE, name = "output", folder = getwd())
```

Arguments

<code>y</code>	Label for dependent variable.
<code>x</code>	Data labels of independent variables.
<code>by</code>	The label for the grouping variable, usually the countries (i.e., <code>by="CNTRYID"</code>), but could be any other categorical variable.
<code>data</code>	An R object, normally a data frame, containing the data from PIAAC.
<code>export</code>	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
<code>name</code>	The name of the exported file.
<code>folder</code>	The folder where the exported file is located.

Value

`piaac.reg` returns a data frame with coefficients, standard errors and t-values. If "by" is specified, results are reported in a list. If the "by" argument is set, then the returning object is of the class "intsvy.reg" with overloaded function `plot()`.

See Also

`pisa.reg`, `pirls.reg`, `timss.reg`

Examples

```
## Not run:  
# install pbierek/PIAAC package from github to have access to piaac data  
piaac.reg(y="AGE_R", x="GENDER_R", by="CNTRYID", data=piaac)  
  
## End(Not run)
```

piaac.reg.pv

Regression analysis with plausible values for PIAAC

Description

piaac.reg.pv performs linear regression analysis (OLS) with plausible values and replicate weights.

Usage

```
piaac.reg.pv(x, pvlabel, by, data,
  export = FALSE, name = "output", std=FALSE, folder = getwd())
```

Arguments

x	Data labels of independent variables.
pvlabel	The names of columns corresponding to the achievement plausible scores.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIAAC.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
std	A logical value. If TRUE standardised regression coefficients are calculated.
folder	The folder where the exported file is located.

Value

piaac.reg.pv returns a data frame with coefficients, standard errors and t-values. If "by" is specified, results are reported in a list. If the "by" argument is set, then the returning object is of the class "intsvy.reg" with overloaded function plot().

See Also

pisa.reg.pv, timss.reg.pv, pirls.reg.pv

Examples

```
## Not run:
# install pbiecek/PIAAC package from github to have access to piaac data
piaac.reg.pv(pvlabel=paste0("PVLIT", 1:10), x="GENDER_R", by = "CNTRYID", data=piaac)

## End(Not run)
```

piaac.table	<i>Frequency table</i>
-------------	------------------------

Description

piaac.table produces a frequency table for a categorical variable printing percentages and standard errors.

Usage

```
piaac.table(variable, by, data, export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	The data label with the variable to be analysed.
by	The label for the grouping variable, usually the countries (i.e., by="CNTRYID"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIAAC.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

piaac.table returns a data frame with percentages and standard errors.

See Also

pisa.table, timss.table, pirls.table

Examples

```
## Not run:  
# install pbiecek/PIAAC package from github to have access to piaac data  
piaac.table(variable="I_Q06A", by="CNTRYID", data=piaac)  
piaac.table(variable="GENDER_R", by="CNTRYID", data=piaac)  
  
## End(Not run)
```

pirls.ben.pv

*PIRLS international benchmarks***Description**

pirls.ben.pv calculates the percentage of students performing at or above the cut-off points (scores) given by the useR. The default are the benchmarks established by PIRLS/TIMSS.

Usage

```
pirls.ben.pv(pvlabel, by, cutoff, data, atlevel=FALSE,
export = FALSE, name = "output", folder = getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores.
cutoff	The cut-off points for the assessment benchmarks (e.g., cutoff = c(400, 475, 550, 625)).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
atlevel	A logical value. If TRUE, percentages at each level are calculated. Otherwise (FALSE), percentages at or above levels are reported.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.ben.pv returns a data frame with the percentage of students at or above the benchmark and the corresponding standard error.

The total weight, "TOTWGT" and the cut-off points or benchmarks are defined in the config object.

See Also

timss.ben.pv, pisa.ben.pv

Examples

```
## Not run:
pirls.ben.pv(pvlabel= paste0("ASRREA0", 1:5), by="IDCNTRYL", data=pirls)

## End(Not run)
```

pirls.log *Logistic regression analysis*

Description

pirls.log performs logistic regression analysis for an observed dependent variable (NOT for plausible values)

Usage

```
pirls.log(y, x, by, data, export = FALSE,
name = "output", folder = getwd())
```

Arguments

y	Label for dependent variable
x	Data labels of independent variables (e.g., x = c("ASDHEHLA", "ITSEX")).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.log prints a data frame with coefficients, standard errors, t-values, and odds ratios. Results are stored in a list object of class "intsvy.reg".

See Also

timss.log, pisa.log

Examples

```
## Not run:

pisa$SKIP[!(pisa$ST09Q01 == "None" & pisa$ST115Q01 == "None")] <- 1
pisa$SKIP[pisa$ST09Q01 == "None" & pisa$ST115Q01 == "None"] <- 0

pisa$LATE[!pisa$ST08Q01 == "None"] <- 1
pisa$LATE[pisa$ST08Q01 == "None"] <- 0

pisa.log(y="SKIP", x="LATE", by="IDCNTRYL", data = pisa)

## End(Not run)
```

pirls.log.pv

Logistic regression analysis with plausible values

Description

pirls.log.pv performs logistic regression with plausible values and replicate weights.

Usage

```
pirls.log.pv(pvlabel, x, cutoff, by,
            data, export=FALSE, name= "output", folder=getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores.
x	Data labels of independent variables.
cutoff	The cut-off point at which the dependent plausible values scores are dichotomised (1 is larger than the cut-off)
by	The label for the categorical grouping variable (i.e., by="IDCNTRYL") or variables (e.g., x= c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.log.pv returns a data frame with coefficients, standard errors, t-values, and odds ratios. If "by" is specified, results are reported in a list.

See Also

pisa.log.pv, timss.log.pv

Examples

```
## Not run:
timss.log.pv(pvlabel=paste0("BSMMAT0", 1:5), cutoff= 550,
x=c("ITSEX", "BSBGSLM"), by="IDCNTRYL", data=timss8g)

intsvy.log.pv(pvlabel=paste0("BSMMAT0", 1:5), cutoff= 550,
x="ITSEX", by="IDCNTRYL", data=timss8g, config=timss8_conf)

## End(Not run)
```

pirls.mean	<i>Calculates mean of variable</i>
------------	------------------------------------

Description

Calculates the mean of an observed variable (NOT one with plausible values) and its standard error.

Usage

```
pirls.mean(variable, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	The label corresponding to the observed variable, for example, "ASDAGE", for the age of the student.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.mean returns a data frame with means and standard errors.

See Also

timss.mean, pisa.mean

Examples

```
## Not run:  
pirls.mean(variable='ASBHELA', by= 'IDCNTRYL', data=pirls)  
  
## End(Not run)
```

`pirls.mean.pv`*Calculates mean achievement score*

Description

`pirls.mean.pv` uses five plausible values to calculate the mean achievement score and its standard error

Usage

```
pirls.mean.pv(pvlabel, by,
data, export = FALSE, name = "output", folder = getwd())
```

Arguments

<code>pvlabel</code>	The names of columns corresponding to the achievement plausible scores, for example, <code>paste0("ASRREA0", 1:5)</code> .
<code>by</code>	The label for the grouping variable, usually the countries (i.e., <code>by="IDCNTRYL"</code>), but could be any other categorical variable.
<code>data</code>	An R object, normally a data frame.
<code>export</code>	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
<code>name</code>	The name of the exported file.
<code>folder</code>	The folder where the exported file is located.

Value

`pirls.mean.pv` returns a data frame with the mean values and standard errors.

See Also

`timss.mean.pv`, `pisa.mean.pv`

Examples

```
## Not run:
pirls.mean.pv(pvlabel= paste0("ASRREA0", 1:5), by= "IDCNTRYL", data=pirls)
pirls.mean.pv(pvlabel= paste0("ASRREA0", 1:5), by= c("IDCNTRYL", "ITSEX"), data=pirls)

## End(Not run)
```

pirls.per.pv *PIRLS percentiles*

Description

Calculates percentiles for plausible values

Usage

```
pirls.per.pv(pvlabel, by, per, data, export=FALSE,
             name= "output", folder=getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores.
per	User-defined percentiles (e.g., per = c(5, 10, 25, 75, 90, 95)).
by	The label of the categorical grouping variable (e.g., by="IDCNTRYL") or variables (e.g., by=c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.per.pv returns a data frame with percentiles and associated standard errors. Default weights (e.g. "TOTWGT" in TIMSS) and percentiles are specified in the config parameter.

See Also

pisa.per.pv, timss.per.pv

Examples

```
## Not run:
pirls.per.pv(pvlabel=paste0("ASRREA0", 1:5),
             per = c(5, 10, 25, 50, 75, 90, 95), by="IDCNTRYL", data=pirls)

## End(Not run)
```

pirls.reg

*Regression analysis***Description**

pirls.reg performs linear regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
pirls.reg(y, x, by, data, export = FALSE,
name = "output", folder = getwd())
```

Arguments

y	Label for dependent variable
x	Data labels of independent variables (e.g., x = c("ASDHEHLA", "ITSEX")).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.reg prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals and replicate coefficients in a list object of class "intsvy.reg".

See Also

timss.reg

Examples

```
## Not run:

# Recode ASBGB00K
table(as.numeric(pirls$ASBGB00K), pirls$ASBGB00K)
pirls$BOOK[as.numeric(pirls$ASBGB00K)==1] <- 5
pirls$BOOK[as.numeric(pirls$ASBGB00K)==2] <- 18
pirls$BOOK[as.numeric(pirls$ASBGB00K)==3] <- 63
pirls$BOOK[as.numeric(pirls$ASBGB00K)==4] <- 151
pirls$BOOK[as.numeric(pirls$ASBGB00K)==5] <- 251
```

```

table(pirls$BOOK)

pirls.reg(y= "BOOK", x= "ITSEX", by="IDCNTRYL", data=pirls)

## End(Not run)

```

pirls.reg.pv

Regression analysis with plausible values

Description

pirls.reg.pv performs linear regression analysis (OLS) with plausible values and replicate weights.

Usage

```

pirls.reg.pv(x, pvlabel, by,
data, std=FALSE, export = FALSE, name = "output", folder = getwd())

```

Arguments

x	Data labels of independent variables (e.g., x = c("ASDHEHLA", "ITSEX")).
pvlabel	The names of columns corresponding to the achievement plausible scores.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
std	A logical value. If TRUE standardised regression coefficients are calculated.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.reg.pv prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals, replicate coefficients, variance within and between, and the regression data.frame in a list object of class "intsvy.reg".

See Also

timss.reg.pv, pisa.reg.pv

Examples

```
## Not run:
pirls$SEX[pirls$ITSEX=="BOY"]=1
pirls$SEX[pirls$ITSEX=="GIRL"]=0
pirls.reg.pv(pvlabel= paste0("ASRREA0", 1:5), by="IDCNTRYL", x="SEX", data=pirls)

## End(Not run)
```

pirls.rho

*Correlation matrix***Description**

pirls.rho produces a correlation matrix for observed variables (NOT for plausible values)

Usage

```
pirls.rho(variables, by, data,
export = FALSE, name = "output", folder = getwd())
```

Arguments

variables	Data labels for the variables in the correlation matrix (e.g., variables=c("ASRREA01", "ASDAGE"))
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.rho returns a matrix including correlation and standard error values.

See Also

timss.rho, pirls.rho.pv, timss.rho.pv

Examples

```
## Not run:
pirls.rho(variables=c("ASRREA01", "ASDAGE"), by="IDCNTRYL", data=pirls)

## End(Not run)
```

pirls.rho.pv

Two-way weighted correlation with plausible values

Description

pirls.rho.pv calculates the correlation and standard error among two achievement variables each based on 5 plausible values or one achievement variable and an observed variable (i.e., with observed scores rather than plausible values).

Usage

```
pirls.rho.pv(variable, pvlabel, by,
data, export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	A data label for the observed variable (e.g., variable="ASDAGE")
pvlabel	The names of columns corresponding to the achievement plausible scores.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.rho.pv returns a matrix with correlations and standard errors.

See Also

timss.rho.pv, pirls.rho, timss.rho

Examples

```
## Not run:
pirls.rho.pv(variable="BSDGEDUP", pvlabel=paste0("BSMMAT0", 1:5), by="IDCNTRYL", data=timss)

## End(Not run)
```

pirls.select.merge *Select and merge data*

Description

pirls.select.merge selects and merges data from PIRLS. Achievement and weight variables (all of them) are selected by default.

Usage

```
pirls.select.merge(folder = getwd(), countries, student = c(),
  home, school, teacher)
```

Arguments

folder	Directory path where the data are located. The data could be organized within folders but it should not be duplicated.
countries	The selected countries, supplied with the abbreviation (e.g., countries=c("AUT", "BGR")) or codes (countries=c(40, 100)). If no countries are selected, all are selected.
student	The data labels for the selected student variables.
home	The data labels for the selected home background variables.
school	The data labels for the selected school variables.
teacher	The data labels for the selected teacher data.

Value

pirls.select.merge returns a data frame with the selected data from PIRLS.

See Also

timssg4.select.merge, timssg8.select.merge, pisa.select.merge

Examples

```
## Not run:
pirls <- pirls.select.merge(folder= getwd(),
  countries= c(36, 40, 31, 957),
  student= c("ITSEX", "ASDAGE", "ASBGSMR"),
  home= c("ASDHEDUP", "ASDHOCPP", "ASDHELA", "ASBHELA"),
  school= c("ACDGDAS", "ACDGCMP", "ACDG03"))

## End(Not run)
```

pirls.table	<i>Frequency table</i>
-------------	------------------------

Description

pirls.table produces a frequency table for a categorical variable printing percentages and standard errors. Information about weight is extracted from `intsvy::pirls_conf`.

Usage

```
pirls.table(variable, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	The data label with the variable to be analysed.
by	The label for the grouping variable, usually the countries (i.e., <code>by="IDCNTRYL"</code>), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pirls.table returns a data frame with percentages and standard errors.

See Also

`timss.table`, `pisa.table`

Examples

```
## Not run:  
pirls.table(variable="ASDHELA", by="IDCNTRYL", data=pirls)  
  
## End(Not run)
```

`pirls.var.label` *Data labels*

Description

`pirls.var.labels` prints and saves variable labels and names of participating countries in a text file

Usage

```
pirls.var.label(folder = getwd(), name = "Variable labels", output = getwd())
```

Arguments

<code>folder</code>	Directory path where the PIRLS data are located. The data could be organized within folders but it should not be duplicated.
<code>name</code>	Name of output file.
<code>output</code>	Folder where output file is located.

Value

`pirls.var.label` returns a list with variable labels for the student, home, school, and teacher data.

See Also

`timssg4.var.label`, `timssg8.var.label`, `pisa.var.label`

Examples

```
## Not run:
pirls.var.label(folder= getwd())

## End(Not run)
```

`pisa.ben.pv` *PISA proficiency levels*

Description

Calculates percentage of students at each proficiency level defined by PISA. Or at proficiency levels provided by the user.

Usage

```
pisa.ben.pv(pvlabel, by, cutoff, data, atlevel=FALSE,
export=FALSE, name= "output", folder=getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores.
cutoff	The cut-off points for the assessment benchmarks (e.g., cutoff= c(357.77, 420.07, 482.38, 544.68, 606.99, 669.30)).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
atlevel	A logical value. If TRUE, percentages at each level are calculated. Otherwise (FALSE), percentages at or above levels are reported.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.ben.pv returns a data frame with the percentage of students at each proficiency level and its corresponding standard error.

The total weight, "TOTWGT" and the cut-off points or benchmarks are defined in the config object.

See Also

timss.ben.pv, pirls.ben.pv

Examples

```
## Not run:
pisa.ben.pv(pvlabel= paste0("PV", 1:10, "MATH"), by="IDCNTRYL", atlevel=TRUE, data=pisa)

## End(Not run)
```

pisa.log

Logistic regression analysis

Description

pisa.log performs logistic regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
pisa.log(y, x, by, data, export=FALSE, name= "output", folder=getwd())
```

Arguments

y	Label for dependent variable.
x	Data labels of independent variables.
by	The label for the grouping variable, usually the countries (i.e., by="CNT"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.log prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores replicate estimates and other regression output in a list object of class "intsvy.reg".

See Also

pirls.log, timss.log

Examples

```
## Not run:

pisa$SKIP[!(pisa$ST09Q01=="None" & pisa$ST115Q01=="None")] <- 1
pisa$SKIP[pisa$ST09Q01=="None" & pisa$ST115Q01=="None"] <- 0

pisa$LATE[!pisa$ST08Q01=="None"] <- 1
pisa$LATE[pisa$ST08Q01=="None"] <- 0

pisa.log(y="SKIP", x="LATE", by="IDCNTRYL", data = pisa)

## End(Not run)
```

pisa.log.pv

Logistic regression analysis with plausible values

Description

pisa.log.pv performs logistic regression with plausible values and replicate weights.

Usage

```
pisa.log.pv(pvlabel, x, by, cutoff,
            data, export=FALSE, name="output", folder=getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores.
x	Data labels of independent variables.
cutoff	The cut-off point at which the dependent plausible values scores are dichotomised (1 is larger than the cut-off)
by	The label for the categorical grouping variable (i.e., by="IDCNTRYL") or variables (e.g., x= c("IDCNTRYL", "ST79Q03")).
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.log.pv returns a data frame with coefficients, standard errors, t-values, and odds ratios. If "by" is specified, results are reported in a list.

See Also

timss.log.pv, pirls.log.pv

Examples

```
## Not run:
timss.log.pv(pvlabel=paste0("BSMMAT0", 1:5), cutoff= 550,
x=c("ITSEX", "BSBGSLM"), by="IDCNTRYL", data=timss8g)

intsvy.log.pv(pvlabel=paste0("BSMMAT0", 1:5), cutoff= 550, x="ITSEX",
by="IDCNTRYL", data=timss8g, config=timss8_conf)

## End(Not run)
```

pisa.mean

Calculates mean of variable

Description

Calculates the mean of an observed variable (NOT one with plausible values) and its standard error.

Usage

```
pisa.mean(variable, by, data, export = FALSE,
name = "output", folder = getwd())
```

Arguments

variable	The label corresponding to the observed variable, for example, ""ESCS"", for the student SES.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.mean returns a data frame with means and standard errors.

See Also

timss.mean, pirls.mean, piaac.mean

Examples

```
## Not run:
pisa.mean(variable="ESCS", by="IDCNTRYL", data=pisa)
pisa.mean(variable="PARED", by="IDCNTRYL", data=pisa)

pisa.mean(variable="BELONG", by="IDCNTRYL", data=pisa)
pisa.mean(variable="BELONG", by=c("IDCNTRYL", "ST04Q01"), data=pisa)

## End(Not run)
```

pisa.mean.pv

Calculates mean achievement score

Description

pisa.mean.pv uses five plausible values to calculate the mean achievement score and its standard error

Usage

```
pisa.mean.pv(pvlabel, by, data, export = FALSE, name = "output",
             folder = getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores, for example, paste0("PV",1:10,"MATH").
by	The label for the grouping variable, usually the countries (i.e., by="IDCOUNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.mean.pv returns a data frame with the mean values and standard errors.

See Also

timss.mean.pv, pirls.mean.pv, pиаac.mean.pv

Examples

```
## Not run:
pisa.mean.pv(pvlabel = paste0("PV",1:10,"MATH"), by = "IDCOUNTRYL", data = pisa)
pisa.mean.pv(pvlabel = paste0("PV",1:10,"MATH"), by = c("IDCOUNTRYL", "ST04Q01"), data = pisa)
pisa.mean.pv(pvlabel = "paste0("PV",1:10,"MATH)", by = "IDCOUNTRYL", data = pisa)

## End(Not run)
```

pisa.per.pv

PISA percentiles

Description

Calculates percentiles for plausible values.

Usage

```
pisa.per.pv(pvlabel, by, per, data, export=FALSE, name= "output",
folder=getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores.
per	User-defined percentiles (e.g., per = c(5, 10, 25, 75, 90, 95)).
by	The label of the categorical grouping variable (e.g., by="IDCNTRYL") or variables (e.g., by=c("IDCNTRYL", "ST79Q03")).
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.per.pv returns a data frame with percentiles and associated standard errors. Default weights (e.g. "TOTWGT" in TIMSS) and percentiles are specified in the config parameter.

See Also

timss.per.pv, pirls.per.pv

Examples

```
## Not run:
pisa.per.pv(pvlabel=paste0("PV",1:10,"MATH"), per=c(10, 25, 75, 90), by="IDCNTRYL", data=pisa)

## End(Not run)
```

pisa.reg

Regression analysis

Description

pisa.reg performs linear regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
pisa.reg(y, x, by, data, export = FALSE, name = "output", folder = getwd())
```

Arguments

y	Label for dependent variable.
x	Data labels of independent variables.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.reg prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals and replicate coefficients in a list object of class "intsvy.reg".

See Also

pirls.reg, timss.reg, piaac.reg

Examples

```
## Not run:
pisa.reg(y="BELONG", x="ST04Q01", by="IDCNTRYL", data=pisa)

## End(Not run)
```

pisa.reg.pv

Regression analysis with plausible values

Description

pisa.reg.pv performs linear regression analysis (OLS) with plausible values and replicate weights.

Usage

```
pisa.reg.pv(x, pvlabel, by, data,
export = FALSE, name = "output", folder = getwd(), std=FALSE)
```

Arguments

x	Data labels of independent variables.
pvlabel	The names of columns corresponding to the achievement plausible scores.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.
std	A logical value. If TRUE standardised regression coefficients are calculated.

Value

pisa.reg.pv prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals, replicate coefficients, variance within and between, and the regression data.frame in a list object of class "intsvy.reg".

See Also

timss.reg.pv, pirls.reg.pv, piaac.reg.pv

Examples

```
## Not run:
pisa.reg.pv(pvlabel=paste0("PV",1:10,"MATH"), x="ST04Q01", by = "IDCNTRYL", data=pisa)

## End(Not run)
```

pisa.rho

Correlation matrix

Description

pisa.rho produces a correlation matrix for observed variables (NOT for plausible values)

Usage

```
pisa.rho(variables, by, data, export=FALSE, name= "output", folder=getwd())
```

Arguments

variables	Data labels for the variables in the correlation matrix (e.g., variables=c("TCHBEHTD", "TCHBEHSO"))
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.rho returns a matrix including correlation and standard error values.

See Also

timss.rho, pirls.rho, pirls.rho.pv, timss.rho.pv

Examples

```
## Not run:
pisa.rho(variables=c("COGACT", "TCHBEHTD", "TCHBEHSO", "CLSMAN" ), by="IDCNTRYL", data=pisa)

## End(Not run)
```

pisa.select.merge *Select and merge data*

Description

pisa.select.merge selects and merges data from PISA. Achievement and weight variables (all of them) are selected by default.

Usage

```
pisa.select.merge(folder=getwd(), student.file, parent.file=c(), school.file=c(),
countries, student=c(), parent, school)
```

Arguments

folder	Directory path where the PISA data are located, if all the data are located in the same folder.
student.file	Student file name if 'folder' is provided, otherwise full path name of student dataset (required argument).

parent.file	Parent file name if 'folder' is provided, otherwise full path name of parent dataset.
school.file	School file name if 'folder' is provided, otherwise full path name of school dataset.
countries	The selected countries, supplied with the abbreviation (e.g., countries=c("DEU", "NOR")) or codes. If no countries are selected, all are selected.
student	The data labels for the selected student variables.
parent	The data labels for the selected parental variables.
school	The data labels for the selected school variables.

Value

pisa.select.merge returns a data frame with the selected data from PISA.

See Also

timssg4.select.merge, timssg8.select.merge, pirls.select.merge

Examples

```
## Not run:
pisa <- pisa.select.merge(folder=getwd(),
  school.file="INT_SCQ12_DEC03.sav",
  student.file="INT_STU12_DEC03.sav",
  parent.file="INT_PAQ12_DEC03.sav",
  student= c("IMMIG", "ESCS", "ST04Q01", "ST61Q04", "ST62Q01", "ST08Q01"),
  parent = c("PARINVOL", "PARSUPP"),
  school = c("STRATIO", "SCHAUTON", "CLSIZE"),
  countries = c("HKG", "USA", "SWE", "POL", "PER"))

## End(Not run)
```

pisa.table	<i>Frequency table</i>
------------	------------------------

Description

pisa.table produces a frequency table for a categorical variable printing percentages and standard errors.

Usage

```
pisa.table(variable, by, data, export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	The data label with the variable to be analysed.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PISA.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

pisa.table returns a data frame with percentages and standard errors.

See Also

timss.table, pirls.table

Examples

```
## Not run:
pisa.table(variable="ST01Q01", by="IDCNTRYL", data=pisa)
pisa.table(variable="ST08Q01", by="IDCNTRYL", data=pisa)

## End(Not run)
```

pisa.var.label	<i>Data labels</i>
----------------	--------------------

Description

pisa.var.labels prints and saves variable labels and names of participating countries in a text file

Usage

```
pisa.var.label(folder=getwd(), student.file, parent.file=c(), school.file=c(),
name="Variable labels", output=getwd())
```

Arguments

folder	Directory path where the PISA data are located, if all the data are located in the same folder.
student.file	Student file name if 'folder' is provided, otherwise full path name of student dataset (required argument).
parent.file	Parent file name if 'folder' is provided, otherwise full path name of parent dataset.

school.file	School file name if 'folder' is provided, otherwise full path name of school dataset.
name	Name of output file.
output	Folder where output file is located.

Value

pisa.var.label returns a list with variable labels for the student, parent, and school data.

See Also

timssg4.var.label, timssg8.var.label, pirls.var.label

Examples

```
## Not run:
pisa.var.label(folder=getwd(), school.file="INT_SCQ12_DEC03.sav",
student.file="INT_STU12_DEC03.sav", parent.file="INT_PAQ12_DEC03.sav")

## End(Not run)
```

plot.intsvy.mean	<i>Graphical representation of means in groups</i>
------------------	--

Description

Functions pisa.mean, pisa.mean.pv, piae.mean, piae.mean.pv produce object of the class intsvy.mean. The function plot.intsvy.mean presents these means graphically.

Usage

```
## S3 method for class 'intsvy.mean'
plot(x, se = TRUE, sort = FALSE, ...)
```

Arguments

x	An object of the class intsvy.mean returned by pisa.mean, pisa.mean.pv, piae.mean or piae.mean.pv functions.
se	If TRUE add whiskers for standard errors.
sort	If TRUE groups are sorted along averages.
...	Not used. Required for cran-check.

Value

Returns object of ggplot class with dotplot. Works for one way, two-way and three-way effects.

See Also

plot.intsvy.table, plot.intsvy.reg

Examples

```
## Not run:
# Country averages
head(pmeansNC <- piaac.mean.pv(pvlabel="NUM", by="CNTRYID", data=piaac, export=FALSE))

# plotting country average NUM performance
plot(pmeansNC) + ggtitle("Country performance in NUM")
# without se bars, not good idea
plot(pmeansNC, se=FALSE)
# sorted, thats better
plot(pmeansNC, sort=TRUE)

# Country averages for different age groups
head(pmeansNCA <- piaac.mean.pv(pvlabel="NUM", by=c("CNTRYID", "AGEG10LFS"),
                                data=piaac, export=FALSE))
#
# plotting country average within
# age groups NUM performance
plot(pmeansNCA, sort=TRUE)

# Country averages for different age and gender groups (changed order)
head(pmeansNCGA <- piaac.mean.pv(pvlabel="NUM", by=c("CNTRYID", "GENDER_R", "AGEG10LFS"),
                                data=piaac, export=FALSE))
#
# plotting country average within
# age and gender groups NUM performance
plot(na.omit(pmeansNCGA), sort=TRUE)

## End(Not run)
```

plot.intsvy.reg

Graphical representation of regression models in groups

Description

Functions pisa.reg, pisa.reg.pv, piaac.reg and piaac.reg.pv produce object of the class intsvy.reg. The function plot.intsvy.reg presents this list of regression models graphically.

Usage

```
## S3 method for class 'intsvy.reg'
plot(x, ..., vars, se = TRUE, sort = FALSE)
```

Arguments

x	An object of the class intsvy.reg returned by pisa.reg, pisa.reg.pv, piaac.reg and piaac.reg.pv functions.
...	Other arguments
vars	Variable labels of coefficients to be plotted. If none selected all coefficients are plotted including the R-squared
se	If TRUE add whiskers for standard errors.
sort	If TRUE groups are sorted in alphabetical order.

Value

Returns object of ggplot class with barplot. As with other ggplot objects the plus sign "+" can be used outside this function to modify graph parameters of the returning ggplot object. Works for one way, two-way and three-way contingency tables.

See Also

plot.intsvy.table, plot.intsvy.mean

Examples

```
## Not run:
# Independent variables
x.vars <- c("ESCS", "COGACT", "TCHBEHTD", "TCHBEHSO")
# Model estimation
my.mod <- pisa.reg.pv(pvlabel="MATH", x=x.vars, by="IDCNTRYL", data=pisa12)
# Plot
plot(gen.mod, vars = c("COGACT", "TCHBEHTD", "TCHBEHSO"), sort=TRUE)

## End(Not run)
```

plot.intsvy.table *Graphical representation of frequency tables*

Description

Functions pisa.table and piaac.table produce object of the class intsvy.table. The function plot.intsvy.table presents this table graphically.

Usage

```
## S3 method for class 'intsvy.table'
plot(x, se=FALSE, stacked=FALSE, centered = FALSE, midpoint = NA, ...)
```

Arguments

x	An object of the class intsvy.table returned by pisa.table or piaeac.table functions.
se	If TRUE add whiskers for standard errors (only for stacked=FALSE).
stacked	If TRUE plot bars stacked one over another.
centered	If TRUE then bars will be centered around midpoint.
midpoint	A single number, which specifies the segment around which bars are centered. By default it's the middle segment calculated as $(n.levels + 1)/2$. If n.levels is odd then bars are centered around the beginning of the selected segment. If n.levels is even then bars are centered around the middle of the selected segment.
...	Not used. Required for cran-check.

Value

Returns object of ggplot class with barplot. Works for one way, two-way and three-way contingency tables.

See Also

plot.intsvy.mean, plot.intsvy.reg

Examples

```
## Not run:
# install pbiiecek/PIAAC package from github to have access to piaeac data
# age distribution in whole dataset
(ptable <- piaeac.table(variable="AGEG10LFS", data=pieaac))

# age distribution in whole dataset
plot(ptable)
plot(ptable, centered=TRUE)

# age distribution within countries
head(ptableC <- piaeac.table(variable="AGEG10LFS", by="CNTRYID", data=pieaac))

# age distribution within countries
plot(ptableC, stacked=TRUE)
plot(na.omit(ptableC), centered=TRUE)

# age distribution within countries and gender segments
head(ptableCA <- piaeac.table(variable="AGEG10LFS", by=c("CNTRYID", "GENDER_R"), data=pieaac))

# age distribution within countries and gender segments
plot(na.omit(ptableCA), stacked=TRUE)
plot(na.omit(ptableCA), centered=TRUE)

## End(Not run)
```

timss.ben.pv

TIMSS international benchmarks

Description

timss.ben.pv calculates the percentage of students performing at or above the cut-off points (scores) given by the useR. The default are the benchmarks established by PIRLS/TIMSS

Usage

```
timss.ben.pv(pvlabel, by, cutoff, data, atlevel=FALSE,
export = FALSE, name = "output", folder = getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores.
cutoff	The cut-off points for the assessment benchmarks (e.g., cutoff = c(400, 475, 550, 625)).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
atlevel	A logical value. If TRUE, percentages at each level are calculated. Otherwise (FALSE), percentages at or above levels are reported.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.ben.pv returns a data frame with the percentage of students at or above the benchmark and the corresponding standard error.

The total weight, "TOTWGT" and the cut-off points or benchmarks are defined in the config object.

See Also

pirls.ben.pv, pisa.ben.pv

Examples

```
## Not run:
timss.ben.pv(pvlabel= paste0("BSMMAT0", 1:5), by="IDCNTRYL",
cutoff = c(400, 475, 550, 625), data=timss8g)

timss.ben.pv(pvlabel= paste0("BSMMAT0", 1:5), by="IDCNTRYL", data=timss4g)

## End(Not run)
```

timss.log	<i>Logistic regression analysis</i>
-----------	-------------------------------------

Description

timss.log performs logistic regression analysis for an observed dependent variable (NOT for plausible values)

Usage

```
timss.log(y, x, by, data, export = FALSE,
name = "output", folder = getwd())
```

Arguments

y	Label for dependent variable
x	Data labels of independent variables (e.g., x = c("ASDHEHLA", "ITSEX")).
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from PIRLS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.log prints a data frame with coefficients, standard errors, t-values, and odds ratios. Results are stored in a list object of class "intsvy.reg".

See Also

pirls.log, pisa.log

Examples

```
## Not run:

pisa$SKIP[!(pisa$ST09Q01 == "None" & pisa$ST115Q01 == "None")] <- 1
pisa$SKIP[pisa$ST09Q01 == "None" & pisa$ST115Q01 == "None"] <- 0

pisa$LATE[!pisa$ST08Q01 == "None"] <- 1
pisa$LATE[pisa$ST08Q01 == "None"] <- 0

pisa.log(y="SKIP", x="LATE", by="IDCNTRYL", data = pisa)

## End(Not run)
```

timss.log.pv

*Logistic regression analysis with plausible values***Description**

timss.log.pv performs logistic regression with plausible values and replicate weights.

Usage

```
timss.log.pv(pvlabel, x, by, cutoff,
            data, export=FALSE, name= "output", folder=getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores.
x	Data labels of independent variables.
cutoff	The cut-off point at which the dependent plausible values scores are dichotomised (1 is larger than the cut-off)
by	The label for the categorical grouping variable (i.e., by="IDCNTRYL") or variables (e.g., x= c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from TIMSS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.log.pv returns a data frame with coefficients, standard errors, t-values, and odds ratios. If "by" is specified, results are reported in a list.

See Also

pisa.log.pv, pirls.log.pv

Examples

```
## Not run:
timss.log.pv(pvlabel=paste0("BSMMAT0", 1:5), cutoff= 550,
            x=c("ITSEX", "BSBGSLM"), by="IDCNTRYL", data=timss8g)

intsvy.log.pv(pvlabel=paste0("BSMMAT0", 1:5), cutoff= 550, x="ITSEX",
            by="IDCNTRYL", data=timss8g, config=timss8_conf)

## End(Not run)
```

timss.mean	<i>Calculates mean of variable</i>
------------	------------------------------------

Description

Calculates the mean of an observed variable (NOT one with plausible values) and its standard error.

Usage

```
timss.mean(variable, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	The label corresponding to the observed variable, for example, "ASDAGE", for the age of the student.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.mean returns a data frame with means and standard errors.

See Also

girls.mean, pisa.mean

Examples

```
## Not run:  
timss.mean(variable='ASBGSLM', by='IDCNTRYL', data=timss4g)  
timss.mean(variable='BSBGSLM', by='IDCNTRYL', data=timss8g)  
  
## End(Not run)
```

`timss.mean.pv`*Calculates mean achievement score*

Description

`timss.mean.pv` uses five plausible values to calculate the mean achievement score and its standard error

Usage

```
timss.mean.pv(pvlabel, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

<code>pvlabel</code>	The names of columns corresponding to the achievement plausible scores, for example, <code>paste0("BSMMAT0", 1:5)</code> .
<code>by</code>	The label for the grouping variable, usually the countries (i.e., <code>by="IDCNTRYL"</code>), but could be any other categorical variable.
<code>data</code>	An R object, normally a data frame.
<code>export</code>	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
<code>name</code>	The name of the exported file.
<code>folder</code>	The folder where the exported file is located.

Value

`timss.mean.pv` returns a data frame with the mean values and standard errors.

See Also

`girls.mean.pv`, `pisa.mean.pv`

Examples

```
## Not run:  
timss.mean.pv(pvlabel= paste0("BSMMAT0", 1:5), by= "IDCNTRYL", data=timss4g)  
timss.mean.pv(pvlabel= paste0("BSMMAT0", 1:5), by= c("IDCNTRYL", "ITSEX"), data=timss8g)  
  
## End(Not run)
```

timss.per.pv

TIMSS percentiles

Description

Calculates percentiles for plausible values

Usage

```
timss.per.pv(pvlabel, by, per, data, export=FALSE, name= "output",
            folder=getwd())
```

Arguments

pvlabel	The names of columns corresponding to the achievement plausible scores.
per	User-defined percentiles (e.g., per = c(5, 10, 25, 75, 90, 95)).
by	The label of the categorical grouping variable (e.g., by="IDCNTRYL") or variables (e.g., by=c("IDCNTRYL", "ITSEX")).
data	An R object, normally a data frame, containing the data from TIMSS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.per.pv returns a data frame with percentiles and associated standard errors. Default weights (e.g. "TOTWGT" in TIMSS) and percentiles are specified in the config parameter.

See Also

pisa.per.pv, pirls.per.pv

Examples

```
## Not run:
timss.per.pv(pvlabel=paste0("BSMMAT0", 1:5),
            per = c(5, 10, 25, 50, 75, 90, 95), by="IDCNTRYL", data=timssg8)

## End(Not run)
```

`timss.reg`*Regression analysis*

Description

`timss.reg` performs linear regression analysis (OLS) for an observed dependent variable (NOT for plausible values)

Usage

```
timss.reg(y, x, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

<code>y</code>	Label for dependent variable.
<code>x</code>	Data labels of independent variables.
<code>by</code>	The label for the grouping variable, usually the countries (i.e., <code>by="IDCNTRYL"</code>), but could be any other categorical variable.
<code>data</code>	An R object, normally a data frame, containing the data from TIMSS.
<code>export</code>	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
<code>name</code>	The name of the exported file.
<code>folder</code>	The folder where the exported file is located.

Value

`timss.reg` prints a `data.frame` with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals and replicate coefficients in a list object of class `"intsvy.reg"`.

See Also

`pirls.reg`

Examples

```
## Not run:  
timss.reg(y="BSDAGE", x="ITSEX", by="IDCNTRYL", data=timss8g)  
  
## End(Not run)
```

Description

timss.reg.pv performs linear regression analysis (OLS) with plausible values and replicate weights.

Usage

```
timss.reg.pv(x, pvlabel, by,
data, std=FALSE, export = FALSE, name = "output", folder = getwd())
```

Arguments

x	Data labels of independent variables.
pvlabel	The names of columns corresponding to the achievement plausible scores.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
std	A logical value. If TRUE standardised regression coefficients are calculated.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.reg.pv prints a data.frame with regression results (i.e., coefficients, standard errors, t-values, R-squared) and stores different regression output including residuals, replicate coefficients, variance within and between, and the regression data.frame in a list object of class "intsvy.reg".

See Also

pirls.reg.pv, pisa.reg.pv

Examples

```
## Not run:
timss8g$SEX[timss8g$ITSEX=="BOY"]=1
timss8g$SEX[timss8g$ITSEX=="GIRL"]=0
timss.reg.pv(pvlabel= paste0("BSMMAT0", 1:5), by=c("IDCNTRYL"), x="SEX", data=timss8g)

## End(Not run)
```

timss.rho	<i>Correlation matrix</i>
-----------	---------------------------

Description

timss.rho produces a correlations matrix for observed variables (NOT for plausible values)

Usage

```
timss.rho(variables, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

variables	Data labels for the variables in the correlation matrix.
by	The label for the grouping variable, usually the countries (i.e., by="IDCNTRYL"), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.rho returns a matrix including correlation and standard error values.

See Also

pirls.rho, pirls.rho.pv, timss.rho.pv

Examples

```
## Not run:  
timss.rho(variables=c("BSMMAT01", "BSDGEDUP"), data=timss)  
  
## End(Not run)
```

`timss.rho.pv`*Two-way weighted correlation with plausible values*

Description

`timss.rho.pv` calculates the correlation and standard error among two achievement variables each based on 5 plausible values or one achievement variable and an observed variable (i.e., with observed scores rather than plausible values).

Usage

```
timss.rho.pv(variable, pvlabel, by,
data, export = FALSE, name = "output", folder = getwd())
```

Arguments

<code>variable</code>	A data label for the observed variable
<code>pvlabel</code>	The names of columns corresponding to the achievement plausible scores.
<code>by</code>	The label for the grouping variable, usually the countries (i.e., <code>by="IDCOUNTRYL"</code>), but could be any other categorical variable.
<code>data</code>	An R object, normally a data frame, containing the data from TIMSS.
<code>export</code>	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
<code>name</code>	The name of the exported file.
<code>folder</code>	The folder where the exported file is located.

Value

`timss.rho.pv` returns a matrix with correlations and standard errors.

See Also

`pirls.rho.pv`, `pirls.rho`, `timss.rho`

Examples

```
## Not run:
timss.rho.pv(variable="BSDGEDUP", pvlabel=paste0("BSMMAT0", 1:5), by="IDCOUNTRYL", data=timss)

## End(Not run)
```

timss.table	<i>Frequency table</i>
-------------	------------------------

Description

timss.table produces a frequency table for a categorical variable printing percentages and standard errors. Information about weight is extracted from `intsvy::pirls_conf`.

Usage

```
timss.table(variable, by, data,  
export = FALSE, name = "output", folder = getwd())
```

Arguments

variable	The data label with the variable to be analysed.
by	The label for the grouping variable, usually the countries (i.e., <code>by="IDCNTRYL"</code>), but could be any other categorical variable.
data	An R object, normally a data frame, containing the data from TIMSS.
export	A logical value. If TRUE, the output is exported to a file in comma-separated value format (.csv) that can be opened from LibreOffice or Excel.
name	The name of the exported file.
folder	The folder where the exported file is located.

Value

timss.table returns a data frame with percentages and standard errors.

See Also

`pirls.table`, `pisa.table`

Examples

```
## Not run:  
timss.table(variable="ASDGSLM", by="IDCNTRYL", data=timss4g)  
timss.table(variable="BSDGSLM", by="IDCNTRYL", data=timss8g)  
  
## End(Not run)
```

timssg4.select.merge *Select and merge data*

Description

timssg4.select.merge selects and merges data from TIMSS G4. Achievement and weight variables (all of them) are selected by default.

Usage

```
timssg4.select.merge(folder = getwd(), countries, student = c(), home, school, teacher)
```

Arguments

folder	Directory path where the data are located. The data could be organized within folders but it should not be duplicated.
countries	The selected countries, supplied with the abbreviation (e.g., countries=c("AUT", "BGR") or codes (countries=c(40, 100)). If no countries are selected, all are selected.
student	The data labels for the selected student variables.
home	The data labels for the selected home background variables.
school	The data labels for the selected school variables.
teacher	The data labels for the selected teacher variables.

Value

timssg4.select.merge returns a data frame with the selected data from TIMSS G4.

See Also

timssg8.select.merge, pirls.select.merge, pisa.select.merge

Examples

```
## Not run:
timss4g <- timssg4.select.merge(folder=getwd(),
  countries=c("AUS", "BHR", "ARM", "CHL"),
  student =c("ITSEX", "ASDAGE", "ASBGSLM", "ASDGSLM"),
  home = c("ASDHEDUP", "ASDHENA"),
  school =c("ACDG03", "ACDGENS"))

## End(Not run)
```

timssg4.var.label *Data labels*

Description

timssg4.var.labels prints and saves variable labels and names of participating countries in a text file

Usage

```
timssg4.var.label(folder = getwd(), name = "Variable labels", output = getwd())
```

Arguments

folder	Directory path where the TIMSS G4 data are located. The data could be organized within folders but it should not be duplicated.
name	Name of output file.
output	Folder where output file is located.

Value

timssg4.var.label returns a list with variable labels for the student, home, school, and teacher data.

See Also

timssg8.var.label, pirls.var.label, pisa.var.label

Examples

```
## Not run:  
timssg4.var.label(folder= getwd())  
  
## End(Not run)
```

timssg8.select.merge *Select and merge data*

Description

timssg8.select.merge selects and merges data from TIMSS G8.

Usage

```
timssg8.select.merge(folder = getwd(), countries, student = c(), school,  
math.teacher, science.teacher)
```

Arguments

folder	Directory path where the data are located. The data could be organized within folders but it should not be duplicated.
countries	The selected countries, supplied with the abbreviation (e.g., countries=c("AUT", "BGR")) or codes (countries=c(40, 100)). If no countries are selected, all are selected.
student	The data labels for the selected student variables.
school	The data labels for the selected school variables.
math.teacher	The data labels for the selected math teacher variables.
science.teacher	The data labels for the selected science teacher variables.

Value

timssg8.select.merge returns a data frame with the selected data from TIMSS G8.

See Also

timssg4.select.merge, pirls.select.merge, pisa.select.merge

Examples

```
## Not run:
timss8g <- timssg8.select.merge(folder=getwd(),
                               countries=c("AUS", "BHR", "ARM", "CHL"),
                               student =c("BSDGEDUP", "ITSEX", "BSDAGE", "BSBGSLM", "BSDGSLM"),
                               school =c("BCBGDAS", "BCDG03"))

## End(Not run)
```

timssg8.var.label	<i>Data labels</i>
-------------------	--------------------

Description

timssg8.var.labels prints and saves variable labels and names of participating countries in a text file

Usage

```
timssg8.var.label(folder = getwd(), name = "Variable labels", output = getwd())
```

Arguments

folder	Directory path where the TIMSS G8 data are located. The data could be organized within folders but it should not be duplicated.
name	Name of output file.
output	Folder where output file is located.

Value

`timssg8.var.label` returns a list with variable labels for the student, home, school, and teacher data.

See Also

`timssg4.var.label`, `pirls.var.label`, `pisa.var.label`

Examples

```
## Not run:  
timssg8.var.label(folder= getwd())  
  
## End(Not run)
```

Index

* datasets

- configs, 4
- configs, 4
- icils_conf (configs), 4
- intsvy (intsvy-package), 3
- intsvy-package, 3
- intsvy.ben.pv, 4
- intsvy.config, 5
- intsvy.log, 7
- intsvy.log.pv, 8
- intsvy.mean, 9
- intsvy.mean.pv, 10
- intsvy.per.pv, 11
- intsvy.reg, 12
- intsvy.reg.pv, 13
- intsvy.rho, 15
- intsvy.rho.pv, 16
- intsvy.select.merge, 17
- intsvy.table, 18
- intsvy.var.label, 19
- llece_conf (configs), 4
- pasec_conf (configs), 4
- piaac.ben.pv, 20
- piaac.mean, 21
- piaac.mean.pv, 22
- piaac.reg, 23
- piaac.reg.pv, 24
- piaac.table, 25
- piaac_conf (configs), 4
- pirls.ben.pv, 26
- pirls.log, 27
- pirls.log.pv, 28
- pirls.mean, 29
- pirls.mean.pv, 30
- pirls.per.pv, 31
- pirls.reg, 32
- pirls.reg.pv, 33
- pirls.rho, 34
- pirls.rho.pv, 35
- pirls.select.merge, 36
- pirls.table, 37
- pirls.var.label, 38
- pirls_conf (configs), 4
- pisa.ben.pv, 38
- pisa.log, 39
- pisa.log.pv, 40
- pisa.mean, 41
- pisa.mean.pv, 42
- pisa.per.pv, 43
- pisa.reg, 44
- pisa.reg.pv, 45
- pisa.rho, 46
- pisa.select.merge, 47
- pisa.table, 48
- pisa.var.label, 49
- pisa_conf (configs), 4
- plot.intsvy.mean, 50
- plot.intsvy.reg, 51
- plot.intsvy.table, 52
- sea_conf (configs), 4
- timss.ben.pv, 54
- timss.log, 55
- timss.log.pv, 56
- timss.mean, 57
- timss.mean.pv, 58
- timss.per.pv, 59
- timss.reg, 60
- timss.reg.pv, 61
- timss.rho, 62
- timss.rho.pv, 63
- timss.table, 64
- timss4_conf (configs), 4
- timss8_conf (configs), 4
- timssg4.select.merge, 65

timssg4.var.label, [66](#)
timssg8.select.merge, [66](#)
timssg8.var.label, [67](#)