

Package ‘iplookupapi’

May 8, 2026

Title Client for the 'iplookupapi.com' IP Lookup API

Version 0.1.0

Description An R client for the 'iplookupapi.com' IP Lookup API. The API requires registration of an API key. Basic features are free, some require a paid subscription. You can find the full API documentation at <https://iplookupapi.com/docs> .

License MIT + file LICENSE

Encoding UTF-8

URL <https://iplookupapi.com>, <https://iplookupapi.com/docs>

RoxygenNote 7.2.3

Imports httr, jsonlite

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Dominik Kukacka [aut, cre]

Maintainer Dominik Kukacka <dominik@everapi.com>

Repository CRAN

Date/Publication 2023-05-11 08:50:09 UTC

Contents

get_api_status	2
get_ip_info	2
iplookupapi_api_key	3
Index	4

get_api_status	<i>Get the current status of the API.</i>
----------------	---

Description

Get the current status of the API.

Usage

```
get_api_status()
```

Value

Returns your current quota. Requests to this endpoint do not count against your quota or rate limit.

get_ip_info	<i>Checks the provided IP address (both v4 & v6 formats) and returns all available information.</i>
-------------	---

Description

Checks the provided IP address (both v4 & v6 formats) and returns all available information.

Usage

```
get_ip_info(ip = NULL, language = NULL)
```

Arguments

ip	The IP address you want to query
language	An ISO Alpha 2 Language Code for localizing the IP data

Value

Returns all available information about an IP address.

iplookupapi_api_key *Iplookupapi API Key*

Description

iplookupapi.com requires authentication via an API key. For this package, the API key is saved as an environmental variable. In interactive mode, using `iplookupapi_api_key` will require you to enter an API key. Alternatively, you can also use `Sys.setenv(IPLOOKUPAPI_API_KEY = <key>)` to set the API key manually.

Usage

```
iplookupapi_api_key(force = FALSE)
```

Arguments

<code>force</code>	If TRUE, resets the API key & requires the user to provide a new API key. If FALSE and an API key already exists, the key will be printed to the console. If no key exists, you will be required to enter a key. <code>force</code> . Defaults to FALSE.
--------------------	--

Value

Returns the set API key that has been stored as an environment variable.

Index

`get_api_status`, 2

`get_ip_info`, 2

`iplookupapi_api_key`, 3