Package ‘itertools’

May 8, 2026

Type Package

Title Iterator Tools

Version 0.1-3

Author Steve Weston, Hadley Wickham

Maintainer Steve Weston <stephen.b.weston@gmail.com>

Description Various tools for creating iterators, many patterned after functions in the Python itertools module, and others patterned after functions in the 'snow' package.

Depends R (>= 2.14.0), iterators(>= 1.0.0)

Imports parallel

Suggests foreach

License GPL-2

Repository CRAN

Repository/R-Forge/Project itertools

Repository/R-Forge/Revision 60

Repository/R-Forge/DateTimeStamp 2014-02-27 22:33:49

Date/Publication 2014-03-12 00:20:01

NeedsCompilation no

Contents

itertools-package 2
chain 3
enumerate 3
hasNext 4
iarray 5
ibreak 6
ichunk 7
ifilter 7
ihasNext 8
ilimit 9

ireadBin 9
ireaddf 10
irecord 11
irep 12
irepeat 12
iRNGStream 13
is.iterator 14
isplitCols 15
isplitIndices 16
isplitRows 17
isplitVector 18
izip 19
product 19
recycle 20
timeout 20
writedf.combiner 21

Index **22**

`itertools-package` *The itertools Package*

Description

The `itertools` package provides a variety of functions used to create iterators, as defined by REvolution Computing's `iterators` package. Many of the functions are patterned after functions of the same name in the Python itertools module, including `chain`, `product`, `izip`, `ifilter`, etc. In addition, a number of functions were inspired by utility functions in the `snow` package, such as `isplitRows`, `isplitCols`, and `isplitIndices`.

There are also several utility functions that were contributed by Hadley Wickham that aid in writing iterators. These include `is.iterator`, `end_iterator`, `iteration_has_ended`, and `new_iterator`.

Details

More information is available on the following topics:

`isplitVector`	splits, or slices, a vector into shorter segments
`isplitCols`	splits a matrix column-wise
`isplitRows`	splits a matrix row-wise
`isplitIndices`	iterate over "chunks" of indices from 1 to n
`chain`	chain multiple iterators together into one iterator
`enumerate`	create an enumeration from an iterator
`ichunk`	create lists of values from an iterator to aid manual chunking
`ihasNext`	add a hasNext method to an iterator
`ifilter`	only return values for which a predicate function returns true
`ifilterfalse`	only return values for which a predicate function returns false
`ilimit`	limit, or truncate, an iterator

ireadBin	reads from a binary connection
irep	an iterator version of the rep function
irepeat	a simple repeating value iterator
izip	zip together multiple iterators
product	zip together multiple iterators in cartesian product fashion
recycle	recycle values from an iterator repeatedly
timeout	iterate for a specified number of seconds
is.iterator	indicates if an object is an iterator
end_iteration	throws an exception to signal end of iteration
iteration_has_ended	tests an exception to see if iteration has ended
new_iterator	creates a new iterator object

For a complete list of functions with individual help pages, use `library(help="itertools")`.

`chain` *Create a chaining iterator*

Description

Create an iterator that chains multiple iterables together.

Usage

```
chain(...)
```

Arguments

...	The iterables to iterate over.

Examples

```
# Iterate over two iterables
as.list(chain(1:2, letters[1:3]))
```

`enumerate` *Create an enumeration object*

Description

Create an iterator that iterates over an iterable, returning the value in a list that includes an index.

Usage

```
enumerate(iterable)
```

Arguments

`iterable`	Iterable to iterate over.

Examples

```
# Create an enumeration of five random numbers
as.list(enumerate(rnorm(5)))
```

---

hasNext — *Does This Iterator Have A Next Element*

Description

`hasNext` is a generic function that indicates if the iterator has another element.

Usage

```
hasNext(obj, ...)

## S3 method for class 'ihasNext'
hasNext(obj, ...)
```

Arguments

`obj`	an iterator object.
`...`	additional arguments that are ignored.

Value

Logical value indicating whether the iterator has a next element.

Examples

```
it <- ihasNext(iter(c('a', 'b', 'c')))
while (hasNext(it))
  print(nextElem(it))
```

iarray *Create an iterator over an array*

Description

Create an iterator over an array.

Usage

```
iarray(X, MARGIN, ..., chunks, chunkSize, drop,
       idx=lapply(dim(X), function(i) TRUE))
```

Arguments

X	Array to iterate over.
MARGIN	Vector of subscripts to iterate over. Note that if the length of MARGIN is greater than one, the resulting iterator will generate iterators which is particularly useful with nested foreach loops.
...	Used to force subsequent arguments to be specified by name.
chunks	Number of elements that the iterator should generate. This can be a single value or a vector the same length as MARGIN. A single value will be recycled for each dimension if MARGIN has more than one value.
chunkSize	The maximum size Number of elements that the iterator should generate. This can be a single value or a vector the same length as MARGIN. A single value will be recycled for each dimension if MARGIN has more than one value.
drop	Should dimensions of length 1 be dropped in the generated values? It defaults to FALSE if either chunks or chunkSize is specified, otherwise to TRUE.
idx	List of indices used to generate a call object.

See Also

apply

Examples

```
# Iterate over matrices in a 3D array
x <- array(1:24, c(2,3,4))
as.list(iarray(x, 3))

# Iterate over subarrays
as.list(iarray(x, 3, chunks=2))

x <- array(1:64, c(4,4,4))
it <- iarray(x, c(2,3), chunks=c(1,2))
jt <- nextElem(it)
nextElem(jt)
```

```
jt <- nextElem(it)
nextElem(jt)

it <- iarray(x, c(2,3), chunks=c(2,2))
jt <- nextElem(it)
nextElem(jt)
nextElem(jt)
jt <- nextElem(it)
nextElem(jt)
nextElem(jt)
```

`ibreak` *Create an iterator that can be told to stop*

Description

Create an iterator that iterates over another iterator until a specified function returns `FALSE`. This can be useful for breaking out of a foreach loop, for example.

Usage

```
ibreak(iterable, finished)
```

Arguments

`iterable`	Iterable to iterate over.
`finished`	Function that returns a logical value. The iterator stops when this function returns `FALSE`.

Examples

```
# See how high we can count in a tenth of a second
mkfinished <- function(time) {
  starttime <- proc.time()[3]
  function() proc.time()[3] > starttime + time
}
length(as.list(ibreak(icount(), mkfinished(0.1))))
```

ichunk — *Create a chunking iterator*

Description

Create an iterator that issues lists of values from the underlying iterable. This is useful for manually "chunking" values from an iterable.

Usage

```
ichunk(iterable, chunkSize, mode='list')
```

Arguments

`iterable`	Iterable to iterate over.
`chunkSize`	Maximum number of values from `iterable` to return in each value issued by the resulting iterator.
`mode`	Mode of the objects returned by the iterator.

See Also

`isplitVector`

Examples

```
# Split the vector 1:10 into "chunks" with a maximum length of three
it <- ihasNext(ichunk(1:10, 3))
while (hasNext(it)) {
  print(unlist(nextElem(it)))
}

# Same as previous, but return integer vectors rather than lists
it <- ihasNext(ichunk(1:10, 3, mode='integer'))
while (hasNext(it)) {
  print(nextElem(it))
}
```

ifilter — *Create a filtering iterator*

Description

The `ifilter` and `ifilterfalse` functions create iterators that return a subset of the values of the specified iterable. `ifilter` returns the values for which the `pred` function returns `TRUE`, and `ifilterfalse` returns the values for which the `pred` function returns `FALSE`.

Usage

```
ifilter(pred, iterable)
ifilterfalse(pred, iterable)
```

Arguments

pred	A function that takes one argument and returns TRUE or FALSE.
iterable	The iterable to iterate over.

Examples

```
# Return the odd numbers between 1 and 10
as.list(ifilter(function(x) x %% 2 == 1, icount(10)))

# Return the even numbers between 1 and 10
as.list(ifilterfalse(function(x) x %% 2 == 1, icount(10)))
```

---

ihasNext *Create an iterator that supports the hasNext method*

Description

ihasNext is a generic function that indicates if the iterator has another element.

Usage

```
ihasNext(iterable)
```

Arguments

iterable	an iterable object, which could be an iterator.

Value

An ihasNext iterator that wraps the specified iterator and supports the hasNext method.

Examples

```
it <- ihasNext(c('a', 'b', 'c'))
while (hasNext(it))
  print(nextElem(it))
```

ilimit — *Create a limited iterator*

Description

Create an iterator that wraps a specified iterable a limited number of times.

Usage

```
ilimit(iterable, n)
```

Arguments

`iterable`	Iterable to iterate over.
`n`	Maximum number of values to return.

Examples

```
# Limit icount to only return three values
as.list(ilimit(icount(), 3))
```

ireadBin — *Create an iterator to read binary data from a connection*

Description

Create an iterator to read binary data from a connection.

Usage

```
ireadBin(con, what='raw', n=1L, size=NA_integer_, signed=TRUE,
         endian=.Platform$endian, ipos=NULL)
```

Arguments

`con`	A connection object or a character string naming a file or a raw vector.
`what`	Either an object whose mode will give the mode of the vector to be read, or a character vector of length one describing the mode: one of "numeric", "double", "integer", "int", "logical", "complex", "character", "raw". Unlike `readBin`, the default value is "raw".
`n`	integer. The (maximal) number of records to be read each time the iterator is called.
`size`	integer. The number of bytes per element in the byte stream. The default, 'NA_integer_', uses the natural size.

signed	logical. Only used for integers of sizes 1 and 2, when it determines if the quantity on file should be regarded as a signed or unsigned integer.
endian	The endian-ness ('"big"' or '"little"') of the target system for the file. Using '"swap"' will force swapping endian-ness.
ipos	iterable. If not NULL, values from this iterable will be used to do a seek on the file before calling readBin.

Examples

```
zz <- file("testbin", "wb")
writeBin(1:100, zz)
close(zz)

it <- ihasNext(ireadBin("testbin", integer(), 10))
while (hasNext(it)) {
  print(nextElem(it))
}
unlink("testbin")
```

---

ireaddf *Create an iterator to read data frames from files*

Description

Create an iterator to read data frames from files.

Usage

```
ireaddf(filenames, n, start=1, col.names, chunkSize=1000)
```

Arguments

filenames	Names of files contains column data.
n	Number of elements to read from each column file.
start	Element to starting reading from.
col.names	Names of the columns.
chunkSize	Number of rows to read at a time.

irecord *Record and replay iterators*

Description

The irecord function records the values issued by a specified iterator to a file or connection object. The ireplay function returns an iterator that will replay those values. This is useful for iterating concurrently over multiple, large matrices or data frames that you can't keep in memory at the same time. These large objects can be recorded to files one at a time, and then be replayed concurrently using minimal memory.

Usage

```
irecord(con, iterable)
ireplay(con)
```

Arguments

con	A file path or open connection.
iterable	The iterable to record to the file.

Examples

```
suppressMessages(library(foreach))

m1 <- matrix(rnorm(70), 7, 10)
f1 <- tempfile()
irecord(f1, iter(m1, by='row', chunksize=3))

m2 <- matrix(1:50, 10, 5)
f2 <- tempfile()
irecord(f2, iter(m2, by='column', chunksize=3))

# Perform a simple out-of-core matrix multiply
p <- foreach(col=ireplay(f2), .combine='cbind') %:%
       foreach(row=ireplay(f1), .combine='rbind') %do% {
         row %*% col
       }

dimnames(p) <- NULL
print(p)
all.equal(p, m1 %*% m2)
unlink(c(f1, f2))
```

irep — *Create a repeating iterator*

Description

Create an iterator version of the `rep` function.

Usage

```
irep(iterable, times, length.out, each)
```

Arguments

`iterable`	The iterable to iterate over repeatedly.
`times`	A vector giving the number of times to repeat each element if the length is greater than one, or to repeat all the elements if the length is one. This behavior is less strict than `rep` since the length of an iterable isn't generally known.
`length.out`	non-negative integer. The desired length of the output iterator.
`each`	non-negative integer. Each element of the iterable is repeated `each` times.

See Also

`rep`

Examples

```
unlist(as.list(irep(1:4, 2)))
unlist(as.list(irep(1:4, each=2)))
unlist(as.list(irep(1:4, c(2,2,2,2))))
unlist(as.list(irep(1:4, c(2,1,2,1))))
unlist(as.list(irep(1:4, each=2, len=4)))
unlist(as.list(irep(1:4, each=2, len=10)))
unlist(as.list(irep(1:4, each=2, times=3)))
```

irepeat — *Create a repeating iterator*

Description

Create an iterator that returns a value a specified number of times.

Usage

```
irepeat(x, times)
```

Arguments

x	The value to return repeatedly.
times	The number of times to repeat the value. Default value is infinity.

Examples

```
# Repeat a value 10 times
unlist(as.list(irepeat(42, 10)))
```

---

iRNGStream *Iterators that support parallel RNG*

Description

The iRNGStream function creates an infinite iterator that calls nextRNGStream repeatedly, and iRNGSubStream creates an infinite iterator that calls nextRNGSubStream repeatedly.

Usage

```
iRNGStream(seed)
iRNGSubStream(seed)
```

Arguments

seed	Either a single number to be passed to set.seed or a vector to be passed to nextRNGStream or nextRNGSubStream.

See Also

set.seed, nextRNGStream, nextRNGSubStream

Examples

```
it <- iRNGStream(313)
print(nextElem(it))
print(nextElem(it))

## Not run:
library(foreach)
foreach(1:3, rseed=iRNGSubStream(1970), .combine='c') %dopar% {
  RNGkind("L'Ecuyer-CMRG") # would be better to initialize workers only once
  assign('.Random.seed', rseed, pos=.GlobalEnv)
  runif(1)
}

## End(Not run)
```

`is.iterator` *Utilities for writing iterators*

Description

`is.iterator` indicates if an object is an iterator. `end_iteration` throws an exception to signal that there are no more values available in an iterator. `iteration_has_ended` tests an exception to see if it indicates that iteration has ended. `new_iterator` returns an iterator object.

Usage

```
is.iterator(x)
end_iteration()
iteration_has_ended(e)
new_iterator(nextElem, ...)
```

Arguments

`x`	any object.
`e`	a condition object.
`nextElem`	a function object that takes no arguments.
`...`	not currently used.

Examples

```
# Manually iterate using the iteration_has_ended function to help
it <- iter(1:3)
tryCatch({
  stopifnot(is.iterator(it))
  repeat {
    print(nextElem(it))
  }
},
error=function(e) {
  if (!iteration_has_ended(e)) {
    stop(e)
  }
})
```

isplitCols — *Create an iterator that splits a matrix into block columns*

Description

Create an iterator that splits a matrix into block columns. You can specify either the number of blocks, using the `chunks` argument, or the maximum size of the blocks, using the `chunkSize` argument.

Usage

```
isplitCols(x, ...)
```

Arguments

`x`	Matrix to iterate over.
`...`	Passed as the second and subsequent arguments to `idiv` function. Currently, `idiv` accepts either a value for `chunks` or `chunkSize`.

Value

An iterator that returns submatrices of `x`.

See Also

`idiv`, `isplitRows`

Examples

```
# Split a matrix into submatrices with a maximum of three columns
x <- matrix(1:30, 3)
it <- ihasNext(isplitCols(x, chunkSize=3))
while (hasNext(it)) {
  print(nextElem(it))
}

# Split the same matrix into five submatrices
it <- ihasNext(isplitCols(x, chunks=5))
while (hasNext(it)) {
  print(nextElem(it))
}
```

isplitIndices *Create an iterator of indices*

Description

Create an iterator of chunks of indices from 1 to n. You can specify either the number of pieces, using the chunks argument, or the maximum size of the pieces, using the chunkSize argument.

Usage

```
isplitIndices(n, ...)
```

Arguments

n	Maximum index to generate.
...	Passed as the second and subsequent arguments to idiv function. Currently, idiv accepts either a value for chunks or chunkSize.

Value

An iterator that returns vectors of indices from 1 to n.

See Also

idiv, isplitVector

Examples

```
# Return indices from 1 to 17 in vectors no longer than five
it <- ihasNext(isplitIndices(17, chunkSize=5))
while (hasNext(it)) {
  print(nextElem(it))
}

# Return indices from 1 to 7 in four vectors
it <- ihasNext(isplitIndices(7, chunks=4))
while (hasNext(it)) {
  print(nextElem(it))
}
```

`isplitRows` *Create an iterator that splits a matrix into block rows*

Description

Create an iterator that splits a matrix into block rows. You can specify either the number of blocks, using the `chunks` argument, or the maximum size of the blocks, using the `chunkSize` argument.

Usage

```
isplitRows(x, ...)
```

Arguments

`x`	Matrix to iterate over.
`...`	Passed as the second and subsequent arguments to `idiv` function. Currently, `idiv` accepts either a value for `chunks` or `chunkSize`.

Value

An iterator that returns submatrices of `x`.

See Also

`idiv`, `isplitCols`

Examples

```
# Split a matrix into submatrices with a maximum of three rows
x <- matrix(1:100, 10)
it <- ihasNext(isplitRows(x, chunkSize=3))
while (hasNext(it)) {
  print(nextElem(it))
}

# Split the same matrix into five submatrices
it <- ihasNext(isplitRows(x, chunks=5))
while (hasNext(it)) {
  print(nextElem(it))
}
```

isplitVector — *Create an iterator that splits a vector*

Description

Create an iterator that splits a vector into smaller pieces. You can specify either the number of pieces, using the `chunks` argument, or the maximum size of the pieces, using the `chunkSize` argument.

Usage

```
isplitVector(x, ...)
```

Arguments

`x`	Vector to iterate over. Note that it doesn't need to be an atomic vector, so a list is acceptable.
`...`	Passed as the second and subsequent arguments to `idiv` function. Currently, `idiv` accepts either a value for `chunks` or `chunkSize`.

Value

An iterator that returns vectors of the same type as `x` with one or more elements from `x`.

See Also

`idiv`

Examples

```
# Split the vector 1:10 into "chunks" with a maximum length of three
it <- ihasNext(isplitVector(1:10, chunkSize=3))
while (hasNext(it)) {
  print(nextElem(it))
}

# Split the vector "letters" into four chunks
it <- ihasNext(isplitVector(letters, chunks=4))
while (hasNext(it)) {
  print(nextElem(it))
}

# Get the first five elements of a list as a list
nextElem(isplitVector(as.list(letters), chunkSize=5))
```

izip — *Create an iterator over multiple iterables*

Description

Create an iterator that iterates over multiple iterables, returning the values as a list.

Usage

```
izip(...)
```

Arguments

`...`	The iterables to iterate over.

Examples

```
# Iterate over two iterables of different sizes
as.list(izip(a=1:2, b=letters[1:3]))
```

product — *Create a cartesian product iterator*

Description

Create an iterator that returns values from multiple iterators in cartesian product fashion. That is, they are combined the manner of nested `for` loops.

Usage

```
product(...)
```

Arguments

`...`	Named iterables to iterate over. The right-most iterables change more quickly, like an odometer.

Examples

```
# Simulate a doubly-nested loop with a single while loop
it <- ihasNext(product(a=1:3, b=1:2))
while (hasNext(it)) {
  x <- nextElem(it)
  cat(sprintf('a = %d, b = %d\n', x$a, x$b))
}
```

recycle *Create a recycling iterator*

Description

Create an iterator that recycles a specified iterable.

Usage

```
recycle(iterable, times=NA_integer_)
```

Arguments

`iterable`	The iterable to recycle.
`times`	integer. Number of times to recycle the values in the iterator. Default value of `NA_integer_` means to recycle forever.

Examples

```
# Recycle over 'a', 'b', and 'c' three times
recycle(letters[1:3], 3)
```

timeout *Create a timeout iterator*

Description

Create an iterator that iterates over another iterator for a specified period of time, and then stops. This can be useful when you want to search for something, or run a test for awhile, and then stop.

Usage

```
timeout(iterable, time)
```

Arguments

`iterable`	Iterable to iterate over.
`time`	The time interval to iterate for, in seconds.

Examples

```
# See how high we can count in a tenth of a second
length(as.list(timeout(icount(), 0.1)))
```

`writedf.combiner` *Create an object that contains a combiner function*

Description

Create an object that contains a combiner function.

Usage

```
writedf.combiner(filenames)
```

Arguments

`filenames`	Names of files to write column data to.

Index

∗ **methods**
  hasNext, 4
∗ **package**
  itertools-package, 2
∗ **utilities**
  chain, 3
  enumerate, 3
  iarray, 5
  ibreak, 6
  ichunk, 7
  ifilter, 7
  ihasNext, 8
  ilimit, 9
  ireadBin, 9
  ireaddf, 10
  irecord, 11
  irep, 12
  irepeat, 12
  iRNGStream, 13
  is.iterator, 14
  isplitCols, 15
  isplitIndices, 16
  isplitRows, 17
  isplitVector, 18
  izip, 19
  product, 19
  recycle, 20
  timeout, 20
  writedf.combiner, 21

apply, *5*

chain, 3

end_iteration *(*is.iterator*)*, 14
enumerate, 3

hasNext, 4

iarray, 5
ibreak, 6
ichunk, 7
idiv, *15–18*
ifilter, 7
ifilterfalse *(*ifilter*)*, 7
ihasNext, 8
ilimit, 9
ireadBin, 9
ireaddf, 10
irecord, 11
irep, 12
irepeat, 12
ireplay *(*irecord*)*, 11
iRNGStream, 13
iRNGSubStream *(*iRNGStream*)*, 13
is.iterator, 14
isplitCols, 15, *17*
isplitIndices, 16
isplitRows, *15*, 17
isplitVector, *7*, *16*, 18
iteration_has_ended *(*is.iterator*)*, 14
itertools *(*itertools-package*)*, 2
itertools-package, 2
izip, 19

new_iterator *(*is.iterator*)*, 14
nextRNGStream, *13*
nextRNGSubStream, *13*

product, 19

recycle, 20
rep, *12*

set.seed, *13*

timeout, 20

writedf.combiner, 21