

# Package ‘metaphonebr’

May 8, 2026

**Title** Custom 'MetaphoneBR' Phonetic Encoding for Brazilian Names

**Version** 0.0.5

**Description** Simplifies Brazilian names phonetically using a custom 'metaphoneBR' algorithm that preserves ending vowels.  
Useful for name matching processing preserving gender information carried generally by ending vowels in Portuguese.  
Mation (2025) <[doi:10.6082/uchicago.15104](https://doi.org/10.6082/uchicago.15104)>.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Imports** lifecycle, stringi

**Suggests** testthat (>= 3.0.0)

**Config/testthat/edition** 3

**URL** <https://github.com/ipeadata-lab/metaphonebr>,  
<https://ipeadata-lab.github.io/metaphonebr/>

**BugReports** <https://github.com/ipeadata-lab/metaphonebr/issues>

**NeedsCompilation** no

**Author** Rodrigo Borges [aut, cre] (ORCID:  
<<https://orcid.org/0000-0003-2076-1424>>),  
Lucas Mation [aut] (ORCID: <<https://orcid.org/0000-0002-7461-932X>>),  
Ipea - Institute for Applied Economic Research [cph, fnd]

**Maintainer** Rodrigo Borges <[rodrigoesborges@gmail.com](mailto:rodrigoesborges@gmail.com)>

**Repository** CRAN

**Date/Publication** 2025-09-18 19:40:02 UTC

## Contents

metaphonebr . . . . .	2
<b>Index</b>	<b>3</b>

---

metaphonebr	<i>Generates Phonetic Code (adapted Metaphone-BR) for Names in Portuguese</i>
-------------	---

---

### Description

Applies a series of phonetic transformations to a person names vector to generate code that represents its approximate pronunciation in Brazilian Portuguese. The objective is to group similar sounding names, even though written in different forms.

### Usage

```
metaphonebr(fullnames, verbose = FALSE)
```

### Arguments

fullnames	A character vector for names to be processed.
verbose	Logical, if TRUE, print progress messages at each step. Default FALSE.

### Details

The treatment process involves:

1. Preprocessing: Removal of accents, numbers and capitalize.
2. Removal of silent letters (initial H).
3. Simplification of common digraphs (LH, NH, CH, SC, QU, etc.).
4. Simplification of similar sounding consonants (C/K/S, G/J, Z/S, etc.).
5. Simplification of ending nasal sounds.
6. Removal of duplicated vowels.
7. Removal/trim of spaces and duplicated letters.

This is an adaption that does not follow strictly any published Metaphone algorithm, but was inspired by them considering brazilian portuguese context.

### Value

A character vector with corresponding phonetic representation for each entry.

### Examples

```
example_names <- c("Jo\u00e3o Silva", "Joao da Silva", "Maria", "Marya",
                  "Helena", "Elena", "Philippe", "Filipe", "Xavier", "Chavier")
phonetic_codes <- metaphonebr(example_names)
print(data.frame(Original = example_names, metaphonebr = phonetic_codes))

# With progress messages
phonetic_codes_verbose <- metaphonebr("Exemplo \u00fanico", verbose = TRUE)
```

# Index

metaphonebr, [2](#)