

# Package ‘outForest’

May 9, 2026

**Title** Multivariate Outlier Detection and Replacement

**Version** 1.0.1

**Description** Provides a random forest based implementation of the method described in Chapter 7.1.2 (Regression model based anomaly detection) of Chandola et al. (2009) <[doi:10.1145/1541880.1541882](https://doi.org/10.1145/1541880.1541882)>. It works as follows: Each numeric variable is regressed onto all other variables by a random forest. If the scaled absolute difference between observed value and out-of-bag prediction of the corresponding random forest is suspiciously large, then a value is considered an outlier. The package offers different options to replace such outliers, e.g. by realistic values found via predictive mean matching. Once the method is trained on a reference data, it can be applied to new data.

**License** GPL (>= 2)

**Depends** R (>= 3.5.0)

**Encoding** UTF-8

**RoxygenNote** 7.2.3

**Imports** FNN, ranger, graphics, stats, missRanger (>= 2.1.0)

**Suggests** knitr, rmarkdown, testthat (>= 3.0.0)

**URL** <https://github.com/mayer79/outForest>

**BugReports** <https://github.com/mayer79/outForest/issues>

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**NeedsCompilation** no

**Author** Michael Mayer [aut, cre]

**Maintainer** Michael Mayer <[mayermichael79@gmail.com](mailto:mayermichael79@gmail.com)>

**Repository** CRAN

**Date/Publication** 2023-05-21 18:50:02 UTC

## Contents

Data . . . . .	2
generateOutliers . . . . .	3
is.outForest . . . . .	4
outForest . . . . .	4
outliers . . . . .	7
plot.outForest . . . . .	8
predict.outForest . . . . .	9
print.outForest . . . . .	10
summary.outForest . . . . .	11
<b>Index</b>	<b>12</b>

---

Data	<i>Extracts Data</i>
------	----------------------

---

### Description

Extracts data with optionally replaced outliers from object of class "outForest".

### Usage

```
Data(object, ...)

## Default S3 method:
Data(object, ...)

## S3 method for class 'outForest'
Data(object, ...)
```

### Arguments

object	An object of class "outForest".
...	Arguments passed from or to other methods.

### Value

A data.frame.

### Methods (by class)

- Data(default): Default method not implemented yet.
- Data(outForest): Extract data from "outForest" object.

### Examples

```
x <- outForest(iris)
head(Data(x))
```

---

generateOutliers	<i>Adds Outliers</i>
------------------	----------------------

---

### Description

Takes a vector, matrix or data frame and replaces some numeric values by outliers.

### Usage

```
generateOutliers(x, p = 0.05, sd_factor = 5, seed = NULL)
```

### Arguments

x	A vector, matrix or data.frame.
p	Proportion of outliers to add to x. In case x is a data.frame, p can also be a vector of probabilities per column or a named vector (see examples).
sd_factor	Each outlier is generated by shifting the original value by a realization of a normal random variable with sd_factor times the original sample standard deviation.
seed	An integer seed.

### Value

x with outliers.

### See Also

[outForest\(\)](#)

### Examples

```
generateOutliers(1:10, seed = 334, p = 0.3)
generateOutliers(cbind(1:10, 10:1), p = 0.2)
head(generateOutliers(iris))
head(generateOutliers(iris, p = 0.2))
head(generateOutliers(iris, p = c(0, 0, 0.5, 0.5, 0.5)))
head(generateOutliers(iris, p = c(Sepal.Length = 0.2)))
```

---

is.outForest	<i>Type Check</i>
--------------	-------------------

---

**Description**

Checks if an object inherits class "outForest".

**Usage**

```
is.outForest(x)
```

**Arguments**

x                   Any object.

**Value**

A logical vector of length one.

**Examples**

```
a <- outForest(iris)
is.outForest(a)
is.outForest("a")
```

---

outForest	<i>Multivariate Outlier Detection and Replacement</i>
-----------	---

---

**Description**

This function provides a random forest based implementation of the method described in Chapter 7.1.2 ("Regression Model Based Anomaly detection") of Chandola et al. Each numeric variable to be checked for outliers is regressed onto all other variables using a random forest. If the scaled absolute difference between observed value and out-of-bag prediction is larger than some predefined threshold (default is 3), then a value is considered an outlier, see Details below. After identification of outliers, they can be replaced, e.g., by predictive mean matching from the non-outliers.

**Usage**

```
outForest(
  data,
  formula = . ~ .,
  replace = c("pmm", "predictions", "NA", "no"),
  pmm.k = 3L,
  threshold = 3,
  max_n_outliers = Inf,
```

```

    max_prop_outliers = 1,
    min.node.size = 40L,
    allow_predictions = FALSE,
    impute_multivariate = TRUE,
    impute_multivariate_control = list(pmm.k = 3L, num.trees = 50L, maxiter = 3L),
    seed = NULL,
    verbose = 1,
    ...
)

```

## Arguments

<code>data</code>	A data.frame to be assessed for numeric outliers.
<code>formula</code>	A two-sided formula specifying variables to be checked (left hand side) and variables used to check (right hand side). Defaults to <code>. ~ .</code> , i.e., use all variables to check all (numeric) variables.
<code>replace</code>	Should outliers be replaced via predictive mean matching "pmm" (default), by "predictions", or by NA ("NA"). Use "no" to keep outliers as they are.
<code>pmm.k</code>	For <code>replace = "pmm"</code> , from how many nearest OOB prediction neighbours (from the original non-outliers) to sample?
<code>threshold</code>	Threshold above which an outlier score is considered an outlier. The default is 3.
<code>max_n_outliers</code>	Maximal number of outliers to identify. Will be used in combination with <code>threshold</code> and <code>max_prop_outliers</code> .
<code>max_prop_outliers</code>	Maximal relative count of outliers. Will be used in combination with <code>threshold</code> and <code>max_n_outliers</code> .
<code>min.node.size</code>	Minimal node size of the random forests. With 40, the value is relatively high. This reduces the impact of outliers.
<code>allow_predictions</code>	Should the resulting "outForest" object be applied to new data? Default is FALSE.
<code>impute_multivariate</code>	If TRUE (default), missing values are imputed by <code>missRanger::missRanger()</code> . Otherwise, by univariate sampling.
<code>impute_multivariate_control</code>	Parameters passed to <code>missRanger::missRanger()</code> (only if data contains missing values).
<code>seed</code>	Integer random seed.
<code>verbose</code>	Controls how much outliers is printed to screen. 0 to print nothing, 1 prints information.
<code>...</code>	Arguments passed to <code>ranger::ranger()</code> . If the data set is large, use less trees (e.g. <code>num.trees = 20</code> ) and/or a low value of <code>mtry</code> .

## Details

The method can be viewed as a multivariate extension of a basic univariate outlier detection method where a value is considered an outlier if it is more than, e.g., three times the standard deviation away from its mean. In the multivariate case, instead of comparing a value with the overall mean, rather the difference to the conditional mean is considered. `outForest()` estimates this conditional mean by a random forest. If the method is trained on a reference data with option `allow_predictions = TRUE`, it can even be applied to new data.

The outlier score of the  $i$ th value  $x_{ij}$  of the  $j$ th variable is defined as  $s_{ij} = (x_{ij} - p_{ij})/\text{rmse}_j$ , where  $p_{ij}$  is the corresponding out-of-bag prediction of the  $j$ th random forest and  $\text{rmse}_j$  its RMSE. If  $|s_{ij}| > L$  with threshold  $L$ , then  $x_{ij}$  is considered an outlier.

For large data sets, just by chance, many values can surpass the default threshold of 3. To reduce the number of outliers, the threshold can be increased. Alternatively, the number of outliers can be limited by the two arguments `max_n_outliers` and `max_prop_outliers`. For instance, if at most ten outliers are to be identified, set `max_n_outliers = 10`.

Since the random forest algorithm "ranger" does not allow for missing values, any missing value is first being imputed by chained random forests.

## Value

An object of class "outForest" and a list with the following elements.

- `Data`: Original data set in unchanged row order but optionally with outliers replaced. Can be extracted with the `Data()` function.
- `outliers`: Compact representation of outliers, for details see the `outliers()` function used to extract them.
- `n_outliers`: Number of outliers per  $v$ .
- `is_outlier`: Logical matrix with outlier status. NULL if `allow_predictions = FALSE`.
- `predData`: `data.frame` with OOB predictions. NULL if `allow_predictions = FALSE`.
- `allow_predictions`: Same as `allow_predictions`.
- `v`: Variables checked.
- `threshold`: The threshold used.
- `rmse`: Named vector of RMSEs of the random forests. Used for scaling the difference between observed values and predicted.
- `forests`: Named list of fitted random forests. NULL if `allow_predictions = FALSE`.
- `used_to_check`: Variables used for checking  $v$ .
- `mu`: Named vector of sample means of the original  $v$  (incl. outliers).

## References

1. Chandola V., Banerjee A., and Kumar V. (2009). Anomaly detection: A survey. *ACM Comput. Surv.* 41, 3, Article 15 <[dx.doi.org/10.1145/1541880.1541882](https://doi.org/10.1145/1541880.1541882)>.
2. Wright, M. N. & Ziegler, A. (2016). ranger: A Fast Implementation of Random Forests for High Dimensional Data in C++ and R. *Journal of Statistical Software*, in press. <[arxiv.org/abs/1508.04409](https://arxiv.org/abs/1508.04409)>.

**See Also**

[outliers\(\)](#), [Data\(\)](#) [plot.outForest\(\)](#), [summary.outForest\(\)](#), [predict.outForest\(\)](#)

**Examples**

```
head(irisWithOut <- generateOutliers(iris, seed = 345))
(out <- outForest(irisWithOut))
outliers(out)
head(Data(out))
plot(out)
plot(out, what = "scores")
```

---

outliers

*Extracts Outliers*

---

**Description**

Extracts outliers from object of class "outForest". The outliers are sorted by their absolute score in descending fashion.

**Usage**

```
outliers(object, ...)

## Default S3 method:
outliers(object, ...)

## S3 method for class 'outForest'
outliers(object, ...)
```

**Arguments**

object            An object of class "outForest".  
...               Arguments passed from or to other methods.

**Value**

A data.frame with one row per outlier. The columns are as follows:

- row, col: Row and column in original data with outlier.
- observed: Observed value.
- predicted: Predicted value.
- rmse: Scaling factor used to normalize the difference between observed and predicted.
- score: Outlier score defined as (observed-predicted)/RMSE.
- threshold: Threshold above which an outlier score counts as outlier.
- replacement: Value used to replace observed value.

**Methods (by class)**

- outliers(default): Default method not implemented yet.
- outliers(outForest): Extract outliers from outForest object.

**Examples**

```
x <- outForest(iris)
outliers(x)
```

---

plot.outForest      *Plots outForest*

---

**Description**

This function can plot aspects of an "outForest" object.

- With what = "counts", the number of outliers per variable is visualized as a barplot.
- With what = "scores", outlier scores (i.e., the scaled difference between predicted and observed value) are shown as scatterplot per variable.

**Usage**

```
## S3 method for class 'outForest'
plot(x, what = c("counts", "scores"), ...)
```

**Arguments**

x	An object of class "outForest".
what	What should be plotted? Either "counts" (the default) or "scores".
...	Arguments passed to <code>graphics::barplot()</code> or <code>graphics::stripchart()</code> .

**Value**

A list.

**Examples**

```
irisWithOutliers <- generateOutliers(iris, seed = 345)
x <- outForest(irisWithOutliers, verbose = 0)
plot(x)
plot(x, what = "scores")
```

---

predict.outForest      *Out-of-Sample Application*

---

### Description

Identifies outliers in new data based on previously fitted "outForest" object. The result of predict() is again an object of class "outForest". All its methods can be applied to it.

### Usage

```
## S3 method for class 'outForest'
predict(
  object,
  newdata,
  replace = c("pmm", "predictions", "NA", "no"),
  pmm.k = 3L,
  threshold = object$threshold,
  max_n_outliers = Inf,
  max_prop_outliers = 1,
  seed = NULL,
  ...
)
```

### Arguments

object	An object of class "outForest".
newdata	A new data.frame to be assessed for numeric outliers.
replace	Should outliers be replaced via predictive mean matching "pmm" (default), by "predictions", or by NA ("NA"). Use "no" to keep outliers as they are.
pmm.k	For replace = "pmm", from how many nearest OOB prediction neighbours (from the original non-outliers) to sample?
threshold	Threshold above which an outlier score is considered an outlier. The default is 3.
max_n_outliers	Maximal number of outliers to identify. Will be used in combination with threshold and max_prop_outliers.
max_prop_outliers	Maximal relative count of outliers. Will be used in combination with threshold and max_n_outliers.
seed	Integer random seed.
...	Further arguments passed from other methods.

### Value

An object of class "outForest".

**See Also**

`outForest()`, `outliers()`, `Data()`

**Examples**

```
(out <- outForest(iris, allow_predictions = TRUE))
iris1 <- iris[1, ]
iris1$Sepal.Length <- -1
pred <- predict(out, newdata = iris1)
outliers(pred)
Data(pred)
plot(pred)
plot(pred, what = "scores")
```

---

print.outForest	<i>Prints outForest</i>
-----------------	-------------------------

---

**Description**

Print method for an object of class "outForest".

**Usage**

```
## S3 method for class 'outForest'
print(x, ...)
```

**Arguments**

x	A on object of class "outForest".
...	Further arguments passed from other methods.

**Value**

Invisibly, the input is returned.

**Examples**

```
x <- outForest(iris)
x
```

---

summary.outForest	<i>Summarizes outForest</i>
-------------------	-----------------------------

---

**Description**

Summary method for an object of class "outForest". Besides the number of outliers per variables, it also shows the worst outliers.

**Usage**

```
## S3 method for class 'outForest'  
summary(object, ...)
```

**Arguments**

object	A on object of class "outForest".
...	Further arguments passed from other methods.

**Value**

A list of summary statistics.

**Examples**

```
out <- outForest(iris, seed = 34, verbose = 0)  
summary(out)
```

# Index

Data, [2](#)

Data(), [6](#), [7](#), [10](#)

generateOutliers, [3](#)

graphics::barplot(), [8](#)

graphics::stripchart(), [8](#)

is.outForest, [4](#)

missRanger::missRanger(), [5](#)

outForest, [4](#)

outForest(), [3](#), [10](#)

outliers, [7](#)

outliers(), [6](#), [7](#), [10](#)

plot.outForest, [8](#)

plot.outForest(), [7](#)

predict.outForest, [9](#)

predict.outForest(), [7](#)

print.outForest, [10](#)

ranger::ranger(), [5](#)

summary.outForest, [11](#)

summary.outForest(), [7](#)