

Package ‘poolVIM’

May 9, 2026

Type Package

Title Gene-Based Association Tests using the Actual Impurity Reduction (AIR) Variable Importance

Version 1.0.0

Date 2018-07-25

Author Stefano Nembrini <stefanonembrini@gmail.com>

Maintainer Stefano Nembrini <stefanonembrini@gmail.com>

Description Gene-based association tests using the actual impurity reduction (AIR) variable importance. The function aggregates AIR importance measures from a group of SNPs or probes and outputs a p-value for each gene. The procedure builds upon the method described in <doi:10.1093/Bioinformatics/Bty373> and will be published soon.

License GPL (>= 2)

LazyData TRUE

Imports stats, ranger

Depends R(>= 3.3.1), EmpiricalBrownsMethod(>= 1.6.0), Hmisc(>= 4.1)

RoxygenNote 6.0.1

NeedsCompilation no

Repository CRAN

Date/Publication 2018-07-30 17:30:08 UTC

Contents

fisher	2
gaussianize	2
m_effective	2
poolVIM	3
tippett	3

Index	5
--------------	----------

fisher	<i>fisher</i>
--------	---------------

Description

fisher

Usage

fisher(p, adjust, R)

Arguments

p	vector of pvalues
adjust	if correlation has to be taken into account
R	correlation matrix

gaussianize	<i>gaussianize null variable importances</i>
-------------	--

Description

gaussianize null variable importances

Usage

gaussianize(x, a)

Arguments

x	distr
a	value to interpolate/extrapolate

m_effective	<i>meff.</i>
-------------	--------------

Description

meff.

Usage

m_effective(R)

Arguments

R	R
---	---

poolVIM	<i>after the Actual Impurity Reduction Importance is computed with a Random Forest, pvalues from different probes or SNPs belonging to the same gene can be aggregated in order to obtain a single pvalue for that gene. Correlation between probes can also be taken into account.</i>
---------	---

Description

after the Actual Impurity Reduction Importance is computed with a Random Forest, pvalues from different probes or SNPs belonging to the same gene can be aggregated in order to obtain a single pvalue for that gene. Correlation between probes can also be taken into account.

Usage

```
poolVIM(rf, genenames, x, method = "Tippett", adjust)
```

Arguments

rf	a ranger object with "importance="impurity_corrected"
genenames	a vector of the name of the gene to which each probe or SNP belongs, it has to be of size dim(x)[1]
x	design matrix used by the random forest
method	one of Tippett, Fisher, Kost, EBM
adjust	"no" / "yes" depending if correlation has to be taken into account

Examples

```
n <- 250
x=replicate(50, runif(n))
dat <- data.frame(y = factor(rbinom(n, 1, .5)), x)
library(ranger)
rf <- ranger(y ~ ., dat, importance = "impurity_corrected", num.trees=100)
genenames=colnames(x)=rep(c("G1", "G2"), 50/2)
poolVIM(rf, genenames, x, method="Fisher", adjust="no")
```

tippett	<i>tippett.</i>
---------	-----------------

Description

tippett.

Usage

```
tippett(p, adjust, R)
```

Arguments

p	vector of pvalues
adjust	if correlation has to be taken into account
R	correlation matrix

Index

fisher, 2

gaussianize, 2

m_effective, 2

poolVIM, 3

tippett, 3