

# Package ‘rpca’

May 9, 2026

**Type** Package

**Title** RobustPCA: Decompose a Matrix into Low-Rank and Sparse Components

**Version** 0.2.3

**Date** 2015-07-19

**Author** Maciek Sykulski [aut, cre]

**Maintainer** Maciek Sykulski <macieksk@gmail.com>

**Description** Suppose we have a data matrix, which is the superposition of a low-rank component and a sparse component. Candes, E. J., Li, X., Ma, Y., & Wright, J. (2011). Robust principal component analysis?. Journal of the ACM (JACM), 58(3), 11. prove that we can recover each component individually under some suitable assumptions. It is possible to recover both the low-rank and the sparse components exactly by solving a very convenient convex program called Principal Component Pursuit; among all feasible decompositions, simply minimize a weighted combination of the nuclear norm and of the L1 norm. This package implements this decomposition algorithm resulting with Robust PCA approach.

**License** GPL-2 | GPL-3

**Imports** compiler

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2015-07-31 01:15:38

## Contents

rpca-package	2
F2norm	3
rpca	4
thresh.l1	6
thresh.nuclear	7

**Index** 9

rpca-package

*RobustPCA: Decompose a Matrix into Low-Rank and Sparse Components***Description**

Suppose we have a data matrix, which is the superposition of a low-rank component and a sparse component. Candes, E. J., Li, X., Ma, Y., & Wright, J. (2011). Robust principal component analysis?. *Journal of the ACM (JACM)*, 58(3), 11. prove that we can recover each component individually under some suitable assumptions. It is possible to recover both the low-rank and the sparse components exactly by solving a very convenient convex program called Principal Component Pursuit; among all feasible decompositions, simply minimize a weighted combination of the nuclear norm and of the L1 norm. This package implements this decomposition algorithm resulting with Robust PCA approach.

**Details**

Index of help topics:

F2norm	Frobenius norm of a matrix
rpca	Decompose a matrix into a low-rank component and a sparse component by solving Principal Components Pursuit
rpca-package	RobustPCA: Decompose a Matrix into Low-Rank and Sparse Components
thresh.l1	Shrinkage operator
thresh.nuclear	Thresholding operator

This package contains `rpca` function, which decomposes a rectangular matrix  $M$  into a low-rank component, and a sparse component, by solving a convex program called Principal Component Pursuit:

$$\begin{aligned} &\text{minimize} && \|L\|_* + \lambda\|S\|_1 \\ &\text{subject to} && L + S = M \end{aligned}$$

where  $\|L\|_*$  is the nuclear norm of  $L$  (sum of singular values).

**Note**

Use `citation("rpca")` to cite this R package.

**Author(s)**

Maciek Sykulski [aut, cre]

Maintainer: Maciek Sykulski <macieksk@gmail.com>

## References

Candès, E. J., Li, X., Ma, Y., & Wright, J. (2011). Robust principal component analysis?. *Journal of the ACM (JACM)*, 58(3), 11.

Yuan, X., & Yang, J. (2009). Sparse and low-rank matrix decomposition via alternating direction methods. preprint, 12.

## See Also

[rpca](#)

---

F2norm

*Frobenius norm of a matrix*

---

## Description

Frobenius norm of a matrix.

## Usage

F2norm(M)

## Arguments

M                    A matrix.

## Value

Frobenius norm of M.

## Examples

```
## The function is currently defined as
function (M)
  sqrt(sum(M^2))

F2norm(matrix(runif(100),nrow=5))
```

---

rpca *Decompose a matrix into a low-rank component and a sparse component by solving Principal Components Pursuit*

---

### Description

This function decomposes a rectangular matrix  $M$  into a low-rank component, and a sparse component, by solving a convex program called Principal Component Pursuit.

### Usage

```
rpca(M,
      lambda = 1/sqrt(max(dim(M))), mu = prod(dim(M))/(4 * sum(abs(M))),
      term.delta = 10^(-7), max.iter = 5000, trace = FALSE,
      thresh.nuclear.fun = thresh.nuclear, thresh.l1.fun = thresh.l1,
      F2norm.fun = F2norm)
```

### Arguments

<code>M</code>	a rectangular matrix that is to be decomposed into a low-rank component and a sparse component $M = L + S$ .
<code>lambda</code>	parameter of the convex problem $\ L\ _* + \lambda\ S\ _1$ which is minimized in the Principal Components Pursuit algorithm. The default value is the one suggested in Candès, E. J., section 1.4, and together with reasonable assumptions about $L$ and $S$ guarantees that a correct decomposition is obtained.
<code>mu</code>	parameter from the augmented Lagrange multiplier formulation of the PCP, Candès, E. J., section 5. Default value is the one suggested in references.
<code>term.delta</code>	The algorithm terminates when $\ M - L - S\ _F \leq \delta\ M\ _F$ where $\ \cdot\ _F$ is Frobenius norm of a matrix.
<code>max.iter</code>	Maximal number of iterations of the augmented Lagrange multiplier algorithm. A warning is issued if the algorithm does not converge by then.
<code>trace</code>	Print out information with every iteration.
<code>thresh.nuclear.fun, thresh.l1.fun, F2norm.fun</code>	Arguments for internal use only.

### Details

These functions decompose a rectangular matrix  $M$  into a low-rank component, and a sparse component, by solving a convex program called Principal Component Pursuit:

$$\begin{aligned} &\text{minimize} && \|L\|_* + \lambda\|S\|_1 \\ &\text{subject to} && L + S = M \end{aligned}$$

where  $\|L\|_*$  is the nuclear norm of  $L$  (sum of singular values).

**Value**

The function returns two matrices  $S$  and  $L$ , which have the property that  $L + S \simeq M$ , where the quality of the approximation depends on the argument `term.delta`, and the convergence of the algorithm.

`S`                    The sparse component of the matrix decomposition.  
`L`                    The low-rank component of the matrix decomposition.  
`L.svd`                The singular value decomposition of  $L$ , as returned by the function `La.svd`.  
`convergence$converged`  
                       TRUE if the algorithm converged with respect to `term.delta`.  
`convergence$iterations`  
                       Number of performed iterations.  
`convergence$final.delta`  
                       The final iteration `delta` which is compared with `term.delta`.  
`convergence$all.delta`  
                       All `delta` from all iterations.

**Author(s)**

Maciek Sykulski [aut, cre]

**References**

Candès, E. J., Li, X., Ma, Y., & Wright, J. (2011). Robust principal component analysis?. *Journal of the ACM (JACM)*, 58(3), 11.  
 Yuan, X., & Yang, J. (2009). Sparse and low-rank matrix decomposition via alternating direction methods. preprint, 12.

**Examples**

```
data(iris)
M <- as.matrix(iris[,1:4])
Mcent <- sweep(M,2,colMeans(M))

res <- rpca(Mcent)

## Check convergence and number of iterations
with(res$convergence,list(converged,iterations))
## Final delta F2 norm divided by F2norm(Mcent)
with(res$convergence,final.delta)

## Check properites of the decomposition
with(res,c(
  all(abs( L+S - Mcent ) < 10^-5),
  all( L == L.svd$u%*(L.svd$d*L.svd$vt) )
))
# [1] TRUE TRUE

## The low rank component has rank 2
```

```

length(res$L.svd$d)
## However, the sparse component is not sparse
## - thus this data set is not the best example here.
mean(res$S==0)

## Plot the first (the only) two principal components
## of the low-rank component L
rpc<-res$L.svd$u%*%diag(res$L.svd$d)
plot(jitter(rpc[,1:2],amount=.001),col=iris[,5])

## Compare with classical principal components
pc <- prcomp(M,center=TRUE)
plot(pc$x[,1:2],col=iris[,5])
points(rpc[,1:2],col=iris[,5],pch="+")

## "Sparse" elements distribution
plot(density(abs(res$S),from=0))
curve(dexp(x,rate=1/mean(abs(res$S))),add=TRUE,lty=2)

## Plot measurements against measurements corrected by sparse components
par(mfcol=c(2,2))
for(i in 1:4) {
plot(M[,i],M[,i]-res$S[,i],col=iris[,5],xlab=colnames(M)[i])
}

```

---

thresh.l1

*Shrinkage operator*


---

### Description

Shrinkage operator:  $S[x] = \text{sgn}(x) \max(|x| - \text{thr}, 0)$ . For description see section 5 of Candès, E. J., Li, X., Ma, Y., & Wright, J. (2011). Robust principal component analysis?.

### Usage

```
thresh.l1(x, thr)
```

### Arguments

x	a vector or a matrix.
thr	threshold $\geq 0$ to shrink with.

### Value

$S[x] = \text{sgn}(x) \max(|x| - \text{thr}, 0)$

**References**

- Candès, E. J., Li, X., Ma, Y., & Wright, J. (2011). Robust principal component analysis?. Journal of the ACM (JACM), 58(3), 11
- Yuan, X., & Yang, J. (2009). Sparse and low-rank matrix decomposition via alternating direction methods. preprint, 12.

**See Also**

[thresh.nuclear](#)

**Examples**

```
## The function is currently defined as
function(x, thr){sign(x)*pmax(abs(x)-thr,0)}

summary(thresh.l1(runif(100),0.3))
```

---

thresh.nuclear	<i>Thresholding operator</i>
----------------	------------------------------

---

**Description**

Thresholding operator, an application of the shrinkage operator on a singular value decomposition:  $D[X] = U S[\text{Sigma}] V$ . For description see section 5 of Candès, E. J., Li, X., Ma, Y., & Wright, J. (2011). Robust principal component analysis?.

**Usage**

```
thresh.nuclear(M, thr)
```

**Arguments**

M                    a rectangular matrix.  
thr                    threshold  $\geq 0$  to shrink singular values with.

**Value**

Returned is a thresholded Singular Value Decomposition with thr subtracted from singular values, and values smaller than 0 dropped together with their singular vectors.

u, d, vt            as in return value of `La.svd`  
L                    the resulting low-rank matrix:  $L = UDV^t$

**References**

- Candès, E. J., Li, X., Ma, Y., & Wright, J. (2011). Robust principal component analysis?. Journal of the ACM (JACM), 58(3), 11
- Yuan, X., & Yang, J. (2009). Sparse and low-rank matrix decomposition via alternating direction methods. preprint, 12.

**See Also**[thresh.l1](#)**Examples**

```
## The function is currently defined as
function (M, thr) {
  s <- La.svd.cmp(M)
  dd <- thresh.l1(s$d, thr)
  id <- which(dd != 0)
  s$d <- dd[id]
  s$u <- s$u[, id, drop = FALSE]
  s$vt <- s$vt[id, , drop = FALSE]
  s$L <- s$u %*% (s$d * s$vt)
  s
}

l<-thresh.nuclear(matrix(runif(600),nrow=20),2)
l$d
```

# Index

- \* **Frobenius norm**
    - F2norm, 3
  - \* **low-rank and sparse components**
    - rpca, 4
  - \* **package**
    - rpca-package, 2
  - \* **robust pca**
    - rpca, 4
    - rpca-package, 2
  - \* **rpca**
    - rpca, 4
    - rpca-package, 2
  - \* **shrinkage operator**
    - thresh.l1, 6
  - \* **sparse and low-rank matrix decomposition**
    - rpca-package, 2
  - \* **thresholding operator**
    - thresh.nuclear, 7
- F2norm, 3
- rpca, 2, 3, 4
- rpca-package, 2
- thresh.l1, 6, 8
- thresh.nuclear, 7, 7