

# Package ‘sunburstR’

May 9, 2026

**Type** Package

**Title** Sunburst 'Htmlwidget'

**Version** 2.1.8

**Date** 2023-02-05

**Maintainer** Kent Russell <kent.russell@timelyportfolio.com>

**URL** <https://github.com/timelyportfolio/sunburstR>

**BugReports** <https://github.com/timelyportfolio/sunburstR/issues>

**Description** Make interactive 'd3.js' sequence sunburst diagrams in R with the convenience and infrastructure of an 'htmlwidget'.

**License** MIT + file LICENSE

**Imports** d3r (>= 0.6.9), dplyr, htmlwidgets, htmltools

**Suggests** jsonlite, knitr, markdown, pipeR, testthat, tidyr (>= 0.7.0), rmarkdown

**Enhances** treemap

**RoxygenNote** 7.2.3

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Mike Bostock [aut, cph] (d3.js library, <http://d3js.org>),  
Kerry Rodden [aut, cph] (sequences library in htmlwidgets/lib,  
<https://gist.github.com/kerryrodden/7090426>),  
Kevin Warne [aut, cph] (d2b sunburst library in htmlwidgets/lib,  
<https://github.com/d2bjs/d2b>),  
Kent Russell [aut, cre] (R interface),  
Florian Breitwieser [ctb] (R interface),  
CJ Yetman [ctb] (R interface, ORCID:  
<<https://orcid.org/0000-0001-5099-9500>>)

**Repository** CRAN

**Date/Publication** 2023-02-05 23:20:02 UTC

## Contents

add_shiny . . . . .	2
d2b-shiny . . . . .	4
sunburst . . . . .	4
sunburst-shiny . . . . .	10
sund2b . . . . .	11
sund2bBreadcrumb . . . . .	13
sund2bTooltip . . . . .	14

<b>Index</b>	<b>16</b>
--------------	-----------

---

add_shiny	<i>Add Shiny Events</i>
-----------	-------------------------

---

### Description

Add Shiny Events

### Usage

```
add_shiny(sunburst = NULL)
```

### Arguments

sunburst            sunburst htmlwidget to which you would like to add event handling

### Value

sunburst htmlwidget

### Examples

```
## Not run:

library(shiny)
library(sunburstR)

sequences <- read.csv(
  system.file("examples/visit-sequences.csv", package="sunburstR")
  ,header=F
  ,stringsAsFactors = FALSE
)

server <- function(input,output,session){

  output$sunburst <- renderSunburst({
    #invalidateLater(1000, session)
  })
}
```

```

    sequences <- sequences[sample(nrow(sequences),1000),]

    add_shiny(sunburst(sequences))
  })

  selection <- reactive({
    input$sunburst_mouseover
  })

  output$selection <- renderText(selection())
}

ui<-fluidPage(
  sidebarLayout(
    sidebarPanel(

    ),

    # plot sunburst
    mainPanel(
      sunburstOutput("sunburst"),
      textOutput("selection")
    )
  )
)

shinyApp(ui = ui, server = server)

# an example with d2b sunburst and Shiny
library(shiny)
library(sunburstR)

# use a sample of the sequences csv data
sequences <- read.csv(
  system.file("examples/visit-sequences.csv",package="sunburstR")
  ,header = FALSE
  ,stringsAsFactors = FALSE
)[1:200,]

# create a d2b sunburst
s2b <- sund2b(sequences)

options(shiny.trace=TRUE)
ui <- sund2bOutput("s2b")
server <- function(input, output, session) {
  output$s2b <- renderSund2b({
    add_shiny(s2b)
  })
}
shinyApp(ui, server)

```

```
## End(Not run)
```

---

d2b-shiny

*Shiny bindings for d2b*


---

### Description

Output and render functions for using d2b within Shiny applications and interactive Rmd documents.

### Usage

```
sund2bOutput(outputId, width = "100%", height = "400px")
```

```
renderSund2b(expr, env = parent.frame(), quoted = FALSE)
```

### Arguments

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a d2b
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

---

sunburst

*'d3.js' Sequence Sunburst Diagrams*


---

### Description

**Sequences sunburst** diagrams provide an interactive method of exploring sequence data, such as website navigation paths.

### Usage

```
sunburst(
  data = NULL,
  legendOrder = NULL,
  colors = NULL,
  valueField = "size",
  percent = TRUE,
  count = FALSE,
  explanation = NULL,
```

```

    breadcrumb = list(),
    legend = list(),
    sortFunction = NULL,
    sumNodes = TRUE,
    withD3 = FALSE,
    width = NULL,
    height = NULL,
    elementId = NULL,
    sizingPolicy = NULL,
    csvdata = NULL,
    jsondata = NULL
  )

```

### Arguments

data	data in csv source,target form or in nested d3 JSON hierarchy with 'name:..., children:[];'. csvdata and jsondata arguments are now deprecated in favor of this single data argument. list, character, or connection data will be assumed to be JSON. data.frame data will be assumed to be csvdata and converted to JSON by <code>sunburstR::csv_to_hier()</code> .
legendOrder	string vector if you would like to manually order the legend. If legendOrder is not provided, then the legend will be in the descending order of the top level hierarchy.
colors	vector of strings representing colors as hexadecimal for manual colors. If you want precise control of colors, supply a list with range and/or domain. For advanced customization, supply a JavaScript function.
valueField	character for the field to use to calculate size. The default value is "size".
percent	logical to include percentage of total in the explanation.
count	logical to include count and total in the explanation.
explanation	JavaScript function to define a custom explanation for the center of the sunburst. Note, this will override percent and count.
breadcrumb	list to customize the breadcrumb trail. This argument should be in the form <code>list(w =, h =, s =, t =)</code> where w is the width, h is the height, s is the spacing, and t is the tail all in px. w is 0 by default for breadcrumbs widths based on text length.
legend	list to customize the legend or logical to disable the legend. The list argument should be in the form <code>list(w =, h =, r =, s =)</code> where w is the width, h is the height, s is the spacing, and r is the radius all in px.
sortFunction	JS function to sort the slices. The default sort is by size.
sumNodes	logical to sum non-leaf nodes. The default <code>sumNodes = TRUE</code> assumes that the user has not already calculated a sum.
withD3	logical to include d3 dependency from d3r. As of version 1.0, sunburst uses a standalone JavaScript build and will not include the entire d3 in the global/window namespace. To include d3.js in this way, use <code>withD3=TRUE</code> .
height,width	height and width of sunburst htmlwidget containing div specified in any valid CSS size unit.

elementId        string id as a valid CSS element id.  
 sizingPolicy    see [sizingPolicy](#).  
 csvdata         deprecated use data argument instead; data in csv source,target form  
 jsondata        deprecated use data argument instead; data in nested d3 JSON hierarchy with  
                  'name:..., children:[];'

## Examples

```

library(sunburstR)

# read in sample visit-sequences.csv data provided in source
# only use first 100 rows to speed package build and check
# https://gist.github.com/kerryrodden/7090426#file-visit-sequences-csv
sequences <- read.csv(
  system.file("examples/visit-sequences.csv",package="sunburstR")
  ,header = FALSE
  ,stringsAsFactors = FALSE
)[1:100,]

sunburst(sequences)

## Not run:

# explore some of the arguments
sunburst(
  sequences
  ,count = TRUE
)

sunburst(
  sequences
  # apply sort order to the legends
  ,legendOrder = unique(unlist(strsplit(sequences[,1],"-")))
  # just provide the name in the explanation in the center
  ,explanation = "function(d){return d.data.name}"
)

# try with json data
sequence_json <- jsonlite::fromJSON(
  system.file("examples/visit-sequences.json",package="sunburstR"),
  simplifyDataFrame = FALSE
)
sunburst(sequence_json)

# try with csv data from this fork
# https://gist.github.com/mkajava/7515402
# great use for new breadbrumb wrapping
sunburst(
  csvdata = read.csv(

```

```

    file = paste0(
      "https://gist.githubusercontent.com/mkajava/",
      "7515402/raw/9f80d28094dc9dfed7090f8fb3376ef1539f4fd2/",
      "comment-sequences.csv"
    )
    ,header = TRUE
    ,stringsAsFactors = FALSE
  )
)

# try with csv data from this fork
# https://gist.github.com/rileycrane/92a2c36eb932b4f99e51/
sunburst( csvdata = read.csv(
  file = paste0(
    "https://gist.githubusercontent.com/rileycrane/",
    "92a2c36eb932b4f99e51/raw/",
    "a0212b4ca8043af47ec82369aa5f023530279aa3/visit-sequences.csv"
  )
  ,header=FALSE
  ,stringsAsFactors = FALSE
))

## End(Not run)
## Not run:
# use sunburst to analyze ngram data from Peter Norvig
# http://norvig.com/mayzner.html

library(sunburstR)
library(pipeR)

# read the csv data downloaded from the Google Fusion Table linked in the article
ngrams2 <- read.csv(
  system.file(
    "examples/ngrams2.csv"
    ,package="sunburstR"
  )
  , stringsAsFactors = FALSE
)

ngrams2 %>>%
  # let's look at ngrams at the start of a word, so columns 1 and 3
  (.[,c(1,3)]) %>>%
  # split the ngrams into a sequence by splitting each letter and adding -
  (
    data.frame(
      sequence = strsplit(.[,1], "") %>>%
        lapply( function(ng){ paste0(ng,collapse = "-") } ) %>>%
        unlist
      ,freq = .[,2]
      ,stringsAsFactors = FALSE
    )
  ) %>>%

```

```

sunburst

library(htmltools)

ngrams2 %>>%
  (
    lapply(
      seq.int(3,ncol(.))
      ,function(letpos){
        (.[,c(1,letpos)]) %>>%
          # split the ngrams into a sequence by splitting each letter and adding -
          (
            data.frame(
              sequence = strsplit(.[,1], "") %>>%
                lapply( function(ng){ paste0(ng,collapse = "-") } ) %>>%
                unlist
              ,freq = .[,2]
              ,stringsAsFactors = FALSE
            )
          ) %>>%
        ( tags$div(style="float:left;",sunburst( ., height = 300, width = 300 )) )
      )
    )
  ) %>>%
tagList %>>%
browsable

## End(Not run)
## Not run:
library(treemap)
library(sunburstR)
library(d3r)

# use example from ?treemap::treemap
data(GNI2014)
tm <- treemap(GNI2014,
  index=c("continent", "iso3"),
  vSize="population",
  vColor="continent",
  type="index")

tm_nest <- d3_nest(
  tm$tm[,c("continent", "iso3", "vSize", "color")],
  value_cols = c("vSize", "color")
)

sunburst(
  data = tm_nest,
  valueField = "vSize",
  count = TRUE,
  # to avoid double counting with pre-summed trees
  # use sumNodes = FALSE

```

```

    sumNodes = FALSE,
    colors = htmlwidgets::JS("function(d){return d3.select(this).datum().data.color;}"),
    withD3 = TRUE
  )

## End(Not run)
# calendar sunburst example

library(sunburstR)

df <- data.frame(
  date = seq.Date(
    as.Date('2014-01-01'),
    as.Date('2016-12-31'),
    by = "days"
  ),
  stringsAsFactors = FALSE
)

df$year = format(df$date, "%Y")
df$quarter = paste0("Q", ceiling(as.numeric(format(df$date, "%m"))/3))
df$month = format(df$date, "%b")
df$path = paste(df$year, df$quarter, df$month, sep="-")
df$count = rep(1, nrow(df))

sunburst(
  data.frame(xtabs(count~path,df)),
  # added a degree of difficulty by providing
  # not easily sortable names
  sortFunction = htmlwidgets::JS(
    "
function(a,b){
  abb = {
    2014:-7,
    2015:-6,
    2016:-5,
    Q1:-4,
    Q2:-3,
    Q3:-2,
    Q4:-1,
    Jan:1,
    Feb:2,
    Mar:3,
    Apr:4,
    May:5,
    Jun:6,
    Jul:7,
    Aug:8,
    Sep:9,
    Oct:10,
    Nov:11,
    Dec:12
  }
}

```

```

    return abb[a.data.name] - abb[b.data.name];
  }
  "
)
)
# sorting example: place data in order of occurrence

library(sunburstR)

df <- data.frame(
  group = c("foo", "bar", "xyz"),
  value = c(1, 3, 2)
)

sunburst(df,
  # create a trivial sort function
  sortFunction = htmlwidgets::JS('function(x) {return x;}'))

new_order <- c(3,2,1)
sunburst(df[new_order,],
  sortFunction = htmlwidgets::JS('function(x) {return x;}'))

```

---

sunburst-shiny

*Shiny bindings for sunburst*


---

## Description

Output and render functions for using sunburst within Shiny applications and interactive Rmd documents.

## Usage

```
sunburstOutput(outputId, width = "100%", height = "400px")
```

```
renderSunburst(expr, env = parent.frame(), quoted = FALSE)
```

## Arguments

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a sunburst
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

---

sund2b *Sunburst Using 'd2b'*

---

## Description

Create interactive sunburst chart with the 'd2b' charting library.

## Usage

```
sund2b(
  data = NULL,
  colors = NULL,
  valueField = "size",
  tooltip = NULL,
  breadcrumbs = NULL,
  rootLabel = NULL,
  showLabels = FALSE,
  width = NULL,
  height = NULL,
  elementId = NULL
)
```

## Arguments

data	data in csv source,target form or in nested d3 JSON hierarchy with 'name:..., children:[];'. list, character, or connection data will be assumed to be JSON. data.frame data will be assumed to be csvdata and converted to JSON by <code>sunburstR::csv_to_hier()</code> .
colors	vector of strings representing colors as hexadecimal for manual colors. If you want precise control of colors, supply a list with range and/or domain. For advanced customization, supply a JavaScript function.
valueField	character for the field to use to calculate size. The default value is "size".
tooltip	list of options for customizing the tooltip. See the helper function <a href="#">sund2bTooltip</a> for more information.
breadcrumbs	list of options for customizing the breadcrumb. See the helper function <a href="#">sund2bBreadcrumb</a> for more information.
rootLabel	character to label root node something other than 'root'.
showLabels	logical to show labels on the slices. The default is FALSE.
height,width	height and width of sunburst htmlwidget containing div specified in any valid CSS size unit.
elementId	string id as a valid CSS element id.

**Examples**

```

if(interactive()){

  # The sund2b() API mirrors sunburst() with fewer arguments.

  library(sunburstR)

  # use a sample of the sequences csv data
  sequences <- read.csv(
    system.file("examples/visit-sequences.csv", package="sunburstR")
    ,header = FALSE
    ,stringsAsFactors = FALSE
  )[1:200,]

  # create a d2b sunburst
  sund2b(sequences)

  # show labels
  sund2b(sequences, showLabels = TRUE)

  # change the colors
  # using d3.js categorical color scheme
  sund2b(
    sequences,
    colors = htmlwidgets::JS("d3.scaleOrdinal(d3.schemeCategory20b)")
  )
}

## Not run:
# using RColorBrewer palette
sund2b(
  sequences,
  colors = list(range = RColorBrewer::brewer.pal(9, "Set3"))
)
# using a color column from the R dataset
# treemap has an amazing treecolors ability
library(treemap)
library(d3r)
rhd <- random.hierarchical.data()
tm <- treemap(
  rhd,
  index = paste0("index", 1:3),
  vSize = "x",
  draw = FALSE
)$tm
sund2b(
  d3_nest(tm, value_cols = colnames(tm)[-1:3]),
  colors = htmlwidgets::JS(
    # yes this is a little different, so please pay attention
    # "function(d) {return d.color}" will not work
    "function(name, d){return d.color || '#ccc';}"
  ),

```

```

    valueField = "vSize"
  )

  # use sund2b in Shiny
  library(shiny)
  ui <- sund2bOutput("sun")
  server <- function(input, output, session) {
    output$sun <- renderSund2b({
      sund2b(sequences)
    })
  }
  shinyApp(ui, server)

## End(Not run)

```

---

sund2bBreadcrumb

*Advanced Customization of 'd2b' Breadcrumb*


---

## Description

Advanced Customization of 'd2b' Breadcrumb

## Usage

```
sund2bBreadcrumb(enabled = NULL, html = NULL, orient = NULL)
```

## Arguments

enabled	boolean to enable or disable the breadcrumbs.
html	character or <code>htmlwidgets::JS</code> to customize the content of the breadcrumb. To provide a function, the arguments for the 'JavaScript' function will be 'function(nodedata, size, percent)' and the function should return a string.
orient	character which should be one of "top", "left", "right", "bottom" to control the orientation of the breadcrumb relative to the chart.

## Value

list

## Examples

```

if(interactive()){

  library(sunburstR)

  # use a sample of the sequences csv data
  sequences <- read.csv(

```

```

system.file("examples/visit-sequences.csv",package="sunburstR")
,header = FALSE
,stringsAsFactors = FALSE
)[1:200,]

# disable the breadcrumb
sund2b(
  sequences,
  breadcrumbs = sund2bBreadcrumb(
    enabled = FALSE
  )
)

# change the breadcrumb content
sund2b(
  sequences,
  breadcrumbs = sund2bBreadcrumb(
    html = htmlwidgets::JS("
function(nodedata, size, percent) {
  return '<span style=\"font-weight: bold;\">' + nodedata.name + '</span>' + ' ' + size
}
")
)
)
}

```

---

sund2bTooltip

*Advanced Customization of 'd2b' Tooltip*


---

## Description

Advanced Customization of 'd2b' Tooltip

## Usage

```
sund2bTooltip(at = NULL, followMouse = NULL, html = NULL, my = NULL)
```

## Arguments

at	character which should be one of "top left", "top center", "top right", "center left", "center center", "center right", "bottom left", "bottom center", "bottom right" to specify where the tooltip will be positioned relative to the hovered item.
followMouse	logical controlling whether the tooltip will follow the mouse instead of being placed in a static position relative to the hovered element
html	character or <code>htmlwidgets::JS</code> to customize the content of the tooltip. To provide a function, the arguments for the 'JavaScript' function will be 'function(nodedata, size, percent)' and the function should return a string.

my character which should be one of "top", "left", "right", "bottom" to control the orientation of the tooltip.

**Value**

list

**Examples**

```
if(interactive()){  
  
  library(sunburstR)  
  
  # use a sample of the sequences csv data  
  sequences <- read.csv(  
    system.file("examples/visit-sequences.csv",package="sunburstR")  
    ,header = FALSE  
    ,stringsAsFactors = FALSE  
  )[1:200,]  
  
  # change the tooltip  
  sund2b(  
    sequences,  
    tooltip = sund2bTooltip(  
      html = htmlwidgets::JS("  
function(nodedata, size, percent) {  
  return '<span style=\"font-weight: bold;\">' + nodedata.name + '</span>' + ' ' + size  
}  
      ")  
    )  
  )  
  
}
```

# Index

[add\\_shiny](#), [2](#)

[d2b-shiny](#), [4](#)

[JS](#), [5](#)

[renderSunburst \(sunburst-shiny\)](#), [10](#)

[renderSund2b \(d2b-shiny\)](#), [4](#)

[sizingPolicy](#), [6](#)

[sunburst](#), [4](#)

[sunburst-shiny](#), [10](#)

[sunburstOutput \(sunburst-shiny\)](#), [10](#)

[sund2b](#), [11](#)

[sund2bBreadcrumb](#), [11](#), [13](#)

[sund2bOutput \(d2b-shiny\)](#), [4](#)

[sund2bTooltip](#), [11](#), [14](#)