

# Package ‘tardis’

May 8, 2026

**Type** Package

**Title** Text Analysis with Rules and Dictionaries for Inferring  
Sentiment

**Version** 0.1.5

**Description** Measure text's sentiment with dictionaries and simple rules covering negations and modifiers. User-supplied dictionaries are supported, including Unicode emojis and multi-word tokens, so this package can also be used to study constructs beyond sentiment.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.2.3

**Imports** dplyr, magrittr, purrr, rlang, stringi, stringr, tidyr

**Depends** R (>= 2.10)

**URL** <https://github.com/chris31415926535/tardis>

**BugReports** <https://github.com/chris31415926535/tardis/issues>

**Suggests** covr, knitr, rmarkdown, testthat (>= 3.0.0)

**Config/testthat/edition** 3

**LinkingTo** cpp11

**VignetteBuilder** knitr

**NeedsCompilation** yes

**Author** Christopher Belanger [aut, cre, cph] (ORCID:  
<<https://orcid.org/0000-0003-2070-5721>>)

**Maintainer** Christopher Belanger <[christopher.a.belanger@gmail.com](mailto:christopher.a.belanger@gmail.com)>

**Repository** CRAN

**Date/Publication** 2025-11-28 16:50:02 UTC

## Contents

dict_modifiers . . . . .	2
dict_negations . . . . .	2
dict_tardis_sentiment . . . . .	3
tardis . . . . .	3
tardis_multidict . . . . .	5

<b>Index</b>	<b>7</b>
--------------	----------

---

dict_modifiers	<i>Modifier dictionary.</i>
----------------	-----------------------------

---

### Description

A `tbl_df` with two columns: token and score, identifying the tokens that increase or decrease other words' sentiments, and the percentage by which they do so.

### Usage

```
dict_modifiers
```

### Format

An object of class `spec_tbl_df` (inherits from `tbl_df`, `tbl`, `data.frame`) with 87 rows and 2 columns.

### Details

Derived originally from the VADER dictionary, but modified.

### Source

<https://CRAN.R-project.org/package=vader>

---

dict_negations	<i>Negation dictionary.</i>
----------------	-----------------------------

---

### Description

A `tbl_df` with one column: token.

### Usage

```
dict_negations
```

**Format**

An object of class `spec_tbl_df` (inherits from `tbl_df`, `tbl`, `data.frame`) with 38 rows and 1 columns.

**Details**

Can include apostrophes or not, but they're removed in processing so there's no need to include *both* words with and without apostrophes.

Derived originally from the VADER dictionary, but modified.

**Source**

<https://CRAN.R-project.org/package=vader>

---

dict\_tardis\_sentiment *Sentiment dictionary for TARDIS package.*

---

**Description**

Combines VADER and emoji dictionaries.

**Usage**

```
dict_tardis_sentiment
```

**Format**

An object of class `spec_tbl_df` (inherits from `tbl_df`, `tbl`, `data.frame`) with 7653 rows and 2 columns.

---

tardis *Text Analysis with Rules and Dictionaries for Inferring Sentiment (TARDIS)*

---

**Description**

This function uses dictionaries (either the included defaults or user-supplied) custom dictionaries) and simple rules to measure the sentiment of supplied text. "Sentiment" means roughly the emotion expressed in the text, where emotions are collapsed into positive (e.g. happy) or negative (e.g. sad, angry).

**Usage**

```
tardis(
  input_text = c("I am happy.", "I am VERY happy!!", "(:)", "Not sad.", "Bad.",
    "Not bad.", "A happy sentence! And a sad one. In the same text."),
  text_column = NA,
  dict_sentiments = NA,
  dict_modifiers = NA,
  dict_negations = NA,
  sigmoid_factor = 15,
  negation_factor = 0.75,
  allcaps_factor = 1.25,
  punctuation_factor = 1.15,
  use_punctuation = TRUE,
  summary_function = c("mean", "median", "max", "min", "sum"),
  simple_count = FALSE,
  verbose = FALSE
)
```

**Arguments**

<code>input_text</code>	Text to analyze, either a character vector or a data.frame with a column of text.
<code>text_column</code>	If using data.frame input, the name of the column of text to analyze.
<code>dict_sentiments</code>	Optional sentiment dictionary, defaults to internal tardis dictionary. A data.frame with two columns: word and value.
<code>dict_modifiers</code>	Optional modifiers dictionary, or "none" to disable modifiers. Defaults to internal tardis dictionary. A data.frame with two columns: word and value.
<code>dict_negations</code>	Optional negation dictionary, or "none" to disable negations. Defaults to internal tardis dictionary. A data.frame with one column: word.
<code>sigmoid_factor</code>	Numeric, default 15. Factor for scaling sentence scores to -1/+1 using a sigmoid function. Set to NA to disable the sigmoid function and just return sums of scores, adjusted by any applicable negators, modifiers, or punctuation/caps effects.
<code>negation_factor</code>	Numeric, default 0.75. Multiplier for damping effects of sentiment-bearing terms after negations. Stacks multiplicatively. Should probably be less than 1.
<code>allcaps_factor</code>	Numeric, default 1.25. Multiplier for scaling effects of of sentiment-bearing terms in ALL CAPS. Should probably be more than 1, to increase effects.
<code>punctuation_factor</code>	Numeric, default 1.15. Multiplier for scaling effects of punctuation. A single question mark has no effect, but one or more exclamation marks does, and question marks have effects in the presence of exclamation marks, up to three punctuation marks total.
<code>use_punctuation</code>	Boolean, default TRUE. Should we consider sentence-level punctuation?

summary_function	For multi-sentence texts, how should we summarise sentence scores into a text score? Default "mean", also accepts "median", "max", "min", and "sum".
simple_count	Boolean, default FALSE. Convenience parameter that overrides many other parameters to enable simple counts of dictionary words: no modifiers, negations, capitalization, or punctuation effects are considered and no sigmoid function is applied.
verbose	For debugging—should it print lots of messages to the console?

## Details

Roughly, each word's sentiment is a property of its dictionary-given sentiment, whether it's written in all-caps or not, and the three preceding words. A preceding negation (e.g. "not") will reverse and reduce the sentiment—turning a positive into a slightly less extreme negative, or vice-versa—and a preceding modifier can either increase/decrease the sentiment (e.g. "very" will increase it, "somewhat" will decrease it).

Sentences are scored based on their words and the presence of exclamation or question marks.

If a supplied text string has more than one sentence, this function will also return the mean, standard deviation, and range of sentiments expressed in its sentences. The rationale is that it doesn't make sense to apply sentence-level analysis to paragraphs, especially for online communications where people can use quick swings in sentiment to express irony.

Input can be supplied in a data.frame or character vector.

## Value

A `tbl_df` with one row for each input text and three new columns: `sentiment_mean`: the average sentiment for each sentence in each text. `sentiment_sd`: the standard deviation of sentence sentiments for each text. `sentiment_range`: the range of sentence sentiments for each text.

---

tardis_multidict	<i>Analyze text with more than one dictionary</i>
------------------	---

---

## Description

This convenience function takes a text and a set of dictionaries, and calls `tardis::tardis()` once for each dictionary. Other parameters are also passed along to `tardis()`.

## Usage

```
tardis_multidict(input_text, text_column = NA, dictionaries, ...)
```

**Arguments**

input_text	A text to be analyzed, either a tbl_df or a character vector.
text_column	If tbl_df input, a character with the name of the input column containing the text to be analyzed.
dictionaries	A single tbl_df with columns dictionary, token, and (optionally, for weighted dictionaries) score.
...	Other parameters passed on to tardis::tardis().

**Details**

Dictionaries must be in a single tbl\_df with at least two columns: token, containing the tokens belonging to each dictionary; and dictionary, which contains a unique identifier mapping each token to a dictionary. Weights, if present, must be in a column named score.

Tokens can be mapped to multiple dictionaries, but each row maps one token to one dictionary.

**Value**

A tbl\_df with new columns for each dictionary.

**Examples**

```
## Not run:
library(magrittr)
# Get NRC emotions dataset from textdata package
nrc_emotion <- textdata::lexicon_nrc() %>%
  dplyr::rename(token = word, dictionary = sentiment) %>%
  dplyr::mutate(score = 1)

# set up some input text
text <- dplyr::tibble(body = c("I am so angry!", "I am angry.",
  "I'm not angry.", "Your mother and I aren't angry, we're just disappointed.))

emotions <- tardis_multidict(input_text = text, text_column = "body",
  dictionaries = nrc_emotion) %>%
  dplyr::select(body, score_anger, score_sadness)

emotions

## End(Not run)
```

# Index

## \* datasets

dict\_modifiers, 2

dict\_negations, 2

dict\_tardis\_sentiment, 3

dict\_modifiers, 2

dict\_negations, 2

dict\_tardis\_sentiment, 3

tardis, 3

tardis\_multidict, 5