

Package ‘thisplot’

May 8, 2026

Type Package

Title Utility Functions for Plotting

Version 0.3.8

Date 2026-04-23

Maintainer Meng Xu <mengxu98@qq.com>

Description Provides utility functions for plotting. Includes functions for color manipulation, plot customization, panel size control, data optimization for plots, and layout adjustments.

License MIT + file LICENSE

URL <https://mengxu98.github.io/thisplot/>,
<https://github.com/mengxu98/thisplot>

BugReports <https://github.com/mengxu98/thisplot/issues>

Depends R (>= 4.1.0)

Imports cli, dendextend, geomtextpath, ggrepel, ggnewscale, ggplot2,
grDevices, grid, gtable, igraph, methods, patchwork, proxyC,
reshape2, stats, thisutils (>= 0.4.3), utils

Suggests circlize, ComplexHeatmap, dplyr, forcats, ggupset,
ggVennDiagram, htmltools, Matrix, png, purrr, ragg, scales,
stringr, testthat (>= 3.0.0), tidy

Config/Needs/website mengxu98/thistemplate

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.3

Language en-US

LazyData true

NeedsCompilation no

Author Meng Xu [aut, cre] (ORCID: <<https://orcid.org/0000-0002-8300-1054>>)

Repository CRAN

Date/Publication 2026-04-24 12:00:02 UTC

Contents

thisplot-package	3
add_grob	4
adjcolors	4
adjustlayout	5
annotate_quadrants	6
annotation_block_fill_graphics	7
annotation_block_graphics	8
annotation_graphics	8
as_grob	9
as_gtable	9
Blend2Color	10
blendcolors	10
BlendRGBList	11
build_heatmap_annotation	12
build_patchwork	13
ChineseColors	14
chinese_colors	15
clip_symmetric_range	16
cluster_within_group2	16
col2hex	17
compute_velocity_on_grid	17
drop_data	20
extractgrobs	21
geom_alluvial	21
geom_alluvial_label	22
geom_sankey	24
geom_sankey_bump	25
geom_sankey_label	26
get_chinese_palettes	27
get_colors	28
get_legend	29
get_vars	29
GraphPlot	30
grid_draw	34
head.colors	35
heatmap_fixsize	35
heatmap_rendersize	36
jitter_highlighted_points	38
make_long	39
mestimate	39
normalize_drawable	40
palette_colors	40
palette_list	42
panel_fix	42
patchwork_grob	45
print.ChineseColors	45

print.colors	46
print.thisplot_logo	46
RGBA2RGB	47
segements_df	47
show_palettes	48
simple_colors	50
slim_data	51
standardise	52
StatPlot	52
theme_blank	56
theme_sankey	57
theme_this	58
thisplot_logo	59
to_percent	59
visual_colors	60

Index	62
--------------	-----------

thisplot-package	<i>Utility Functions for Data Visualization and Plotting</i>
------------------	--

Description

Provides utility functions for data visualization and plotting in R. Includes functions for color manipulation, plot customization, panel size control, data optimization for plots, and layout adjustments. Designed to enhance workflows with ggplot2, patchwork, and ComplexHeatmap.

Author(s)

Meng Xu (Maintainer), <mengxu98@qq.com>

Source

<https://mengxu98.github.io/thisplot/>

See Also

Useful links:

- <https://mengxu98.github.io/thisplot/>
- Report bugs at <https://github.com/mengxu98/thisplot/issues>

`add_grob` *Add a grob to a gtable*

Description

Add a grob to a gtable at a specified position (top, bottom, left, or right).

Usage

```
add_grob(
  gtable,
  grob,
  position = c("top", "bottom", "left", "right", "none"),
  space = NULL,
  clip = "on"
)
```

Arguments

<code>gtable</code>	A gtable object.
<code>grob</code>	A grob or gtable object to add.
<code>position</code>	The position to add the grob. One of "top", "bottom", "left", "right", or "none".
<code>space</code>	The space to allocate for the grob. If NULL, will be calculated automatically.
<code>clip</code>	The clipping mode. Default is "on".

Value

A gtable object with the grob added.

`adjcolors` *Convert a color with specified alpha level*

Description

Convert a color with specified alpha level

Usage

```
adjcolors(colors, alpha)
```

Arguments

<code>colors</code>	Color vectors.
<code>alpha</code>	Alpha level in $[0, 1]$.

Value

A character vector of hexadecimal color codes with the specified alpha level.

Examples

```
colors <- c("red", "blue", "green")
adjcolors(colors, 0.5)
ggplot2::alpha(colors, 0.5)

show_palettes(
  list(
    "raw" = colors,
    "adjcolors" = adjcolors(colors, 0.5),
    "ggplot2::alpha" = ggplot2::alpha(colors, 0.5)
  )
)
```

adjustlayout

Adjust graph layout to avoid node overlaps

Description

Adjust the layout of a graph to prevent node overlaps by considering node widths and heights.

Usage

```
adjustlayout(graph, layout, width, height = 2, scale = 100, iter = 100)
```

Arguments

graph	An igraph graph object.
layout	A matrix with two columns representing the initial layout coordinates.
width	A numeric vector of node widths.
height	The height constraint for nodes. Default is 2.
scale	The scaling factor for the layout. Default is 100.
iter	The number of iterations for the adjustment algorithm. Default is 100.

Value

A matrix with adjusted layout coordinates.

annotate_quadrants *Annotate plot quadrants with percentages*

Description

Annotate plot quadrants with percentages

Usage

```
annotate_quadrants(  
  plot,  
  x,  
  y,  
  cutoffs,  
  line_color = "grey30",  
  line_type = "solid",  
  line_width = 0.5,  
  label_size = 3,  
  group = NULL  
)
```

Arguments

plot	A 'ggplot' object.
x	Name of the x variable in 'plot\$data'.
y	Name of the y variable in 'plot\$data'.
cutoffs	Cut points for x and y axes. Can be a numeric vector of length 1 or 2, or a list with the x and y cut points.
line_color	Quadrant line color.
line_type	Quadrant line type.
line_width	Quadrant line width.
label_size	Label size.
group	Optional grouping column used to compute percentages within each group.

Value

A 'ggplot' object.

Examples

```
df <- data.frame(  
  x = c(0.1, 0.2, 0.8, 0.9),  
  y = c(0.1, 0.8, 0.2, 0.9)  
)  
p <- ggplot2::ggplot(df, ggplot2::aes(x = x, y = y)) +
```

```
ggplot2::geom_point()
p
annotate_quadrants(p, x = "x", y = "y", cutoffs = 0.5)
```

annotation_block_fill_graphics
Build block fill panel function

Description

Build block fill panel function

Usage

```
annotation_block_fill_graphics(
  levels,
  palette = NULL,
  palcolor = NULL,
  fill_values = NULL,
  border = TRUE
)
```

Arguments

levels	Character/factor levels used as keys for fill mapping.
palette	Palette name. All available palette names can be queried with show_palettes .
palcolor	Custom colors used to create a color palette.
fill_values	Optional named fill vector. Names should match levels.
border	Whether to draw block border.

Value

A function with signature (index, levels) suitable for panel_fun in [ComplexHeatmap::anno_block](#).

Examples

```
library(ggplot2)
lv <- c("A", "B", "C")
panel_fun <- annotation_block_fill_graphics(
  levels = lv,
  fill_values = c(A = "#1b9e77", B = "#d95f02", C = "#7570b3")
)
ComplexHeatmap::anno_block(panel_fun = panel_fun)
```

annotation_block_graphics

Build block panel function

Description

Build block panel function

Usage

```
annotation_block_graphics(subplot, name, border = TRUE)
```

Arguments

subplot	A single drawable subplot object.
name	A name assigned to the generated grob.
border	Whether to draw a rectangle border around the block.

Value

A function with signature (index, levels) suitable for panel_fun in [ComplexHeatmap::anno_block](#).

Examples

```
library(ggplot2)
p <- ggplot2::ggplot(mtcars, ggplot2::aes(wt, mpg)) +
  ggplot2::geom_point()
panel_fun <- annotation_block_graphics(
  subplot = p, name = "demo-block"
)
ComplexHeatmap::anno_block(panel_fun = panel_fun)
```

annotation_graphics *Build graphics callback list for anno_customize*

Description

Build graphics callback list for anno_customize

Usage

```
annotation_graphics(subplots, prefix)
```

Arguments

subplots	A named list of subplot objects.
prefix	Prefix used to generate stable grob names.

Value

A named list of callback functions accepted by `ComplexHeatmap::anno_customize`.

as_grob	<i>Convert a plot object to a grob</i>
---------	--

Description

Convert various plot objects (gList, patchwork, ggplot) to a grob object.

Usage

```
as_grob(plot, ...)
```

Arguments

plot	A plot object (gList, patchwork, or ggplot).
...	Additional arguments passed to other functions.

Value

A grob object.

as_gtable	<i>Convert a plot object to a gtable</i>
-----------	--

Description

Convert various plot objects (gtable, grob, patchwork, ggplot) to a gtable object.

Usage

```
as_gtable(plot, ...)
```

Arguments

plot	A plot object (gtable, grob, patchwork, or ggplot).
...	Additional arguments passed to other functions.

Value

A gtable object.

 Blend2Color

Blend two colors using a specified mode

Description

Blend two colors with alpha channels using one of several blending modes: blend, average, screen, or multiply.

Usage

```
Blend2Color(C1, C2, mode = "blend")
```

Arguments

C1	A list containing the first color RGB values and alpha channel.
C2	A list containing the second color RGB values and alpha channel.
mode	The blending mode to use. One of "blend", "average", "screen", or "multiply". Default is "blend".

Value

A list containing the blended RGB values and alpha channel.

 blendcolors

Blends a list of colors using the specified blend mode

Description

Blends a list of colors using the specified blend mode

Usage

```
blendcolors(colors, mode = c("blend", "average", "screen", "multiply"))
```

Arguments

colors	Color vectors.
mode	Blend mode. One of "blend", "average", "screen", or "multiply".

Value

A character vector of hexadecimal color codes representing the blended color.

Examples

```
blend <- c(
  "red",
  "green",
  blendcolors(c("red", "green"),
    mode = "blend"
  )
)
average <- c(
  "red",
  "green",
  blendcolors(c("red", "green"),
    mode = "average"
  )
)
screen <- c(
  "red",
  "green",
  blendcolors(c("red", "green"),
    mode = "screen"
  )
)
multiply <- c(
  "red",
  "green",
  blendcolors(c("red", "green"),
    mode = "multiply"
  )
)
show_palettes(
  list(
    "blend" = blend,
    "average" = average,
    "screen" = screen,
    "multiply" = multiply
  )
)
```

BlendRGBList*Blend a list of colors*

Description

Blend multiple colors with alpha channels into a single color using a specified blending mode.

Usage

```
BlendRGBList(Clist, mode = "blend", RGB_BackGround = c(1, 1, 1))
```

Arguments

clist	A list of colors, where each color is a list containing RGB values and alpha channel.
mode	The blending mode to use. One of "blend", "average", "screen", or "multiply". Default is "blend".
RGB_BackGround	The background RGB color to composite with. Default is c(1, 1, 1) (white).

Value

A numeric vector of RGB values.

build_heatmap_annotation

Build HeatmapAnnotation with safe parameter merge

Description

Build HeatmapAnnotation with safe parameter merge

Usage

```
build_heatmap_annotation(
  annotations,
  which,
  show_annotation_name = TRUE,
  annotation_name_side = NULL,
  border = NULL,
  params = NULL
)
```

Arguments

annotations	Named list of annotation components (for example, anno_simple, anno_block, anno_customize).
which	Annotation direction ("row" or "column").
show_annotation_name	Whether to show annotation names.
annotation_name_side	Side for annotation names.
border	Whether to draw a rectangle border around the block.
params	Additional user parameters; duplicated keys are ignored if already set explicitly.

Value

A `ComplexHeatmap::HeatmapAnnotation` object.

Examples

```

anno <- list(
  group = ComplexHeatmap::anno_simple(
    x = c("A", "B", "A"),
    col = c(A = "#1b9e77", B = "#d95f02"),
    which = "column"
  )
)
ha <- build_heatmap_annotation(
  annotations = anno,
  which = "column",
  show_annotation_name = TRUE,
  annotation_name_side = "left",
  params = list(gap = grid::unit(1, "mm"))
)
ha

```

build_patchwork	<i>Build a patchwork gtable</i>
-----------------	---------------------------------

Description

Build a gtable from a patchwork object by arranging multiple plots according to the layout specification.

Usage

```

build_patchwork(
  x,
  guides = "auto",
  table_rows = 18,
  table_cols = 15,
  panel_row = 10,
  panel_col = 8
)

```

Arguments

x	A patchwork object.
guides	How to handle guides. Default is "auto".
table_rows	The number of rows in the table grid. Default is 18.
table_cols	The number of columns in the table grid. Default is 15.
panel_row	The row index for panels. Default is 10.
panel_col	The column index for panels. Default is 8.

Value

A gtable object.

ChineseColors	<i>Chinese traditional colors system</i>
---------------	--

Description

A color system based on Chinese traditional colors with 1058 colors.

Usage

```
ChineseColors()
```

Value

A ChineseColors object. Detailed information can be found in [print.ChineseColors\(\)](#).

See Also

[chinese_colors](#) for the dataset of Chinese traditional colors. [get_chinese_palettes](#) for getting Chinese color palettes. [visual_colors](#) for visualizing any color vector. [get_colors](#) for searching colors in dataset and palettes.

Examples

```
cc <- ChineseColors()
cc

# Get a color by pinyin
get_colors("pinlan")

# By number
get_colors(44)

# By hex code
get_colors("#2B73AF")

# Multiple colors
get_colors("pinlan", "piao")
get_colors(91:100)

# Chinese names
cc$visual_colors(
  loc_range = c(1, 180),
  num_per_row = 30,
  title = "Chinese Traditional Colors",
  name_type = "chinese"
)

# pinyin as names
cc$visual_colors(
  loc_range = c(1, 120),
```

```
    title = "Chinese Traditional Colors",
    name_type = "pinyin"
  )

  # rgb as names
  cc$visual_colors(
    loc_range = c(1, 120),
    title = "Colors with RGB values",
    name_type = "rgb"
  )

  # hex as names
  cc$visual_colors(
    loc_range = c(1, 120),
    title = "Colors with hex codes",
    name_type = "hex"
  )
}
```

chinese_colors

Chinese traditional colors dataset

Description

A dataset containing optimized traditional Chinese colors. These colors are extracted from those books:

- Chinese Traditional Colors - Color Aesthetics in the Forbidden City (ISBN: 9787521716054)
- Chinese Beautiful Colors - The Most Chinese Culture Vol.3 (ISBN: 9781672897198)
- Chinese Colors (ISBN: 9787558016479)
- Chinese Journal of Chromatography (ISSN 1000-8713)
- Chinese Color Atlas

Thanks to the author of the [blog](#) for providing the data.

Examples

```
data(chinese_colors)
color_sets <- attr(chinese_colors, "color_sets")
show_palettes(
  list(
    color_sets$Chinese,
    color_sets$ChineseSet8,
    color_sets$ChineseSet16,
    color_sets$ChineseSet32
  )
)

# Use ChineseColors class
cc <- ChineseColors()
```

```
cc$visual_colors(  
  loc_range = c(1, 180),  
  num_per_row = 30,  
  title = "Chinese Traditional Colors",  
  name_type = "chinese"  
)
```

clip_symmetric_range *Clip values to a symmetric range*

Description

Clip values to a symmetric range

Usage

```
clip_symmetric_range(data, value_col = "avg_log2FC")
```

Arguments

data A data frame.
value_col Name of the numeric column to clip.

Value

A list containing the clipped data frame and clipping limits.

Examples

```
df <- data.frame(avg_log2FC = c(-10, -2, 0, 2, 10))  
clip_symmetric_range(df)
```

cluster_within_group2 *Cluster within group*

Description

Cluster within group

Usage

```
cluster_within_group2(mat, factor)
```

Arguments

mat A matrix of data
factor A factor

Value

A dendrogram with ordered leaves

Examples

```
mat <- matrix(rnorm(100), 10, 10)
factor <- factor(rep(1:2, each = 5))
dend <- cluster_within_group2(mat, factor)
dend
plot(dend)
```

col2hex

Convert color names to hexadecimal format

Description

Convert color names to hexadecimal RGB color codes.

Usage

```
col2hex(cname)
```

Arguments

cname A character vector of color names.

Value

A character vector of hexadecimal color codes.

compute_velocity_on_grid

Compute velocity on grid

Description

Compute velocity on grid

Usage

```

compute_velocity_on_grid(
    x_emb,
    v_emb,
    density = 1,
    smooth = 0.5,
    n_neighbors = ceiling(n_obs/50),
    min_mass = 1,
    scale = 1,
    adjust_for_stream = FALSE,
    cutoff_perc = 5
)

```

Arguments

x_emb	A matrix of dimension n_obs x n_dim specifying the embedding coordinates of the cells.
v_emb	A matrix of dimension n_obs x n_dim specifying the velocity vectors of the cells.
density	A numeric value specifying the density of the grid points along each dimension. Default is 1.
smooth	A numeric value specifying the smoothing factor for the velocity vectors. Default is 0.5.
n_neighbors	A numeric value specifying the number of nearest neighbors for each grid point. Default is ceiling(n_obs / 50).
min_mass	A numeric value specifying the minimum mass required for a grid point to be considered. Default is 1.
scale	A numeric value specifying the scaling factor for the velocity vectors. Default is 1.
adjust_for_stream	Whether to adjust the velocity vectors for streamlines. Default is FALSE.
cutoff_perc	A numeric value specifying the percentile cutoff for removing low-density grid points. Default is 5.

Value

A list with two components: x_grid, the grid coordinates, and v_grid, the smoothed velocity vectors on the grid.

References

https://github.com/theislab/scvelo/blob/master/scvelo/plotting/velocity_embedding_grid.py

Examples

```

x_emb <- matrix(
  c(
    0, 0,
    1, 0,
    0, 1,
    1, 1
  ),
  ncol = 2,
  byrow = TRUE
)
v_emb <- matrix(
  c(
    1, 0,
    1, 0,
    0, 1,
    0, 1
  ),
  ncol = 2,
  byrow = TRUE
)

velocity_grid <- compute_velocity_on_grid(
  x_emb = x_emb,
  v_emb = v_emb,
  density = 0.1,
  n_neighbors = 2,
  adjust_for_stream = TRUE
)

names(velocity_grid)
dim(velocity_grid$x_grid)
dim(velocity_grid$v_grid)
head(velocity_grid$x_grid)
head(velocity_grid$v_grid)

grid_df <- expand.grid(
  x = velocity_grid$x_grid[1, ],
  y = velocity_grid$x_grid[2, ]
)

plot_df <- data.frame(
  x = grid_df$x,
  y = grid_df$y,
  xend = grid_df$x + c(velocity_grid$v_grid[1, , ]) * 0.2,
  yend = grid_df$y + c(velocity_grid$v_grid[2, , ]) * 0.2
)

ggplot2::ggplot(plot_df) +
  ggplot2::geom_segment(
    ggplot2::aes(x = x, y = y, xend = xend, yend = yend),
    arrow = grid::arrow(length = grid::unit(0.12, "inches")),

```

```
    na.rm = TRUE
  ) +
  ggplot2::coord_equal()
```

drop_data

Drop unused data in the plot

Description

Drop unused data points from a ggplot or patchwork object while preserving the plot structure. This function keeps only a single row of data for each unique combination of used variables, which can significantly reduce the object size when the original data contains many rows that are not displayed in the plot (e.g., due to scale limits or filtering).

Usage

```
drop_data(p)

## S3 method for class 'ggplot'
drop_data(p)

## S3 method for class 'patchwork'
drop_data(p)

## Default S3 method:
drop_data(p)
```

Arguments

p A ggplot object or a patchwork object.

Value

A ggplot or patchwork object with unused data points removed.

Examples

```
library(ggplot2)
library(patchwork)
p <- ggplot(
  data = mtcars,
  aes(x = mpg, y = wt, colour = cyl)
) +
  geom_point() +
  scale_x_continuous(limits = c(10, 30)) +
  scale_y_continuous(limits = c(1, 6))
object.size(p)

p_drop <- drop_data(p)
```

```
object.size(p_drop)
```

```
p / p_drop
```

extractgrobs	<i>Extract grobs from a list</i>
--------------	----------------------------------

Description

Extract grobs from a named list of grobs based on the specified x and y indices.

Usage

```
extractgrobs(vlnplots, x_nm, y_nm, x, y)
```

Arguments

vlnplots	A named list of grobs.
x_nm	A character vector of names for the x dimension.
y_nm	A character vector of names for the y dimension.
x	An integer index for the x dimension.
y	An integer index for the y dimension.

Value

The extracted grob(s).

geom_alluvial	<i>geom_alluvial</i>
---------------	----------------------

Description

Creates an alluvial plot which visualize flows between nodes. Each observation needs to have a 'x' aesthetic as well as a 'next_x' column which declares where that observation should flow. Also each observation should have a 'node' and a 'next_node' aesthetic which provide information about which group in the y-direction.

Usage

```
geom_alluvial(  
  mapping = NULL,  
  data = NULL,  
  position = "identity",  
  na.rm = FALSE,  
  show.legend = NA,  
  space = 0,  
  width = 0.1,  
  smooth = 8,  
  inherit.aes = TRUE,  
  ...  
)
```

Arguments

mapping	Provide you own mapping. Both x and y need to be numeric.
data	Provide you own data.
position	Change position.
na.rm	Remove missing values.
show.legend	Show legend in plot.
space	Space between nodes in the y-direction.
width	Width of nodes.
smooth	How much smooth should the curve have? More means steeper curve.
inherit.aes	Should the geom inherit aesthetics.
...	Other arguments to be passed to the geom.

Value

A ggplot layer.

geom_alluvial_label *geom_alluvial_label*

Description

Creates centered labels or text in nodes of your alluvial plot. Needs to have the exact same aesthetics as the call to 'geom_alluvial' to work.

Usage

```
geom_alluvial_text(  
  mapping = NULL,  
  data = NULL,  
  position = "identity",  
  na.rm = FALSE,  
  show.legend = NA,  
  space = 0,  
  width = 0.1,  
  inherit.aes = TRUE,  
  ...  
)  
  
geom_alluvial_label(  
  mapping = NULL,  
  data = NULL,  
  position = "identity",  
  na.rm = FALSE,  
  show.legend = NA,  
  space = 0,  
  width = 0.1,  
  inherit.aes = TRUE,  
  ...  
)
```

Arguments

mapping	Provide you own mapping. Both x and y need to be numeric.
data	Provide you own data.
position	Change position.
na.rm	Remove missing values.
show.legend	Show legend in plot.
space	Space between nodes in the y-direction.
width	Width of nodes.
inherit.aes	Should the geom inherit aesthetics.
...	Other arguments to be passed to the geom.

Details

Other important arguments are; 'space' which provides the space between nodes in the y-direction; 'shift' which shifts nodes in the y-direction.

Value

A ggplot layer.

geom_sankey

*geom_sankey***Description**

Creates a sankey plot which visualize flows between nodes. Each observation needs to have a 'x' aesthetic as well as a 'next_x' column which declares where that observation should flow. Also each observation should have a 'node' and a 'next_node' aesthetic which provide information about which group in the y-direction. By default each row of the data frame is counted to calculate the size of flows. A manual flow value can be added with the 'value' aesthetic.

Usage

```
geom_sankey(
  mapping = NULL,
  data = NULL,
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  space = NULL,
  type = "sankey",
  width = 0.1,
  smooth = 8,
  inherit.aes = TRUE,
  ...
)
```

Arguments

mapping	Provide you own mapping. Both x and y need to be numeric.
data	Provide you own data.
position	Change position.
na.rm	Remove missing values.
show.legend	Show legend in plot.
space	Space between nodes in the y-direction.
type	Either 'sankey' or 'alluvial'.
width	Width of nodes.
smooth	How much smooth should the curve have? More means steeper curve.
inherit.aes	Should the geom inherit aesthetics.
...	Other arguments to be passed to the geom.

Value

A ggplot layer.

Aesthetics

geom_sankey understand the following aesthetics (required aesthetics are in bold):

- **x0** - **y0** - **a** - **b** - **angle** - m1 - m2 - color - fill - size - linetype - alpha - lineend

Examples

```
dat <- data.frame(
  Group = c("A", "A", "B", "B", "C"),
  Type = c("X", "Y", "X", "Y", "X")
)
long <- make_long(dat, Group, Type)
ggplot2::ggplot(
  long,
  ggplot2::aes(
    x = x,
    next_x = next_x,
    node = node,
    next_node = next_node,
    fill = node
  )
) +
  geom_sankey() +
  theme_sankey()
```

 geom_sankey_bump

 geom_sankey_bump

Description

Creates a sankey bump plot which visualize flows between nodes. Each observation needs to have a 'x' aesthetic as well as a 'next_x' column which declares where that observation should flow. Also, each observation should have a 'node' and a 'next_node' aesthetic which provide information about which group in the y-direction.

Usage

```
geom_sankey_bump(
  mapping = NULL,
  data = NULL,
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  smooth = 8,
  type = "sankey",
  inherit.aes = TRUE,
  ...
)
```

Arguments

mapping	Provide you own mapping. Both x and y need to be numeric.
data	Provide you own data.
position	Change position.
na.rm	Remove missing values.
show.legend	Show legend in plot.
smooth	How much smooth should the curve have? More means steeper curve.
type	Either 'sankey' or 'alluvial'.
inherit.aes	Should the geom inherit aesthetics.
...	Other arguments to be passed to the geom.

Details

Other important arguments are; 'space' which provides the space between nodes in the y-direction; 'shift' which shifts nodes in the y-direction.

Value

A ggplot layer.

geom_sankey_label	<i>geom_sankey_label</i>
-------------------	--------------------------

Description

Creates centered labels or text in nodes of your sankey plot. Needs to have the exact same aesthetics as the call to 'geom_sankey' to work.

Usage

```
geom_sankey_label(
  mapping = NULL,
  data = NULL,
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  space = NULL,
  type = "sankey",
  width = 0.1,
  inherit.aes = TRUE,
  ...
)

geom_sankey_text(
```

```

    mapping = NULL,
    data = NULL,
    position = "identity",
    na.rm = FALSE,
    show.legend = NA,
    space = NULL,
    type = "sankey",
    width = 0.1,
    inherit.aes = TRUE,
    ...
  )

```

Arguments

mapping	Provide you own mapping. Both x and y need to be numeric.
data	Provide you own data.
position	Change position.
na.rm	Remove missing values.
show.legend	Show legend in plot.
space	Space between nodes in the y-direction.
type	Either 'sankey' or 'alluvial'.
width	Width of nodes.
inherit.aes	Should the geom inherit aesthetics.
...	Other arguments to be passed to the geom.

Value

A ggplot layer.

get_chinese_palettes *Get Chinese color palettes*

Description

Get Chinese color palettes

Usage

```
get_chinese_palettes(prefix = "Chinese")
```

Arguments

prefix	The prefix of the palette names. Default is "Chinese_".
--------	---

Value

A list of Chinese color palettes.

Examples

```
show_palettes(get_chinese_palettes())
```

get_colors

Get colors from Chinese colors dataset or palettes

Description

Search for colors in the Chinese colors dataset and all available palettes. This function can search by palette names, color names (pinyin or Chinese), numbers, or hex codes. It automatically searches in all palettes and reports which palette(s) contain the found colors.

Usage

```
get_colors(..., palettes = NULL)
```

Arguments

... One or more search values. Can be palette names, color names (pinyin or Chinese), numbers, or hex codes. If NULL, using all Chinese colors.

palettes Optional. A named list of palettes to search in. If NULL (default), searches in all available palettes.

Value

A data frame with class `colors` containing matching color information. The result is automatically printed using `print.colors()`.

See Also

[chinese_colors](#) for the dataset of Chinese traditional colors. [get_chinese_palettes](#) for getting Chinese color palettes. [ChineseColors](#) for the ChineseColors object.

Examples

```
get_colors("Paired")

get_colors("#FF7F00")

get_colors("pinlan")
get_colors(44)
get_colors("#2B73AF")

get_colors("cyan", palettes = "ChineseSet64")
```

get_legend	<i>Extract legend from a plot</i>
------------	-----------------------------------

Description

Extract the legend grob from a plot object.

Usage

```
get_legend(plot)
```

Arguments

plot A plot object.

Value

The legend grob.

get_vars	<i>Get used vars in a ggplot object</i>
----------	---

Description

Get used vars in a ggplot object

Usage

```
get_vars(p, reverse = FALSE, verbose = TRUE)
```

Arguments

p A ggplot object.
reverse Whether to return unused vars. Default is FALSE.
verbose Whether to print the message. Default is TRUE.

Value

A character vector of variable names. If reverse is FALSE, returns used variables; if TRUE, returns unused variables.

Examples

```
library(ggplot2)
p <- ggplot(
  data = mtcars,
  aes(x = mpg, y = wt, colour = cyl)
) +
  geom_point()
get_vars(p)
get_vars(p, reverse = TRUE)
```

GraphPlot

Graph Plot

Description

A function to plot a graph with nodes and edges.

Usage

```
GraphPlot(
  node,
  edge,
  transition = NULL,
  node_coord = c("x", "y"),
  node_group = NULL,
  node_palette = "Chinese",
  node_palcolor = NULL,
  node_size = 4,
  node_alpha = 1,
  node_highlight = NULL,
  node_highlight_color = "red",
  label = FALSE,
  label.size = 3.5,
  label.fg = "white",
  label.bg = "black",
  label.bg.r = 0.1,
  label_insitu = FALSE,
  label_repel = FALSE,
  label_repulsion = 20,
  label_point_size = 1,
  label_point_color = "black",
  label_segment_color = "black",
  edge_threshold = 0.01,
  use_triangular = c("upper", "lower", "both"),
  edge_line = c("straight", "curved"),
  edge_line_curvature = 0.3,
  edge_line_angle = 90,
```

```

edge_color = "grey30",
edge_size = c(0.2, 1),
edge_alpha = 0.5,
edge_shorten = 0,
edge_offset = 0,
edge_highlight = NULL,
edge_highlight_color = "red",
transition_threshold = 0.01,
transition_line = c("straight", "curved"),
transition_line_curvature = 0.3,
transition_line_angle = 90,
transition_color = "black",
transition_size = c(0.2, 1),
transition_alpha = 1,
transition_arrow_type = "closed",
transition_arrow_angle = 20,
transition_arrow_length = grid::unit(0.02, "npc"),
transition_shorten = 0.05,
transition_offset = 0,
transition_highlight = NULL,
transition_highlight_color = "red",
aspect.ratio = 1,
title = NULL,
subtitle = NULL,
xlab = NULL,
ylab = NULL,
legend.position = "right",
legend.direction = "vertical",
theme_use = "theme_this",
theme_args = list(),
return_layer = FALSE
)

```

Arguments

node	A data frame representing the nodes of the graph.
edge	A matrix representing the edges of the graph.
transition	A matrix representing the transitions between nodes.
node_coord	A character vector specifying the names of the columns in node that represent the x and y coordinates.
node_group	A character vector specifying the name of the column in node that represents the grouping of the nodes.
node_palette	A character vector specifying the name of the color palette for node groups.
node_palcolor	A character vector specifying the names of the colors for each node group.
node_size	A numeric value or column name of node specifying the size of the nodes.
node_alpha	A numeric value or column name of node specifying the transparency of the nodes.

`node_highlight` A character vector specifying the names of nodes to highlight.
`node_highlight_color`
 A character vector specifying the color for highlighting nodes.
`label` Whether to show labels for the nodes.
`label.size` The size of the labels.
`label.fg` A character vector specifying the foreground color of the labels.
`label.bg` A character vector specifying the background color of the labels.
`label.bg.r` The background color transparency of the labels.
`label_insitu` Whether to display the node group labels in situ or as numeric values.
`label_repel` Whether to use force-directed label repulsion.
`label_repulsion`
 The repulsion force for labels.
`label_point_size`
 The size of the label points.
`label_point_color`
 A character vector specifying the color of the label points.
`label_segment_color`
 A character vector specifying the color for the label segments.
`edge_threshold` The threshold for removing edges.
`use_triangular` A character vector specifying which part of the edge matrix to use (upper, lower, both).
`edge_line` A character vector specifying the type of line for edges (straight, curved).
`edge_line_curvature`
 The curvature of curved edges.
`edge_line_angle`
 The angle of curved edges.
`edge_color` A character vector specifying the color of the edges.
`edge_size` A numeric vector specifying the range of edge sizes.
`edge_alpha` The transparency of the edges.
`edge_shorten` The length of the edge shorten.
`edge_offset` The length of the edge offset.
`edge_highlight` A character vector specifying the names of edges to highlight.
`edge_highlight_color`
 A character vector specifying the color for highlighting edges.
`transition_threshold`
 The threshold for removing transitions.
`transition_line`
 A character vector specifying the type of line for transitions (straight, curved).
`transition_line_curvature`
 The curvature of curved transitions.
`transition_line_angle`
 The angle of curved transitions.

`transition_color` A character vector specifying the color of the transitions.
`transition_size` A numeric vector specifying the range of transition sizes.
`transition_alpha` The transparency of the transitions.
`transition_arrow_type` A character vector specifying the type of arrow for transitions (closed, open).
`transition_arrow_angle` The angle of the transition arrow.
`transition_arrow_length` The length of the transition arrow.
`transition_shorten` The length of the transition shorten.
`transition_offset` The length of the transition offset.
`transition_highlight` A character vector specifying the names of transitions to highlight.
`transition_highlight_color` A character vector specifying the color for highlighting transitions.
`aspect.ratio` Aspect ratio passed to `theme()`.
`title` Plot title.
`subtitle` Plot subtitle.
`xlab` Label for the x axis.
`ylab` Label for the y axis.
`legend.position` Legend position passed to `theme()`.
`legend.direction` Legend direction passed to `theme()`.
`theme_use` Theme function applied to the plot.
`theme_args` A named list of arguments passed to `theme_use`.
`return_layer` Whether to return the plot layers as a list. Defaults is FALSE.

Examples

```

node <- data.frame(
  x = c(0.2, 0.3, 0.5, 0.3),
  y = c(0.2, 0, 0.6, 0.7),
  group = c("A", "B", "C", "B"),
  row.names = c("n1", "n2", "n3", "n4")
)
edge <- matrix(
  c(
    0, 0.4, 0.2, 0.1,
    0.4, 0, 0.3, 0.2,

```

```

    0.2, 0.3, 0 , 0.5,
    0.2, 0.2, 0.5, 0.3
  ),
  nrow = 4,
  byrow = TRUE,
  dimnames = list(rownames(node), rownames(node))
)
GraphPlot(
  node = node,
  edge = edge
)

GraphPlot(
  node = node,
  edge = edge,
  node_group = "group",
  node_highlight = "n1",
  label = TRUE,
  label_repel = TRUE
)

```

grid_draw

Draw grobs at specified positions

Description

Draw a list of grobs at specified positions with given widths and heights.

Usage

```
grid_draw(groblist, x, y, width, height)
```

Arguments

groblist	A grob or a list of grobs to draw.
x	A numeric vector of x positions for each grob.
y	A numeric vector of y positions for each grob.
width	A numeric vector of widths for each grob.
height	A numeric vector of heights for each grob.

Value

No return value, called for side effects (drawing grobs).

head.colors	<i>Return the first part of a colors object</i>
-------------	---

Description

Returns the first part of a colors object, similar to `head()` for data frames.

Usage

```
## S3 method for class 'colors'  
head(x, n = 6L, ...)
```

Arguments

x	A colors object (data frame with color information).
n	Number of rows to return. Default is 6.
...	Additional arguments passed to <code>head()</code> .

Value

A colors object with the first n rows.

Examples

```
head(get_colors())  
  
head(get_colors(), n = 10)
```

heatmap_fixsize	<i>Compute fixed heatmap device size</i>
-----------------	--

Description

Compute fixed heatmap device size

Usage

```
heatmap_fixsize(  
  width,  
  width_sum,  
  height,  
  height_sum,  
  units,  
  ht_list,  
  legend_list  
)
```

Arguments

width	Optional user-provided target width. If NULL, width is estimated from the drawn heatmap layout.
width_sum	Numeric baseline width used when heatmap body size is in npc units.
height	Optional user-provided target height. If NULL, height is estimated from the drawn heatmap layout.
height_sum	Numeric baseline height used when heatmap body size is in npc units.
units	Output unit string passed to grid conversion helpers, such as "in", "cm", or "mm".
ht_list	A ComplexHeatmap::Heatmap or ComplexHeatmap::HeatmapList object.
legend_list	A list of ComplexHeatmap::Legend objects.

Value

A list with two converted units: ht_width and ht_height.

Examples

```
mat <- matrix(rnorm(100), nrow = 10)
ht <- ComplexHeatmap::Heatmap(mat, name = "expr")
lgd <- list(ComplexHeatmap::Legend(title = "expr", at = c(-2, 0, 2)))
out <- heatmap_fixsize(
  width = NULL,
  width_sum = 6,
  height = NULL,
  height_sum = 4,
  units = "in",
  ht_list = ht,
  legend_list = lgd
)
out
```

heatmap_rendersize *Estimate heatmap render size*

Description

Estimate heatmap render size

Usage

```
heatmap_rendersize(
  width,
  height,
  units,
  ht_top_list,
```

```

    ha_left,
    ha_right,
    ht_list,
    legend_list,
    flip
  )

```

Arguments

width	Numeric vector of heatmap body widths. Interpretation depends on flip.
height	Numeric vector of heatmap body heights. Interpretation depends on flip.
units	Unit string for numeric-to-grid conversion (for example, "in", "cm", "mm").
ha_top_list	A list of top annotations (typically <code>ComplexHeatmap::HeatmapAnnotation</code> objects).
ha_left	Optional left annotation.
ha_right	Optional right annotation.
ht_list	A <code>ComplexHeatmap::Heatmap</code> or <code>ComplexHeatmap::HeatmapList</code> object.
legend_list	A list containing legend objects; NULL entries are ignored.
flip	Logical; when TRUE, width/height interpretation follows the flipped layout branch.

Value

A list with numeric `width_sum` and `height_sum` in units.

Examples

```

mat <- matrix(rnorm(100), nrow = 10)
ht <- ComplexHeatmap::Heatmap(mat, name = "expr")
size <- heatmap_rendersize(
  width = c(4),
  height = c(3),
  units = "in",
  ha_top_list = list(),
  ha_left = NULL,
  ha_right = NULL,
  ht_list = ht,
  legend_list = list(),
  flip = FALSE
)
size

```

`jitter_highlighted_points`*Jitter highlighted points deterministically*

Description

Jitter highlighted points deterministically

Usage

```
jitter_highlighted_points(  
  data,  
  jitter_width = 0.2,  
  jitter_height = 0.2,  
  seed = 11  
)
```

Arguments

<code>data</code>	A data frame containing 'x', 'y', and 'border' columns.
<code>jitter_width</code>	Width of the x jitter.
<code>jitter_height</code>	Height of the y jitter.
<code>seed</code>	Numeric value used to offset the deterministic sequence.

Value

A data frame with 'x_plot' and 'y_plot' columns.

Examples

```
df <- data.frame(  
  x = c(0, 1),  
  y = c(0, 1),  
  border = c(FALSE, TRUE)  
)  
jitter_highlighted_points(df, jitter_width = 0.2, jitter_height = 0.2)
```

make_long	<i>Make a long data frame for sankey plot</i>
-----------	---

Description

Prepares a 'wide' data frame into a format that 'geom_sankey' or 'geom_alluvial' understands. Useful to show flows between dimensions in dataset.

Usage

```
make_long(.df, ..., value = NULL)
```

Arguments

.df	a data frame
...	unquoted columnnames of df that you want to include in the plot.
value	if each row have a weight this weight could be kept by providing column name of weight.

Value

a longer data frame

mestimate	<i>Estimate the fuzzifier parameter m</i>
-----------	---

Description

Estimate the fuzzifier parameter m for fuzzy clustering based on the data dimensions.

Usage

```
mestimate(data)
```

Arguments

data	A matrix or data frame.
------	-------------------------

Value

The estimated fuzzifier parameter m.

normalize_drawable *Normalize drawable objects to grobs*

Description

Normalize drawable objects to grobs

Usage

```
normalize_drawable(obj)
```

Arguments

obj A drawable object, such as a ggplot, patchwork, or grid grob.

Value

A grid grob object. If the input is not drawable, returns a null grob.

Examples

```
library(ggplot2)
p <- ggplot2::ggplot(mtcars, ggplot2::aes(wt, mpg)) +
  ggplot2::geom_point()
g <- normalize_drawable(p)
p + g
```

palette_colors *Color palettes collected*

Description

This function creates a color palette for a given vector of values.

Usage

```
palette_colors(
  x,
  n = 100,
  palette = "Chinese",
  palcolor = NULL,
  type = c("auto", "discrete", "continuous"),
  matched = FALSE,
  reverse = FALSE,
  NA_keep = FALSE,
  NA_color = "grey80"
)
```

Arguments

x	A vector of character/factor or numeric values. If missing, numeric values 1:n will be used as x.
n	The number of colors to return for numeric values.
palette	Palette name. All available palette names can be queried with show_palettes .
palcolor	Custom colors used to create a color palette.
type	Type of x. Can be one of "auto", "discrete" or "continuous". The default is "auto", which automatically detects if x is a numeric value.
matched	Whether to return a color vector of the same length as x. Default is FALSE.
reverse	Whether to invert the colors. Default is FALSE.
NA_keep	Whether to keep the color assignment to NA in x. Default is FALSE.
NA_color	Color assigned to NA if NA_keep is TRUE. Default is "grey80".

Value

A character vector of color codes (hexadecimal format) corresponding to the input values x. The length and structure depend on the matched parameter.

See Also

[show_palettes](#), [palette_list](#)

Examples

```
x <- c(1:3, NA, 3:5)
(pal1 <- palette_colors(
  x,
  palette = "Spectral"
))
(pal2 <- palette_colors(
  x,
  palcolor = c("red", "white", "blue")
))
(pal3 <- palette_colors(
  x,
  palette = "Spectral",
  n = 10
))
(pal4 <- palette_colors(
  x,
  palette = "Spectral",
  n = 10,
  reverse = TRUE
))
(pal5 <- palette_colors(
  x,
  palette = "Spectral",
  matched = TRUE
))
```

```

))
(pal6 <- palette_colors(
  x,
  palette = "Spectral",
  matched = TRUE,
  NA_keep = TRUE
))
show_palettes(
  list(pal1, pal2, pal3, pal4, pal5, pal6)
)

# Use Chinese color palettes
palette_colors(
  x = letters[1:5],
  palette = "ChineseRed",
  type = "discrete"
)
palette_colors(
  x = letters[1:5],
  palette = "Chinese",
  type = "discrete"
)

all_palettes <- show_palettes(return_palettes = TRUE)
names(all_palettes)

```

palette_list	<i>A list of palettes for use in data visualization</i>
--------------	---

Description

A list of palettes for use in data visualization

panel_fix	<i>Set the panel width/height of a plot to a fixed value</i>
-----------	--

Description

The ggplot object, when stored, can only specify the height and width of the entire plot, not the panel. The latter is obviously more important to control the final result of a plot. This function can set the panel width/height of plot to a fixed value and rasterize it.

Usage

```

panel_fix(
  x = NULL,
  panel_index = NULL,
  respect = NULL,
  width = NULL,
  height = NULL,
  margin = 1,
  padding = 0,
  units = "in",
  raster = FALSE,
  dpi = 300,
  return_grob = FALSE,
  bg_color = "white",
  save = NULL,
  verbose = FALSE,
  ...
)

panel_fix_overall(
  x,
  panel_index = NULL,
  respect = NULL,
  width = NULL,
  height = NULL,
  margin = 1,
  units = "in",
  raster = FALSE,
  dpi = 300,
  return_grob = FALSE,
  bg_color = "white",
  save = NULL,
  verbose = TRUE
)

```

Arguments

x	A ggplot object, a grob object, or a combined plot made by patchwork or cowplot package.
panel_index	Specify the panel to be fixed. If NULL, will fix all panels.
respect	Whether row heights and column widths should respect each other.
width	The desired width of the fixed panels.
height	The desired height of the fixed panels.
margin	The margin to add around each panel, in inches. Default is 1.
padding	The padding to add around each panel, in inches. Default is 0.
units	The units in which height, width and margin are given. Can be "mm", "cm", "in", etc. See grid::unit .

raster	Whether to rasterize the panel.
dpi	Plot resolution.
return_grob	Whether to return a grob object instead of a wrapped patchwork object. Default is FALSE.
bg_color	The background color of the plot.
save	NULL or the file name used to save the plot.
verbose	Whether to print the message. Default is TRUE.
...	Additional arguments passed to other functions.

Value

If `return_grob` is TRUE, returns a gtable object. Otherwise, returns a patchwork object with fixed panel sizes. The returned object has a size attribute containing width, height, and units.

Examples

```
library(ggplot2)
p <- ggplot(
  data = mtcars, aes(x = mpg, y = wt, colour = cyl)
) +
  geom_point() +
  facet_wrap(~gear, nrow = 2)
# fix the size of panel
panel_fix(
  p,
  width = 5,
  height = 3,
  units = "cm"
)
# rasterize the panel
panel_fix(
  p,
  width = 5,
  height = 3,
  units = "cm",
  raster = TRUE,
  dpi = 90
)

# `panel_fix` will build and render the plot when input a ggplot object.
# so after `panel_fix`, the size of the object will be changed.
object.size(p)
object.size(
  panel_fix(
    p,
    width = 5,
    height = 3,
    units = "cm"
  )
)
```

patchwork_grob	<i>Convert a patchwork object to a grob</i>
----------------	---

Description

Convert a patchwork object to a gtable grob by processing annotations and building the patchwork layout.

Usage

```
patchwork_grob(x, ...)
```

Arguments

x	A patchwork object.
...	Additional arguments passed to other functions.

Value

A gtable object.

print.ChineseColors	<i>Print ChineseColors object</i>
---------------------	-----------------------------------

Description

Print ChineseColors object

Usage

```
## S3 method for class 'ChineseColors'  
print(x, ...)
```

Arguments

x	A ChineseColors object.
...	Additional arguments.

Value

Details of the ChineseColors object.

<code>print.colors</code>	<i>Print colors object</i>
---------------------------	----------------------------

Description

Print colors object

Usage

```
## S3 method for class 'colors'  
print(x, ...)
```

Arguments

<code>x</code>	A colors object (data frame with color information).
<code>...</code>	Additional arguments passed to print.

Value

Details of the colors objec.

<code>print.thisplot_logo</code>	<i>Print logo</i>
----------------------------------	-------------------

Description

Print logo

Usage

```
## S3 method for class 'thisplot_logo'  
print(x, ...)
```

Arguments

<code>x</code>	Input information.
<code>...</code>	Other parameters.

Value

Print the ASCII logo

RGBA2RGB	<i>Convert RGBA color to RGB with background</i>
----------	--

Description

Convert an RGBA (Red, Green, Blue, Alpha) color to RGB by compositing it with a background color based on the alpha channel.

Usage

```
RGBA2RGB(rgba, Background = c(1, 1, 1))
```

Arguments

rgba	A list containing RGB values and alpha channel.
Background	The background RGB color to composite with. Default is c(1, 1, 1) (white).

Value

A numeric vector of RGB values.

segments_df	<i>Shorten and offset the segment</i>
-------------	---------------------------------------

Description

This function takes a data frame representing segments in a plot and shortens and offsets them based on the provided arguments.

Usage

```
segments_df(data, shorten_start, shorten_end, offset)
```

Arguments

data	A data frame containing the segments. It should have columns 'x', 'y', 'xend', and 'yend' representing the start and end points of each segment.
shorten_start	The amount to shorten the start of each segment by.
shorten_end	The amount to shorten the end of each segment by.
offset	The amount to offset each segment by.

Value

The modified data frame with the shortened and offset segments.

Examples

```
library(ggplot2)
temp_nodes <- data.frame(
  "x" = c(10, 40),
  "y" = c(10, 30)
)
data <- data.frame(
  "x" = c(10, 40),
  "y" = c(10, 30),
  "xend" = c(40, 10),
  "yend" = c(30, 10)
)

ggplot(temp_nodes, aes(x = x, y = y)) +
  geom_point(size = 12) +
  xlim(0, 50) +
  ylim(0, 50) +
  geom_segment(
    data = data,
    aes(x = x, xend = xend, y = y, yend = yend)
  )

ggplot(temp_nodes, aes(x = x, y = y)) +
  geom_point(size = 12) +
  xlim(0, 50) +
  ylim(0, 50) +
  geom_segment(
    data = segments_df(
      data,
      shorten_start = 2,
      shorten_end = 3,
      offset = 1
    ),
    aes(x = x, xend = xend, y = y, yend = yend)
  )
```

show_palettes

Show the color palettes

Description

This function displays color palettes using ggplot2.

Usage

```
show_palettes(
  palettes = NULL,
  type = c("discrete", "continuous"),
  index = NULL,
```

```

    palette_names = NULL,
    return_names = TRUE,
    return_palettes = FALSE
  )

```

Arguments

palettes	A list of color palettes. Default is NULL.
type	The type of palettes to include. Default is "discrete".
index	The indices of the palettes to include. Default is NULL.
palette_names	The names of the palettes to include. Default is NULL.
return_names	Whether to return the names of the selected palettes. Default is TRUE.
return_palettes	Whether to return the colors of selected palettes. Default is FALSE.

Value

If return_palettes is TRUE, returns a list of color palettes. If return_names is TRUE (default), returns a character vector of palette names. Otherwise, returns NULL (called for side effects to display the plot).

See Also

[palette_colors](#), [palette_list](#)

Examples

```

show_palettes(
  palettes = list(
    c("red", "blue", "green"),
    c("yellow", "purple", "orange")
  )
)
all_palettes <- show_palettes(return_palettes = TRUE)
names(all_palettes)
all_palettes[["simspec"]]
show_palettes(index = 1:10)
show_palettes(
  type = "discrete",
  index = 1:10
)
show_palettes(
  type = "continuous",
  index = 1:10
)
show_palettes(
  palette_names = c(
    "Paired", "nejm", "simspec", "Spectral", "jet", "Chinese"
  ),
  return_palettes = TRUE
)

```

```
)  
# Include Chinese palettes via prefix  
show_palettes(  
  palette_names = c("ChineseRed", "ChineseBlue"),  
  return_palettes = TRUE  
)
```

simple_colors

Simple random color selection

Description

Simple random color selection

Usage

```
simple_colors(n = 10, palette = NULL)
```

Arguments

n	The number of colors to return. Default is 10.
palette	The name of the palette to use. Default is NULL, colors will be selected from ChineseColors. Otherwise, colors will be selected from the specified palette. Available palette names can be queried with show_palettes .

Value

A character vector of hexadecimal color codes.

Examples

```
simple_colors()  
  
show_palettes(simple_colors(n = 5))  
  
# Get colors from a specific palette  
simple_colors(n = 10, palette = "Paired")  
simple_colors(n = 10, palette = "ChineseBlue")  
simple_colors(n = 10, palette = "Spectral")
```

`slim_data`*Slim unused data in the plot*

Description

Remove unused columns from the data in a ggplot or patchwork object. This function keeps only the columns that are actually used in the plot (e.g., in mappings, aesthetics, or facets), which can significantly reduce the object size when the original data contains many unused columns.

Usage

```
slim_data(p)

## S3 method for class 'ggplot'
slim_data(p)

## S3 method for class 'patchwork'
slim_data(p)
```

Arguments

`p` A ggplot object or a patchwork object.

Value

A ggplot or patchwork object with unused data columns removed.

Examples

```
library(ggplot2)
p <- ggplot(
  data = mtcars,
  aes(x = mpg, y = wt, colour = cyl)
) +
  geom_point()
object.size(p)
colnames(p$data)

p_slim <- slim_data(p)
object.size(p_slim)
colnames(p_slim$data)
```

standardise	<i>Standardize data by rows</i>
-------------	---------------------------------

Description

Standardize each row of a data matrix by subtracting the mean and dividing by the standard deviation.

Usage

```
standardise(data)
```

Arguments

data A matrix or data frame to standardize.

Value

The standardized data with the same structure as input.

StatPlot	<i>Statistic Plot</i>
----------	-----------------------

Description

Visualizes data using various plot types such as bar plots, rose plots, ring plots, pie charts, trend plots, area plots, dot plots, sankey plots, chord plots, venn diagrams, and upset plots.

Usage

```
StatPlot(
  meta.data,
  stat.by,
  group.by = NULL,
  split.by = NULL,
  bg.by = NULL,
  flip = FALSE,
  NA_color = "grey",
  NA_stat = TRUE,
  keep_empty = FALSE,
  individual = FALSE,
  stat_level = NULL,
  plot_type = c("bar", "rose", "ring", "pie", "trend", "area", "dot", "sankey", "chord",
    "venn", "upset"),
  stat_type = c("percent", "count"),
  position = c("stack", "dodge"),
```

```

palette = "Chinese",
palcolor = NULL,
alpha = 1,
bg_palette = "Chinese",
bg_palcolor = NULL,
bg_alpha = 0.2,
label = FALSE,
label.size = 3.5,
label.fg = "black",
label.bg = "white",
label.bg.r = 0.1,
aspect.ratio = NULL,
title = NULL,
subtitle = NULL,
xlab = NULL,
ylab = NULL,
legend.position = "right",
legend.direction = "vertical",
theme_use = "theme_this",
theme_args = list(),
grid_major = TRUE,
grid_major_colour = "grey80",
grid_major_linetype = 2,
grid_major_linewidth = 0.3,
combine = TRUE,
nrow = NULL,
ncol = NULL,
byrow = TRUE,
force = FALSE,
seed = 11
)

```

Arguments

<code>meta.data</code>	The data frame containing the data to be plotted.
<code>stat.by</code>	The column name(s) in <code>meta.data</code> specifying the variable(s) to be plotted.
<code>group.by</code>	The column name(s) in <code>meta.data</code> specifying the grouping variable(s). Default is <code>NULL</code> .
<code>split.by</code>	The column name in <code>meta.data</code> specifying the variable to split plots by. Default is <code>NULL</code> .
<code>bg.by</code>	The column name in <code>meta.data</code> specifying the background variable for bar plots.
<code>flip</code>	Whether to flip the plot. Default is <code>FALSE</code> .
<code>NA_color</code>	The color to use for missing values.
<code>NA_stat</code>	Whether to include missing values in the plot. Default is <code>TRUE</code> .
<code>keep_empty</code>	Whether to keep empty groups in the plot. Default is <code>FALSE</code> .

<code>individual</code>	Whether to plot individual groups separately. Default is FALSE.
<code>stat_level</code>	The level(s) of the variable(s) specified in <code>stat.by</code> to include in the plot. Default is NULL.
<code>plot_type</code>	The type of plot to create. Can be one of "bar", "rose", "ring", "pie", "trend", "area", "dot", "sankey", "chord", "venn", or "upset".
<code>stat_type</code>	The type of statistic to compute for the plot. Can be one of "percent" or "count".
<code>position</code>	The position adjustment for the plot. Can be one of "stack" or "dodge".
<code>palette</code>	The name of the color palette to use. Default is "Chinese".
<code>palcolor</code>	Custom colors to use instead of palette. Default is NULL.
<code>alpha</code>	The transparency level for the plot.
<code>bg_palette</code>	The name of the background color palette to use for bar plots.
<code>bg_palcolor</code>	The color to use in the background color palette.
<code>bg_alpha</code>	The transparency level for the background color in bar plots.
<code>label</code>	Whether to add labels on the plot. Default is FALSE.
<code>label.size</code>	The size of the labels.
<code>label.fg</code>	The foreground color of the labels.
<code>label.bg</code>	The background color of the labels.
<code>label.bg.r</code>	The radius of the rounded corners of the label background.
<code>aspect.ratio</code>	Aspect ratio of the panel. Default is NULL.
<code>title</code>	The title of the plot. Default is NULL.
<code>subtitle</code>	The subtitle of the plot. Default is NULL.
<code>xlab</code>	The label for the x-axis. Default is NULL.
<code>ylab</code>	The label for the y-axis. Default is NULL.
<code>legend.position</code>	The position of the legend. Can be one of "none", "left", "right", "bottom", "top", or a two-element numeric vector. Default is "right".
<code>legend.direction</code>	The direction of the legend. Can be one of "vertical" or "horizontal". Default is "vertical".
<code>theme_use</code>	The theme to use for the plot. Default is "theme_this".
<code>theme_args</code>	Additional arguments to pass to the theme function. Default is <code>list()</code> .
<code>grid_major</code>	Whether to show major panel grid lines. Default is TRUE.
<code>grid_major_colour</code>	Color of major panel grid lines.
<code>grid_major_linetype</code>	Linetype of major panel grid lines.
<code>grid_major_linewidth</code>	Line width of major panel grid lines.
<code>combine</code>	Whether to combine multiple plots into one. Default is TRUE.

nrow	Number of rows when combining plots. Default is NULL.
ncol	Number of columns when combining plots. Default is NULL.
byrow	Whether to fill plots by row when combining. Default is TRUE.
force	Whether to force plotting even when variables have more than 100 levels. Default is FALSE.
seed	Random seed for reproducibility. Default is 11.

Examples

```
set.seed(1)
meta_data <- data.frame(
  Type = factor(
    sample(c("A", "B", "C"),
          50,
          replace = TRUE,
          prob = c(0.5, 0.3, 0.2)
        )
  ),
  Group = factor(sample(c("X", "Y", "Z"), 50, replace = TRUE)),
  Batch = factor(sample(c("B1", "B2"), 50, replace = TRUE))
)
meta_data$Region <- factor(
  ifelse(meta_data$Group %in% c("X", "Y"), "R1", "R2"),
  levels = c("R1", "R2")
)

StatPlot(
  meta_data,
  stat.by = "Type",
  group.by = "Group",
  split.by = "Batch",
  plot_type = "bar",
  position = "dodge"
)

StatPlot(
  meta_data,
  stat.by = "Type",
  group.by = "Group",
  stat_type = "count",
  plot_type = "ring",
  position = "dodge"
)

StatPlot(
  meta_data,
  stat.by = "Type",
  group.by = "Group",
  stat_type = "count"
)
```

```
StatPlot(  
  meta_data,  
  stat.by = "Type",  
  plot_type = "pie"  
)  
  
StatPlot(  
  meta_data,  
  stat.by = "Type",  
  group.by = "Group",  
  stat_type = "count",  
  plot_type = "area"  
)  
  
StatPlot(  
  meta_data,  
  stat.by = "Type",  
  group.by = "Group",  
  plot_type = "dot"  
)  
  
StatPlot(  
  meta_data,  
  stat.by = "Type",  
  group.by = "Group",  
  stat_type = "count",  
  plot_type = "trend"  
)
```

theme_blank

Blank theme

Description

This function creates a theme with all elements blank except for axis lines and labels. It can optionally add coordinate axes in the plot.

Usage

```
theme_blank(  
  add_coord = TRUE,  
  xlen_npc = 0.15,  
  ylen_npc = 0.15,  
  xlab = "",  
  ylab = "",  
  lab_size = 12,  
  ...  
)
```

Arguments

add_coord	Whether to add coordinate arrows. Default is TRUE.
xlen_npc	The length of the x-axis arrow in "npc".
ylen_npc	The length of the y-axis arrow in "npc".
xlab	The label of the x-axis.
ylab	The label of the y-axis.
lab_size	The size of the axis labels.
...	Arguments passed to the <code>ggplot2::theme</code> .

Value

A list containing ggplot2 theme objects and annotation objects. If `add_coord` is TRUE, returns a list with coordinate arrows; otherwise returns a list with theme only.

Examples

```
library(ggplot2)
p <- ggplot(mtcars, aes(x = wt, y = mpg, colour = factor(cyl))) +
  geom_point()
p + theme_blank()
p + theme_blank(xlab = "x-axis", ylab = "y-axis", lab_size = 16)
```

 theme_sankey

Themes for sankey plot

Description

Minimal themes for sankey, alluvial and sankey bump plots

Usage

```
theme_sankey(
  base_size = 11,
  base_family = "",
  base_line_size = base_size/22,
  base_rect_size = base_size/22
)

theme_alluvial(
  base_size = 11,
  base_family = "",
  base_line_size = base_size/22,
  base_rect_size = base_size/22
)
```

```
theme_sankey_bump(
  base_size = 11,
  base_family = "",
  base_line_size = base_size/22,
  base_rect_size = base_size/22
)
```

Arguments

base_size Base font size, given in pts.
 base_family Base font family.
 base_line_size Base size for line elements.
 base_rect_size Base size for rect elements.

theme_this	<i>The default theme for scop plot function.</i>
------------	--

Description

The default theme for scop plot function.

Usage

```
theme_this(aspect.ratio = NULL, base_size = 12, ...)
```

Arguments

aspect.ratio Aspect ratio of the panel.
 base_size Base font size
 ... Arguments passed to the [ggplot2::theme](#).

Value

A ggplot2 theme object (class theme, gg).

Examples

```
library(ggplot2)
p <- ggplot(
  data = mtcars,
  aes(x = wt, y = mpg, colour = factor(cyl))
) +
  geom_point()
p + theme_this()
```

thisplot_logo	<i>The logo of thisplot</i>
---------------	-----------------------------

Description

The thisplot logo, using ASCII or Unicode characters Use [cli::ansi_strip](#) to get rid of the colors.

Usage

```
thisplot_logo(unicode = cli::is_utf8_output())
```

Arguments

unicode Unicode symbols on UTF-8 platforms. Default is [cli::is_utf8_output](#).

Value

A character vector with class `thisplot_logo`.

References

<https://github.com/tidyverse/tidyverse/blob/main/R/logo.R>

Examples

```
thisplot_logo()
```

to_percent	<i>Convert proportions to percentages</i>
------------	---

Description

Convert proportions to percentages

Usage

```
to_percent(x)
```

Arguments

x A numeric vector.

Value

A numeric vector expressed as percentages.

Examples

```
to_percent(c(1, 1, 2))
to_percent(c(0, 0))
```

visual_colors	<i>Visualize colors in HTML widget</i>
---------------	--

Description

Display a grid of color swatches with optional names or color codes.

Usage

```
visual_colors(
  colors,
  names = NULL,
  num_per_row = 30,
  title = NULL,
  label_mode = c("auto", "chinese", "pinyin", "rgb", "hex")
)
```

Arguments

colors	A character vector of hex color codes.
names	Optional. A character vector of names for each color. Default is NULL, which means hex color codes will be displayed. You can pass any labels (e.g., RGB values, custom names) via this parameter.
num_per_row	Number of colors per row. Default is 30.
title	Optional title for the visualization. Default is NULL.
label_mode	Label layout mode. Default is "auto", which detects the label type from names. Use "chinese", "pinyin", "rgb", or "hex" to force a layout optimized for that label style.

Value

An HTML widget.

Examples

```
# Visualize a simple color palette
visual_colors(
  colors = c("#FF0000", "#00FF00", "#0000FF"),
  names = c("Red", "Green", "Blue")
)

visual_colors(
  colors = c("#FF0000", "#00FF00"),
```

```
names = c("(255, 0, 0)", "(0, 255, 0)")
)

visual_colors(thisplot::palette_list$Paired)

# Use with ChineseColors
cc <- ChineseColors()
visual_colors(
  colors = cc$blue[1:60],
  title = "Chinese Blue Colors"
)
```

Index

- * **data**
 - chinese_colors, 15
 - palette_list, 42
- add_grob, 4
- adjcolors, 4
- adjustlayout, 5
- annotate_quadrants, 6
- annotation_block_fill_graphics, 7
- annotation_block_graphics, 8
- annotation_graphics, 8
- as_grob, 9
- as_gtable, 9

- Blend2Color, 10
- blendcolors, 10
- BlendRGBList, 11
- build_heatmap_annotation, 12
- build_patchwork, 13

- chinese_colors, 14, 15, 28
- ChineseColors, 14, 28
- cli::ansi_strip, 59
- cli::is_utf8_output, 59
- clip_symmetric_range, 16
- cluster_within_group2, 16
- col2hex, 17
- ComplexHeatmap::anno_block, 7, 8
- ComplexHeatmap::anno_customize, 9
- ComplexHeatmap::HeatmapAnnotation, 12
- compute_velocity_on_grid, 17

- drop_data, 20

- extractgrobs, 21

- geom_alluvial, 21
- geom_alluvial_label, 22
- geom_alluvial_text
 - (geom_alluvial_label), 22
- geom_sankey, 24

- geom_sankey_bump, 25
- geom_sankey_label, 26
- geom_sankey_text (geom_sankey_label), 26
- get_chinese_palettes, 14, 27, 28
- get_colors, 14, 28
- get_legend, 29
- get_vars, 29
- ggplot2::theme, 57, 58
- GraphPlot, 30
- grid::unit, 43
- grid_draw, 34

- head(), 35
- head.colors, 35
- heatmap_fixsize, 35
- heatmap_rendersize, 36

- jitter_highlighted_points, 38

- make_long, 39
- mestimate, 39

- normalize_drawable, 40

- palette_colors, 40, 49
- palette_list, 41, 42, 49
- panel_fix, 42
- panel_fix_overall (panel_fix), 42
- patchwork_grob, 45
- print.ChineseColors, 45
- print.ChineseColors(), 14
- print.colors, 46
- print.colors(), 28
- print.thisplot_logo, 46

- RGBA2RGB, 47

- segments_df, 47
- show_palettes, 7, 41, 48, 50
- simple_colors, 50
- slim_data, 51

standardise, [52](#)
StatPlot, [52](#)

theme_alluvial (theme_sankey), [57](#)
theme_blank, [56](#)
theme_sankey, [57](#)
theme_sankey_bump (theme_sankey), [57](#)
theme_this, [58](#)
thisplot (thisplot-package), [3](#)
thisplot-package, [3](#)
thisplot_logo, [59](#)
to_percent, [59](#)

visual_colors, [14](#), [60](#)