

Package ‘tidyBdE’

May 8, 2026

Title Download Data from Bank of Spain

Version 0.6.0

Description Tools to download data series from 'Banco de España' ('BdE') on 'tibble' format. 'Banco de España' is the national central bank and, within the framework of the Single Supervisory Mechanism ('SSM'), the supervisor of the Spanish banking system along with the European Central Bank. This package is in no way sponsored endorsed or administered by 'Banco de España'.

License GPL (>= 3)

URL <https://ropenspain.github.io/tidyBdE/>,
<https://github.com/rOpenSpain/tidyBdE>

BugReports <https://github.com/rOpenSpain/tidyBdE/issues>

Depends R (>= 4.1.0)

Imports dplyr (>= 0.7.0), ggplot2 (>= 3.5.0), readr (>= 1.0.0), scales (>= 1.1.0), tibble (>= 3.0.0), tidyr, utils

Suggests knitr, lifecycle, quarto, testthat (>= 3.0.0)

VignetteBuilder quarto

Config/Needs/coverage covr

Config/Needs/website cpp11, devtools, progress, reactable, remotes, styler, tidyverse, ropenspain/rotemplate

Config/testthat/edition 3

Config/testthat/parallel true

Copyright See file inst/COPYRIGHTS

Encoding UTF-8

LazyData true

RoxygenNote 7.3.3

X-schema.org-applicationCategory Macroeconomics

X-schema.org-isPartOf <https://ropenspain.es/>

X-schema.org-keywords api, bde, cran, ggplot2, macroeconomics, r, r-package, ropenspain, rstats, series-data, spain

NeedsCompilation no

Author Diego H. Herrero [aut, cre, cph] (ORCID: <https://orcid.org/0000-0001-8457-4658>)

Maintainer Diego H. Herrero <dev.dieghernan@gmail.com>

Repository CRAN

Date/Publication 2026-03-23 21:40:10 UTC

Contents

bde_catalog_load	2
bde_catalog_search	4
bde_catalog_update	5
bde_indicators	6
bde_ind_db	7
bde_parse_dates	8
bde_series_full_load	10
bde_series_load	11
bde_tidy_palettes	14
scales_bde	15
theme_tidybde	16
Index	19

bde_catalog_load	<i>Load BdE catalogs</i>
------------------	--------------------------

Description

Load the time series catalogs provided by the BdE.

Usage

```
bde_catalog_load(
  catalog = c("ALL", "BE", "SI", "TC", "TI", "PB"),
  parse_dates = TRUE,
  cache_dir = NULL,
  update_cache = FALSE,
  verbose = FALSE
)
```

Arguments

catalog	A single value indicating the catalog to be updated or "ALL" as a shorthand. See Details .
parse_dates	Logical. If TRUE, dates are parsed using bde_parse_dates() .
cache_dir	A path to a cache directory. The directory can also be set via options with <code>options(bde_cache_dir = "path/to/dir")</code> .
update_cache	Logical. If TRUE, the requested file is updated in cache_dir.
verbose	Logical TRUE or FALSE, display information useful for debugging.

Details

Accepted values for catalog are:

CODE	PUBLICATION	UPDATE FREQUENCY	FREQUENCY
"BE"	Statistical Bulletin	Daily	Monthly
"SI"	Summary Indicators	Daily	Daily
"TC"	Exchange Rates	Daily	Daily
"TI"	Interest Rates	Daily	Daily
"PB"	Bank Lending Survey	Quarterly	Quarterly

Use "ALL" as a shorthand for updating all the catalogs at a glance.

If the requested catalog is not cached, [bde_catalog_update\(\)](#) is invoked.

Value

A [tibble](#) object.

Source

[time series bulk data download](#).

See Also

Other catalog: [bde_catalog_search\(\)](#), [bde_catalog_update\(\)](#)

Examples

```
bde_catalog_load("TI", verbose = TRUE)
```

bde_catalog_search *Search BdE catalogs*

Description

Search for keywords on the time series catalogs.

Usage

```
bde_catalog_search(pattern, ...)
```

Arguments

`pattern` [regex](#) pattern to search. See **Details** and **Examples**.

`...` Arguments passed on to [bde_catalog_load](#)

`catalog` A single value indicating the catalog to be updated or "ALL" as a shorthand. See **Details**.

`parse_dates` Logical. If TRUE, dates are parsed using [bde_parse_dates\(\)](#).

`update_cache` Logical. If TRUE, the requested file is updated in `cache_dir`.

`cache_dir` A path to a cache directory. The directory can also be set via options with `options(bde_cache_dir = "path/to/dir")`.

`verbose` Logical TRUE or FALSE, display information useful for debugging.

Details

Note: BdE files are currently provided only in Spanish. Therefore, search terms should be provided in Spanish to obtain search results.

This function uses `base::grep()` function for finding matches on the catalogs. You can pass [regular expressions](#) to broaden the search.

Value

A [tibble](#) object with the results of the query.

See Also

[bde_catalog_load\(\)](#), `base::regex`

Other catalog: [bde_catalog_load\(\)](#), [bde_catalog_update\(\)](#)

Examples

```
# Simple search (needs to be in Spanish)
# !! PIB [es] == GDP [en]

bde_catalog_search("PIB")
```

```
# More complex - Single
bde_catalog_search("Francia(*)PIB")

# Even more complex - Double
bde_catalog_search("Francia(*)PIB|Italia(*)PIB|Alemania(*)PIB")
```

bde_catalog_update *Update BdE catalogs*

Description

Update the time series catalogs provided by BdE.

Usage

```
bde_catalog_update(
  catalog = c("ALL", "BE", "SI", "TC", "TI", "PB"),
  cache_dir = NULL,
  verbose = FALSE
)
```

Arguments

catalog A character string indicating the catalog to be updated or "ALL" as a shorthand. See **Details**.

cache_dir A path to a cache directory. The directory can also be set via options with `options(bde_cache_dir = "path/to/dir")`.

verbose Logical TRUE or FALSE, display information useful for debugging.

Details

Accepted values for catalog are:

CODE	PUBLICATION	UPDATE FREQUENCY	FREQUENCY
"BE"	Statistical Bulletin	Daily	Monthly
"SI"	Summary Indicators	Daily	Daily
"TC"	Exchange Rates	Daily	Daily
"TI"	Interest Rates	Daily	Daily
"PB"	Bank Lending Survey	Quarterly	Quarterly

Use "ALL" as a shorthand for updating all the catalogs at a glance.

Value

None. Downloads the catalog file(s) to the local machine.

Source

[time series bulk data download](#).

See Also

Other catalog: [bde_catalog_load\(\)](#), [bde_catalog_search\(\)](#)

Examples

```
bde_catalog_update("TI", verbose = TRUE)
```

bde_indicators

Relevant Indicators of Spain

Description

Set of helper functions for downloading some of the most relevant macroeconomic indicators of Spain. Metadata available in [bde_ind_db](#).

Usage

```
bde_ind_gdp_var(series_label = "GDP_YoY", ...)
```

```
bde_ind_unemployment_rate(series_label = "Unemployment_Rate", ...)
```

```
bde_ind_euribor_12m_monthly(series_label = "Euribor_12M_Monthly", ...)
```

```
bde_ind_euribor_12m_daily(series_label = "Euribor_12M_Daily", ...)
```

```
bde_ind_cpi_var(series_label = "Consumer_price_index_YoY", ...)
```

```
bde_ind_ibex_monthly(series_label = "IBEX_index_month", ...)
```

```
bde_ind_ibex_daily(series_label = "IBEX_index_day", ...)
```

```
bde_ind_gdp_quarterly(series_label = "GDP_quarterly_value", ...)
```

```
bde_ind_population(series_label = "Population_Spain", ...)
```

Arguments

series_label	Optional. Character vector or value. Allows specifying a custom label for the series extracted.
...	Arguments passed on to bde_series_load
out_format	Whether the format should be returned as "long" or "wide". Possible values are "wide" or "long". See Value for details and section Examples .
parse_numeric	Logical. If TRUE the columns would be parsed to double (numeric) values. See Note .
extract_metadata	Logical TRUE/FALSE. On TRUE the output is the metadata of the requested series.
parse_dates	Logical. If TRUE, dates are parsed using bde_parse_dates() .
update_cache	Logical. If TRUE, the requested file is updated in cache_dir.
cache_dir	A path to a cache directory. The directory can also be set via options with <code>options(bde_cache_dir = "path/to/dir")</code> .
verbose	Logical TRUE or FALSE, display information useful for debugging.

Details

These functions are convenient wrappers around [bde_series_load\(\)](#) for specific series. Use `verbose = TRUE`, `extract_metadata = TRUE` to see the specification and the source.

Value

A [tibble](#) with the required series.

See Also

[bde_series_load\(\)](#), [bde_catalog_search\(\)](#)

Other indicators: [bde_ind_db](#)

Examples

```
bde_ind_gdp_var()
```

bde_ind_db

Database of selected macroeconomic indicators

Description

Minimal metadata of the selected macroeconomic indicators included in helper functions of **tidyBdE** (see [bde_indicators](#)). Full metadata can be accessed via [bde_catalog_load\(\)](#)

Format

A [tibble](#) of 9 rows and 7 columns with the following fields:

tidyBdE_fun Function name, see [bde_indicators](#).

Numero_secuencial Series code, see [bde_series_load\(\)](#).

Descripcion_de_la_serie Description of the series in Spanish.

Fecha_de_la_primera_observacion Starting date of the indicator.

Fecha_de_la_ultima_observacion Most recent date available.

Fuente Data source.

Details

tidyBdE_fun	Numero_secuencial	Descripcion_de_la_serie
bde_ind_cpi_var	1489713	Estadísticas Generales. IPCA. Base 2015. Índice general. Tasa inter
bde_ind_euribor_12m_daily	905842	Tipo de interés. UEM. Mercado monetario. Euríbor. A 12 meses
bde_ind_euribor_12m_monthly	587853	Tipo de interés. UEM. Mercado monetario. Euríbor. A 12 meses
bde_ind_gdp_quarterly	4663160	Estadísticas Generales. Cuentas Nacionales. SEC2010. Año base 20
bde_ind_gdp_var	4663788	Estadísticas Generales. CNTR. Base 2020. PIB. Precios constantes.
bde_ind_ibex_daily	821340	Cotización y contratación. Acciones. Sociedad de Bolsas y Socieda
bde_ind_ibex_monthly	254433	Cotización y contratación. Acciones. Sociedad de Bolsas y Socieda
bde_ind_population	4637737	Estadísticas generales. INE. EPA. Base 2021. Total Nacional. Amb
bde_ind_unemployment_rate	4635980	Estadísticas Generales. EPA. Base 2021. Total Nacional. Tasa de pa

See Also

Other indicators: [bde_indicators](#)

Examples

```
data("bde_ind_db")
bde_ind_db
```

Description

This function is tailored for date formats used in this package and may fail with other datasets. See **Examples** for formats that are supported.

Date Formats:

FREQUENCY	FORMAT
Daily / Business day	DD MMMMYYYY
Monthly	MMM YYYY
Quarterly	MMM YYYY, where MMM is the first or the last month of the quarter, depending on the value of its
Half-yearly	MMM YYYY, where MMM is the first or the last month of the halfyear period, depending on the value
Annual	YYYY

Usage

```
bde_parse_dates(dates_to_parse)
```

Arguments

dates_to_parse Dates to parse

Details

Tries to parse strings representing dates using `as.Date()`

Value

A `Date` object.

See Also

`as.Date()`

Examples

```
# Formats parsed
would_parse <- c(
  "02 FEB2019", "15 ABR 1890", "MAR 2020", "ENE2020",
  "2020", "12-1993", "01-02-2014", "01/02/1990"
)

parsed_ok <- bde_parse_dates(would_parse)

class(parsed_ok)

tibble::tibble(raw = would_parse, parsed = parsed_ok)

#-----
# Formats not admitted
```

```
wont_parse <- c("JAN2001", "2010-01-12", "01 APR 2017", "01/31/1990")
parsed_fail <- bde_parse_dates(wont_parse)
class(parsed_fail)

tibble::tibble(raw = wont_parse, parsed = parsed_fail)
```

bde_series_full_load *Load BdE full time series files*

Description

Load a full time series file provided by BdE.

Usage

```
bde_series_full_load(
  series_csv,
  parse_dates = TRUE,
  parse_numeric = TRUE,
  cache_dir = NULL,
  update_cache = FALSE,
  verbose = FALSE,
  extract_metadata = FALSE
)
```

Arguments

series_csv	csv file of a series, as defined in the field Nombre del archivo con los valores de la serie of the corresponding catalog. See bde_catalog_load() .
parse_dates	Logical. If TRUE, dates are parsed using bde_parse_dates() .
parse_numeric	Logical. If TRUE the columns would be parsed to double (numeric) values. See Note .
cache_dir	A path to a cache directory. The directory can also be set via options with <code>options(bde_cache_dir = "path/to/dir")</code> .
update_cache	Logical. If TRUE, the requested file is updated in cache_dir.
verbose	Logical TRUE or FALSE, display information useful for debugging.
extract_metadata	Logical TRUE/FALSE. On TRUE the output is the metadata of the requested series.

Details

About BdE file naming:

The series name is a positional code showing the location of the table. For example, table **be_6_1** represents the Table 1, Chapter 6 of the Statistical Bulletin ("BE"). Although it is a unique value, it is subject to change (i.e. a new table is inserted before).

For that reason, the function `bde_series_load()` is more suitable for extracting specific time series.

Value

A *tibble* with a field `Date` and the alias of the fields `series` as described on the catalogs. See `bde_catalog_load()`.

Note

This function tries to coerce the columns to numbers. For some series a warning may be displayed if the parser fails. You can override the default behavior with `parse_numeric = FALSE`

See Also

Other series: `bde_series_load()`

Examples

```
# Metadata
bde_series_full_load("TI_1_1.csv", extract_metadata = TRUE)

# Data
bde_series_full_load("TI_1_1.csv")
```

<code>bde_series_load</code>	<i>Load a single BdE time series</i>
------------------------------	--------------------------------------

Description

The series alias is a positional code showing the location (column and/or row) of the series in the table. However, although it is unique, it is not a good candidate to be used as the series ID, as it is subject to change. If a series changes position in the table, its alias will also change.

To ensure series can still be identified, even after these changes, they are assigned a sequential number (referred to as `series_code` in this function).

Note that a single series may appear in different tables, so it can have several aliases. If you need to search by alias, use `bde_series_full_load()`.

Usage

```
bde_series_load(
  series_code,
  series_label = NULL,
  out_format = "wide",
  parse_dates = TRUE,
  parse_numeric = TRUE,
  cache_dir = NULL,
  update_cache = FALSE,
  verbose = FALSE,
  extract_metadata = FALSE
)
```

Arguments

series_code	A numeric value (or coercible with <code>base::as.double()</code>) or vector of time series code(s), as defined in the field <code>Número secuencial</code> of the corresponding series. See <code>bde_catalog_load()</code> .
series_label	Optional. Character vector or value. Allows specifying a custom label for the series extracted.
out_format	Whether the format should be returned as "long" or "wide". Possible values are "wide" or "long". See Value for details and section Examples .
parse_dates	Logical. If TRUE, dates are parsed using <code>bde_parse_dates()</code> .
parse_numeric	Logical. If TRUE the columns would be parsed to double (numeric) values. See Note .
cache_dir	A path to a cache directory. The directory can also be set via options with <code>options(bde_cache_dir = "path/to/dir")</code> .
update_cache	Logical. If TRUE, the requested file is updated in <code>cache_dir</code> .
verbose	Logical TRUE or FALSE, display information useful for debugging.
extract_metadata	Logical TRUE/FALSE. On TRUE the output is the metadata of the requested series.

Details

Load a single time series provided by Bde.

Value

A `tibble` with a field `Date`:

- With `out_format = "wide"`, each series is presented in a separate column with the name defined by `series_label`.
- With `out_format = "long"`, the tibble has two additional columns:
 - `serie_name` with the label of each series.
 - `serie_value` with the corresponding value.

"wide" format is more suitable for exporting to a `.csv` file while "long" format is more suitable for creating plots with `ggplot2::ggplot()`. See also `tidyr::pivot_longer()` and `tidyr::pivot_wider()`.

Note

This function attempts to coerce the columns to numbers. For some series, a warning may be displayed if the parsing fails.

See Also

[bde_catalog_load\(\)](#), [bde_catalog_search\(\)](#), [bde_indicators\(\)](#)

Other series: [bde_series_full_load\(\)](#)

Examples

```
# Metadata
bde_series_load(573234, verbose = TRUE, extract_metadata = TRUE)

# Data
bde_series_load(573234, extract_metadata = FALSE)

# Vectorized
bde_series_load(c(573234, 573214),
  series_label = c("US/EUR", "GBP/EUR"),
  extract_metadata = TRUE
)

wide <- bde_series_load(c(573234, 573214),
  series_label = c("US/EUR", "GBP/EUR")
)

# Wide format
wide

# Long format
long <- bde_series_load(c(573234, 573214),
  series_label = c("US/EUR", "GBP/EUR"),
  out_format = "long"
)

long

# Use with ggplot
library(ggplot2)

ggplot(long, aes(Date, serie_value)) +
  geom_line(aes(group = serie_name, color = serie_name)) +
  scale_color_bde_d() +
  theme_tidybde()
```

bde_tidy_palettes *BdE color palettes*

Description

Custom palettes based on the publications of BdE. These are manual palettes with a maximum of 6 colors.

Usage

```
bde_tidy_palettes(  
  n = 6,  
  palette = c("bde_vivid_pal", "bde_rose_pal", "bde_qual_pal"),  
  alpha = NULL,  
  rev = FALSE  
)
```

Arguments

n	The number of colors (≥ 1) in the palette.
palette	A valid palette name.
alpha	An alpha-transparency level in the range $[0,1]$ (0 means transparent and 1 means opaque). A missing, i.e., <code>alpha = NULL</code> , does not add opacity codes ("FF") to the individual color hex codes. See ggplot2::alpha() .
rev	Logical indicating whether the ordering of the colors should be reversed.

Value

A vector of colors.

See Also

Other bde_plot: [scales_bde](#), [theme_tidybde\(\)](#)

Examples

```
# BdE vivid pal  
scales::show_col(bde_tidy_palettes(palette = "bde_vivid_pal"),  
  labels = FALSE  
)  
  
# BdE rose pal  
scales::show_col(bde_tidy_palettes(palette = "bde_rose_pal"),  
  labels = FALSE  
)  
  
# BdE qual pal  
scales::show_col(bde_tidy_palettes(palette = "bde_qual_pal"),
```

```

  labels = FALSE
)

```

scales_bde *BdE scales for R* <https://CRAN.R-project.org/package=ggplot2> **ggplot2**

Description

Scales to be used with the **ggplot2** package. Discrete palettes are named `scale*_bde_d`, while continuous palettes are named `scale*_bde_c`.

Usage

```

scale_color_bde_d(
  palette = c("bde_vivid_pal", "bde_rose_pal", "bde_qual_pal"),
  alpha = NULL,
  rev = FALSE,
  ...
)

scale_fill_bde_d(
  palette = c("bde_vivid_pal", "bde_rose_pal", "bde_qual_pal"),
  alpha = NULL,
  rev = FALSE,
  ...
)

scale_color_bde_c(
  palette = c("bde_rose_pal", "bde_vivid_pal", "bde_qual_pal"),
  alpha = NULL,
  rev = FALSE,
  guide = "colorbar",
  ...
)

scale_fill_bde_c(
  palette = c("bde_rose_pal", "bde_vivid_pal", "bde_qual_pal"),
  alpha = NULL,
  rev = FALSE,
  guide = "colorbar",
  ...
)

```

Arguments

`palette` Name of the BdE palette to apply. See [bde_tidy_palettes\(\)](#) for details.

alpha	An alpha-transparency level in the range $[\ 0, 1]$ (0 means transparent and 1 means opaque). A missing, i.e., <code>alpha = NULL</code> , does not add opacity codes ("FF") to the individual color hex codes. See <code>ggplot2::alpha()</code> .
rev	Logical indicating whether the ordering of the colors should be reversed.
...	Further arguments of <code>ggplot2::discrete_scale()</code> or <code>ggplot2::continuous_scale()</code> .
guide	A function used to create a guide or its name. See <code>guides()</code> for more information.

Value

A **ggplot2** color scale.

See Also

`ggplot2::discrete_scale()`, `ggplot2::continuous_scale()`

Other bde_plot: `bde_tidy_palettes()`, `theme_tidybde()`

Examples

```
library(ggplot2)

set.seed(596)
txsamp <- subset(
  txhousing,
  city %in% c(
    "Houston", "Fort Worth",
    "San Antonio", "Dallas", "Austin"
  )
)

ggplot(txsamp, aes(x = sales, y = median)) +
  geom_point(aes(colour = city)) +
  scale_color_bde_d() +
  theme_minimal()

ggplot(txsamp, aes(x = sales, y = median)) +
  geom_point(aes(colour = city)) +
  scale_color_bde_d("bde_qual_pal") +
  theme_minimal()
```

theme_tidybde

BdE
theme

Rhref<https://CRAN.R-project.org/package=ggplot2>**ggplot2**

Description

A custom **ggplot2** theme based on the publications of BdE.

Usage

```
theme_tidybde(...)
```

Arguments

```
...           Arguments passed on to ggplot2::theme_classic
base_size    base font size, given in pts.
base_family   base font family
header_family font family for titles and headers. The default, NULL, uses
              theme inheritance to set the font. This setting affects axis titles, legend
              titles, the plot title and tag text.
base_line_size base size for line elements
base_rect_size base size for rect elements
ink,paper,accent colour for foreground, background, and accented elements
              respectively.
```

Details

Theme based on `ggplot2::theme_classic()`.

Value

A **ggplot2** `theme()`.

See Also

`ggplot2::theme_classic()`

Other bde_plot: `bde_tidy_palettes()`, `scales_bde`

Examples

```
library(ggplot2)
library(dplyr)
library(tidyr)

series_TC <- bde_series_full_load("TC_1_1.csv")

# If download was OK then plot
if (nrow(series_TC) > 0) {
  series_TC <- series_TC[c(1, 2)]

  series_TC_pivot <- series_TC |>
    filter(
      Date >= "2020-01-01" & Date <= "2020-12-31",
      !is.na(series_TC[[2]])
    )

  names(series_TC_pivot) <- c("x", "y")
```

```
ggplot(series_TC_pivot, aes(x = x, y = y)) +  
  geom_line(linewidth = 0.8, color = bde_tidy_palettes(n = 1)) +  
  labs(  
    title = "Title",  
    subtitle = "Some metric",  
    caption = "Bank of Spain"  
  ) +  
  theme_tidybde()  
}
```

Index

- * **bde_plot**
 - bde_tidy_palettes, 14
 - scales_bde, 15
 - theme_tidybde, 16
- * **catalog**
 - bde_catalog_load, 2
 - bde_catalog_search, 4
 - bde_catalog_update, 5
- * **indicators**
 - bde_ind_db, 7
 - bde_indicators, 6
- * **series**
 - bde_series_full_load, 10
 - bde_series_load, 11
- * **utils**
 - bde_parse_dates, 8
- as.Date(), 9
- base::as.double(), 12
- base::grep(), 4
- base::regex, 4
- bde_catalog_load, 2, 4, 6
- bde_catalog_load(), 4, 7, 10–13
- bde_catalog_search, 3, 4, 6
- bde_catalog_search(), 7, 13
- bde_catalog_update, 3, 4, 5
- bde_catalog_update(), 3
- bde_ind_cpi_var (bde_indicators), 6
- bde_ind_db, 6, 7, 7
- bde_ind_euribor_12m_daily
 - (bde_indicators), 6
- bde_ind_euribor_12m_monthly
 - (bde_indicators), 6
- bde_ind_gdp_quarterly (bde_indicators), 6
- bde_ind_gdp_var (bde_indicators), 6
- bde_ind_ibex (bde_indicators), 6
- bde_ind_ibex_daily (bde_indicators), 6
- bde_ind_ibex_monthly (bde_indicators), 6
- bde_ind_population (bde_indicators), 6
- bde_ind_unemployment_rate
 - (bde_indicators), 6
- bde_indicators, 6, 7, 8
- bde_indicators(), 13
- bde_parse_dates, 8
- bde_parse_dates(), 3, 4, 7, 10, 12
- bde_series_full_load, 10, 13
- bde_series_full_load(), 11
- bde_series_load, 7, 11, 11
- bde_series_load(), 7, 8, 11
- bde_tidy_palettes, 14, 16, 17
- bde_tidy_palettes(), 15
- Date, 9
- ggplot2::alpha(), 14, 16
- ggplot2::continuous_scale(), 16
- ggplot2::discrete_scale(), 16
- ggplot2::ggplot(), 12
- ggplot2::theme_classic, 17
- ggplot2::theme_classic(), 17
- guides(), 16
- regex, 4
- regular expressions, 4
- scale_color_bde_c (scales_bde), 15
- scale_color_bde_d (scales_bde), 15
- scale_colour_bde_c (scales_bde), 15
- scale_colour_bde_d (scales_bde), 15
- scale_fill_bde_c (scales_bde), 15
- scale_fill_bde_d (scales_bde), 15
- scales_bde, 14, 15, 17
- theme(), 17
- theme_tidybde, 14, 16, 16
- tibble, 3, 4, 7, 8, 11, 12
- tidyr::pivot_longer(), 12
- tidyr::pivot_wider(), 12