

# Package ‘tidymodels’

May 8, 2026

**Title** Easily Install and Load the 'Tidymodels' Packages

**Version** 1.5.0

**Description** The tidy modeling “verse” is a collection of packages for modeling and statistical analysis that share the underlying design philosophy, grammar, and data structures of the tidyverse.

**License** MIT + file LICENSE

**URL** <https://tidymodels.tidymodels.org>,  
<https://github.com/tidymodels/tidymodels>

**BugReports** <https://github.com/tidymodels/tidymodels/issues>

**Depends** R (>= 4.1)

**Imports** broom (>= 1.0.12), cli (>= 3.6.6), conflicted (>= 1.2.0),  
dials (>= 1.4.3), dplyr (>= 1.2.1), ggplot2 (>= 4.0.3), hardhat  
(>= 1.4.3), infer (>= 1.1.0), modeldata (>= 1.5.1), parsnip (>= 1.5.0), purrr (>= 1.2.2), recipes (>= 1.3.2), rlang (>= 1.2.0),  
rsample (>= 1.3.2), rstudioapi (>= 0.18.0), tailor (>= 0.1.0),  
tidyr (>= 1.3.2), tune (>= 2.1.0), workflows (>= 1.3.0),  
workflowssets (>= 1.1.1), yardstick (>= 1.4.0)

**Suggests** covr, glue, knitr, rmarkdown, testthat (>= 3.0.0), xml2

**VignetteBuilder** knitr

**Config/Needs/website** tidyverse/tidytemplate

**Config/testthat/edition** 3

**Config/usethis/last-upkeep** 2025-04-27

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**NeedsCompilation** no

**Author** Max Kuhn [aut, cre] (ORCID: <<https://orcid.org/0000-0003-2402-136X>>),  
Hadley Wickham [aut],  
Posit Software, PBC [cph, fnd] (ROR: <<https://ror.org/03wc8by49>>)

**Maintainer** Max Kuhn <max@posit.co>

**Repository** CRAN

**Date/Publication** 2026-04-23 06:20:02 UTC

## Contents

pkg_deps . . . . .	2
tag_show . . . . .	2
tidymodels_conflicts . . . . .	3
tidymodels_packages . . . . .	4
tidymodels_prefer . . . . .	4
tidymodels_update . . . . .	5
<b>Index</b>	<b>6</b>

---

pkg_deps	<i>List all dependencies</i>
----------	------------------------------

---

### Description

List all dependencies

### Usage

```
pkg_deps(x = "tidymodels", recursive = FALSE)
```

### Arguments

x	A character string for the packages being evaluated.
recursive	If TRUE, will also list all dependencies of tidymodels packages.

---

tag_show	<i>Facilities for loading and updating other packages</i>
----------	---

---

### Description

The tidymodels metapackage contains a set of tags for specific topics in modeling and analysis. These can be used to load packages in groups.

### Usage

```
tag_show()
tag_attach(tag)
tag_update(tag)
```

## Arguments

`tag` A character string for the tag. Current options are: 'Bayesian analysis', 'deep learning', 'ensembles', 'extra models', 'extra recipes', 'feature engineering', 'interpretation', 'parallel processing', 'parameter tuning', 'resampling', 'text analysis', 'time series', and 'visualization'.

## Examples

```
tag_show()
```

---

`tidymodels_conflicts` *Conflicts between the tidymodels and other packages*

---

## Description

This function lists all the conflicts between packages in the tidymodels and other packages that you have loaded.

## Usage

```
tidymodels_conflicts()
```

## Details

There are four conflicts that are deliberately ignored: `intersect`, `union`, `setequal`, and `setdiff` from `dplyr`. These functions make the base equivalents generic, so shouldn't negatively affect any existing code.

To manage conflicts, you can use the `conflicted` package. To prefer tidymodels functions over other functions, use `tidymodels_prefer()`.

## See Also

[tidymodels\\_prefer\(\)](#)

## Examples

```
tidymodels_conflicts()
```

tidymodels\_packages    *List all packages in the tidymodels*

---

**Description**

List all packages in the tidymodels

**Usage**

```
tidymodels_packages(include_self = TRUE)
```

**Arguments**

include\_self    Include tidymodels in the list?

**Examples**

```
tidymodels_packages()
```

---

tidymodels\_prefer    *Resolve conflicts between tidymodels packages and others*

---

**Description**

tidymodels\_prefer() uses the conflicted package to handle common conflicts with tidymodels and other packages.

**Usage**

```
tidymodels_prefer(quiet = TRUE)
```

**Arguments**

quiet            If TRUE, all output will be suppressed

**Details**

The list of conflicts includes several dozen that are known issues with other packages.

Note that the **conflicted** package is used to manage which packages take precedence. Using tidymodels\_prefer() will turn on general conflict resolution during the R session.

**See Also**

[tidymodels\\_conflicts\(\)](#)

**Examples**

```
tidymodels_prefer(quiet = FALSE)
```

---

tidymodels_update	<i>Update tidymodels packages</i>
-------------------	-----------------------------------

---

**Description**

This will check to see if all tidymodels packages (and optionally, their dependencies) are up-to-date, and will install after an interactive confirmation.

**Usage**

```
tidymodels_update(pkg = "tidymodels", recursive = FALSE, ...)
```

**Arguments**

pkg	A character string for the model being updated.
recursive	If TRUE, will also check all dependencies of tidymodels packages.
...	Extra arguments to pass to <a href="#">utils::install.packages()</a>

**Value**

Nothing is returned but a message is printed to the console about which packages (if any) should be installed along with code to do so.

**Examples**

```
## Not run:  
tidymodels_update()  
  
## End(Not run)
```

# Index

`pkg_deps`, 2

`tag_attach(tag_show)`, 2

`tag_show`, 2

`tag_update(tag_show)`, 2

`tags(tag_show)`, 2

`tidymodels_conflicts`, 3

`tidymodels_conflicts()`, 4

`tidymodels_packages`, 4

`tidymodels_prefer`, 4

`tidymodels_prefer()`, 3

`tidymodels_update`, 5

`utils::install.packages()`, 5