

Package ‘tsSelect’

May 8, 2026

Type Package

Title Execution of Time Series Models

Version 0.1.8

Author Avi Blinder <aviblinder@gmail.com>

Maintainer Avi Blinder <aviblinder@gmail.com>

Description Execution of various time series models and choosing the best one either by a specific error metric or by picking the best one by majority vote. The models are based on the ``forecast" package, written by Prof. Rob Hyndman.

License GPL-2

LazyData TRUE

Depends R (>= 3.0.2)

Imports forecast

RoxygenNote 5.0.1

NeedsCompilation no

Repository CRAN

Date/Publication 2016-10-06 01:38:48

Contents

check_object	2
ros1_ts	2
ros2_ts	3
run_models	4

Index	5
--------------	----------

check_object	<i>Check Object class</i>
--------------	---------------------------

Description

Internal function that verifies the class of the object (should be time series)

Usage

```
check_object(x)
```

Arguments

x A timeseries object

Details

internal function for verifying that the object belongs to class "time series"

Value

stops if object not a ts class

Author(s)

Avi Blinder

ros1_ts	<i>"Time Series sample"</i>
---------	-----------------------------

Description

This sample dataset is taken from a Kaggle's competition ("Rossman Store Sales")

Usage

```
data("ros1_ts")
```

Format

The format is: Time-Series [1:365] from 1 to 365: 0.1 5530 4327 4486 4997 ...

Details

Only 2013 sales data from the first store are represented in the dataset

Source

```
"https://www.kaggle.com/c/rossmann-store-sales/data"
```

Examples

```
data(ros1_ts)
## maybe str(ros1_ts) ; plot(ros1_ts) ...
```

```
ros2_ts           "Time Series sample 2"
```

Description

This sample dataset is taken from a Kaggle's competition ("Rossman Store Sales")

Usage

```
data("ros2_ts")
```

Format

The format is: Time-Series [1:365] from 1 to 365: 0.1 5530 4327 4486 4997 ...

Details

Sales data from the second store are represented in the dataset

Source

```
"https://www.kaggle.com/c/rossmann-store-sales/data"
```

Examples

```
data(ros2_ts)
```

`run_models`*Run ts Models*

Description

Function that executes several models and picks the best one.

Usage

```
run_models(ts1, accuracy_measure = NULL)
```

Arguments

`ts1` A timeseries object
`accuracy_measure` - Possible error measures: ME, RMSE, MAE, MPE, MAPE, MASE, ACF1

Value

the best time series model

Author(s)

Avi Blinder

Examples

```
data(ros1_ts)
run_models(ros1_ts)
run_models(ros1_ts, "RMSE")
```

Index

* **datasets**

ros1_ts, [2](#)

ros2_ts, [3](#)

check_object, [2](#)

ros1_ts, [2](#)

ros2_ts, [3](#)

run_models, [4](#)