

Package ‘ttScreening’

May 8, 2026

Title Genome-Wide DNA Methylation Sites Screening by Use of Training and Testing Samples

Version 1.8

Description A screening process utilizing training and testing samples to filter out uninformative DNA methylation sites. Surrogate variables (SVs) of DNA methylation are included in the filtering process to explain unknown factor effects. This package also provides two screening functions for screening high-dimensional predictors when the events are rare. The first method is called 'Rare-Screening' which employs a repeated random sampling with replacement and using linear modeling with Bayes adjustment. The second method is called 'Firth-ttScreening' which uses 'ttScreening' method with additional Firth correction term in the maximum likelihood for the logistic regression model. These methods handle the high-dimensionality and low event rates.

License Artistic-2.0

Encoding UTF-8

RoxygenNote 7.3.3

Depends matrixStats,sva,limma

Imports graphics,stats,corpcor,simsalapar,MASS,brglm2

Suggests mvtnorm

NeedsCompilation no

Author Meredith Ray [aut, cre],
Mohammad Nahian Ferdous Abrar [aut],
Yu Jiang [aut],
Xin Tong [aut],
Hongmei Zhang [aut]

Maintainer Meredith Ray <maray@memphis.edu>

Repository CRAN

Date/Publication 2026-01-30 17:50:02 UTC

Contents

ttScreening-package	2
-------------------------------	---

firth_screening	3
irwsva.build2	4
num.sv2	5
Rare_Screening	6
sva2	7
ttScreening	9

Index 13

ttScreening-package	<i>Genome-Wide DNA Methylation Sites Screening by Use of Training and Testing Samples</i>
---------------------	---

Description

ttScreening is a screening process to filter out non-informative DNA methylation sites by applying (ordinary or robust) linear regressions to training data, and the results are further examined using testing samples. Surrogate variables are included to account for unknown factors. This package also contains two additional functions, Rare_Screening and firth_screening, for predictor screening in high-dimensional settings when the outcome is binary and is rare (binary with low prevalence). These methods were developed to handle challenges while screening predictors such as separation and small event counts and high-dimensionality, which are common in genomic and epigenomic studies.

Details

Package:	ttScreening
Type:	Package
Version:	1.8
Date:	2025-12-10
License:	Artistic-2.0

This package utilizes training and testing samples to filter out uninformative DNA methylation sites for continuous and rare binary outcomes. Surrogate variables (SVs) of DNA methylation are included in the filtering process to explain unknown factor effects.

Author(s)

Meredith Ray, Mohammad Abrar, Yu Jiang, Xin Tong, Hongmei Zhang
 Maintainer: Meredith Ray <maray@memphis.edu>

References

Ray MA, Tong X, Lockett GA, Zhang H, and Karmaus WJJ. (2016) "An Efficient Approach to Screening Epigenome-Wide Data", BioMed Research International.
 Leek JT and Storey JD. (2007) "Capturing heterogeneity in gene expression studies by 'Surrogate Variable Analysis'." PLoS Genetics, 3: e161.

firth_screening	<i>ttScreening with Firth bias-reduced logistic regression + multiple testing</i>
-----------------	---

Description

firth_screening: a two-stage approach combining ttScreening with Firth's bias-reduced logistic regression. This method is designed to handle small sample sizes and rare outcomes by reducing bias in logistic regression coefficients.

Two-stage screening: (1) Pre-screen each predictor with bias-reduced logistic regression (brglm2). (2) For predictors passing pre-screen, run repeated train/test splits and count how often the test p-value < 0.05. Also report Bonferroni and FDR sets from the pre-screen p-values.

Dr. Abrar maintains and is the author of this functions, for questions contact him at abrar0708@gmail.com.

Usage

```
firth_screening(
  predictor_list,
  Outcome,
  iteration,
  train_frac = 0.67,
  alpha = 0.05,
  firth_count_threshold = 50,
  verbose = TRUE
)
```

Arguments

predictor_list	Numeric matrix of dimension n x p (rows = subjects, cols = predictors). Column names are treated as predictor IDs; if missing, they will be generated.
Outcome	Integer or logical vector of length n with values in {0,1}.
iteration	Integer, number of train/test resampling iterations (e.g., 100).
train_frac	Numeric in (0,1); fraction of each class used for training (default 0.67).
alpha	Numeric in (0,1) p-value cutoff used inside splits (default 0.05).
firth_count_threshold	Integer, minimum number of "successes" to call a predictor selected by the ttScreening path (default 50).
verbose	Logical; if TRUE prints a short summary (default TRUE).

Value

A list with:

- firth_tt: character vector of predictor IDs selected by repeated ttScreening (count >= firth_count_threshold)
- Bonferroni: character vector selected by Bonferroni-adjusted p < 0.05 (pre-screen)

- FDR: character vector selected by FDR-adjusted $p < 0.05$ (pre-screen)
- prescreen_p: named numeric vector of pre-screen p-values
- counts: named integer vector of ttScreening success counts

Examples

```
## Not run:
res <- firth_screening(
  predictor_list, Outcome,
  iteration = 100, train_frac = 0.67, alpha = 0.05, firth_count_threshold = 50
)
length(res$firth_tt); head(res$firth_tt)

## End(Not run)
```

irwsva.build2	<i>Adjusted irwsva.build which builds surrogate variables from gene expression data</i>
---------------	---

Description

This function is directly modified from the original `irwsva.build()` in the SVA package. It was noticed that under certain circumstances a subscript out of bounds error would occur while running the SVA function. Therefore, this modified code has a single line altered that conditionally uses the generic singular decomposition, `svd()`, instead of fast singular decomposition, `fast.svd()`.

Usage

```
irwsva.build2(dat, mod, mod0 = NULL, n.sv, B = 5)
```

Arguments

<code>dat</code>	A m CpG sites by n subjects matrix of methylation data.
<code>mod</code>	A n by k model matrix corresponding to the primary model fit (see <code>model.matrix</code>)
<code>mod0</code>	A n by k_0 model matrix corresponding to the null model to be compared to <code>mod</code> .
<code>n.sv</code>	The number of surrogate variables to construct.
<code>B</code>	The number of iterations of the algorithm to perform.

Details

See <http://www.bioconductor.org/packages/release/bioc/manuals/sva/man/sva.pdf>

Value

sv	A n by n.sv matrix where each column is a distinct surrogate variable.
pprob.gam	A vector with the posterior probability estimates that each row is affected by dependence.
pprob.b	A vector with the posterior probability estimates that each row is affected by the variables in mod, but not in mod0.
n.sv	The number of surrogate variables estimated.

Note

sva Vignette <http://www.biostat.jhsph.edu/~jleek/sva/>

Author(s)

Original irwsva.build: Jeffrey T. Leek <jleek@jhsph.edu>, John Storey jstorey@princeton.edu

References

- Original sva: Leek JT and Storey JD. (2008) A general framework for multiple testing dependence. Proceedings of the National Academy of Sciences, 105: 18718-18723.
- Leek JT and Storey JD. (2007) Capturing heterogeneity in gene expression studies by surrogate variable analysis. PLoS Genetics, 3: e161.

num.sv2	<i>Adjusted num.sv which estimates the number of important surrogate variables from a gene expression data set.</i>
---------	---

Description

This function is directly modified from the original num.sv() in the SVA package on Bioconductor. This function has the tolerance level in the fast.svd() function set back to its original default instead of 0.

Usage

```
num.sv2(dat, mod, method = c("be", "leek"), vfilter = NULL,
        B = 20, sv.sig = 0.1, seed = NULL)
```

Arguments

dat	A m genes by n arrays matrix of expression data.
mod	A n by k model matrix corresponding to the primary model fit (see model.matrix).
method	The method to use for estimating surrogate variables, for now there is only one option (based on Buja and Eyuboglu 1992).

vfilter	The number of most variable genes to use when building SVs, must be between 100 and m.
B	The number of null iterations to perform. Only used when method="be".
sv.sig	The significance cutoff for eigengenes. Only used when method="be".
seed	A numeric seed for reproducible results. Optional, only used when method="be".

Details

See <http://www.bioconductor.org/packages/release/bioc/manuals/sva/man/sva.pdf>

Value

n.sv The number of significant surrogate variables

Note

sva Vignette <http://www.biostat.jhsph.edu/~jleek/sva/>

Author(s)

Original num.sv: Jeffrey T. Leek <jleek@jhsph.edu>, John Storey jstorey@princeton.edu

References

Original sva: Leek JT and Storey JD. (2008) A general framework for multiple testing dependence. *Proceedings of the National Academy of Sciences*, 105: 18718-18723.

Leek JT and Storey JD. (2007) Capturing heterogeneity in gene expression studies by surrogate variable analysis. *PLoS Genetics*, 3: e161.

Rare_Screening

Rare_Screening: resampling-based screening with limma

Description

Rare_Screening: a resampling-based method that repeatedly samples cases and controls with replacement and applies bayes moderated linear modeling (limma) to identify predictors that are consistently significant. The function runs a rare-event resampling procedure on user provided data and returns the selected predictors along with iteration-wise selection counts.

Dr. Abrar maintains and is the author of this functions, for questions contact him at abrar0708@gmail.com.

Usage

Rare_Screening(predictor_list, Outcome, iteration, cut)

Arguments

predictor_list	Numeric matrix of size $n \times p$ (rows = subjects, columns = predictors). Column names are treated as predictor IDs; if missing, they will be generated.
Outcome	Integer or logical vector of length n with values in $\{0,1\}$.
iteration	Integer, number of bootstrap iterations (e.g., 100).
cut	Integer, selection count threshold (e.g., 70) used to define final selection.

Value

A list with:

- final_selection: character vector of selected predictor IDs (selection count \geq cut)
- counts: integer vector of selection counts for all predictors (names = predictors)
- sel_mat: $p \times$ iteration matrix of 0/1 selections per iteration
- selected: integer indices of the predictors that met cut

Examples

```
## Not run:
# predictor_list: n x p matrix; Outcome: 0/1 vector of length n
res <- Rare_Screening(predictor_list, Outcome, iteration = 100, cut = 70)
head(res$final_selection)

## End(Not run)
```

sva2

The adjusted sva code using irwsva.build2

Description

This function is the modified SVA function in which it uses the `irwsva.build2` function rather than the `irwsva.build` function to build the surrogate variables. Thus, only a single line has been altered from the original surrogate variable analysis function.

Usage

```
sva2(dat, mod, mod0 = NULL, n.sv = NULL, method = c("irw", "two-step"),
vfilter = NULL, B = 5, numSVmethod = "be")
```

Arguments

dat	An m by n (m cpG sites by n subjects) matrix of methylation data.
mod	A n by k model matrix corresponding to the primary model fit (see model.matrix).
mod0	A n by k0 model matrix corresponding to the null model to be compared to mod.
n.sv	Optional. The number of surrogate variables to estimate, can be estimated using the num.sv function.
method	Choose between the iteratively re-weighted or two-step surrogate variable estimation algorithms.
vfilter	The number of most variable CpG sites to use when building SVs, must be between 100 and m.
B	The number of iterations of the algorithm to perform.
numSVmethod	The method for determining the number of surrogate variables to use.

Details

See <http://www.bioconductor.org/packages/release/bioc/manuals/sva/man/sva.pdf>

Value

sv	A n by n.sv matrix where each column is a distinct surrogate variable.
pprob.gam	A vector with the posterior probability estimates that each row is affected by dependence.
pprob.b	A vector with the posterior probability estimates that each row is affected by the variables in mod, but not in mod0.
n.sv	The number of surrogate variables estimated.

Note

sva Vignette <http://www.biostat.jhsph.edu/~jleek/sva/>

Author(s)

Original sva: Jeffrey T. Leek <jleek@jhsph.edu>, John Storey jstorey@princeton.edu

References

- Original sva: Leek JT and Storey JD. (2008) A general framework for multiple testing dependence. Proceedings of the National Academy of Sciences, 105: 18718-18723.
- Leek JT and Storey JD. (2007) Capturing heterogeneity in gene expression studies by surrogate variable analysis. PLoS Genetics, 3: e161.

ttScreening

*A screening process built upon training and testing samples***Description**

A screening process to filter out non-informative DNA methylation sites by applying (ordinary or robust) linear regressions to training data, and the results are further examined using testing samples. Surrogate variables are included to account for unknown factors.

Usage

```
ttScreening(y = y, formula, imp.var, data, B.values=FALSE, iterations = 100,
  sva.method = c("two-step", "irw"), cv.cutoff = 50, n.sv = NULL,
  train.alpha = 0.05, test.alpha = 0.1, FDR.alpha = 0.05, Bon.alpha = 0.05,
  percent = (2/3), linear = c("robust", "ls"), vfilter = NULL, B = 5,
  numSVmethod = "be", rowname = NULL, maxit=20)
```

Arguments

y	Data matrix of DNA methylation measures (m by n, m CpG sites and n subjects). Each column represents DNA methylation measures of all CpG sites for one subject.
formula	An object of class <code>formula</code> (or one that can be coerced to that class): a symbolic description of the model to be fitted. The details of model specification are given under "Details".
imp.var	A vector indicating the location of the term(s) in the formula option on which the selection of CpG sites are made. Interactions are considered a single term. For example, suppose the right-hand side of the equation is: $x + z + x:z$. If the decision of selecting a CpG site is based on one single term, e.g., the significance of interaction effect, then <code>imp.var</code> is set as the location of that term, e.g., <code>imp.var=3</code> (the third term). If the decision is desired to base on all the three terms, then <code>imp.var=c(1,2,3)</code> .
data	Data frame created from <code>model.frame</code> . Also is the data frame containing the variables defined in formula.
B.values	Logical, TRUE if indicating the methylation is measured as beta values, FALSE if methylation is measured as M-values. The default is FALSE.
iterations	Number of loops for the training/testing (TT) procedure. The default is 100.
sva.method	Option of the two surrogate variable estimation algorithms, the iteratively re-weighted, "irw", or two-step, "two-step". The default is "two-step".
cv.cutoff	The minimum frequency required for a DNA methylation site to be treated as an informative site. After "iterations" iterations, the frequency of each DNA methylation being selected out of "iterations" iterations is recorded. The higher the frequency, the more likely the site is informative. The default is 50.
n.sv	Number of surrogate variables. If NULL, the number of surrogate variables will be determined based on the data. The default is NULL.

<code>train.alpha</code>	Significance level for training samples. The default is 0.05.
<code>test.alpha</code>	Significance level for testing samples. The default is 0.05.
<code>FDR.alpha</code>	False discovery rate. The default is 0.05. This is to fit the need of selecting variables based on FDR.
<code>Bon.alpha</code>	Overall significance level by use of the Bonferroni method for multiple testing correction. The default is 0.05. This is to fit the need of selecting variables based on the Bonferroni multiple testing correction.
<code>percent</code>	Proportion of the full sample to be used for training. The default is 2/3.
<code>linear</code>	Choice of linear regression methods, "robust" (robust regression) or "ls" (ordinary least squares). The default is "ls".
<code>vfilter</code>	The number of most variable CpG sites to use when building SVs, must be between 100 and the number of genes; Must be NULL or numeric (> 0), The default is NULL.
<code>B</code>	Number of iterations in generating surrogate variables. The default is 5.
<code>numSVmethod</code>	The method for determining the number of surrogate variables to use. The default is "be", the other method is "leek".
<code>rowname</code>	Optional, NULL or "TRUE". The default is NULL. If rownames are not already present within the data, the order in which the DNA methylation sites are listed will become the rowname. Surrogate variable estimates are formed based on the algorithms in Leek and Storey (2007).
<code>maxit</code>	Optional, controls the number of iterations for linear regression estimation methods. The default is 20.

Details

See [lm](#) or [glm](#) for details.

Value

<code>sub.remove</code>	Denotes which subjects (based on order) were removed due to incomplete or missing data within the prediction variables defined in the formula argument.
<code>train.cpg</code>	Number of DNA methylation sites selected after the training step of each loop.
<code>test.cpg</code>	Number of DNA methylation sites selected after the testing step of each loop.
<code>selection</code>	Indicator matrix for the TT method after the testing step. The number of rows is the number of methylation sites, and the number of columns is the number of iterations. An entry of 1 indicates the selection of a site, and 0 otherwise.
<code>pvalue.matrix</code>	Matrix of p-values of the selected DNA methylation sites after the testing step. The number of rows is the number of methylation sites and the number of columns is the number of iterations. For methylation sites not selected, NA is listed.
<code>TT.cpg</code>	Final list of the DNA methylation sites by their original rownames selected from the TT method.
<code>FDR.cpg</code>	Final list of the DNA methylation sites by their original rownames selected from the FDR method.

Bon.cpg	Final list of the DNA methylation sites by their original rownames selected from the Bonferroni method.
SV.output	Data frame containing the estimated surrogate variables.
TT.output	Data frame containing the list of DNA methylation sites selected from the TT method and the respective coefficients and pvalues for the variables and SVs.
FDR.output	Data frame containing the list of DNA methylation sites selected from the FDR method and the respective coefficients and pvalues for the variables and SVs.
Bon.output	Data frame containing the list of DNA methylation sites selected from the Bonferroni method and the respective coefficients and pvalues for the variables and SVs.

References

- Meredith Ray, Xin Tong, Hongmei Zhang, and Wilfred Karmaus. (2014) "DNA methylation sites screening with surrogate variables", unpublished manuscript.
- Leek JT and Storey JD. (2007) "Capturing heterogeneity in gene expression studies by 'Surrogate Variable Analysis'." *PLoS Genetics*, 3: e161.

Examples

```
## Not run:
library(mvtnorm)
nsub=600
imp=100
num=2000

set.seed(1)
x1= rnorm(nsub,1,1)
size1<-rmultinom(1,nsub,c(0.15,0.25,0.25,0.35))
x2= matrix(sample(c(rep(0,size1[1,]),
rep(1,size1[2,]),
rep(2,size1[3,]),
rep(3,size1[4,])),replace=F),byrow=250,ncol=1)

sur1<-rnorm(nsub,0,5)
sur2<-rnorm(nsub,3,1)
sur3<-rnorm(nsub,0,1)
sur4<-rnorm(nsub,2,4)
sur5<-rnorm(nsub,0,3)

sigma1<-matrix(0,nrow=num,ncol=num)
diag(sigma1)<-1.5

beta0<-0.5
beta1<-0.3
beta2<-0.3
beta3<-0.3

sbeta1<-rnorm(1,0.5,0.01)
sbeta2<-rnorm(1,0.5,0.01)
```

```

sbeta3<-rnorm(1,0.5,0.01)
sbeta4<-rnorm(1,0.5,0.01)
sbeta5<-rnorm(1,0.5,0.01)

#beta matrix#
beta<-as.matrix(cbind(beta0,beta1,beta2,beta3,sbeta1,sbeta2,sbeta3,sbeta4,sbeta5))
beta.no2<-as.matrix(cbind(beta0,beta1,beta3,sbeta1,sbeta2,sbeta3,sbeta4,sbeta5))
beta.sur<-as.matrix(cbind(sbeta1,sbeta2,sbeta3,sbeta4,sbeta5))
#design matrix#
X<-as.matrix(cbind(rep(1,length(x1)),x1,x2,x1*x2,sur1,sur2,sur3,sur4,sur5))
X.no2<-as.matrix(cbind(rep(1,length(x1)),x1,x1*x2,sur1,sur2,sur3,sur4,sur5))
X.sur<-as.matrix(cbind(sur1,sur2,sur3,sur4,sur5))
#mu matrix#
imp1.mu<-matrix(rep(X%*%t(beta),9),nrow=nsup,ncol=(imp*0.9))
imp2.mu<-matrix(rep(X.no2%*%t(beta.no2),1),nrow=nsup,ncol=(imp*0.1))
noimp.mu<-matrix(rep(X.sur%*%t(beta.sur),num-imp),nrow=nsup,ncol=num-imp)
mu.matrix=cbind(imp1.mu, imp2.mu, noimp.mu)
error<-rmvnorm(nsup,mean=rep(0,num),sigma=sigma1,method = "chol")
y<-t(mu.matrix+error)

runs<-ttScreening(y=y,formula=~x1+x2+x1:x2,imp.var=3,data=data.frame(x1,x2),sva.method="two-step",
B.values=FALSE,iterations=100,cv.cutoff=50,n.sv=NULL,train.alpha=0.05,
test.alpha=0.05,FDR.alpha=0.05,Bon.alpha=0.05,percent=(2/3),linear= "ls",
vfilter = NULL, B = 5, numSVmethod = "be",rowname=NULL,maxit=20)

runs$TT.output
runs$FDR.output
runs$Bon.output

## End(Not run)

```

Index

* **ttScreening**

ttScreening-package, [2](#)

firth_screening, [3](#)

formula, [9](#)

glm, [10](#)

irwsva.build2, [4](#)

lm, [10](#)

num.sv2, [5](#)

Rare_Screening, [6](#)

sva2, [7](#)

ttScreening, [9](#)

ttScreening-package, [2](#)