

Package ‘wget’

May 8, 2026

Title Setting Download Method to 'wget'

Version 0.0.4

Description

Provides function, `wget_set()`, to change the method (default to 'wget -c') using in `download.file()`.
Using 'wget -c' allowing continued downloading, which is especially useful for slow internet connection and for downloading large files.
User can run `wget_unset()` to restore previous setting.

Imports yulab.utils (>= 0.2.1)

License Artistic-2.0

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Guangchuang Yu [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-6485-8781>>)

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Repository CRAN

Date/Publication 2025-08-19 15:50:02 UTC

Contents

wget_set	2
wget_unset	2

Index	4
--------------	----------

 wget_set

wget_set

Description

set "download.file.method" to "wget" and "download.file.extra" to "-c"

Usage

```
wget_set(method = "wget", extra = "-c")
```

Arguments

method	download method (wget, default)
extra	extra parameter (-c, default)

Details

setting download method to "wget -c", so that it can continue the download from where it left off.

Value

No return value, called for side effects

Author(s)

Guangchuang Yu

Examples

```
wget_set()
```

 wget_unset

wget_unset

Description

unset download method setting by wget_set

Usage

```
wget_unset()
```

Details

set the download method and extra parameter back to what it is or NULL if it is not specify

Value

No return value, called for side effects

Author(s)

Guangchuang Yu

Examples

`wget_unset()`

Index

wget_set, 2
wget_unset, 2