

Package ‘yesno’

May 8, 2026

Title Ask Yes-No Questions

Version 0.1.3

Description Asks Yes-No questions with variable or custom responses.

License MIT + file LICENSE

URL <https://github.com/poissonconsulting/yesno>,
<https://poissonconsulting.github.io/yesno/>

BugReports <https://github.com/poissonconsulting/yesno/issues>

Depends R (>= 3.4)

Imports utils

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Ayla Pearson [cre] (ORCID: <<https://orcid.org/0000-0001-7388-1222>>),
Joe Thorley [aut, cph] (ORCID: <<https://orcid.org/0000-0002-7683-4592>>),
Hadley Wickham [aut, cph] (ORCID:
<<https://orcid.org/0000-0003-4757-117X>>)

Maintainer Ayla Pearson <ayla@poissonconsulting.ca>

Repository CRAN

Date/Publication 2024-07-26 23:20:02 UTC

Contents

yesno	2
yesno2	3
Index	4

yesno

Yes No with Variable Responses

Description

Asks a custom yes-no question with randomly varying responses. Returns a flag indicating whether the user answered yes or no. It is designed to be used in situations where the users needs to confirm an affirmative action.

Usage

```
yesno(...)
```

Arguments

... Objects to paste and then output to produce the question.

Details

The objects are first pasted without separators and collapsed using `[paste0](..., collapse = "")` before being output using `cat()`.

The order and phrasing of the possible responses varies randomly to ensure the user consciously chooses (as opposed to automatically types their response).

A total of three responses are offered - two of which correspond to No and one of which corresponds to Yes. The possible responses are skewed to No to reduce the chances that a blindly-typing user mistakenly chooses an affirmative action. For the same reason, selection of uncertain responses such as 'Uhhh... Maybe?' is considered to be a No. Selection of a 0 (to exit) is also considered to be No. Questions should be phrased accordingly.

Value

A flag indicating whether the user answered yes or no.

See Also

[yesno2\(\)](#)

Examples

```
## Not run:  
yesno("Do you like ", R.Version()$nickname, "?")  
  
## End(Not run)
```

`yesno2`*Yes No with Two Custom Responses*

Description

Asks a custom yes-no question with two responses (by default 'Yes' or 'No'). Returns a flag indicating which response the user choose. It is designed to be used in situations where a user needs to choose one of two affirmative options.

Usage

```
yesno2(..., yes = "Yes", no = "No")
```

Arguments

<code>...</code>	Objects to paste and then output to produce the question.
<code>yes</code>	A string of the first response.
<code>no</code>	A string of the second response.

Details

The objects are first pasted without separators and collapsed using `[paste0](..., collapse = "")` before being output using `cat()`.

Selection of a 0 (to exit) causes the code to throw an error.

Value

A flag indicating whether the user selected the first (TRUE) or second (FALSE) response.

See Also

[yesno\(\)](#)

Examples

```
## Not run:  
yesno2("Do you like this question?", yes = "I really do")  
  
## End(Not run)
```

Index

`cat()`, [2](#), [3](#)

`yesno`, [2](#)

`yesno()`, [3](#)

`yesno2`, [3](#)

`yesno2()`, [2](#)