

Package ‘zoomr’

May 8, 2026

Title Connect to Your 'Zoom' Data

Version 0.4.0

Description Facilitates making a connection to the 'Zoom' API and executing various queries. You can use it to get data on 'Zoom' webinars and 'Zoom' meetings. The 'Zoom' documentation is available at [<https://developers.zoom.us/docs/api/>](https://developers.zoom.us/docs/api/). This package is not supported by 'Zoom' (owner of the software).

URL <https://github.com/chrisumphlett/zoomr>

BugReports <https://github.com/chrisumphlett/zoomr/issues>

License CC0

Encoding UTF-8

Imports dplyr (>= 1.0.0), magrittr (>= 1.5), jsonlite (>= 1.6.1), httr (>= 1.4.1), glue (>= 1.4.2), rlang (>= 1.0.4), tidyr (>= 1.1.4), janitor (>= 2.1.0), tidyselect (>= 1.1.1), purrr (>= 0.3.4)

RoxygenNote 7.3.2

NeedsCompilation no

Author Chris Umphlett [aut, cre],
Paul Schmidt [ctb]

Maintainer Chris Umphlett <christopher.umphlett@gmail.com>

Repository CRAN

Date/Publication 2025-07-28 14:20:02 UTC

Contents

get_account_users	2
get_meeting_details	3
get_meeting_participants	4
get_panelists	5
get_registration_questions	6
get_tracking_sources	7

get_webinar_details	8
get_webinar_participants	9
get_webinar_polls	10
get_webinar_qanda	11
get_webinar_registrants	12
list_meetings	13
list_webinars	14

Index	16
--------------	-----------

get_account_users	<i>Get All Users in an Account</i>
-------------------	------------------------------------

Description

Get all users in a zoom account. The user id is required to get a list of webinars hosted by a particular user.

Usage

```
get_account_users(account_id, client_id, client_secret)
```

Arguments

account_id	Account Id granted by the Zoom developer app.
client_id	Client Id granted by the Zoom developer app.
client_secret	Client secret granted by the Zoom developer app.

Value

A data frame with the list of all users in the account.

See Also

See <<https://marketplace.zoom.us/docs/api-reference/zoom-api/>> for documentation on the Zoom API.

Examples

```
## Not run:
dat <- get_account_users(your_account_id,
  your_client_id,
  your_client_secret)

## End(Not run)
```

get_meeting_details *Get Meeting Details*

Description

Get metadata about a single meeting including participant count, duration, and other meeting statistics.

Usage

```
get_meeting_details(meeting_id, account_id, client_id, client_secret)
```

Arguments

meeting_id	Zoom Meeting ID (from list_meetings).
account_id	Account ID granted by the Zoom developer app.
client_id	Client ID granted by the Zoom developer app.
client_secret	Client secret granted by the Zoom developer app.

Details

This function retrieves basic meeting metadata. For more comprehensive meeting analytics and participant data, users with Pro+ Zoom accounts can access the Reports API endpoints which provide enhanced meeting details and participant information.

Value

A data frame with the metadata about a meeting. The type column contains integer codes describing the meeting structure/format, while meeting_format_label provides human-readable descriptions:

- 1 = Instant meeting
- 2 = Scheduled meeting
- 3 = Recurring meeting (no fixed time)
- 8 = Recurring meeting (fixed time)
- 10 = Screen share only meeting

See Also

Official Zoom API documentation: <https://developers.zoom.us/docs/api/meetings/#tag/meetings/get/meetings/{meetingId}>

Examples

```
## Not run:
dat <- get_meeting_details(meeting_id = "81753923023",
  your_account_id,
  your_client_id,
  your_client_secret)

## End(Not run)
```

get_meeting_participants

Get Meeting Participants

Description

Get participant information from all instances of a meeting. For recurring meetings, this function automatically retrieves participants from all occurrences, making it ideal for workshop attendance tracking.

Usage

```
get_meeting_participants(
  meeting_id,
  account_id,
  client_id,
  client_secret,
  page_size = 300
)
```

Arguments

meeting_id	Zoom Meeting ID (from list_meetings).
account_id	Account ID granted by the Zoom developer app.
client_id	Client ID granted by the Zoom developer app.
client_secret	Client secret granted by the Zoom developer app.
page_size	Number of records per page. Default is 300.

Details

Important Limitations:

- Meeting instances older than 15 months cannot be retrieved
- This function works with all Zoom account types

Enhanced Features for Pro+ Users: Users with Pro+ Zoom accounts can access additional Reports API endpoints that provide more detailed participant analytics, custom date ranges, and enhanced filtering capabilities.

Value

A data frame with data on each participant at a meeting. Includes an 'instance_date' column to identify which occurrence each participant attended (NA for non-recurring meetings).

See Also

Official Zoom API documentation: https://developers.zoom.us/docs/api/meetings/#tag/meetings/get/past_meetings/{meetingId}/instances and <https://developers.zoom.us/docs/api/meetings/#tag/reports/get/report/meetings/{meetingUuid}/participants>

Examples

```
## Not run:  
# Get participants from all instances of a meeting  
dat <- get_meeting_participants(  
  meeting_id = "81753923023",  
  your_account_id,  
  your_client_id,  
  your_client_secret)  
  
## End(Not run)
```

get_panelists

Get Webinar Panelists

Description

Get the list of attendees who were also panelists from a single webinar.

Usage

```
get_panelists(webinar_id, account_id, client_id, client_secret)
```

Arguments

webinar_id	Zoom Webinar Id, typically an 11 digit number.
account_id	Account Id granted by the Zoom developer app.
client_id	Client Id granted by the Zoom developer app.
client_secret	Client secret granted by the Zoom developer app.

Value

A data frame with the list of panelists from that webinar.

See Also

See <https://marketplace.zoom.us/docs/api-reference/zoom-api/> for documentation on the Zoom API.

Examples

```
## Not run:
dat <- get_webinar_panelists(webinar_id = "99911112222",
  your_account_id,
  your_client_id,
  your_client_secret)

## End(Not run)
```

get_registration_questions

Get Webinar Registration Question Responses

Description

Get registration question answers from all registrants for a single webinar.

Usage

```
get_registration_questions(
  webinar_id,
  account_id,
  client_id,
  client_secret,
  registrant_status = c("approved")
)
```

Arguments

webinar_id	Zoom Webinar Id, typically an 11 digit number.
account_id	Account Id granted by the Zoom developer app.
client_id	Client Id granted by the Zoom developer app.
client_secret	Client secret granted by the Zoom developer app.
registrant_status	One or more of "approved", "pending", or "denied". Default is "approved" only.

Value

A data frame with the registration question answers.

See Also

See <https://marketplace.zoom.us/docs/api-reference/zoom-api/> for documentation on the Zoom API.

Examples

```
## Not run:
dat <- get_registration_questions(webinar_id = "99911112222",
  your_account_id,
  your_client_id,
  your_client_secret,
  c("approved", "denied", "pending"))

## End(Not run)
```

get_tracking_sources *Get Webinar Tracking Sources*

Description

Get a summary of registrations and visitors by tracking source for a specific webinar.

Usage

```
get_tracking_sources(webinar_id, account_id, client_id, client_secret)
```

Arguments

webinar_id Zoom Webinar Id, typically an 11 digit number.
account_id Account Id granted by the Zoom developer app.
client_id Client Id granted by the Zoom developer app.
client_secret Client secret granted by the Zoom developer app.

Value

A data frame with the list of panelists from that webinar.

See Also

See <<https://marketplace.zoom.us/docs/api-reference/zoom-api/>> for documentation on the Zoom API.

Examples

```
## Not run:
dat <- get_tracking_sources(webinar_id = "99911112222",
  your_account_id,
  your_client_id,
  your_client_secret)

## End(Not run)
```

get_webinar_details *Get Webinar Details*

Description

Get metadata about a single webinar.

Usage

```
get_webinar_details(webinar_id, account_id, client_id, client_secret)
```

Arguments

webinar_id	Zoom Webinar Id, typically an 11 digit number.
account_id	Account Id granted by the Zoom developer app.
client_id	Client Id granted by the Zoom developer app.
client_secret	Client secret granted by the Zoom developer app.

Value

A data frame with the metadata about a webinar.

See Also

See <<https://marketplace.zoom.us/docs/api-reference/zoom-api/>> for documentation on the Zoom API.

Examples

```
## Not run:  
dat <- get_webinar_details(webinar_id = "99911112222",  
  your_account_id,  
  your_client_id,  
  your_client_secret)  
  
## End(Not run)
```

get_webinar_participants
Get Webinar Participants

Description

Get participant info about a single webinar.

Usage

```
get_webinar_participants(webinar_id, account_id, client_id, client_secret)
```

Arguments

webinar_id	Zoom Webinar Id, typically an 11 digit number.
account_id	Account Id granted by the Zoom developer app.
client_id	Client Id granted by the Zoom developer app.
client_secret	Client secret granted by the Zoom developer app.

Value

A data frame with data on each participant at a webinar.

See Also

See <<https://marketplace.zoom.us/docs/api-reference/zoom-api/>> for documentation on the Zoom API.

Examples

```
## Not run:  
dat <- get_webinar_participants(webinar_id = "99911112222",  
  your_account_id,  
  your_client_id,  
  your_client_secret)  
  
## End(Not run)
```

get_webinar_polls	<i>Get Webinar Polls</i>
-------------------	--------------------------

Description

Get the polls summary from a single webinar.

Usage

```
get_webinar_polls(webinar_id, account_id, client_id, client_secret)
```

Arguments

webinar_id	Zoom Webinar Id, typically an 11 digit number.
account_id	Account Id granted by the Zoom developer app.
client_id	Client Id granted by the Zoom developer app.
client_secret	Client secret granted by the Zoom developer app.

Value

A data frame with poll results from a webinar.

See Also

See <https://marketplace.zoom.us/docs/api-reference/zoom-api/> for documentation on the Zoom API.

Examples

```
## Not run:  
dat <- get_webinar_polls(webinar_id = "99911112222",  
  your_account_id,  
  your_client_id,  
  your_client_secret)  
  
## End(Not run)
```

get_webinar_qanda	<i>Get Webinar Q & A</i>
-------------------	------------------------------

Description

Get the Q&A summary from a single webinar.

Usage

```
get_webinar_qanda(webinar_id, account_id, client_id, client_secret)
```

Arguments

webinar_id	Zoom Webinar Id, typically an 11 digit number.
account_id	Account Id granted by the Zoom developer app.
client_id	Client Id granted by the Zoom developer app.
client_secret	Client secret granted by the Zoom developer app.

Value

A data frame with all of the Q&A data from a webinar.

See Also

See <https://marketplace.zoom.us/docs/api-reference/zoom-api/> for documentation on the Zoom API.

Examples

```
## Not run:
dat <- get_webinar_qanda(webinar_id = "99911112222",
  your_account_id,
  your_client_id,
  your_client_secret)

## End(Not run)
```

`get_webinar_registrants`*Get Webinar Registrants*

Description

Get registrant info about a single webinar.

Usage

```
get_webinar_registrants(  
  webinar_id,  
  account_id,  
  client_id,  
  client_secret,  
  registrant_status = c("approved")  
)
```

Arguments

<code>webinar_id</code>	Zoom Webinar Id, typically an 11 digit number.
<code>account_id</code>	Account Id granted by the Zoom developer app.
<code>client_id</code>	Client Id granted by the Zoom developer app.
<code>client_secret</code>	Client secret granted by the Zoom developer app.
<code>registrant_status</code>	One or more of "approved", "pending", or "denied". Default is "approved" only.

Value

A data frame with data on all the registrants for a webinar.

See Also

See <<https://marketplace.zoom.us/docs/api-reference/zoom-api/>> for documentation on the Zoom API.

Examples

```
## Not run:  
dat <- get_webinar_registrants(webinar_id = "99911112222",  
  your_account_id,  
  your_client_id,  
  your_client_secret,  
  c("approved", "denied", "pending"))  
  
## End(Not run)
```

list_meetings	<i>Get List of Meetings for a User</i>
---------------	--

Description

Get list of meetings for a User. This function retrieves meeting IDs and UUIDs to pass into other functions for detailed analysis.

Usage

```
list_meetings(
  user_id,
  account_id,
  client_id,
  client_secret,
  meeting_type = "previous_meetings",
  page_size = 300
)
```

Arguments

user_id	Zoom User ID or email address.
account_id	Account ID granted by the Zoom developer app.
client_id	Client ID granted by the Zoom developer app.
client_secret	Client secret granted by the Zoom developer app.
meeting_type	Type of meetings to retrieve. Options are: <ul style="list-style-type: none"> • "previous_meetings" = All previous meetings (default) • "scheduled" = All valid previous, live, and upcoming scheduled meetings • "upcoming" = All upcoming meetings, including live meetings • "upcoming_meetings" = All upcoming meetings, including live meetings • "live" = Currently ongoing meetings
page_size	Number of records per page. Maximum 300, default 300.

Details

Important Limitations:

- **6-month historical limit:** When using "upcoming", "upcoming_meetings", or "previous_meetings", only meetings from the last 6 months are returned
- **Scheduled meetings only:** Does not return instant meetings
- **Unexpired meetings only:** Only returns meetings that haven't expired

For Enhanced Historical Data Access: Users with Pro+ Zoom accounts can access the Reports API endpoint `/report/users/{userId}/meetings` which offers:

- Date range filtering with from and to parameters
- Enhanced meeting details including participant information
- Better historical data retrieval capabilities

Value

A data frame with meetings hosted by the specified user. The meetings_type column contains integer codes describing the meeting structure/format, while meeting_format_label provides human-readable descriptions:

- 1 = Instant meeting
- 2 = Scheduled meeting
- 3 = Recurring meeting (no fixed time)
- 8 = Recurring meeting (fixed time)
- 10 = Screen share only meeting

See Also

Official Zoom API documentation: <https://developers.zoom.us/docs/api/meetings/#tag/meetings/get/users/{userId}/meetings>

Examples

```
## Not run:
dat <- list_meetings(user_id = "user_id_string",
  your_account_id,
  your_client_id,
  your_client_secret,
  meeting_type = "previous_meetings")

## End(Not run)
```

list_webinars

Get List of Webinars for a User.

Description

Get list of webinars for a User. This is used to get the webinar Id's to pass into other functions.

Usage

```
list_webinars(user_id, account_id, client_id, client_secret)
```

Arguments

<code>user_id</code>	Zoom User Id.
<code>account_id</code>	Account Id granted by the Zoom developer app.
<code>client_id</code>	Client Id granted by the Zoom developer app.
<code>client_secret</code>	Client secret granted by the Zoom developer app.

Value

A data frame with all of the webinars hosted by a specific user.

See Also

See <https://marketplace.zoom.us/docs/api-reference/zoom-api/> for documentation on the Zoom API.

Examples

```
## Not run:  
dat <- get_webinar_details(user_id = "user_id_string",  
  your_account_id,  
  your_client_id,  
  your_client_secret)  
  
## End(Not run)
```

Index

[get_account_users](#), 2
[get_meeting_details](#), 3
[get_meeting_participants](#), 4
[get_panelists](#), 5
[get_registration_questions](#), 6
[get_tracking_sources](#), 7
[get_webinar_details](#), 8
[get_webinar_participants](#), 9
[get_webinar_polls](#), 10
[get_webinar_qanda](#), 11
[get_webinar_registrants](#), 12

[list_meetings](#), 13
[list_webinars](#), 14